

# SAFETY DATA SHEET



Date of issue/Date of revision

: 2 September 2025

Version

: 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : ABC#3 RED 283S5772 AF-NAVY  
**Product code** : 00333505  
**Product type** : Liquid.  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Used by spraying.  
**Use of the substance/mixture** : Coating.; Antifouling products  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to UK CLP/GHS

Flam. Liq. 3, H226  
Acute Tox. 4, H302  
Skin Irrit. 2, H315  
Eye Dam. 1, H318  
Skin Sens. 1, H317  
Aquatic Acute 1, H400  
Aquatic Chronic 1, H410


The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### **Hazard pictograms**



**Signal word** : Danger



Code : 00333505

Date of issue/Date of revision

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

**SECTION 3: Composition/information on ingredients**

|                                     |                                                                                        |             |                                                                                                                                                                                        |         |
|-------------------------------------|----------------------------------------------------------------------------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| rosin                               | REACH #:<br>01-2119480418-32<br>EC: 232-475-7<br>CAS: 8050-09-7<br>Index: 650-015-00-7 | ≥5.0 - ≤10  | STOT SE 3, H336<br>Skin Sens. 1, H317                                                                                                                                                  | [1] [2] |
| xylene                              | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7                        | ≥5.0 - ≤8.4 | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412         | [1] [2] |
| N-ethyl-o(or p)-toluenesulphonamide | EC: 232-465-2<br>CAS: 8047-99-2                                                        | ≥1.0 - ≤3.3 | STOT SE 3, H336                                                                                                                                                                        | [1]     |
| copper(II) oxide                    | REACH #:<br>01-2119502447-44<br>EC: 215-269-1<br>CAS: 1317-38-0<br>Index: 029-016-00-6 | ≥1.0 - ≤5.0 | Aquatic Acute 1, H400 (M=100)<br>Aquatic Chronic 1, H410 (M=10)                                                                                                                        | [1]     |
| n-butyl acetate                     | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1  | ≤1.7        | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066                                                                                                                                        | [1] [2] |
| copper                              | REACH #:<br>01-2119480154-42<br>EC: 231-159-6<br>CAS: 7440-50-8                        | ≥1.0 - ≤5.0 | Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 3, H412                                                                                                                                 | [1]     |
| methanol                            | REACH #:<br>01-2119433307-44<br>EC: 200-659-6<br>CAS: 67-56-1<br>Index: 603-001-00-X   | ≤0.30       | Flam. Liq. 2, H225<br>Acute Tox. 3, H301<br>Acute Tox. 3, H311<br>Acute Tox. 3, H331<br>STOT SE 1, H370<br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

**Code** : 00333505

**Date of issue/Date of revision**

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

|                                   |                                                          |
|-----------------------------------|----------------------------------------------------------|
| <b>Code</b> : 00333505            | <b>Date of issue/Date of revision</b> : 2 September 2025 |
| <b>ABC#3 RED 283S5772 AF-NAVY</b> |                                                          |

## SECTION 5: Firefighting measures

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

|                                   |                                                          |
|-----------------------------------|----------------------------------------------------------|
| <b>Code</b> : 00333505            | <b>Date of issue/Date of revision</b> : 2 September 2025 |
| <b>ABC#3 RED 283S5772 AF-NAVY</b> |                                                          |

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

|                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Protective measures</b>                    | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| <b>Advice on general occupational hygiene</b> | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

**7.2 Conditions for safe storage, including any incompatibilities**

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**7.3 Specific end use(s)**

See Section 1.2 for Identified uses.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

| Product/ingredient name                                                                           | Exposure limit values                                                                                                                                                                          |
|---------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  dicopper oxide | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [Copper and compounds]</b><br>STEL 15 minutes: 2 mg/m³ (as Cu). Form: Dusts and Mists.<br>TWA 8 hours: 1 mg/m³ (as Cu). Form: Dusts and Mists. |
| butan-1-ol                                                                                        | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.</b><br>STEL 15 minutes: 154 mg/m³.<br>STEL 15 minutes: 50 ppm.                                                          |
| rosin                                                                                             | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) Inhalation sensitiser.</b><br>STEL 15 minutes: 0.15 mg/m³. Form: Fume.<br>TWA 8 hours: 0.05 mg/m³. Form: Fume.                                 |
| xylene                                                                                            | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers] Absorbed through skin.</b><br>STEL 15 minutes: 441 mg/m³.                                                  |

Code : 00333505

Date of issue/Date of revision

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

**SECTION 8: Exposure controls/personal protection**

|                 |                                                                                                                                                                                                                                                                                            |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| n-butyl acetate | TWA 8 hours: 50 ppm.<br>TWA 8 hours: 220 mg/m <sup>3</sup> .<br>STEL 15 minutes: 100 ppm.<br><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b><br>STEL 15 minutes: 966 mg/m <sup>3</sup> .<br>STEL 15 minutes: 200 ppm.<br>TWA 8 hours: 724 mg/m <sup>3</sup> .<br>TWA 8 hours: 150 ppm. |
| methanol        | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin.<br>STEL 15 minutes: 333 mg/m <sup>3</sup> .<br>STEL 15 minutes: 250 ppm.<br>TWA 8 hours: 266 mg/m <sup>3</sup> .<br>TWA 8 hours: 200 ppm.                                                                       |

**Biological exposure indices**

| Product/ingredient name | Exposure indices                                                                                                                                                                           |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xylene                  | <b>EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers]</b><br>BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine].<br>Sampling time: post shift. |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name             | Type | Exposure              | Value                    | Population         | Effects  |
|-------------------------------------|------|-----------------------|--------------------------|--------------------|----------|
| dicopper oxide                      | DNEL | Long term Inhalation  | 1 mg/m <sup>3</sup>      | Workers            | Local    |
|                                     | DNEL | Long term Inhalation  | 1 mg/m <sup>3</sup>      | Workers            | Systemic |
|                                     | DNEL | Long term Dermal      | 137 mg/kg bw/day         | Workers            | Systemic |
|                                     | DNEL | Long term Oral        | 0.041 mg/kg bw/day       | General population | Systemic |
|                                     | DNEL | Short term Oral       | 0.082 mg/kg bw/day       | General population | Systemic |
| butan-1-ol                          | DNEL | Long term Oral        | 1.5625 mg/kg bw/day      | General population | Systemic |
|                                     | DNEL | Long term Dermal      | 3.125 mg/kg bw/day       | General population | Systemic |
|                                     | DNEL | Long term Inhalation  | 55.357 mg/m <sup>3</sup> | General population | Systemic |
|                                     | DNEL | Long term Inhalation  | 155 mg/m <sup>3</sup>    | General population | Local    |
|                                     | DNEL | Long term Inhalation  | 310 mg/m <sup>3</sup>    | Workers            | Local    |
| xylene                              | DNEL | Long term Oral        | 5 mg/kg bw/day           | General population | Systemic |
|                                     | DNEL | Long term Inhalation  | 65.3 mg/m <sup>3</sup>   | General population | Local    |
|                                     | DNEL | Long term Inhalation  | 65.3 mg/m <sup>3</sup>   | General population | Systemic |
|                                     | DNEL | Long term Dermal      | 125 mg/kg bw/day         | General population | Systemic |
|                                     | DNEL | Long term Dermal      | 212 mg/kg bw/day         | Workers            | Systemic |
|                                     | DNEL | Long term Inhalation  | 221 mg/m <sup>3</sup>    | Workers            | Local    |
|                                     | DNEL | Long term Inhalation  | 221 mg/m <sup>3</sup>    | Workers            | Systemic |
|                                     | DNEL | Short term Inhalation | 260 mg/m <sup>3</sup>    | General population | Local    |
|                                     | DNEL | Short term Inhalation | 260 mg/m <sup>3</sup>    | General population | Systemic |
|                                     | DNEL | Short term Inhalation | 442 mg/m <sup>3</sup>    | Workers            | Local    |
| N-ethyl-o(or p)-toluenesulphonamide | DNEL | Short term Inhalation | 442 mg/m <sup>3</sup>    | Workers            | Systemic |
|                                     | DNEL | Long term Oral        | 1.6 mg/kg bw/day         | General population | Systemic |
|                                     | DNEL | Long term Inhalation  | 5.65 mg/m <sup>3</sup>   | General population | Systemic |
|                                     | DNEL | Long term Dermal      | 8.1 mg/kg bw/day         | General population | Systemic |
|                                     | DNEL | Long term Dermal      | 13.5 mg/kg bw/day        | Workers            | Systemic |
| copper(II) oxide                    | DNEL | Long term Inhalation  | 19.1 mg/m <sup>3</sup>   | Workers            | Systemic |
|                                     | DNEL | Long term Inhalation  | 1 mg/m <sup>3</sup>      | Workers            | Local    |

|                            |            |                                |                    |
|----------------------------|------------|--------------------------------|--------------------|
| Code                       | : 00333505 | Date of issue/Date of revision | : 2 September 2025 |
| ABC#3 RED 283S5772 AF-NAVY |            |                                |                    |

SECTION 8: Exposure controls/personal protection

|                 |      |                       |                    |                    |          |
|-----------------|------|-----------------------|--------------------|--------------------|----------|
| n-butyl acetate | DNEL | Long term Inhalation  | 1 mg/m³            | Workers            | Systemic |
|                 | DNEL | Long term Dermal      | 137 mg/kg bw/day   | Workers            | Systemic |
|                 | DNEL | Long term Oral        | 0.041 mg/kg bw/day | General population | Systemic |
|                 | DNEL | Short term Oral       | 0.082 mg/kg bw/day | General population | Systemic |
|                 | DNEL | Long term Inhalation  | 300 mg/m³          | Workers            | Systemic |
|                 | DNEL | Long term Dermal      | 11 mg/m³           | Workers            | Systemic |
|                 | DNEL | Long term Oral        | 2 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Short term Oral       | 2 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Long term Dermal      | 3.4 mg/kg bw/day   | General population | Systemic |
|                 | DNEL | Short term Dermal     | 6 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Long term Dermal      | 7 mg/kg bw/day     | Workers            | Systemic |
|                 | DNEL | Short term Dermal     | 11 mg/kg bw/day    | Workers            | Systemic |
|                 | DNEL | Long term Inhalation  | 12 mg/m³           | General population | Systemic |
|                 | DNEL | Long term Inhalation  | 35.7 mg/m³         | General population | Local    |
|                 | DNEL | Long term Inhalation  | 48 mg/m³           | Workers            | Systemic |
| copper          | DNEL | Short term Inhalation | 300 mg/m³          | General population | Local    |
|                 | DNEL | Short term Inhalation | 300 mg/m³          | General population | Systemic |
|                 | DNEL | Long term Inhalation  | 300 mg/m³          | Workers            | Local    |
|                 | DNEL | Short term Inhalation | 600 mg/m³          | Workers            | Local    |
| methanol        | DNEL | Short term Inhalation | 600 mg/m³          | Workers            | Systemic |
|                 | DNEL | Long term Dermal      | 137 mg/kg bw/day   | General population | Systemic |
|                 | DNEL | Long term Dermal      | 137 mg/kg bw/day   | Workers            | Systemic |
|                 | DNEL | Short term Dermal     | 273 mg/kg bw/day   | General population | Systemic |
|                 | DNEL | Short term Dermal     | 273 mg/kg bw/day   | Workers            | Systemic |
|                 | DNEL | Short term Oral       | 4 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Long term Oral        | 4 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Short term Dermal     | 4 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Long term Dermal      | 4 mg/kg bw/day     | General population | Systemic |
|                 | DNEL | Short term Dermal     | 20 mg/kg bw/day    | Workers            | Systemic |
|                 | DNEL | Long term Dermal      | 20 mg/kg bw/day    | Workers            | Systemic |
|                 | DNEL | Short term Inhalation | 26 mg/m³           | General population | Local    |
|                 | DNEL | Long term Inhalation  | 26 mg/m³           | General population | Local    |
|                 | DNEL | Short term Inhalation | 26 mg/m³           | General population | Systemic |
|                 | DNEL | Long term Inhalation  | 26 mg/m³           | General population | Systemic |
|                 | DNEL | Short term Inhalation | 130 mg/m³          | Workers            | Local    |
|                 | DNEL | Long term Inhalation  | 130 mg/m³          | Workers            | Local    |
|                 | DNEL | Short term Inhalation | 130 mg/m³          | Workers            | Systemic |
|                 | DNEL | Long term Inhalation  | 130 mg/m³          | Workers            | Systemic |

PNECs

| Product/ingredient name | Compartment Detail     | Value          | Method Detail            |
|-------------------------|------------------------|----------------|--------------------------|
| copper oxide            | Fresh water            | 0.0078 mg/l    | -                        |
|                         | Fresh water sediment   | 87.1 mg/kg dwt | -                        |
|                         | Marine water           | 0.0056 mg/l    | -                        |
|                         | Marine water sediment  | 676 mg/kg dwt  | -                        |
|                         | Soil                   | 64.6 mg/kg dwt | -                        |
|                         | Sewage Treatment Plant | 0.23 mg/l      | -                        |
| zinc oxide              | Fresh water            | 20.6 µg/l      | Sensitivity Distribution |
|                         | Marine water           | 6.1 µg/l       | Sensitivity Distribution |
|                         | Fresh water sediment   | 117 mg/kg dwt  | Sensitivity Distribution |
|                         | Sewage Treatment Plant | 52 µg/l        | Assessment Factors       |
|                         | Marine water sediment  | 56.5 mg/kg dwt | Assessment Factors       |
|                         | Soil                   | 35.6 mg/kg dwt | Sensitivity Distribution |
| butan-1-ol              | Fresh water            | 0.082 mg/l     | -                        |
|                         | Marine water           | 0.0082 mg/l    | -                        |
|                         | Fresh water sediment   | 0.178 mg/kg    | -                        |
|                         | Marine water sediment  | 0.0178 mg/kg   | -                        |
|                         | Soil                   | 0.015 mg/kg    | -                        |
|                         | Sewage Treatment Plant | 2476 mg/l      | -                        |
| rosin                   | Fresh water            | 0.002 mg/l     | Assessment Factors       |
|                         | Marine water           | 0 mg/l         | Assessment Factors       |
|                         | Sewage Treatment Plant | 1000 mg/l      | Assessment Factors       |

Code : 00333505

Date of issue/Date of revision

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

**SECTION 8: Exposure controls/personal protection**

|                 |                        |                 |                          |
|-----------------|------------------------|-----------------|--------------------------|
| xylene          | Fresh water sediment   | 0.007 mg/kg dwt | Equilibrium Partitioning |
|                 | Marine water sediment  | 0.001 mg/kg dwt | Equilibrium Partitioning |
|                 | Soil                   | 0 mg/kg dwt     | Equilibrium Partitioning |
|                 | Fresh water            | 0.327 mg/l      | -                        |
|                 | Marine water           | 0.327 mg/l      | -                        |
| n-butyl acetate | Sewage Treatment Plant | 6.58 mg/l       | -                        |
|                 | Fresh water sediment   | 12.46 mg/kg dwt | -                        |
|                 | Marine water sediment  | 12.46 mg/kg dwt | -                        |
|                 | Soil                   | 2.31 mg/kg      | -                        |
|                 | Fresh water            | 0.18 mg/l       | -                        |
| methanol        | Marine water           | 0.018 mg/l      | -                        |
|                 | Fresh water sediment   | 0.981 mg/kg     | -                        |
|                 | Marine water sediment  | 0.0981 mg/kg    | -                        |
|                 | Sewage Treatment Plant | 35.6 mg/l       | -                        |
|                 | Soil                   | 0.0903 mg/kg    | -                        |
|                 | Fresh water            | 20.8 mg/l       | Assessment Factors       |
|                 | Marine water           | 2.08 mg/l       | Assessment Factors       |
|                 | Sewage Treatment Plant | 100 mg/l        | Assessment Factors       |
|                 | Fresh water sediment   | 77 mg/kg        | Equilibrium Partitioning |
|                 | Marine water sediment  | 7.7 mg/kg       | Equilibrium Partitioning |
|                 | Soil                   | 100 mg/kg       | Assessment Factors       |

**8.2 Exposure controls****Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures****Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection**

: Chemical splash goggles and face shield.

**Skin protection****Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

butyl rubber

**Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection**

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code : 00333505

Date of issue/Date of revision

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

**SECTION 8: Exposure controls/personal protection**

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties**Appearance

- Physical state** : Liquid.
- Colour** : Red.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- Melting point/freezing point** :
- Initial boiling point and boiling range** : >37.78°C (>100°F)
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Not available.
- Flash point** : Closed cup: 28.33°C (83°F)
- Auto-ignition temperature** :

| Ingredient name | °C  | °F  | Method  |
|-----------------|-----|-----|---------|
| butan-1-ol      | 355 | 671 | EU A.15 |

- pH** : Not applicable.
- Viscosity** : Not applicable. insoluble in water.
- Solubility(ies)** : ☒ Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm²/s

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Solubility in water** : 1.4 g/l
- Miscible with water** : No.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** : 1.3 kPa (10 mm Hg)
- Evaporation rate** : 0.63 (butyl acetate = 1)
- Relative density** : 2.04
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.
- Particle characteristics**
- Median particle size** : Not applicable.

|                            |            |                                |                    |
|----------------------------|------------|--------------------------------|--------------------|
| Code                       | : 00333505 | Date of issue/Date of revision | : 2 September 2025 |
| ABC#3 RED 283S5772 AF-NAVY |            |                                |                    |

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:  
oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following  
materials: carbon oxides nitrogen oxides sulfur oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name             | Result                          | Species | Dose         | Exposure |
|-------------------------------------|---------------------------------|---------|--------------|----------|
| dicopper oxide                      | LC50 Inhalation Dusts and mists | Rat     | 3.34 mg/l    | 4 hours  |
|                                     | LD50 Dermal                     | Rat     | >2000 mg/kg  | -        |
|                                     | LD50 Oral                       | Rat     | 500 mg/kg    | -        |
| zinc oxide                          | LC50 Inhalation Dusts and mists | Rat     | >5700 mg/m³  | 4 hours  |
|                                     | LD50 Dermal                     | Rat     | >2000 mg/kg  | -        |
|                                     | LD50 Oral                       | Rat     | >5000 mg/kg  | -        |
| butan-1-ol                          | LC50 Inhalation Vapour          | Rat     | 24000 mg/m³  | 4 hours  |
|                                     | LD50 Dermal                     | Rabbit  | 3400 mg/kg   | -        |
|                                     | LD50 Oral                       | Rat     | 790 mg/kg    | -        |
| rosin                               | LD50 Dermal                     | Rat     | >2000 mg/kg  | -        |
|                                     | LD50 Oral                       | Rat     | 7600 mg/kg   | -        |
| xylene                              | LD50 Dermal                     | Rabbit  | 1.7 g/kg     | -        |
|                                     | LD50 Oral                       | Rat     | 4.3 g/kg     | -        |
| N-ethyl-o(or p)-toluenesulphonamide | LD50 Oral                       | Rat     | 2250 mg/kg   | -        |
| copper(II) oxide                    | LD50 Oral                       | Rat     | >2000 mg/kg  | -        |
|                                     | LC50 Inhalation Vapour          | Rat     | >21.1 mg/l   | 4 hours  |
|                                     | LC50 Inhalation Vapour          | Rat     | 2000 ppm     | 4 hours  |
| n-butyl acetate                     | LD50 Dermal                     | Rabbit  | >17600 mg/kg | -        |
|                                     | LD50 Oral                       | Rat     | 10.768 g/kg  | -        |
|                                     | LC50 Inhalation Dusts and mists | Rat     | >5.11 mg/l   | 4 hours  |
| copper                              |                                 |         |              |          |
| methanol                            | LC50 Inhalation Vapour          | Rat     | 64000 ppm    | 4 hours  |
|                                     | LD50 Dermal                     | Rabbit  | 15800 mg/kg  | -        |
|                                     | LD50 Oral                       | Rat     | 5600 mg/kg   | -        |

- Conclusion/Summary : There are no data available on the mixture itself.
- Acute toxicity estimates

Code : 00333505

Date of issue/Date of revision

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

**SECTION 11: Toxicological information**

| Product/ingredient name             | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| ABC#3 RED 283S5772 AF-NAVY          | 901.6        | 19918.3        | N/A                      | 137.6                       | 7.0                                 |
| dicopper oxide                      | 500          | N/A            | N/A                      | N/A                         | 3.34                                |
| butan-1-ol                          | 790          | 3400           | N/A                      | 24                          | N/A                                 |
| rosin                               | 7600         | N/A            | N/A                      | N/A                         | N/A                                 |
| xylene                              | 4300         | 1700           | N/A                      | 11                          | N/A                                 |
| N-ethyl-o(or p)-toluenesulphonamide | 2250         | N/A            | N/A                      | N/A                         | N/A                                 |
| n-butyl acetate                     | 10768        | N/A            | N/A                      | N/A                         | N/A                                 |
| methanol                            | 100          | 300            | 64000                    | 3                           | N/A                                 |

**Irritation/Corrosion**

| Product/ingredient name | Result                                            | Species          | Score  | Exposure             | Observation |
|-------------------------|---------------------------------------------------|------------------|--------|----------------------|-------------|
| butan-1-ol<br>xylene    | Eyes - Cornea opacity<br>Skin - Moderate irritant | Rabbit<br>Rabbit | 4<br>- | -<br>24 hours 500 mg | -<br>-      |

**Conclusion/Summary** : Not available.**Skin** : There are no data available on the mixture itself.**Eyes** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Sensitisation****Conclusion/Summary****Skin** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Mutagenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Carcinogenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Reproductive toxicity****Conclusion/Summary** : There are no data available on the mixture itself.**Teratogenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Specific target organ toxicity (single exposure)**

| Product/ingredient name             | Category   | Route of exposure | Target organs                |
|-------------------------------------|------------|-------------------|------------------------------|
| butan-1-ol                          | Category 3 | -                 | Respiratory tract irritation |
| -                                   | Category 3 | -                 | Narcotic effects             |
| xylene                              | Category 3 | -                 | Respiratory tract irritation |
| N-ethyl-o(or p)-toluenesulphonamide | Category 3 | -                 | Narcotic effects             |
| n-butyl acetate                     | Category 3 | -                 | Narcotic effects             |
| methanol                            | Category 1 | -                 | -                            |

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |

**Code : 00333505****Date of issue/Date of revision****: 2 September 2025****ABC#3 RED 283S5772 AF-NAVY****SECTION 11: Toxicological information****Information on likely routes of exposure** : Not available.**Potential acute health effects**

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

**Long term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

**Potential chronic health effects**

Not available.

- Conclusion/Summary** : Not available.
- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.**SECTION 12: Ecological information****12.1 Toxicity**

Code : 00333505

Date of issue/Date of revision

: 2 September 2025

ABC#3 RED 283S5772 AF-NAVY

**SECTION 12: Ecological information**

| Product/ingredient name                               | Result                                                                             | Species                                                                                                    | Exposure                                    |
|-------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| nickel<br>copper oxide<br>zinc oxide                  | LC50 0.003 mg/l<br>Acute EC50 0.17 mg/l<br>Acute EC50 0.481 mg/l Fresh water       | Fish<br>Algae<br>Daphnia - Water flea - <i>Daphnia magna</i> - Neonate                                     | 96 hours<br>72 hours<br>48 hours            |
| butan-1-ol<br>N-ethyl-o(or p)-<br>toluenesulphonamide | Chronic NOEC 0.017 mg/l Fresh water<br>Acute LC50 1376 mg/l<br>EC50 >1000 mg/l     | Algae<br>Fish<br>Daphnia - <i>Daphnia magna</i>                                                            | 72 hours<br>96 hours<br>48 hours            |
| n-butyl acetate<br>copper                             | LC50 130 mg/l<br>Acute LC50 18 mg/l<br>Acute LC50 810 ppb<br>Chronic EC10 8.1 µg/l | Fish - <i>Lepomis macrochirus</i><br>Fish<br>Fish<br>Daphnia - Water flea - <i>Daphnia magna</i> - Neonate | 96 hours<br>96 hours<br>96 hours<br>21 days |
| methanol                                              | Acute LC50 13 mg/l Fresh water                                                     | Fish - Trout                                                                                               | 96 hours                                    |

**Conclusion/Summary** : Not available.**12.2 Persistence and degradability**

| Product/ingredient name | Test               | Result                   | Dose | Inoculum |
|-------------------------|--------------------|--------------------------|------|----------|
| n-butyl acetate         | TEPA and OECD 301D | 83 % - Readily - 28 days | -    | -        |

**Conclusion/Summary** : Not available.

| Product/ingredient name   | Aquatic half-life | Photolysis | Biodegradability   |
|---------------------------|-------------------|------------|--------------------|
| xylene<br>n-butyl acetate | -<br>-            | -<br>-     | Readily<br>Readily |

**12.3 Bioaccumulative potential**

| Product/ingredient name                 | LogP <sub>ow</sub> | BCF         | Potential |
|-----------------------------------------|--------------------|-------------|-----------|
| butan-1-ol                              | 1                  | -           | Low       |
| rosin                                   | 1.9 to 7.7         | -           | High      |
| xylene                                  | 3.12               | 7.4 to 18.5 | Low       |
| N-ethyl-o(or p)-<br>toluenesulphonamide | 1.87               | -           | Low       |
| n-butyl acetate                         | 2.3                | -           | Low       |
| methanol                                | -0.77              | -           | Low       |

**12.4 Mobility in soil****Soil/water partition coefficient** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**Code : 00333505****Date of issue/Date of revision****: 2 September 2025****ABC#3 RED 283S5772 AF-NAVY****SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste****Waste catalogue**

| Waste code | Waste designation              |
|------------|--------------------------------|
| 08 01 99   | wastes not otherwise specified |

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue          |
|-------------------|--------------------------|
| Container         | 15 01 06 mixed packaging |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

|                                        | ADR/RID         | ADN             | IMDG             | IATA                                                               |
|----------------------------------------|-----------------|-----------------|------------------|--------------------------------------------------------------------|
| <b>14.1 UN number</b>                  | UN1263          | UN1263          | UN1263           | UN1263                                                             |
| <b>14.2 UN proper shipping name</b>    | PAINT           | PAINT           | PAINT            | PAINT                                                              |
| <b>14.3 Transport hazard class(es)</b> | 3               | 3               | 3                | 3                                                                  |
| <b>14.4 Packing group</b>              | III             | III             | III              | III                                                                |
| <b>14.5 Environmental hazards</b>      | Yes.            | Yes.            | Yes.             | Yes. The environmentally hazardous substance mark is not required. |
| <b>Marine pollutant substances</b>     | Not applicable. | Not applicable. | (dicopper oxide) | Not applicable.                                                    |

**Additional information**

**ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**Tunnel code** : (D/E)

**ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

|                            |            |                                |                    |
|----------------------------|------------|--------------------------------|--------------------|
| Code                       | : 00333505 | Date of issue/Date of revision | : 2 September 2025 |
| ABC#3 RED 283S5772 AF-NAVY |            |                                |                    |

SECTION 14: Transport information

|      |                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------|
| IMDG | : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.                    |
| IATA | : The environmentally hazardous substance mark may appear if required by other transportation regulations. |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Explosive precursors** : Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name                                                                                                    | Entry Number (REACH) |
|----------------------------------------------------------------------------------------------------------------------------|----------------------|
|  ABC#3 RED 283S5772 AF-NAVY<br>methanol | 3<br>69              |

**Labelling** : Not applicable.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category                                                                                     |
|----------------------------------------------------------------------------------------------|
|  5c<br>E1 |

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = GB CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

**Code** : 00333505**Date of issue/Date of revision**

: 2 September 2025

**ABC#3 RED 283S5772 AF-NAVY****SECTION 16: Other information**

| Classification                                                                                                                                                | Justification                                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

**Full text of abbreviated H statements**

|        |                                                       |
|--------|-------------------------------------------------------|
| H225   | Highly flammable liquid and vapour.                   |
| H226   | Flammable liquid and vapour.                          |
| H301   | Toxic if swallowed.                                   |
| H302   | Harmful if swallowed.                                 |
| H304   | May be fatal if swallowed and enters airways.         |
| H311   | Toxic in contact with skin.                           |
| H312   | Harmful in contact with skin.                         |
| H315   | Causes skin irritation.                               |
| H317   | May cause an allergic skin reaction.                  |
| H318   | Causes serious eye damage.                            |
| H319   | Causes serious eye irritation.                        |
| H331   | Toxic if inhaled.                                     |
| H332   | Harmful if inhaled.                                   |
| H335   | May cause respiratory irritation.                     |
| H336   | May cause drowsiness or dizziness.                    |
| H370   | Causes damage to organs.                              |
| H400   | Very toxic to aquatic life.                           |
| H410   | Very toxic to aquatic life with long lasting effects. |
| H412   | Harmful to aquatic life with long lasting effects.    |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

**Full text of classifications**

|                   |                                                               |
|-------------------|---------------------------------------------------------------|
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                   |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                   |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1               |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3               |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                        |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                               |
| STOT SE 1         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

**History****Date of issue/ Date of revision** : 2 September 2025**Date of previous issue** : 20 December 2023**Prepared by** : EHS**Version** : 1.02**Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.