

SAFETY DATA SHEET



Date of issue/Date of revision

: 29 September 2025

Version

: 1.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : AMERSHIELD BASE (TINTED)
Product code : 00296492
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier
+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture
Classification according to UK CLP/GHS
Flam. Liq. 3, H226
Skin Sens. 1, H317
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.
See Section 16 for the full text of the H statements declared above.
See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Flammable liquid and vapour.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Code	: 00296492	Date of issue/Date of revision	: 29 September 2025
AMERSHIELD BASE (TINTED)			

SECTION 2: Hazards identification

Prevention	: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapour.
Response	: Take off contaminated clothing and wash it before reuse.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P210, P273, P261, P362 + P364, P501
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Type
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - ≤17	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥5.0 - <10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≥0.10 - ≤2.1	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3,	[1] [2]

English (GB)

United Kingdom (UK)

2/19

Code : 00296492

Date of issue/Date of revision

: 29 September 2025

AMERSHIELD BASE (TINTED)

SECTION 3: Composition/information on ingredients

reaction mass of N, N'-ethane-1,2-diylbis(hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl]octadecanamide and N, N'-ethane-1,2-diylbis(12-hydroxyoctadecanamide)	REACH #: 01-0000017860-69 EC: 432-430-3 CAS: SUB102035 Index: 616-200-00-1	≥1.0 - ≤5.0	H412 Aquatic Chronic 4, H413	[1]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤1.0	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
1,2,3,4-tetrahydronaphthalene	EC: 204-340-2 CAS: 119-64-2	<1.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH019	[1]
Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119978273-29 EC: 288-306-2 CAS: 85711-46-2	≤0.30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	[1]
2-butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.30	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.30	Repr. 2, H361fd	[1]
2-hydroxyethyl methacrylate	EC: 212-782-2 CAS: 868-77-9 Index: 607-124-00-X	≤0.30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.10	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071	[1] [2]
See Section 16 for the full text of the H statements declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

Code : 00296492	Date of issue/Date of revision : 29 September 2025
AMERSHIELD BASE (TINTED)	

SECTION 3: Composition/information on ingredients

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-----------------------------------|---|
| Eye contact | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- | | |
|---------------------|--|
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |

Over-exposure signs/symptoms

- | | |
|---------------------|---|
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following:
irritation
redness
dryness
cracking |
| Ingestion | : No specific data. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|----------------------------|---|
| Notes to physician | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|---------------------------------------|--|
| Suitable extinguishing media | : Use dry chemical, CO ₂ , water spray (fog) or foam. |
| Unsuitable extinguishing media | : Do not use water jet. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--|--|
| Hazards from the substance or mixture | : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
|--|--|

Code : 00296492	Date of issue/Date of revision : 29 September 2025
AMERSHIELD BASE (TINTED)	

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
sulfur oxides
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Code	: 00296492	Date of issue/Date of revision	: 29 September 2025
AMERSHIELD BASE (TINTED)			

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
 n-butyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 966 mg/m³. STEL 15 minutes: 200 ppm. TWA 8 hours: 724 mg/m³. TWA 8 hours: 150 ppm.
xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m³. STEL 15 minutes: 100 ppm.
2-methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 548 mg/m³. TWA 8 hours: 50 ppm.

ethylbenzene	TWA 8 hours: 274 mg/m³. STEL 15 minutes: 100 ppm. EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 552 mg/m³. STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m³.
2-butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m³. TWA 8 hours: 123 mg/m³.
maleic anhydride	EH40/2005 WELs (United Kingdom (UK), 1/2020) Inhalation sensitiser. STEL 15 minutes: 3 mg/m³. TWA 8 hours: 1 mg/m³.

Product/ingredient name	Exposure indices
xylene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.
2-butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

DNELs/DMELs					
Product/ingredient name	Type	Exposure	Value	Population	Effects
n-butyl acetate	DNEL	Long term Inhalation	300 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	11 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	35.7 mg/m ³	General population	Local
	DNEL	Long term Inhalation	48 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	300 mg/m ³	General population	Local
	DNEL	Short term Inhalation	300 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	300 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	600 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	600 mg/m ³	Workers	Systemic
xylene	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic

Code : 00296492

Date of issue/Date of revision

: 29 September 2025

AMERSHIELD BASE (TINTED)

SECTION 8: Exposure controls/personal protection

2-methoxy-1-methylethyl acetate	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m ³	General population	Local
	DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	33 mg/m ³	General population	Local
ethylbenzene	DNEL	Long term Inhalation	33 mg/m ³	General population	Systemic
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	275 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	320 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	550 mg/m ³	Workers	Local
	DNEL	Long term Dermal	796 mg/kg bw/day	Workers	Systemic
	DMEL	Long term Inhalation	442 mg/m ³	Workers	Local
	DMEL	Short term Inhalation	884 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	15 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
reaction mass of N, N'-ethane1,2-diylbis (hexanamide) and 12-hydroxy-N-[2-[(1-oxylhexyl) amino]ethyl]octadecanamide and N, N'-ethane-1,2-diylbis (12-hydroxyoctadecan amide)	DNEL	Long term Inhalation	293 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	35.24 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	10 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	10 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	35.24 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	0.167 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.835 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.65 mg/m ³	Workers	Local
1,2,3,4-tetrahydronaphthalene	DNEL	Long term Inhalation	1.65 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	8.25 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	8.25 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
Fatty acids, C14-18 and C16-18-unsatd., maleated	DNEL	Long term Dermal	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m ³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	0.34 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.34 mg/kg bw/day	General population	Systemic
2-butoxyethanol	DNEL	Long term Inhalation	0.58 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.94 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.3 mg/m ³	Workers	Systemic
propylidynetrimethanol	DNEL	Long term Inhalation	3.3 mg/m ³	Workers	Systemic

2-hydroxyethyl methacrylate	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.39 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.45 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.9 mg/m ³	Workers	Systemic
maleic anhydride	DNEL	Long term Inhalation	0.4 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.4 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.05 mg/m ³	General population	Systemic
	DNEL	Long term Oral	0.06 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.08 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.081 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.081 mg/m ³	Workers	Systemic
	DNEL	Short term Oral	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	0.2 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.2 mg/m ³	Workers	Systemic

Product/ingredient name	Compartment Detail	Value	Method Detail
n-butyl acetate	Fresh water	0.18 mg/l	-
	Marine water	0.018 mg/l	-
	Fresh water sediment	0.981 mg/kg	-
	Marine water sediment	0.0981 mg/kg	-
	Sewage Treatment Plant	35.6 mg/l	-
	Soil	0.0903 mg/kg	-
xylene	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Fresh water sediment	12.46 mg/kg dwt	-
	Marine water sediment	12.46 mg/kg dwt	-
	Soil	2.31 mg/kg	-
2-methoxy-1-methylethyl acetate	Fresh water	0.635 mg/l	-
	Marine water	0.0635 mg/l	-
	Fresh water sediment	3.29 mg/kg	-
	Marine water sediment	0.329 mg/kg	-
	Soil	0.29 mg/kg	-
	Sewage Treatment Plant	100 mg/l	-
ethylbenzene	Fresh water	0.1 mg/l	Assessment Factors
	Marine water	0.01 mg/l	Assessment Factors
	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
	Secondary Poisoning	20 mg/kg	-
	Fresh water	0.009 mg/l	-
reaction mass of N, N'-ethane1,2-diylbis (hexanamide) and 12-hydroxy-N-[2-(1-oxyhexyl)amino]ethyl]octadecanamide and N, N'-ethane-1,2-diylbis(12-hydroxyoctadecanamide)	Marine water	0.001 mg/l	-
	Sewage Treatment Plant	100 mg/l	-
	Fresh water sediment	384 mg/kg dwt	-
	Marine water sediment	38.4 mg/kg dwt	-
	Soil	52.1 mg/kg dwt	-
	2-butoxyethanol	Fresh water	8.8 mg/l
	Marine water	0.88 mg/l	Assessment Factors
	Fresh water sediment	34.6 mg/kg	Equilibrium Partitioning
	Marine water sediment	3.46 mg/kg	Equilibrium Partitioning
	Soil	3.13 mg/kg	Equilibrium Partitioning

Code : 00296492 **Date of issue/Date of revision** : 29 September 2025
AMERSHIELD BASE (TINTED)

SECTION 8: Exposure controls/personal protection

maleic anhydride	Sewage Treatment Plant	463 mg/l	Assessment Factors
	Fresh water	0.1 mg/l	Assessment Factors
	Marine water	0.01 mg/l	Assessment Factors
	Sewage Treatment Plant	44.6 mg/l	Assessment Factors
	Fresh water sediment	0.334 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.033 mg/kg dwt	Equilibrium Partitioning
	Soil	0.042 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code	: 00296492	Date of issue/Date of revision	: 29 September 2025
AMERSHIELD BASE (TINTED)			

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state : Liquid.
- Colour : Various
- Odour : Aromatic. [Strong]
- Odour threshold : Not available.
- Melting point/freezing point :
- Initial boiling point and boiling range : >37.78°C (>100°F)
- Flammability (solid, gas) : liquid
- Upper/lower flammability or explosive limits : Not available.
- Flash point : Closed cup: 26°C (78.8°F)
- Auto-ignition temperature :

Ingredient name	°C	°F	Method
2-methoxy-1-methylethyl acetate	333	631.4	DIN 51794

- pH : Not applicable.
- : Not applicable. insoluble in water.

- Viscosity : Dynamic (room temperature): Not available.
- : Kinematic (room temperature): >400 mm²/s
- : Kinematic (40°C): >21 mm²/s

- Solubility(ies) :

Media	Result
cold water	Not soluble

- Miscible with water : No.
- Partition coefficient: n-octanol/ water : Not applicable.
- Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-butyl acetate	11.25096	1.5	DIN EN 13016-2			

- Relative density : 1.41
- Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties : Product does not present an oxidizing hazard.
- Particle characteristics
- Median particle size : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Code : 00296492	Date of issue/Date of revision : 29 September 2025
AMERSHIELD BASE (TINTED)	
SECTION 10: Stability and reactivity	

- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:
oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following
materials: carbon oxides sulfur oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
xylene	LD50 Oral	Rat	10.768 g/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
2-methoxy-1-methylethyl acetate	LC50 Inhalation Vapour	Rat	30 mg/l	4 hours
ethylbenzene	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	6190 mg/kg	-
	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
reaction mass of N, N'-ethane-1,2-diylbis (hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl] octadecanamide and N, N'-ethane-1,2-diylbis (12-hydroxyoctadecanamide)	LD50 Oral	Rat	3.5 g/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rat	>3170 mg/kg	-
2-butoxyethanol	LD50 Oral	Rat - Male, Female	3230 mg/kg	-
	LC50 Inhalation Vapour	Rat	3 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
propylidynetrimethanol	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Dermal	Rabbit	10 g/kg	-
2-hydroxyethyl methacrylate	LD50 Oral	Rat	14000 mg/kg	-
	LD50 Dermal	Rabbit	>5 g/kg	-
maleic anhydride	LD50 Oral	Rat	5050 mg/kg	-
	LD50 Dermal	Rabbit	2620 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-

- Conclusion/Summary** : There are no data available on the mixture itself.
- Acute toxicity estimates

Code : 00296492	Date of issue/Date of revision : 29 September 2025
AMERSHIELD BASE (TINTED)	

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
AMERSHIELD BASE (TINTED)	N/A	27985.7	N/A	142.3	N/A
n-butyl acetate	10768	N/A	N/A	N/A	N/A
xylene	4300	1700	N/A	11	N/A
2-methoxy-1-methylethyl acetate	6190	N/A	N/A	30	N/A
ethylbenzene	3500	17800	N/A	17.8	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
2-butoxyethanol	1200	N/A	N/A	3	N/A
propylidynetrimethanol	14000	10000	N/A	N/A	N/A
2-hydroxyethyl methacrylate	5050	N/A	N/A	N/A	N/A
maleic anhydride	400	2620	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
2-butoxyethanol	Eyes - Irritant	Rabbit	-	24 hours	21 days
	Skin - Moderate irritant	Rabbit	-	4 hours	28 days

- Conclusion/Summary** : Not available.
- Skin** : There are no data available on the mixture itself.
- Eyes** : There are no data available on the mixture itself.
- Respiratory** : There are no data available on the mixture itself.

Sensitisation

- Conclusion/Summary**
- Skin** : There are no data available on the mixture itself.
- Respiratory** : There are no data available on the mixture itself.

Mutagenicity

- Conclusion/Summary** : There are no data available on the mixture itself.

Carcinogenicity

- Conclusion/Summary** : There are no data available on the mixture itself.

Reproductive toxicity

- Conclusion/Summary** : There are no data available on the mixture itself.

Teratogenicity

- Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-butyl acetate	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
maleic anhydride	Category 1	inhalation	respiratory system

Aspiration hazard

Code : 00296492 **Date of issue/Date of revision** : 29 September 2025
AMERSHIELD BASE (TINTED)

SECTION 11: Toxicological information

Product/ingredient name	Result
xylene ethylbenzene 1,2,3,4-tetrahydronaphthalene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.
General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Code : 00296492

Date of issue/Date of revision

: 29 September 2025

AMERSHIELD BASE (TINTED)

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
☒ butyl acetate 2-methoxy-1-methylethyl acetate ethylbenzene reaction mass of N, N'-ethane-1,2-diylbis (hexanamide) and 12-hydroxy-N-[2-[(1-oxyhexyl)amino]ethyl] octadecanamide and N, N'-ethane-1,2-diylbis (12-hydroxyoctadecanamide) Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 2-butoxyethanol propylidynetrimethanol	Acute LC50 18 mg/l Acute LC50 134 mg/l Fresh water Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water Acute LC50 >1000 mg/l EC50 1.68 mg/l LC50 0.9 mg/l Acute LC50 1474 mg/l Chronic NOEC >100 mg/l Acute LC50 >1000 mg/l	Fish Fish - Trout - <i>Oncorhynchus mykiss</i> Daphnia Daphnia - <i>Ceriodaphnia dubia</i> Fish Algae Fish Fish Fish Fish	96 hours 96 hours 48 hours - 96 hours 72 hours 96 hours 96 hours 21 days 96 hours

Conclusion/Summary : Not available.**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
☒ butyl acetate 2-methoxy-1-methylethyl acetate ethylbenzene	TEPA and OECD 301D - -	83 % - Readily - 28 days 83 % - Readily - 28 days 79 % - Readily - 10 days	- - -	- - -

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
☒ butyl acetate xylene 2-methoxy-1-methylethyl acetate ethylbenzene 2-butoxyethanol	- - - - -	- - - - -	Readily Readily Readily Readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
☒ butyl acetate xylene 2-methoxy-1-methylethyl acetate ethylbenzene 1,2,3,4-tetrahydronaphthalene 2-butoxyethanol propylidynetrimethanol 2-hydroxyethyl methacrylate maleic anhydride	2.3 3.12 1.2 3.6 3.78 0.81 -0.47 0.42 -2.78	- 7.4 to 18.5 - 79.43 162.4 to 1514 - - - -	Low Low Low Low High Low Low Low Low

Code	: 00296492	Date of issue/Date of revision	: 29 September 2025
AMERSHIELD BASE (TINTED)			
SECTION 12: Ecological information			

12.4 Mobility in soil

Soil/water partition coefficient	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	: No known significant effects or critical hazards.
----------------------------	---

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste
Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
---------------------	--

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
---------------------	---

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III

Code	: 00296492	Date of issue/Date of revision	: 29 September 2025
AMERSHIELD BASE (TINTED)			

SECTION 14: Transport information

14.5 Environmental hazards Marine pollutant substances	No. Not applicable.	Yes. Not applicable.	No. Not applicable.	No. Not applicable.
--	----------------------------	-----------------------------	----------------------------	----------------------------

Additional information				
ADR/RID	:	This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.		
Tunnel code	:	(D/E)		
ADN	:	The product is only regulated as an environmentally hazardous substance when transported in tank vessels. This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.		
IMDG	:	This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.		
IATA	:	None identified.		

14.6 Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
-----------------------------------	---	---	--	--

14.7 Transport in bulk according to IMO instruments	:	Not available.		
---	---	----------------	--	--

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
<u>UK (GB)/REACH</u>				
<u>Annex XIV - List of substances subject to authorisation</u>				
<u>Annex XIV</u>				
None of the components are listed.				
<u>Substances of very high concern</u>				
None of the components are listed.				
<u>Explosive precursors</u>		:	Not applicable.	
<u>Ozone depleting substances</u>				
Not listed.				

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	
Product/ingredient name	Entry Number (REACH)
AMERSHIELD BASE (TINTED)	3

Labelling	:	Not applicable.		
-----------	---	-----------------	--	--

Seveso Directive				
This product is controlled under the Seveso Directive.				
Danger criteria				

Category
P5c

Code : 00296492

Date of issue/Date of revision

: 29 September 2025

AMERSHIELD BASE (TINTED)

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = GB CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 Skin Sens. 1, H317 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2

Code	: 00296492	Date of issue/Date of revision	: 29 September 2025
AMERSHIELD BASE (TINTED)			

SECTION 16: Other information

Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision	: 29 September 2025
Date of previous issue	: 15 January 2025
Prepared by	: EHS
Version	: 1.05

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.