# SAFETY DATA SHEET



Date of issue/Date of revision 1 October 2025

Version 1

## **Section 1. Identification**

Product name : PPG AQUACOVER 200/400 HARDENER

Product code : O1500220698
Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Hardener.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272

**Emergency telephone** 

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number**: 888-977-4762

## Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 1B

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 72%

**GHS** label elements

Hazard pictograms :





Signal word : Danger

United States Page: 1/14

### **Product name PPG AQUACOVER 200/400 HARDENER**

## Section 2. Hazards identification

**Hazard statements** 

: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May damage fertility or the unborn child.

**Precautionary statements** 

**Prevention** 

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

: IF exposed or concerned: Get medical advice or attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Emits toxic fumes when heated.

Hazards not otherwise

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product name : PPG AQUACOVER 200/400 HARDENER

Ingredient name	Synonyms	%	CAS number
bis-[4-(2,3-epoxipropoxi)phenyl]propane	2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)]bisoxirane; Oxirane, 2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)]bis-; Bisphenol A diglycidyl ether; Bisphenol A, diglycidyl ether; Bis-[4- (2,3-epoxypropoxy)phenyl]propane; 2,2-bis[4-(2,3-epoxypropoxy)phenyl] propane; Propane, 2,2-bis(p- (2,3-epoxypropoxy)phenyl)-; diglycidyl ether of bisphenol-A; 2,2-bis (4-hydroxyphenyl) propane bis (2,3-epoxypropyl) ether; Araldite; DIPHENYLOL PROPANE DIGLYCIDYL ETHER	30 - 60	1675-54-3
bisphenol F diglycidyl ether, isomer mixture		10 - 30	Not available.
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs.; Alkyl (C12-C14) Glycidyl Ether; Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives; (C12-14) Alkylglycidyl ether;	5 - 10	68609-97-2

United States Page: 2/14

Product code O1500220698	Date of issue 1 October 20	25 Version 1	
Product name PPG AQUACOVER 200/400 HARDENER			
Section 3. Compos	ition/information on ingredients		
	Oxirane, mono((C12-14-alkyloxy)methyl) derivatives; Alkyl -C12-14-glycidyl ether; 2-[(Alkyloxy)methyl]oxirane; Oxirane 2-[ (alkyl(C12-14)oxy)methyl] derivatives; oxirane, mono[(C12-14-alkyloxy)methyl] derivs; Alkyl(C8-18) glycidyl ether; Oxirane, mono[(alkyl(C=12-14)oxy) methyl] derivs.		

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### **Description of necessary first aid measures**

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show this container or label. Keep Ingestion

person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eve contact** : Causes serious eye irritation.

: No known significant effects or critical hazards. Inhalation

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion

### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> pain or irritation watering

Inhalation : Adverse symptoms may include the following:

redness

reduced fetal weight increase in fetal deaths skeletal malformations

**United States** Page: 3/14

### **Product name PPG AQUACOVER 200/400 HARDENER**

### Section 4. First aid measures

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

rom the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon oxides

halogenated compounds

**Special protective actions** 

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

United States Page: 4/14

Product name PPG AQUACOVER 200/400 HARDENER

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special precautions** 

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

United States Page: 5/14

Date of issue 1 October 2025

Version 1

Product name PPG AQUACOVER 200/400 HARDENER

# Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name	Exposure limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane	None.
bisphenol F diglycidyl ether, isomer mixture	None.
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	None.

#### Key to abbreviations

= Acceptable Maximum Peak S = Potential skin absorption SR ACGIH = American Conference of Governmental Industrial Hygienists. = Respiratory sensitization С = Ceiling Limit SS = Skin sensitization

F = Fume STEL = Short term Exposure limit values **IPEL** = Internal Permissible Exposure Limit TD = Total dust

= Occupational Safety and Health Administration. TLV OSHA = Threshold Limit Value = Time Weighted Average TWA

= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

### Consult local authorities for acceptable exposure limits.

procedures

**Recommended monitoring**: Reference should be made to appropriate monitoring standards. Reference to national quidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Chemical splash goggles.

**United States** Page: 6/14

Product name PPG AQUACOVER 200/400 HARDENER

## Section 8. Exposure controls/personal protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

**Gloves** : butvl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

: Respirator selection must be based on known or anticipated exposure levels, the Respiratory protection

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The respiratory protection shall be in accordance to 29 CFR 1910.134.

## Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color Colorless. Odor : Amine-like.

: 8 pН

**Melting point** : Not available. : >37.78°C (>100°F) **Boiling point** 

: Closed cup: Not applicable. Flash point

**Auto-ignition temperature** : Not available. : Not available. **Decomposition temperature** : Not available. **Flammability** Lower and upper explosive

(flammable) limits

: Not available.

: Not available. Vapor pressure Vapor density Not available.

1.08 Relative density : 9.01 Density (lbs/gal)

Media Result Solubility(ies)

cold water Partially soluble

Partition coefficient: n-

octanol/water

: Not applicable.

**United States** Page: 7/14

**Product name PPG AQUACOVER 200/400 HARDENER** 

## Section 9. Physical and chemical properties

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

% Solid. (w/w) : 72

**Particle characteristics** 

Median particle size : Not applicable.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials:

carbon oxides halogenated compounds

## **Section 11. Toxicological information**

# Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Dose
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit - Dermal - LD50 Rat - Oral - LD50	23000 mg/kg 15000 mg/kg
bisphenol F diglycidyl ether, isomer mixture	Rat - Male, Female - Oral - LD50 Rat - Male, Female - Dermal - LD50	>2000 mg/kg >2000 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Rat - Oral - LD50	17100 mg/kg
	Rabbit - Dermal - LD50	>4000 mg/kg

Product Conclusion : There are no data available on the mixture itself.

### Skin corrosion/irritation

Product/ingredient name	Species	Dose	Score
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Rabbit - Skin - Erythema/ Eschar	Duration of treatment/exposure: 4 hours	Irritation score: 0.8
	Rabbit - Skin - Edema	Duration of treatment/exposure: 4 hours	Irritation score: 0.5
	Rabbit - Skin - Mild irritant	Duration of treatment/exposure: 4 hours	-

United States Page: 8/14

Date of issue 1 October 2025

Version 1

### **Product name PPG AQUACOVER 200/400 HARDENER**

## **Section 11. Toxicological information**

**Conclusion/Summary** 

There are no data available on the mixture itself.

Serious eye damage/eye irritation

Product/ingredient name	Species	Dose	Score
	the conjunctivae	Duration of treatment/exposure: 24 hours Duration of treatment/exposure: 24 hours Fully reversible in 7 days or less	Irritation score: 0.4

**Conclusion/Summary**: There are no data available on the mixture itself.

**Respiratory corrosion/irritation** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Sensitization** 

Product/ingredient name	Species	Result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Mouse - skin	Result: Sensitizing

Skin

**Conclusion/Summary** : There are no data available on the mixture itself.

Respiratory

**Conclusion/Summary**: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-epoxipropoxi)phenyl] propane	-	3	-

Carcinogen Classification

IARC: 1, 2A, 2B, 3, 4

code: NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

<u>Target organs</u>: Contains material which may cause damage to the following organs: the

reproductive system, skin, eyes.

### Information on the likely routes of exposure

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

	<b>United States</b>	Page: 9/14
--	----------------------	------------

### **Product name PPG AQUACOVER 200/400 HARDENER**

## **Section 11. Toxicological information**

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. If splashed in the eyes, the liquid

may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate: There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

**Potential immediate** : There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Conclusion/Summary : There are no data available on the mixture itself.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility or the unborn child.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

United States Page: 10/14

Date of issue 1 October 2025

Version 1

Product name PPG AQUACOVER 200/400 HARDENER

# Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PPG AQUACOVER 200/400 HARDENER bis-[4-(2,3-epoxipropoxi)phenyl]propane bisphenol F diglycidyl ether, isomer mixture oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	17369.8	11574.4	N/A	N/A	N/A
	15000	23000	N/A	N/A	N/A
	2500	2500	N/A	N/A	N/A
	17100	2500	N/A	N/A	N/A

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Chronic - NOEC	Daphnia
	0.3 mg/l [21 days]	
	Acute - LC50 - Fresh water	Daphnia - daphnia magna
	1.8 mg/l [48 hours]	
bisphenol F diglycidyl ether, isomer mixture	LC50	Fish
	2.54 mg/l [96 hours]	
	EC50	Daphnia
	>1000 mg/l [48 hours]	
	EC50	Algae
	>1.8 mg/l [72 hours]	
	NOEC	Daphnia
	0.3 mg/l [21 days]	
oxirane, mono[(C12-14-alkyloxy)methyl]	LC50	Fish
derivs.	OECD [Fish, Acute Toxicity Test]	
	>1.8 mg/l [96 hours]	
	EC50	Daphnia
	OECD [Daphnia sp. Acute	
	Immobilization Test and	
	Reproduction Test]	
	7.2 mg/l [48 hours]	
	EC50	Algae
	OECD [Alga, Growth Inhibition	
	Test]	
	844 mg/l [72 hours]	

**Conclusion/Summary** : Not available.

### Persistence and degradability

Product/ingredient name	Result
bisphenol F diglycidyl ether, isomer mixture oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	0% [28 days] - Not readily OECD [Ready Biodegradability - Manometric Respirometry Test] 87% [28 days] - Readily

**Conclusion/Summary** : Not available.

U	Inited States	Page: 11/14
---	---------------	-------------

Date of issue 1 October 2025

Version 1

**Product name PPG AQUACOVER 200/400 HARDENER** 

## **Section 12. Ecological information**

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
bisphenol F diglycidyl ether, isomer mixture oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	3.6 3.77	- 160 to 263	Low

### **Mobility in soil**

Soil/Water partition coefficient

: Not available.

## Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**United States** 

Page: 12/14

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## 14. Transport information

	DOT	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol F diglycidyl ether, isomer mixture)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane, bisphenol F diglycidyl ether, isomer mixture)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane, bisphenol F diglycidyl ether, isomer mixture)
Transport hazard class (es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.

### **Product name PPG AQUACOVER 200/400 HARDENER**

## 14. Transport information

Marine pollutant	(bisphenol F diglycidyl ether,	(bis-[4-(2,3-epoxipropoxi)	Not applicable.
substances	isomer mixture)	phenyl]propane)	

### **Additional information**

**DOT** : Non-bulk packages of this product are not regulated as hazardous materials unless transported by

inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

## **Section 15. Regulatory information**

### **United States**

**United States inventory (TSCA 8b)**: All components are active or exempted.

**SARA 302/304** 

SARA 304 RQ : Not applicable.

**Composition/information on ingredients** 

No products were found.

**SARA 311/312** 

Classification : SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 1B

### **Composition/information on ingredients**

Name	%	Classification
bis-[4-(2,3-epoxipropoxi)phenyl]	≥50 - ≤75	SKIN IRRITATION - Category 2
propane		EYE IRRITATION - Category 2A
		SKIN SENSITIZATION - Category 1B
bisphenol F diglycidyl ether,	≥10 - ≤20	SKIN IRRITATION - Category 2
isomer mixture		EYE IRRITATION - Category 2B
		SKIN SENSITIZATION - Category 1
oxirane, mono[(C12-14-alkyloxy)	≥5.0 - ≤10	SKIN IRRITATION - Category 2
methyl] derivs.		EYE IRRITATION - Category 2A
		SKIN SENSITIZATION - Category 1B
		TOXIC TO REPRODUCTION - Category 1B

United States Page: 13/14

**Product name PPG AQUACOVER 200/400 HARDENER** 

## Section 15. Regulatory information

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications. The customer is responsible for determining the PPE code for this material.

: EHS

Date of previous issue : No previous validation

Organization that prepared

the SDS

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

**UN = United Nations** 

✓ Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 14/14