

SAFETY DATA SHEET

Date of issue/Date of revision

: 3 October 2025

Version

: 1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMARINE 48 GREY 5163

Product code : 000010024376

Other means of identification

00445043; 00445044 ; 00461216

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Skin Sens. 1, H317

Repr. 1B, H360D

STOT SE 3, H336

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour.
Response	:	IF exposed or concerned: Get medical advice or attention.
Storage	:	Store in a well-ventilated place. Keep container tightly closed.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P210, P260, P308 + P313, P403 + P233, P501
Hazardous ingredients	:	naphtha (petroleum), hydrodesulphurized heavy Note P ; 2-ethylhexanoic acid and cobalt bis(2-ethylhexanoate)
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	:	Based on available data, the classification criteria are not met.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 2: Hazards identification

Other hazards which do not result in classification	: Prolonged or repeated contact may dry skin and cause irritation. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.
---	---

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
naphtha (petroleum), hydrodesulphurized heavy Note P	EC: 265-185-4 CAS: 64742-82-1 Index: 649-330-00-2	≥10 - <25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	-	[1]
Naphtha (petroleum), hydrotreated heavy Nota(s) P	EC: 265-150-3 CAS: 64742-48-9 Index: 649-327-00-6	≥10 - <20	Flam. Liq. 3, H226 Asp. Tox. 1, H304 EUH066	EUH066: C ≥ 20%	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
2-ethylhexanoic acid	REACH #: 01-2119488942-23 EC: 205-743-6 CAS: 149-57-5 Index: 607-230-00-6	≥1.0 - ≤5.0	Repr. 1B, H360D	-	[1] [2]
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 Index: 607-230-00-6	<0.30	Repr. 1B, H360D	-	[1] [2]
cobalt bis (2-ethylhexanoate)	REACH #: 01-2119524678-29 EC: 205-250-6 CAS: 136-52-7 Index: 607-230-00-6	<0.30	Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 1B, H360FD Aquatic Acute 1, H400 Aquatic Chronic 3, H412	M [Acute] = 1	[1] [2]
calcium bis (2-ethylhexanoate)	REACH #: 01-2119978297-19 EC: 205-249-0 CAS: 136-51-6 Index: 607-230-00-6	<0.30	Eye Dam. 1, H318 Repr. 1B, H360D See Section 16 for the full text of the H statements declared above.	-	[1]

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations

Code : 000010024376

Date of issue/Date of revision

: 3 October 2025

SIGMARINE 48 GREY 5163

SECTION 4: First aid measures

Skin contact : Adverse symptoms may include the following:

irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides
Formaldehyde.

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 7: Handling and storage

Advice on general occupational hygiene	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.
2-ethylhexanoic acid	ACGIH TLV (United States, 1/2024) TWA 8 hours: 5 mg/m³. Form: Inhalable fraction and vapor.
2-ethylhexanoic acid, zirconium salt	ACGIH TLV (United States, 1/2024) [Zirconium and compounds] A4. TWA 8 hours: 5 mg/m³ (as Zr). STEL 15 minutes: 10 mg/m³ (as Zr).
cobalt bis(2-ethylhexanoate)	ACGIH TLV (United States, 1/2024) [cobalt and inorganic compounds] A3. Skin sensitiser , Inhalation sensitiser. TWA 8 hours: 0.02 mg/m³ (as Co).

Code : 000010024376

Date of issue/Date of revision

: 3 October 2025

SIGMARINE 48 GREY 5163

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
naphtha (petroleum), hydrodesulphurized heavy Note P	DNEL - Workers - Long term - Inhalation	<i>Systemic</i> 1286 mg/m ³
	DNEL - General population - Long term - Inhalation	<i>Systemic</i> 0.41 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Systemic</i> 1.9 mg/m ³
	DNEL - General population - Long term - Inhalation	<i>Local</i> 178.57 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Local</i> 640 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Local</i> 837.5 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Local</i> 1066.67 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 570 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Systemic</i> 570 mg/m ³
	DNEL - General population - Long term - Dermal	<i>Systemic</i> 12 mg/kg bw/day
	DNEL - General population - Long term - Oral	<i>Systemic</i> 21 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	<i>Systemic</i> 21 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	<i>Systemic</i> 0.41 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Systemic</i> 1.9 mg/m ³
Naphtha (petroleum), hydrotreated heavy Nota(s) P	DNEL - General population - Long term - Inhalation	<i>Local</i> 178.57 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Local</i> 640 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Local</i> 837.5 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Local</i> 1066.67 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 1152 mg/m ³
	DNEL - Workers - Short term - Inhalation	<i>Systemic</i> 1286.4 mg/m ³
	DNEL - General population - Long term - Oral	<i>Systemic</i> 5 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	<i>Local</i> 65.3 mg/m ³
	DNEL - General population - Long term - Inhalation	<i>Systemic</i> 65.3 mg/m ³
	DNEL - General population - Long term - Dermal	<i>Systemic</i> 125 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	<i>Systemic</i> 212 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	<i>Local</i> 221 mg/m ³
	DNEL - Workers - Long term - Inhalation	<i>Systemic</i> 221 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Local</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
xylene	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³
	DNEL - General population - Short term - Inhalation	<i>Systemic</i> 260 mg/m ³

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 8: Exposure controls/personal protection

2-ethylhexanoic acid	DNEL - Workers - Short term - Inhalation	Local	442 mg/m³
	DNEL - Workers - Short term - Inhalation	Systemic	442 mg/m³
	DNEL - General population - Long term - Oral	Systemic	1 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic	1 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	2 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	3.5 mg/m³
2-ethylhexanoic acid, zirconium salt	DNEL - Workers - Long term - Inhalation	Systemic	14 mg/m³
	DNEL - General population - Long term - Inhalation	Systemic	0.58 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	2.351 mg/m³
	DNEL - General population - Long term - Oral	Systemic	0.167 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic	0.167 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	0.333 mg/kg bw/day
cobalt bis (2-ethylhexanoate)	DNEL - General population - Long term - Inhalation	Local	0.7 mg/m³
	DNEL - Workers - Long term - Inhalation	Local	2.82 mg/m³
	DNEL - General population - Long term - Inhalation	Local	37 µg/m³
	DNEL - General population - Long term - Oral	Systemic	175 µg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Local	235.1 µg/m³
	DNEL - General population - Long term - Oral	Systemic	0.167 mg/kg bw/day
calcium bis (2-ethylhexanoate)	DNEL - General population - Long term - Dermal	Systemic	0.167 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	0.333 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	0.58 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	2.351 mg/m³
	DNEL - General population - Long term - Inhalation	Local	0.66 mg/m³
	DNEL - Workers - Long term - Inhalation	Local	2.66 mg/m³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage Treatment Plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dw
	Marine water sediment	12.46 mg/kg dw
	Soil	2.31 mg/kg
cobalt bis(2-ethylhexanoate)	Fresh water - Sensitivity Distribution	0.6 µg/l
	Marine water - Sensitivity Distribution	2.36 µg/l
	Sewage Treatment Plant - Assessment Factors	0.37 mg/l
	Fresh water sediment - Sensitivity Distribution	9.5 mg/kg dw
	Marine water sediment - Sensitivity Distribution	9.5 mg/kg dw
	Soil - Sensitivity Distribution	10.9 mg/kg dw

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Code : 000010024376

Date of issue/Date of revision

: 3 October 2025

SIGMARINE 48 GREY 5163

SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Grey.
- Odour** : Characteristic.
- Melting point/freezing point** : Not determined.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 9: Physical and chemical properties

Boiling point or initial boiling point and boiling range	: >37.78°C																				
Flammability	: Not determined. There are no data available on the mixture itself.																				
Lower and upper explosion limit	: Not available.																				
Flash point	: Closed cup: 42°C																				
Auto-ignition temperature	:																				
<table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>naphtha (petroleum), hydrodesulphurized heavy Note P</td><td>280 to 470</td><td>536 to 878</td><td></td></tr></table>		Ingredient name	°C	°F	Method	naphtha (petroleum), hydrodesulphurized heavy Note P	280 to 470	536 to 878													
Ingredient name	°C	°F	Method																		
naphtha (petroleum), hydrodesulphurized heavy Note P	280 to 470	536 to 878																			
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).																				
pH	: Not applicable. insoluble in water.																				
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): >21 mm²/s																				
Solubility	:																				
<table><tr><th>Media</th><th>Result</th></tr><tr><td>cold water</td><td>Not soluble</td></tr></table>		Media	Result	cold water	Not soluble																
Media	Result																				
cold water	Not soluble																				
Partition coefficient n-octanol/ water (log Pow)	: Not applicable.																				
Vapour pressure	:																				
<table><tr><th rowspan="2">Ingredient name</th><th colspan="3">Vapour Pressure at 20°C</th><th colspan="3">Vapour pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>xylene</td><td>6.7</td><td>0.89</td><td></td><td></td><td></td><td></td></tr></table>		Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	xylene	6.7	0.89				
Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C																	
	mm Hg	kPa	Method	mm Hg	kPa	Method															
xylene	6.7	0.89																			
Relative density	: 1.02																				
<u>Particle characteristics</u>																					
Median particle size	: Not applicable.																				
9.2 Other information																					
9.2.1 Information with regard to physical hazard classes																					
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.																				
Oxidising properties	: Product does not present an oxidizing hazard.																				
No additional information.																					

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 10: Stability and reactivity

- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.
- Causes skin irritation.
 - May cause an allergic skin reaction.
 - May damage the unborn child.
 - May cause drowsiness or dizziness.
 - Causes damage to organs through prolonged or repeated exposure.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
naphtha (petroleum), hydrodesulphurized heavy Note P	Rat - Oral - LD50	>5000 mg/kg
	Rabbit - Dermal - LD50	>2000 mg/kg
Naphtha (petroleum), hydrotreated heavy Nota(s) P	Rat - Oral - LD50	>6 g/kg
	Rabbit - Dermal - LD50	>5000 mg/kg
xylene	Rat - Oral - LD50	4.3 g/kg
	Rabbit - Dermal - LD50	1.7 g/kg
2-ethylhexanoic acid	Rat - Oral - LD50	3640 mg/kg
	Rat - Dermal - LD50	>2000 mg/kg
2-ethylhexanoic acid, zirconium salt	Rabbit - Dermal - LD50	>5 g/kg
	Rat - Oral - LD50	>5 g/kg
	<u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity)	
cobalt bis(2-ethylhexanoate)	Rabbit - Dermal - LD50	>5 g/kg
	<u>Toxic effects:</u> Skin After topical exposure - Primary irritation	
	Rat - Oral - LD50	3129 mg/kg

Acute toxicity estimates

Route	ATE value
Dermal	103496.2 mg/kg
Inhalation (vapours)	669.68 mg/l

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

- Skin** : Causes skin irritation.
- Eyes** : Based on available data, the classification criteria are not met.
- Respiratory** : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 11: Toxicological information

Conclusion/Summary

Skin : May cause an allergic skin reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
naphtha (petroleum), hydrodesulphurized heavy Note P	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation

Conclusion/Summary :

May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
naphtha (petroleum), hydrodesulphurized heavy Note P	Category 1	-	-

Conclusion/Summary :

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Product/ingredient name	Result
naphtha (petroleum), hydrodesulphurized heavy Note P	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrotreated heavy Nota(s) P	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Ingestion : Can cause central nervous system (CNS) depression.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations

Code : 000010024376

Date of issue/Date of revision

: 3 October 2025

SIGMARINE 48 GREY 5163

SECTION 11: Toxicological information

Ingestion : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage the unborn child.

Other information : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
2-ethylhexanoic acid, zirconium salt	Acute - LC50	Fish	>100 mg/l [96 hours]

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
naphtha (petroleum), hydrodesulphurized heavy	-	10 to 2500	High
Note P			
xylene	3.12	7.4 to 18.5	Low
2-ethylhexanoic acid	2.7	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
2-ethylhexanoic acid	1.8	66.4852
cobalt bis(2-ethylhexanoate)	1.8	66.4852
calcium bis(2-ethylhexanoate)	1.8	66.4852

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste :	
<u>European waste catalogue (EWC)</u>	
Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

<u>Packaging</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
---------------------	---

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.

English (GB)	Europe	16/19
--------------	--------	-------

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 14: Transport information

Tunnel code	: (D/E)
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation

Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
SIGMARINE 48 GREY 5163	3
2-ethylhexanoic acid	30
	30

Labelling : Restricted to professional users.

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)
Not listed.

Persistent Organic Pollutants
Not listed.

Seveso Directive
This product is controlled under the Seveso Directive.
Danger criteria

Category
P5c

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Code	: 000010024376	Date of issue/Date of revision	: 3 October 2025
SIGMARINE 48 GREY 5163			

SECTION 16: Other information

Date of issue/ Date of revision : 3 October 2025

Date of previous issue : No previous validation

Prepared by : EHS

Version : 1

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.