

# SAFETY DATA SHEET



Date of issue/Date of revision

: 17 October 2025

Version

: 1.04

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : AMERCOAT 5450 WHITE  
**Product code** : 00334701  
**Product type** : Liquid.  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Used by spraying.  
**Use of the substance/mixture** : Coating.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

**Supplier**  
+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture  
**Classification according to UK CLP/GHS**  
Flam. Liq. 3, H226  
Skin Sens. 1, H317  
Carc. 1B, H350  
Repr. 1B, H360D  
STOT SE 3, H336  
STOT RE 1, H372  
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.  
See Section 16 for the full text of the H statements declared above.  
See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger



**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

### SECTION 3: Composition/information on ingredients

|                                      |                                                                                         |             |                                                                                                                                                                                                                                                                 |         |
|--------------------------------------|-----------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| 2-ethylhexanoic acid, zirconium salt | EC: 918-668-5<br>CAS: 128601-23-0                                                       |             | STOT SE 3, H335<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>EUH066<br>Repr. 1B, H360D                                                                                                                                                 | [1] [2] |
| n-butyl acetate                      | REACH #:<br>01-2119979088-21<br>EC: 245-018-1<br>CAS: 22464-99-9<br>Index: 607-230-00-6 | ≥1.0 - ≤5.0 |                                                                                                                                                                                                                                                                 |         |
| butanone oxime                       | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1   | ≥1.0 - ≤5.0 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066                                                                                                                                                                                                                 | [1] [2] |
|                                      | REACH #:<br>01-2119539477-28<br>EC: 202-496-6<br>CAS: 96-29-7<br>Index: 616-014-00-0    | ≤0.30       | Acute Tox. 3, H301<br>Acute Tox. 4, H312<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Carc. 1B, H350<br>STOT SE 1, H370<br>(upper respiratory tract)<br>STOT SE 3, H336<br>STOT RE 2, H373<br>(blood system)                             | [1]     |
| cobalt bis(2-ethylhexanoate)         | REACH #:<br>01-2119524678-29<br>EC: 205-250-6<br>CAS: 136-52-7<br>Index: 607-230-00-6   | <0.30       | Eye Irrit. 2, H319<br>Skin Sens. 1A, H317<br>Repr. 1B, H360FD<br>Aquatic Acute 1, H400<br>(M=1)<br>Aquatic Chronic 3, H412                                                                                                                                      | [1] [2] |
| maleic anhydride                     | REACH #:<br>01-2119472428-31<br>EC: 203-571-6<br>CAS: 108-31-6<br>Index: 607-096-00-9   | <0.0010     | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1, H334<br>Skin Sens. 1A, H317<br>STOT RE 1, H372<br>(respiratory system)<br>(inhalation)<br>EUH071<br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
 nausea or vomiting  
 headache  
 drowsiness/fatigue  
 dizziness/vertigo  
 unconsciousness  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 6: Accidental release measures

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| <b>Code</b> : 00334701     | <b>Date of issue/Date of revision</b> : 17 October 2025 |
| <b>AMERCOAT 5450 WHITE</b> |                                                         |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

| Product/ingredient name                   | Exposure limit values                                                                                                                                               |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | <b>EU OEL (Europe)</b><br>TWA: 19 ppm.<br>TWA: 100 mg/m³.                                                                                                           |
| 2-ethylhexanoic acid, zirconium salt      | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [zirconium compounds]</b><br>STEL 15 minutes: 10 mg/m³ (as Zr).<br>TWA 8 hours: 5 mg/m³ (as Zr).                    |
| n-butyl acetate                           | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b><br>STEL 15 minutes: 966 mg/m³.<br>STEL 15 minutes: 200 ppm.<br>TWA 8 hours: 724 mg/m³.<br>TWA 8 hours: 150 ppm. |
| cobalt bis(2-ethylhexanoate)              | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [cobalt and cobalt compounds]</b> Carc. Inhalation sensitiser.<br>TWA 8 hours: 0.1 mg/m³ (as Co).                   |
| maleic anhydride                          | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Inhalation sensitiser.<br>STEL 15 minutes: 3 mg/m³.<br>TWA 8 hours: 1 mg/m³.                                    |

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name                   | Type | Exposure              | Value              | Population         | Effects  |
|-------------------------------------------|------|-----------------------|--------------------|--------------------|----------|
| stoddard solvent Nota(s) P                | DNEL | Long term Dermal      | 3.78 mg/cm²        | General population | Local    |
|                                           | DNEL | Long term Dermal      | 7.56 mg/cm²        | Workers            | Local    |
|                                           | DNEL | Long term Oral        | 10.56 mg/kg bw/day | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 22 mg/m³           | General population | Local    |
|                                           | DNEL | Long term Inhalation  | 22 mg/m³           | General population | Systemic |
|                                           | DNEL | Short term Dermal     | 30 mg/kg bw/day    | Workers            | Systemic |
|                                           | DNEL | Long term Dermal      | 40 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Long term Inhalation  | 44 mg/m³           | Workers            | Local    |
|                                           | DNEL | Long term Inhalation  | 44 mg/m³           | Workers            | Systemic |
|                                           | DNEL | Short term Oral       | 50 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Short term Inhalation | 55 mg/m³           | General population | Local    |
|                                           | DNEL | Short term Inhalation | 55 mg/m³           | General population | Systemic |
|                                           | DNEL | Short term Inhalation | 55 mg/m³           | Workers            | Local    |
|                                           | DNEL | Short term Inhalation | 55 mg/m³           | Workers            | Systemic |
|                                           | DNEL | Short term Dermal     | 60 mg/kg bw/day    | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 80 mg/kg bw/day    | Workers            | Systemic |
|                                           | DNEL | Long term Inhalation  | 150 mg/m³          | Workers            | Systemic |
| Hydrocarbons, C9, aromatics > 0.1% cumene | DNEL | Long term Dermal      | 25 mg/kg bw/day    | Workers            | Systemic |
|                                           | DNEL | Long term Inhalation  | 32 mg/m³           | General population | Systemic |
|                                           | DNEL | Long term Dermal      | 11 mg/kg bw/day    | General population | Systemic |

|                     |            |                                |                   |
|---------------------|------------|--------------------------------|-------------------|
| Code                | : 00334701 | Date of issue/Date of revision | : 17 October 2025 |
| AMERCOAT 5450 WHITE |            |                                |                   |

SECTION 8: Exposure controls/personal protection

|                                         |      |                       |                    |                    |          |
|-----------------------------------------|------|-----------------------|--------------------|--------------------|----------|
| 2-ethylhexanoic acid,<br>zirconium salt | DNEL | Long term Oral        | 11 mg/kg bw/day    | General population | Systemic |
|                                         | DNEL | Long term Inhalation  | 0.58 mg/m³         | General population | Systemic |
| n-butyl acetate                         | DNEL | Long term Inhalation  | 2.351 mg/m³        | Workers            | Systemic |
|                                         | DNEL | Long term Oral        | 0.167 mg/kg bw/day | General population | Systemic |
|                                         | DNEL | Long term Dermal      | 0.167 mg/kg bw/day | General population | Systemic |
|                                         | DNEL | Long term Dermal      | 0.333 mg/kg bw/day | Workers            | Systemic |
|                                         | DNEL | Long term Inhalation  | 0.7 mg/m³          | General population | Local    |
|                                         | DNEL | Long term Inhalation  | 2.82 mg/m³         | Workers            | Local    |
|                                         | DNEL | Long term Inhalation  | 300 mg/m³          | Workers            | Systemic |
|                                         | DNEL | Long term Dermal      | 11 mg/m³           | Workers            | Systemic |
|                                         | DNEL | Long term Oral        | 2 mg/kg bw/day     | General population | Systemic |
|                                         | DNEL | Short term Oral       | 2 mg/kg bw/day     | General population | Systemic |
|                                         | DNEL | Long term Dermal      | 3.4 mg/kg bw/day   | General population | Systemic |
|                                         | DNEL | Short term Dermal     | 6 mg/kg bw/day     | General population | Systemic |
|                                         | DNEL | Long term Dermal      | 7 mg/kg bw/day     | Workers            | Systemic |
|                                         | DNEL | Short term Dermal     | 11 mg/kg bw/day    | Workers            | Systemic |
|                                         | DNEL | Long term Inhalation  | 12 mg/m³           | General population | Systemic |
|                                         | DNEL | Long term Inhalation  | 35.7 mg/m³         | General population | Local    |
|                                         | DNEL | Long term Inhalation  | 48 mg/m³           | Workers            | Systemic |
|                                         | DNEL | Short term Inhalation | 300 mg/m³          | General population | Local    |
|                                         | DNEL | Short term Inhalation | 300 mg/m³          | General population | Systemic |
|                                         | DNEL | Long term Inhalation  | 300 mg/m³          | Workers            | Local    |
| butanone oxime                          | DNEL | Short term Inhalation | 600 mg/m³          | Workers            | Local    |
|                                         | DNEL | Short term Inhalation | 600 mg/m³          | Workers            | Systemic |
|                                         | DMEL | Long term Oral        | 1.6 µg/kg bw/day   | General population | Systemic |
|                                         | DMEL | Long term Dermal      | 4 µg/kg bw/day     | Workers            | Systemic |
| cobalt bis(2-ethylhexanoate)            | DMEL | Long term Inhalation  | 4.82 µg/m³         | General population | Systemic |
|                                         | DMEL | Long term Inhalation  | 28 µg/m³           | Workers            | Systemic |
|                                         | DNEL | Long term Inhalation  | 0.43 mg/m³         | General population | Local    |
|                                         | DNEL | Long term Inhalation  | 0.9 mg/m³          | Workers            | Local    |
| maleic anhydride                        | DNEL | Long term Inhalation  | 37 µg/m³           | General population | Local    |
|                                         | DNEL | Long term Oral        | 175 µg/kg bw/day   | General population | Systemic |
|                                         | DNEL | Long term Inhalation  | 235.1 µg/m³        | Workers            | Local    |
|                                         | DNEL | Long term Inhalation  | 0.4 mg/m³          | Workers            | Systemic |
|                                         | DNEL | Long term Inhalation  | 0.4 mg/m³          | Workers            | Local    |
|                                         | DNEL | Long term Inhalation  | 0.05 mg/m³         | General population | Systemic |
|                                         | DNEL | Long term Oral        | 0.06 mg/kg bw/day  | General population | Systemic |
|                                         | DNEL | Long term Inhalation  | 0.08 mg/m³         | General population | Local    |
|                                         | DNEL | Long term Inhalation  | 0.081 mg/m³        | Workers            | Local    |
|                                         | DNEL | Long term Inhalation  | 0.081 mg/m³        | Workers            | Systemic |
|                                         | DNEL | Short term Oral       | 0.1 mg/kg bw/day   | General population | Systemic |
|                                         | DNEL | Short term Dermal     | 0.1 mg/kg bw/day   | General population | Systemic |
|                                         | DNEL | Long term Dermal      | 0.1 mg/kg bw/day   | General population | Systemic |
|                                         | DNEL | Short term Dermal     | 0.2 mg/kg bw/day   | Workers            | Systemic |
|                                         | DNEL | Long term Dermal      | 0.2 mg/kg bw/day   | Workers            | Systemic |
|                                         | DNEL | Short term Inhalation | 0.2 mg/m³          | Workers            | Local    |
|                                         | DNEL | Short term Inhalation | 0.2 mg/m³          | Workers            | Systemic |

PNECs

| Product/ingredient name      | Compartment Detail     | Value        | Method Detail            |
|------------------------------|------------------------|--------------|--------------------------|
| n-butyl acetate              | Fresh water            | 0.18 mg/l    | -                        |
|                              | Marine water           | 0.018 mg/l   | -                        |
|                              | Fresh water sediment   | 0.981 mg/kg  | -                        |
|                              | Marine water sediment  | 0.0981 mg/kg | -                        |
|                              | Sewage Treatment Plant | 35.6 mg/l    | -                        |
|                              | Soil                   | 0.0903 mg/kg | -                        |
| butanone oxime               | Fresh water            | 0.256 mg/l   | Assessment Factors       |
|                              | Sewage Treatment Plant | 177 mg/l     | Assessment Factors       |
| cobalt bis(2-ethylhexanoate) | Fresh water            | 0.6 µg/l     | Sensitivity Distribution |
|                              | Marine water           | 2.36 µg/l    | Sensitivity Distribution |
|                              | Sewage Treatment Plant | 0.37 mg/l    | Assessment Factors       |

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 8: Exposure controls/personal protection

|                  |                        |                 |                          |
|------------------|------------------------|-----------------|--------------------------|
| maleic anhydride | Fresh water sediment   | 9.5 mg/kg dwt   | Sensitivity Distribution |
|                  | Marine water sediment  | 9.5 mg/kg dwt   | Sensitivity Distribution |
|                  | Soil                   | 10.9 mg/kg dwt  | Sensitivity Distribution |
|                  | Fresh water            | 0.1 mg/l        | Assessment Factors       |
|                  | Marine water           | 0.01 mg/l       | Assessment Factors       |
|                  | Sewage Treatment Plant | 44.6 mg/l       | Assessment Factors       |
|                  | Fresh water sediment   | 0.334 mg/kg dwt | Equilibrium Partitioning |
|                  | Marine water sediment  | 0.033 mg/kg dwt | Equilibrium Partitioning |
|                  | Soil                   | 0.042 mg/kg dwt | Equilibrium Partitioning |

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.  
butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

|                     |            |                                |                   |
|---------------------|------------|--------------------------------|-------------------|
| Code                | : 00334701 | Date of issue/Date of revision | : 17 October 2025 |
| AMERCOAT 5450 WHITE |            |                                |                   |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state : Liquid.
- Colour : White.
- Odour : Characteristic.
- Odour threshold : Not available.
- Melting point/freezing point :
- Initial boiling point and boiling range : >37.78°C (>100°F)
- Flammability (solid, gas) : liquid
- Upper/lower flammability or explosive limits : Not available.
- Flash point : Closed cup: 38°C (100.4°F)
- Auto-ignition temperature :

| Ingredient name            | °C         | °F         | Method |
|----------------------------|------------|------------|--------|
| stoddard solvent Nota(s) P | 230 to 240 | 446 to 464 |        |

- pH : Not applicable.
- Viscosity : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm²/s

Solubility(ies)

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Solubility in water : 0.1 g/l
- Miscible with water : No.
- Partition coefficient: n-octanol/ water : Not applicable.
- Vapour pressure : 0.67 kPa (5 mm Hg)
- Evaporation rate : 0.34 (butyl acetate = 1)
- Relative density : 1.15
- Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties : Product does not present an oxidizing hazard.
- Particle characteristics
- Median particle size : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability : The product is stable.
- 10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| <b>Code</b> : 00334701     | <b>Date of issue/Date of revision</b> : 17 October 2025 |
| <b>AMERCOAT 5450 WHITE</b> |                                                         |

**SECTION 10: Stability and reactivity**

Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

Acute toxicity

| Product/ingredient name                    | Result                 | Species      | Dose         | Exposure |
|--------------------------------------------|------------------------|--------------|--------------|----------|
| solvent naphtha (petroleum), medium aliph. | LD50 Dermal            | Rabbit       | >3000 mg/kg  | -        |
|                                            | LD50 Oral              | Rat          | >5000 mg/kg  | -        |
| stoddard solvent Nota(s) P                 | LD50 Oral              | Rat          | >5 g/kg      | -        |
|                                            | LD50 Dermal            | Rabbit       | >3160 mg/kg  | -        |
| Hydrocarbons, C9, aromatics > 0.1% cumene  | LD50 Oral              | Rat - Female | 3492 mg/kg   | -        |
|                                            | LD50 Dermal            | Rabbit       | >5 g/kg      | -        |
| 2-ethylhexanoic acid, zirconium salt       | LD50 Oral              | Rat          | >5 g/kg      | -        |
|                                            | LC50 Inhalation Vapour | Rat          | >21.1 mg/l   | 4 hours  |
| n-butyl acetate                            | LC50 Inhalation Vapour | Rat          | 2000 ppm     | 4 hours  |
|                                            | LD50 Dermal            | Rabbit       | >17600 mg/kg | -        |
| butanone oxime                             | LD50 Oral              | Rat          | 10.768 g/kg  | -        |
|                                            | LD50 Dermal            | Rabbit       | 1100 mg/kg   | -        |
| cobalt bis(2-ethylhexanoate)               | LD50 Oral              | Rat          | 100 mg/kg    | -        |
|                                            | LD50 Dermal            | Rabbit       | >5 g/kg      | -        |
| maleic anhydride                           | LD50 Oral              | Rat          | 3129 mg/kg   | -        |
|                                            | LD50 Dermal            | Rabbit       | 2620 mg/kg   | -        |
|                                            | LD50 Oral              | Rat          | 400 mg/kg    | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

Acute toxicity estimates

| Product/ingredient name                   | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| AMERCOAT 5450 WHITE                       | 41215.1      | N/A            | N/A                      | N/A                         | N/A                                 |
| Hydrocarbons, C9, aromatics > 0.1% cumene | 3492         | N/A            | N/A                      | N/A                         | N/A                                 |
| n-butyl acetate                           | 10768        | N/A            | N/A                      | N/A                         | N/A                                 |
| butanone oxime                            | 100          | 1100           | N/A                      | N/A                         | N/A                                 |
| cobalt bis(2-ethylhexanoate)              | 3129         | N/A            | N/A                      | N/A                         | N/A                                 |
| maleic anhydride                          | 400          | 2620           | N/A                      | N/A                         | N/A                                 |

Irritation/Corrosion

**Conclusion/Summary** : Not available.

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

Sensitisation

**Conclusion/Summary**

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 11: Toxicological information

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name                                                                 | Category                               | Route of exposure | Target organs                                                   |
|-----------------------------------------------------------------------------------------|----------------------------------------|-------------------|-----------------------------------------------------------------|
| solvent naphtha (petroleum), medium aliph.<br>Hydrocarbons, C9, aromatics > 0.1% cumene | Category 3<br>Category 3               | -<br>-            | Narcotic effects<br>Respiratory tract irritation                |
| -<br>n-butyl acetate<br>butanone oxime                                                  | Category 3<br>Category 3<br>Category 1 | -<br>-<br>-       | Narcotic effects<br>Narcotic effects<br>upper respiratory tract |
| -                                                                                       | Category 3                             | -                 | Narcotic effects                                                |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name                    | Category                 | Route of exposure | Target organs                      |
|--------------------------------------------|--------------------------|-------------------|------------------------------------|
| solvent naphtha (petroleum), medium aliph. | Category 1               | -                 | central nervous system (CNS)       |
| stoddard solvent Nota(s) P                 | Category 1               | -                 | central nervous system (CNS)       |
| butanone oxime<br>maleic anhydride         | Category 2<br>Category 1 | -<br>inhalation   | blood system<br>respiratory system |

### Aspiration hazard

| Product/ingredient name                                                                                               | Result                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| solvent naphtha (petroleum), medium aliph.<br>stoddard solvent Nota(s) P<br>Hydrocarbons, C9, aromatics > 0.1% cumene | ASPIRATION HAZARD - Category 1<br>ASPIRATION HAZARD - Category 1<br>ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage the unborn child.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name                   | Result               | Species | Exposure |
|-------------------------------------------|----------------------|---------|----------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | EC50 3.2 mg/l        | Daphnia | 48 hours |
| 2-ethylhexanoic acid, zirconium salt      | LC50 9.2 mg/l        | Fish    | 96 hours |
| n-butyl acetate                           | Acute LC50 >100 mg/l | Fish    | 96 hours |
|                                           | Acute LC50 18 mg/l   | Fish    | 96 hours |

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

| Product/ingredient name                   | Test               | Result                   | Dose | Inoculum |
|-------------------------------------------|--------------------|--------------------------|------|----------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | -                  | 75 % - Readily - 28 days | -    | -        |
| n-butyl acetate                           | TEPA and OECD 301D | 83 % - Readily - 28 days | -    | -        |

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 12: Ecological information

**Conclusion/Summary** : Not available.

| Product/ingredient name                   | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------------------------|-------------------|------------|------------------|
| Hydrocarbons, C9, aromatics > 0.1% cumene | -                 | -          | Readily          |
| n-butyl acetate                           | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name    | LogP <sub>ow</sub> | BCF               | Potential |
|----------------------------|--------------------|-------------------|-----------|
| stoddard solvent Nota(s) P | 3.16 to 7.06       | -                 | High      |
| n-butyl acetate            | 2.3                | -                 | Low       |
| butanone oxime             | 0.63               | 5.01 [OECD 305 C] | Low       |
| maleic anhydride           | -2.78              | -                 | Low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Hazardous waste

#### Waste catalogue

| Waste code | Waste designation              |
|------------|--------------------------------|
| 08 01 99   | wastes not otherwise specified |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue          |
|-------------------|--------------------------|
| Container         | 15 01 06 mixed packaging |

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| <b>Code</b> : 00334701     | <b>Date of issue/Date of revision</b> : 17 October 2025 |
| <b>AMERCOAT 5450 WHITE</b> |                                                         |

**SECTION 13: Disposal considerations**

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Special precautions</b> | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**SECTION 14: Transport information**

|                                        | <b>ADR/RID</b>  | <b>ADN</b>      | <b>IMDG</b>     | <b>IATA</b>     |
|----------------------------------------|-----------------|-----------------|-----------------|-----------------|
| <b>14.1 UN number</b>                  | UN1263          | UN1263          | UN1263          | UN1263          |
| <b>14.2 UN proper shipping name</b>    | PAINT           | PAINT           | PAINT           | PAINT           |
| <b>14.3 Transport hazard class(es)</b> | 3               | 3               | 3               | 3               |
| <b>14.4 Packing group</b>              | III             | III             | III             | III             |
| <b>14.5 Environmental hazards</b>      | No.             | Yes.            | No.             | No.             |
| <b>Marine pollutant substances</b>     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

|                    |                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------|
| <b>ADR/RID</b>     | : None identified.                                                                                          |
| <b>Tunnel code</b> | : (D/E)                                                                                                     |
| <b>ADN</b>         | : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. |
| <b>IMDG</b>        | : None identified.                                                                                          |
| <b>IATA</b>        | : None identified.                                                                                          |

|                                          |                                                                                                                                                                                                                     |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>14.6 Special precautions for user</b> | : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                            |                  |
|------------------------------------------------------------|------------------|
| <b>14.7 Transport in bulk according to IMO instruments</b> | : Not available. |
|------------------------------------------------------------|------------------|

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**UK (GB)/REACH**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Explosive precursors** : Not applicable.

**Ozone depleting substances**

Not listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| <b>Code</b> : 00334701     | <b>Date of issue/Date of revision</b> : 17 October 2025 |
| <b>AMERCOAT 5450 WHITE</b> |                                                         |

SECTION 15: Regulatory information

| Product/ingredient name              | Entry Number (REACH) |
|--------------------------------------|----------------------|
| AMERCOAT 5450 WHITE                  | 3                    |
|                                      | 28                   |
| 2-ethylhexanoic acid, zirconium salt | 30                   |
| butanone oxime                       | 30                   |
|                                      | 28                   |

**Labelling** : Restricted to professional users.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|----------|
| P5c      |

National regulations

| Product/ingredient name      | List name      | Name on list                | Classification | Notes |
|------------------------------|----------------|-----------------------------|----------------|-------|
| cobalt bis(2-ethylhexanoate) | EH40/2005 WELs | cobalt and cobalt compounds | Carc           | -     |

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- : ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

| Classification                                                                                                                                 | Justification                                                                                                                                             |
|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Flam. Liq. 3, H226<br>Skin Sens. 1, H317<br>Carc. 1B, H350<br>Repr. 1B, H360D<br>STOT SE 3, H336<br>STOT RE 1, H372<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

Full text of abbreviated H statements

|      |                                                                            |
|------|----------------------------------------------------------------------------|
| H226 | Flammable liquid and vapour.                                               |
| H301 | Toxic if swallowed.                                                        |
| H302 | Harmful if swallowed.                                                      |
| H304 | May be fatal if swallowed and enters airways.                              |
| H312 | Harmful in contact with skin.                                              |
| H314 | Causes severe skin burns and eye damage.                                   |
| H315 | Causes skin irritation.                                                    |
| H317 | May cause an allergic skin reaction.                                       |
| H318 | Causes serious eye damage.                                                 |
| H319 | Causes serious eye irritation.                                             |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation.                                          |
| H336 | May cause drowsiness or dizziness.                                         |

**Code** : 00334701  
**AMERCOAT 5450 WHITE**

**Date of issue/Date of revision** : 17 October 2025

## SECTION 16: Other information

|        |                                                                    |
|--------|--------------------------------------------------------------------|
| H350   | May cause cancer.                                                  |
| H360D  | May damage the unborn child.                                       |
| H360FD | May damage fertility. May damage the unborn child.                 |
| H370   | Causes damage to organs.                                           |
| H372   | Causes damage to organs through prolonged or repeated exposure.    |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.                                        |
| H411   | Toxic to aquatic life with long lasting effects.                   |
| H412   | Harmful to aquatic life with long lasting effects.                 |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |
| EUH071 | Corrosive to the respiratory tract.                                |

### Full text of classifications

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Carc. 1B          | CARCINOGENICITY - Category 1B                                   |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Repr. 1B          | REPRODUCTIVE TOXICITY - Category 1B                             |
| Resp. Sens. 1     | RESPIRATORY SENSITISATION - Category 1                          |
| Skin Corr. 1B     | SKIN CORROSION/IRRITATION - Category 1B                         |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 1         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1   |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

### History

**Date of issue/ Date of revision** : 17 October 2025

**Date of previous issue** : 16 October 2025

**Prepared by** : EHS

**Version** : 1.04

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*