

# SAFETY DATA SHEET

Date of issue/Date of revision

: 30 October 2025

Version

: 2



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PITT-CHAR NX BASE WHITE SF

**Product code** : 000001198486

**Other means of identification**

00472890

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.  
PO Box 7509  
Dammam 31472  
Saudi Arabia  
Tel: 00966 138 47 31 00  
Fax: 00966 138 47 17 34

**e-mail address of person  
responsible for this SDS** : ndpic@sfd.a.gov.sa

**1.4 Emergency telephone  
number** : 00966 138473100 extn 1001

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
Carc. 2, H351  
Repr. 2, H361d  
Aquatic Acute 1, H400  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.


See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



SECTION 2: Hazards identification

Signal word	: Warning
Hazard statements	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging the unborn child. Very toxic to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
Prevention	: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Avoid breathing vapour.
Response	: Collect spillage.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations. P202, P280, P273, P261, P391, P501
Hazardous ingredients	: hexaboron dizinc undecaoxide; bis-[4-(2,3-epoxipropoxi)phenyl]propane; epoxy resin (MW ≤ 700); Cashew, nutshell liq. and 2,2-bis(acryloyloxymethyl)butyl acrylate
Supplemental label elements	: Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
<u>Special packaging requirements</u>	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:  May cause endocrine disruption.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Code : 000001198486

Date of issue/Date of revision

: 30 October 2025

PITT-CHAR NX BASE WHITE SF

## SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hexaboron dizinc undecaoxide	REACH #: 01-2119691658-19 EC: 235-804-2 CAS: 12767-90-7	≥10 - ≤25	Eye Irrit. 2, H319 Repr. 2, H361d (oral) Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M [Acute] = 1	[1] [2]
Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	REACH #: 01-2119970312-43 EC: 234-521-1 CAS: 12046-04-7	≥10 - ≤25	Repr. 2, H361d	Repr. 2, H361d: C ≥ 4.8%	[1] [2]
bis-[4-(2,3-epoxipropoxy) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
phosphorous oxychloride, reaction products with propylene oxide	EC: 807-935-0 CAS: 1244733-77-4	≥5.0 - ≤10	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]
triphenyl phosphate	EC: 204-112-2 CAS: 115-86-6	≥5.0 - ≤10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [3]
epoxy resin (MW ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Cashew, nutshell liq.	EC: 232-355-4 CAS: 8007-24-7	≥1.0 - <3.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1]
2,2-bis(acryloyloxymethyl) butyl acrylate	REACH #: 01-2119489896-11 EC: 239-701-3 CAS: 15625-89-5 Index: 607-111-00-9	≥1.0 - ≤4.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Quaternary ammonium compounds, benzylbis (hydrogenated tallow alkyl) methyl, chlorides	EC: 263-082-9 CAS: 61789-73-9	≤0.30	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 <b>See Section 16 for the full text of the H statements declared above.</b>	M [Acute] = 1 M [Chronic] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance of equivalent concern - Endocrine disrupting properties

Occupational exposure limits, if available, are listed in Section 8.

Code : 000001198486

Date of issue/Date of revision

: 30 October 2025

PITT-CHAR NX BASE WHITE SF

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.  
In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.  
In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Code : 000001198486

Date of issue/Date of revision

: 30 October 2025

PITT-CHAR NX BASE WHITE SF

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
phosphorus oxides  
halogenated compounds  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code : 000001198486

Date of issue/Date of revision

: 30 October 2025

PITT-CHAR NX BASE WHITE SF

## SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits



Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
hexaboron dizinc undecaoxide	<b>ACGIH TLV (United States, 1/2013)</b> TWA: 3 mg/m³ (Dusts and mists). Form: Respirable fraction. TWA: 10 mg/m³ (Dusts and mists). Form: .
Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	<b>ACGIH TLV (United States)</b> TWA: 10 mg/m³. Form: inhalable dust. TWA: 3 mg/m³. Form: Respirable dust.
triphenyl phosphate	<b>Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) A4.</b> TWA 8 hours: 3 mg/m³. <b>Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)</b> TWA 8 hours: 3 mg/m³. <b>ACGIH TLV (United States, 1/2024) A4.</b> TWA 8 hours: 3 mg/m³.
Synthetic fibers, alk. earth silicate	<b>ACGIH TLV (United States, 2011)</b> TWA 8 hours: 10 mg/m³ (Total dust). TWA 8 hours: 3 mg/m³ (Respirable fraction).

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

SECTION 8: Exposure controls/personal protection

Gloves	: polyethylene butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Colour

Odour

Odour threshold

Melting point/freezing point

Initial boiling point and boiling range

Flammability

Upper/lower flammability or explosive limits

Flash point

Auto-ignition temperature

Decomposition temperature

pH

Viscosity

Viscosity

Solubility(ies)

: Liquid.

: White.

: Aromatic. [Slight]

: Not available.

: Not determined.

: >37.78°C

: Not determined. There are no data available on the mixture itself.

: Not available.

: Closed cup: 120°C

:

Ingredient name

°C

°F

Method

2-bis(acryloyloxymethyl)butyl acrylate

385

725

EU A.15

: Stable under recommended storage and handling conditions (see Section 7).

: Not applicable.

: Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm²/s

: > 100 s (ISO 6mm)

:

Media

Result

cold water

Not soluble

Partition coefficient: n-octanol/ water

: Not applicable.

Vapour pressure

:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2,2-bis(acryloyloxymethyl)butyl acrylate	0.00075	0.0001	OECD 104			



Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

SECTION 9: Physical and chemical properties

Relative density	: 1.55
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- Causes serious eye irritation.
- Causes skin irritation.
- May cause an allergic skin reaction.
- Suspected of damaging fertility. Suspected of damaging the unborn child.
- Suspected of causing cancer.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
hexaboron dizinc undecaoxide	Rabbit - Dermal - LD50	>5000 mg/kg
	Rat - Oral - LD50	>5000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5 mg/l [4 hours]
ammonium pentaborate	Rabbit - Dermal - LD50	>2000 mg/kg
	Rat - Oral - LD50	4200 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit - Dermal - LD50	23000 mg/kg
	Rat - Oral - LD50	15000 mg/kg
phosphorous oxychloride, reaction products with propylene oxide	Rat - Oral - LD50	630 to 2000 mg/kg
	Rabbit - Dermal - LD50	>2000 mg/kg

**Code** : 000001198486 **Date of issue/Date of revision** : 30 October 2025  
PITT-CHAR NX BASE WHITE SF

Triphenylphosphate	Rat - Inhalation - LC50 Dusts and mists Rabbit - Dermal - LD50 Rat - Oral - LD50 <u>Toxic effects</u> : Behavioral - Tremor Behavioral - Ataxia Gastrointestinal - Hypermotility, diarrhea	>7 mg/l [4 hours] >7900 mg/kg 3500 mg/kg
EPOXY RESIN ( AVERAGE MOLECULAR WT < 700)	Rat - Oral - LD50	>2 g/kg
2,2-bis(acryloyloxymethyl)butyl acrylate	Rabbit - Dermal - LD50 Rabbit - Dermal - LD50 Rat - Oral - LD50	>2 g/kg 5170 mg/kg 5.19 g/kg

#### Acute toxicity estimates

Route	ATE value
Oral	4574.89 mg/kg
Dermal	67901.23 mg/kg

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Irritation/Corrosion

Product/ingredient name	Result
hexaboron dizinc undecaoxide	<u>Rabbit - Eyes - Cornea opacity</u> Amount/concentration applied: 0.083g Duration of treatment/exposure: 24 hours Observation period: 74 hours Irritation score: 33 Fully reversible in more than 7 days
bis-[4-(2,3-epoxipropoxy)phenyl] propane	<u>Rabbit - Eyes - Redness of the conjunctivae</u> Duration of treatment/exposure: 24 hours Irritation score: 0.4
-	<u>Rabbit - Eyes - Mild irritant</u> Duration of treatment/exposure: 24 hours Fully reversible in 7 days or less
-	<u>Rabbit - Skin - Erythema/Eschar</u> Duration of treatment/exposure: 4 hours Irritation score: 0.8
-	<u>Rabbit - Skin - Oedema</u> Duration of treatment/exposure: 4 hours Irritation score: 0.5
-	<u>Rabbit - Skin - Mild irritant</u> Duration of treatment/exposure: 4 hours
epoxy resin (MW ≤ 700)	<u>Rabbit - Skin - Mild irritant</u>
-	<u>Rabbit - Eyes - Mild irritant</u>
2,2-bis(acryloyloxymethyl)butyl acrylate	<u>Rabbit - Skin - Irritant</u>

#### Conclusion/Summary

**Skin** : Causes skin irritation.

**Eyes** : Causes serious eye irritation.

**Respiratory** : Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitization

**Code** : 000001198486 **Date of issue/Date of revision** : 30 October 2025  
PITT-CHAR NX BASE WHITE SF

Product/ingredient name	Test	Result
bis-[4-(2,3-epoxipropoxy)phenyl] propane	Mouse - skin	Sensitising
epoxy resin (MW ≤ 700)	Mouse - skin OECD 429	Sensitising
2,2-bis(acryloyloxymethyl)butyl acrylate	Rabbit - skin	Sensitising

#### Conclusion/Summary

**Skin** : May cause an allergic skin reaction.  
**Respiratory** : Based on available data, the classification criteria are not met.

#### Mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

Product/ingredient name	Test	Result
hexaboron dizinc undecaoxide	Rat - Oral OECD 408 375 mg/kg [7 days per week] [90 days]	Developmental: Positive Maternal toxicity: Positive Fertility effects: Positive

Suspected of damaging fertility. Suspected of damaging the unborn child.

#### Specific target organ toxicity (single exposure)

#### Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure** : Not available.

#### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.  
**Eye contact** : Causes serious eye irritation.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations  
**Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Short term exposure**

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

**Long term exposure**

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

**Potential chronic health effects**

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : Suspected of damaging the unborn child.

**Other information** : Not available.

Sanding and grinding dusts may be harmful if inhaled. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.

**11.2 Information on other hazards**

**11.2.1 Endocrine disrupting properties**

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

**11.2.2 Other information**

Not available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Product/ingredient name	Result	Species	Dose / Exposure
hexaboron dizinc undecaoxide	Acute - EC50	Daphnia - <i>Daphnia magna</i>	76 mg/l [48 hours]
	Acute - LC50	Fish - <i>Salmo gairdneri</i>	2.17 mg/l [96 hours]
Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-	Acute - LC50	Fish	>100 mg/l [96 hours]
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Chronic - NOEC	Daphnia	0.3 mg/l [21 days]
	Acute - LC50 - Fresh water	Daphnia - <i>daphnia magna</i>	1.8 mg/l [48 hours]

Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

SECTION 12: Ecological information

phosphorous oxychloride, reaction products with propylene oxide	EC50	Algae	82 mg/l [72 hours]
	LC50	Fish	51 mg/l [96 hours]
	EC50	Daphnia	131 mg/l [48 hours]
	NOEC	Daphnia	32 mg/l [48 hours]
triphenyl phosphate	Chronic - NOEC	Algae - Green algae - <i>Desmodesmus subspicatus</i>	0.1 mg/l [3 days]
	Acute - LC50 - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	0.09 mg/l [48 hours]
epoxy resin (MW ≤ 700)	Chronic - NOEC	Daphnia	0.3 mg/l [21 days]
	Acute - LC50	Daphnia	1.8 mg/l [48 hours]
2,2-bis(acryloyloxymethyl)butyl acrylate	Acute - LC50	Fish	0.87 mg/l [96 hours]

**Conclusion/Summary** : Very toxic to aquatic life.  
Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
epoxy resin (MW ≤ 700)	OECD 301F	5% [28 days]		

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi)phenyl]propane	-	-	Not readily
epoxy resin (MW ≤ 700)	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
hexaboron dizinc undecaoxide	-	60960	High
phosphorous oxychloride, reaction products with propylene oxide	2.68	0.8 to 14	Low
triphenyl phosphate	4.63	190.55	Low
epoxy resin (MW ≤ 700)	3	31	Low
Cashew, nutshell liq.	>4.78	-	High
2,2-bis(acryloyloxymethyl)butyl acrylate	0.67	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
bis-[4-(2,3-epoxipropoxi)phenyl]propane	4	10465.7
triphenyl phosphate	4.3	21731.8
epoxy resin (MW ≤ 700)	2.6	445
2,2-bis(acryloyloxymethyl)butyl acrylate	2.2	157.193

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Code : 000001198486

Date of issue/Date of revision : 30 October 2025

PITT-CHAR NX BASE WHITE SF

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

May cause endocrine disruption.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

English (GB)

United Arab Emirates

14/16



Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

SECTION 14: Transport information			
	(hexaboron dizinc undecaoxide, bis-[4-(2,3-epoxipropoxi)phenyl] propane)		
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(hexaboron dizinc undecaoxide)	Not applicable.

Additional information

- ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- Tunnel code** : (-)
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**14.6 Special precautions for user** : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not applicable.

SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
EU Regulation (EC) No. 1907/2006 (REACH)  
Annex XIV - List of substances subject to authorisation  
Annex XIV  
None of the components are listed.  
Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Endocrine disrupting properties for environment	triphenyl phosphate	Candidate	D(2024) 6225-DC	11/7/2024

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

Other national and international regulations.  
**Explosive precursors** : Not applicable.

Code	: 000001198486	Date of issue/Date of revision	: 30 October 2025
PITT-CHAR NX BASE WHITE SF			

SECTION 15: Regulatory information

Ozone depleting substances (EU 2024/590)  
Not listed.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

**Full text of abbreviated H statements** : H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H361d Suspected of damaging the unborn child.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

**Full text of classifications [CLP/GHS]** : Acute Tox. 4 ACUTE TOXICITY - Category 4  
Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1  
Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1  
Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2  
Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  
Carc. 2 CARCINOGENICITY - Category 2  
Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
Repr. 2 REPRODUCTIVE TOXICITY - Category 2  
Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2  
Skin Sens. 1 SKIN SENSITISATION - Category 1

**History**

**Date of issue/ Date of revision** : 30 October 2025

**Date of previous issue** : 28 April 2025

**Prepared by** : EHS

**Version** : 2

**Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.