

SAFETY DATA SHEET



Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Date of issue/Date of revision 5 November 2025

Version 2.07

Section 1. Chemical product and company identification

Product code : 000001161550
Product name : SIGMARINE 48 YELLOW/SIGMA 3138
Product name : SIGMARINE 48 YELLOW/SIGMA 3138
Other means of identification : 00219234; 00219235
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Not applicable.

Supplier's details : PPG Coatings (Kunshan) Co., Ltd
53 Jinyang Road, Lujia Town,
215331 Kunshan City, Jiangsu Province, P.R. China
Tel: 86 512 57678859 Fax: 86 512 57678857

Emergency telephone number (with hours of operation) : 00 86 532 83889090

Section 2. Hazards identification

Classification of the substance or mixture according to GB 30000.1-2024 and GB 30000-2013

Emergency overview

Liquid.
Yellow.
Aromatic. [Slight]
Flammable liquid and vapour.
May be harmful in contact with skin.
Causes skin irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
Toxic to aquatic life.
Toxic to aquatic life with long lasting effects.
Prolonged or repeated contact may dry skin and cause irritation.

IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation occurs: Get medical advice or attention.

See Section 12 for environmental precautions.

Section 2. Hazards identification

Classification of the substance or mixture

- : FLAMMABLE LIQUIDS - Category 3
- ACUTE TOXICITY (dermal) - Category 5
- ACUTE TOXICITY (inhalation) - Category 4
- SKIN CORROSION/IRRITATION - Category 2
- REPRODUCTIVE TOXICITY - Category 1B
- SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
- SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
- SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2
- LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
- Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 57%
- Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 73.5%
- Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 37.8%

GHS label elements

Hazard pictograms



Signal word

- : Danger

Hazard statements

- : Flammable liquid and vapour.
- May be harmful in contact with skin.
- Causes skin irritation.
- Harmful if inhaled.
- May cause drowsiness or dizziness.
- May damage fertility or the unborn child.
- Causes damage to organs through prolonged or repeated exposure.
- Toxic to aquatic life.
- Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response

- : Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation occurs: Get medical advice or attention.

Suitable extinguishing media

- : Use dry chemical, CO₂, water spray (fog) or foam.

Section 2. Hazards identification

Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	: Flammable liquid and vapour.
Health hazards	: Causes skin irritation. Harmful if inhaled. May cause drowsiness or dizziness. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact may dry skin and cause irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Section 2. Hazards identification

Environmental hazards : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : 00219234; 00219235

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
Naphtha (petroleum), hydrodesulfurized heavy nonane and its isomers	25 - <40	64742-82-1
1,2,4-trimethylbenzene	1 - <10	111-84-2
Talc , not containing asbestiform fibres	1 - <10	95-63-6
xylene isomers mixture	1 - <10	14807-96-6
2-ethylhexanoic acid, zirconium salt	1 - <10	1330-20-7
ethylbenzene	0.1 - <1	22464-99-9
calcium bis(2-ethylhexanoate)	0.1 - <1	100-41-4
neodecanoic acid, cobalt salt	0.1 - <1	136-51-6
	0.1 - <1	27253-31-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin.

Section 4. First aid measures

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Section 5. Firefighting measures

Specific hazards arising from the chemical	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
----------------------------------	--

Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 6. Accidental release measures

Section 7. Handling and storage

- Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
- Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
nonane	GBZ 2.1 (China, 7/2024) PC-TWA 8 hours: 500 mg/m³.
1,2,4-trimethylbenzene	ACGIH TLV (United States, 1/2024) TWA 8 hours: 10 ppm.
Talc , not containing asbestiform fibres	GBZ 2.1 (China, 7/2024) PC-TWA 8 hours: 3 mg/m³. Form: Total dust. PC-TWA 8 hours: 1 mg/m³. Form: Respirable dust.
xylene	GBZ 2.1 (China, 7/2024) [Xylene] PC-TWA 8 hours: 50 mg/m³. PC-STEEL 15 minutes: 100 mg/m³.
2-ethylhexanoic acid, zirconium salt	GBZ 2.1 (China, 7/2024) [Zirconium and compounds]

Section 8. Exposure controls/personal protection

ethylbenzene	PC-TWA 8 hours: 5 mg/m ³ (as Zr). PC-STEL 15 minutes: 10 mg/m ³ (as Zr). GBZ 2.1 (China, 7/2024) PC-TWA 8 hours: 100 mg/m ³ . PC-STEL 15 minutes: 150 mg/m ³ .
neodecanoic acid, cobalt salt	ACGIH TLV (United States, 1/2024) [cobalt and inorganic compounds] Skin sensitiser , Inhalation sensitiser. TWA 8 hours: 0.02 mg/m ³ (as Co).

- Recommended monitoring procedures**

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls**

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection

: Chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

 Recommended: neoprene, polyvinyl alcohol (PVA), Viton®
 May be used: nitrile rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
Colour : Yellow.
Odour : Aromatic. [Slight]
Boiling point : >37.78°C (>100°F)
Flash point : Closed cup: 44°C (111.2°F)
Lower and upper explosive (flammable) limits : Not available.
Relative density : 0.96

Solubility(ies) :

Media	Result
cold water	Not soluble

- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s

- Viscosity** : > 100 s (ISO 6mm)

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

- Chemical stability** : The product is stable.

- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose
Naphtha (petroleum), hydrodesulfurized heavy	Rat - Oral - LD50	>5000 mg/kg
-	Rabbit - Dermal - LD50	>2000 mg/kg
nonane and its isomers	Rat - Inhalation - LC50 Vapour	16790 mg/m ³ [4 hours]
-	Rat - Inhalation - LC50 Gas.	3200 ppm [4 hours]
1,2,4-trimethylbenzene	Rat - Oral - LD50	5 g/kg
-	Rat - Inhalation - LC50 Vapour	18000 mg/m ³ [4 hours]
xylene isomers mixture	Rat - Oral - LD50	4.3 g/kg
-	Rabbit - Dermal - LD50	1.7 g/kg
2-ethylhexanoic acid, zirconium salt	Rabbit - Dermal - LD50	>5 g/kg
-	Rat - Oral - LD50	>5 g/kg
ethylbenzene	Rat - Oral - LD50	3.5 g/kg
-	Rabbit - Dermal - LD50	17.8 g/kg
-	Rat - Inhalation - LC50 Vapour	17.8 mg/l [4 hours]
neodecanoic acid, cobalt salt	Rat - Female - Oral - LD50	1098 mg/kg

Product Conclusion : There are no data available on the mixture itself.

Skin corrosion/irritation

Product/ingredient name	Species	Dose	Score
xylene isomers mixture	Rabbit - Skin - Moderate irritant	Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours	-

Conclusion/Summary : There are no data available on the mixture itself.

Serious eye damage/eye irritation

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory corrosion/irritation

Conclusion/Summary : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Species	Result
neodecanoic acid, cobalt salt	Mouse - skin OECD 429	Result: Sensitising

Skin

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory

Conclusion/Summary : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	IARC
xylene isomers mixture	3
ethylbenzene	2B
neodecanoic acid, cobalt salt	2B

Reproductive toxicity

Section 11. Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
1,2,4-trimethylbenzene	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
Talc , not containing asbestiform fibres	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
neodecanoic acid, cobalt salt	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (gastrointestinal tract) (oral) - Category 1

Aspiration hazard

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations

Section 11. Toxicological information

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

- Conclusion/Summary** : There are no data available on the mixture itself.
- General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMARINE 48 YELLOW/SIGMA 3138	63085.9	3024.4	18611.9	46.0	8.8
Naphtha (petroleum), hydrodesulfurized heavy	N/A	2500	N/A	N/A	N/A
nonane and its isomers	N/A	N/A	3200	16.79	N/A
1,2,4-trimethylbenzene	5000	N/A	N/A	18	1.5
xylene isomers mixture	4300	1700	N/A	11	1.5
ethylbenzene	3500	17800	N/A	17.8	1.5
neodecanoic acid, cobalt salt	1098	N/A	N/A	N/A	N/A

Other information :

Section 11. Toxicological information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
2-ethylhexanoic acid, zirconium salt ethylbenzene	Acute - LC50	Fish	>100 mg/l [96 hours]
	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	1 mg/l

Conclusion/Summary : Not available.

Persistence/degradability

Product/ingredient name	Test	Result	Dose / Inoculum
ethylbenzene	-	79% [10 days] - Readily	

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene isomers mixture	-	-	Readily
ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Naphtha (petroleum), hydrodesulfurized heavy nonane and its isomers	-	10 to 2500	High
1,2,4-trimethylbenzene	5.65	-	High
xylene isomers mixture	3.63	120.23	Low
ethylbenzene	3.12	7.4 to 18.5	Low
	3.6	79.43	Low

Mobility in soil

Soil/water partition coefficient : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3	3
Packing group	III	III	III	III
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Naphtha (petroleum), hydrodesulfurized heavy)	Not applicable.

Additional information

CN : None identified.

UN : None identified.

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

China inventory (IECSC) : All components are listed or exempted.

References :

- Production Safety Law of the People's Republic of China
- Code of Occupational Disease Prevention of the People's Republic of China
- Environmental Protection Law of the People's Republic of China
- Fire Control Law of the People's Republic of China
- Regulations on the Control over Safety of Dangerous Chemicals
- Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1)
- Specification for classification and labelling of chemicals according to Part 1: General rules (GB 30000.1-2024)
- Safety data sheet for chemical products - Content and order of sections (GB/T16483)
- Guidance on the compilation of safety data sheet for chemical products (GB/T17519)
- General rule for preparation of precautionary label for chemicals (GB15258)
- Safety rules for classification, precautionary labeling and precautionary statements of chemicals (GB30000.2-29)

Section 16. Other information

History

Date of issue/Date of revision : 5 November 2025

Version : 2.07

Date of previous issue : 8/8/2025

First issue date : 1/13/2021

Prepared by : EHS

Key to abbreviations :

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- UN = United Nations



Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.