SAFETY DATA SHEET

Date of issue/Date of revision : 2 December 2025 Version : 1.01



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : NOVAGUARD 4801 CATALYST

Product code : 000001090258

Other means of identification

00346208; 00673779

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Org. Perox. C, H242 Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412

English (GB) Europe 1/17

NOVAGUARD 4801 CATALYST

SECTION 2: Hazards identification

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms









Signal word

: Danger

Hazard statements

: Heating may cause a fire.

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. May cause respiratory irritation.

May cause cancer.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

only in original packaging.

Response : IF exposed or concerned: Get medical advice or attention.

Storage : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

P280, P210, P234, P308 + P313, P403, P501

Hazardous ingredients : α, α-dimethylbenzyl hydroperoxide; 2-Butanone, peroxide; tert-butyl perbenzoate and

cumene

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

lastonings

Tactile warning of danger : Not applicable.

2.3 Other hazards

English (GB) Europe 2/17

NOVAGUARD 4801 CATALYST

SECTION 2: Hazards identification

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.

: Based on available data, the classification criteria are not met.

Other hazards which do not result in classification

: Temperature control may be required. Hazardous decomposition may occur. Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
α, α-dimethylbenzyl hydroperoxide	REACH #: 01-2119475796-19 EC: 201-254-7 CAS: 80-15-9 Index: 617-002-00-8	≥10 - ≤21	Org. Perox. E, H242 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411	ATE [Oral] = 382 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l Skin Corr. 1B, H314: $C \ge 10\%$ Skin Irrit. 2, H315: 3% $\le C < 10\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Irrit. 2, H319: 1% $\le C < 3\%$ STOT SE 3, H335: $C \ge 1\%$	[1]
2-Butanone, peroxide	EC: 215-661-2 CAS: 1338-23-4	≥10 - ≤25	Org. Perox. D, H242 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318	ATE [Oral] = 470 mg/ kg	[1] [2]
tert-butyl perbenzoate	REACH #: 01-2119513317-46 EC: 210-382-2 CAS: 614-45-9	≥5.0 - ≤10	Org. Perox. C, H242 Acute Tox. 4, H332 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Inhalation (dusts and mists)] = 1.5 mg/l M [Acute] = 1	[1]
cumene	REACH #: 01-2119473983-24 EC: 202-704-5 CAS: 98-82-8 Index: 601-024-00-X	≥1.0 - ≤3.5	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	-	[1] [2]

English (GB) Europe 3/17

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Inhalation

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Skin contact: Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

Ingestion: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

English (GB) Europe 4/17

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments**

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

media

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Runoff to sewer may create fire or explosion hazard. This material increases the risk of fire and may aid combustion. Heating may cause a fire. May re-ignite itself after fire is extinguished. Hazardous decomposition may occur. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

Decomposition products may include the following materials:

carbon oxides

5.3 Advice for firefighters

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

English (GB)	Europe	5/17
Liigiisii (OD)	Luiope	U/ 1 /

NOVAGUARD 4801 CATALYST

SECTION 6: Accidental release measures

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid contamination with reactive substances. Dilute with water and mop up if water-soluble. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid contamination with reactive substances. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Keep away from clothing, incompatible materials and combustible materials. Temperature control may be required. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: To avoid the risk of formation of shock-sensitive crystals or loss of stability, it is important to store the product within the recommended temperature range. Temperature control may be required. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store at temperatures not exceeding 20°C/68°F. Store locked up. Eliminate all ignition sources. Separate from reducing agents and combustible materials. Keep away from rust, iron and copper. Keep container tightly closed and sealed until ready for use. Prevent product contamination. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental

English (GB) Europe 6/17

NOVAGUARD 4801 CATALYST

SECTION 7: Handling and storage

contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butanone, peroxide	ACGIH TLV (United States, 1/2025)
•	C: 0.2 ppm.
	C: 1.5 mg/m³.
cumene	EU OEL (Europe, 1/2022) Absorbed through skin.
	TWA 8 hours: 10 ppm.
	TWA 8 hours: 50 mg/m³.
	STEL 15 minutes: 50 ppm.
	STEL 15 minutes: 250 mg/m³.

procedures

Recommended monitoring: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure		Value
α, α-dimethylbenzyl hydroperoxide	DNEL - Workers - Long term - Inhalation	Systemic	6 mg/m³
2-Butanone, peroxide	DNEL - General population - Long term - Oral	Systemic	0.26 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	0.44 mg/m³
	DNEL - General population - Long term - Dermal	Systemic	0.51 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	1.43 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Systemic	2.52 mg/m ³
	DNEL - Workers - Short term - Inhalation	Systemic	7.55 mg/m³
tert-butyl perbenzoate	DNEL - Workers - Long term - Dermal	Systemic	17.5 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Systemic	24.7 mg/m³
cumene	DNEL - General population - Long term - Dermal	Systemic	1.2 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	15.4 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Systemic	100 mg/m³
	DNEL - Workers - Short term - Inhalation	Local	250 mg/m³
	DNEL - General population - Long term - Oral	Systemic	5 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	16.6 mg/m³

PNECs

English (GB)	Europe	7/17

NOVAGUARD 4801 CATALYST

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail - Method	Value
α, α-dimethylbenzyl hydroperoxide	Fresh water - Assessment Factors	0.003 mg/l
	Sewage Treatment Plant - Assessment Factors	0.35 mg/l
	Fresh water sediment - Equilibrium Partitioning	0.023 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.002 mg/kg dwt
	Soil - Equilibrium Partitioning	0.003 mg/kg dwt
cumene	Fresh water - Assessment Factors	0.035 mg/l
	Marine water - Assessment Factors	0.004 mg/l
	Sewage Treatment Plant - Assessment Factors	200 mg/l
	Fresh water sediment - Equilibrium Partitioning	3.22 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.322 mg/kg dwt
	Soil - Equilibrium Partitioning	0.624 mg/kg dwt

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Use with adequate ventilation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Chemical splash goggles and face shield. Use eye protection according to EN 166.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves

: butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

English (GB) Europe 8/17

NOVAGUARD 4801 CATALYST

SECTION 8: Exposure controls/personal protection

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Clear.

Odour Not available. Melting point/freezing point : Not determined. : >37.78°C **Boiling point or initial boiling**

point and boiling range

Flammability

Lower and upper explosion

limit

Flash point

: Not determined. There are no data available on the mixture itself.

Closed cup: Not applicable.

: Not available.

Auto-ignition temperature

Ingredient name	°C	°F	Method
tert-butyl perbenzoate	93	199.4	

Decomposition temperature

: Stable under recommended storage and handling conditions (see Section 7).

Hq

: Not applicable, insoluble in water.

Viscosity

Dynamic (room temperature): Not available. Kinematic (room temperature): Not available.

Kinematic (40°C): >21 mm²/s

Solubility

Media	Result
cold water	Not soluble

Partition coefficient n-octanol/ : Not applicable.

water (log Pow)

Vapour pressure

:		Vapour Pressure at 20°C			Vapour pressure at 50°C		
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
	cumene	3.72032	0.5				

Relative density 1.05

English (GB) **Europe** 9/17

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 9: Physical and chemical properties

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of

vapour or dust with air is possible.

Oxidising properties : Not available.

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : This product possesses explosive properties but, as packaged, will not detonate or

deflagrate rapidly or undergo a thermal explosion.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Hazardous reactions or instability may occur under certain conditions of storage or use.

Conditions may include the following:

temperature increase high temperature

Reactions may include the following:

hazardous decomposition risk of causing fire

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous

decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Acute toxicity

English (GB) Europe 10/17

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 11: Toxicological information

Product/ingredient name	Result	Dose / Exposure
α, α-dimethylbenzyl hydroperoxide	Rat - Oral - LD50	382 mg/kg
	<u>Toxic effects</u> : Kidney, Ureter, and Bladder -	
	Hematuria	
	Rat - Dermal - LD50	1200 to 1520 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	1.37 mg/l [4 hours]
2-Butanone, peroxide	Rat - Oral - LD50	470 mg/kg
	Rat - Inhalation - LC50 Vapour	1440 mg/m³ [4 hours]
	Rat - Inhalation - LC50 Gas.	200 ppm [4 hours]
	Toxic effects: Lung, Thorax, or Respiration -	
	Dyspnea	
tert-butyl perbenzoate	Rat - Oral - LD50	1012 mg/kg
	Toxic effects: Lung, Thorax, or Respiration -	
	Respiratory depression Gastrointestinal -	
	Necrotic changes Liver - Other changes	
cumene	Rabbit - Dermal - LD50	12.3 g/kg
	Rat - Oral - LD50	2260 mg/kg
	Rat - Inhalation - LC50 Vapour	39000 mg/m³ [4 hours]

Acute toxicity estimates

Route	ATE value
Oral	1265.26 mg/kg
Dermal	6111.11 mg/kg
Inhalation (dusts and mists)	2.42 mg/l

Conclusion/Summary: Harmful if swallowed or if inhaled.

Irritation/Corrosion

Product/ingredient name	Result
	Rabbit - Skin - Visible necrosis Duration of treatment/exposure: 24 hours Observation period: 24 hours

Conclusion/Summary

Skin : Causes severe burns.

Eyes : Causes serious eye damage.

Respiratory: Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Conclusion/Summary

Skin : May cause an allergic skin reaction.

Respiratory: Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

English (GB) Europe 11/17

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 11: Toxicological information

	Product/ingredient name	• •	Route of exposure	Target organs
- 1		Category 3 Category 3		Respiratory tract irritation Respiratory tract irritation

Conclusion/Summary

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	3 3 3	Route of exposure	Target organs
α, α-dimethylbenzyl hydroperoxide	Category 2	-	-

Conclusion/Summary

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Product/ingredient name	Result	
cumene	ASPIRATION HAZARD - Category 1	

Conclusion/Summary

Based on available data, the classification criteria are not met.

Information on likely

routes of exposure

: Not available.

Potential acute health effects

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Ingestion: Harmful if swallowed.

Skin contact: Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion: Adverse symptoms may include the following:

stomach pains

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

Eye contact: Adverse symptoms may include the following:

pain watering redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: No known significant effects or critical hazards.

effects

Potential delayed effects: No known significant effects or critical hazards.

Long term exposure

English (GB) Europe 12/17

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 11: Toxicological information

Potential immediate effects

: No known significant effects or critical hazards.

Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards. Reproductive toxicity : No known significant effects or critical hazards.

Other information : Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to

high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may

lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
α, α-dimethylbenzyl hydroperoxide	Acute - EC50 Chronic - NOEC Acute - LC50 - Fresh water	Algae	3.1 mg/l [72 hours] 1 mg/l [72 hours] 23.4 mg/l [96 hours]

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
α, α-dimethylbenzyl hydroperoxide	-	-	Not readily

12.3 Bioaccumulative potential

E !!! (OD)	—	40/4=
English (GB)	Europe	13/17
Linguisti (SD)	Ediopo	10,11

Code	: 000001090258	Date of issue/Date of revision	: 2 December 2025
NOVAG	UARD 4801 CATALYST		

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
α, α-dimethylbenzyl hydroperoxide	1.6	-	Low
2-Butanone, peroxide	<0.3	-	Low
tert-butyl perbenzoate	3	-	Low
cumene	3.55	35.48	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
2-Butanone, peroxide tert-butyl perbenzoate	2.3 1.9	46.6217 213.717 81.0594 521.484

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

English (GB)	Europe	14/17
English (OD)	Luiope	17/1/

NOVAGUARD 4801 CATALYST

SECTION 13: Disposal considerations

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3103	UN3103	UN3103	UN3103
14.2 UN proper shipping name	ORGANIC PEROXIDE TYPE C, LIQUID			
	(Cumyl hydroperoxide, 2-Butanone, peroxide)			
14.3 Transport hazard class(es)	5.2	5.2	5.2	5.2
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank

vessels.

IMDG : None identified. IATA : None identified.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO

instruments

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

English (GB) 15/17 **Europe**

Code : 000001090258 Date of issue/Date of revision : 2 December 2025

NOVAGUARD 4801 CATALYST

SECTION 15: Regulatory information

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
NOVAGUARD 4801 CATALYST	3
	28
cumene	28

Labelling : Restricted to professional users.

Other EU regulations

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P6b

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Full text of abbreviated H statements

English (GB) Europe 16/17

NOVAGUARD 4801 CATALYST

SECTION 16: Other information

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

	·
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Org. Perox. C	ORGANIC PEROXIDES - Type C
Org. Perox. D	ORGANIC PEROXIDES - Type D
Org. Perox. E	ORGANIC PEROXIDES - Type E
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN ŤOXICITY - REPEATED EXPOSURE -
	Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -
	Category 3

History

Date of issue/ Date of : 2 December 2025

revision

Date of previous issue : 8 September 2025

Prepared by : EHS Version : 1.01

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) Europe 17/17