

# SAFETY DATA SHEET



Date of issue/Date of revision 18 December 2025

Version 10

## Section 1. Identification

**Product name** : AMERCOAT 370 DEEP TINT RESIN CANADA

**Product code** : 00371593

**Other means of identification** : Not available.

**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/ mixture** : Coating.

**Uses advised against** : Not applicable.

**Manufacturer** : PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272

**Emergency telephone number** : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
SETIQ Interior de la República: 800-00-214-00 (México)  
SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number** : 888-977-4762

## Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : **FLAMMABLE LIQUIDS** - Category 3  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1A  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
**Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:** 22.6% (oral), 22.6% (dermal), 47.7% (inhalation)  
This product contains TiO<sub>2</sub> which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO<sub>2</sub> is utilized as a raw material in a liquid coating formulation. In this case, the TiO<sub>2</sub> particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO<sub>2</sub> when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).

## Section 2. Hazards identification

### GHS label elements

#### Hazard pictograms



#### Signal word

: Danger

#### Hazard statements

: Flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause cancer.  
Causes damage to organs through prolonged or repeated exposure.

### Precautionary statements

#### Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### Response

: If exposed or concerned: Get medical advice or attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

#### Storage

: Store locked up.

#### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### Supplemental label elements

: Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.

#### Hazards not otherwise classified

: Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

#### Substance/mixture

: Mixture

#### Product name

: AMERCOAT 370 DEEP TINT RESIN CANADA

## Section 3. Composition/information on ingredients

| Ingredient name                                     | %       | CAS number |
|-----------------------------------------------------|---------|------------|
| Barium sulfate                                      | 15 - 40 | 7727-43-7  |
| crystalline silica, respirable powder (<10 microns) | 10 - 30 | 14808-60-7 |
| 4-methylpentan-2-one                                | 7 - 13  | 108-10-1   |
| titanium dioxide                                    | 5 - 10  | 13463-67-7 |
| Epoxy Resin (700<MW<=1100)                          | 5 - 10  | 25036-25-3 |
| Epoxy resin (MW ≤ 700)                              | 1 - 5   | 25068-38-6 |
| butanone                                            | 1 - 5   | 78-93-3    |
| xylene                                              | 1 - 5   | 1330-20-7  |
| ethylbenzene                                        | 0.1 - 1 | 100-41-4   |
| maleic anhydride                                    | <0.1    | 108-31-6   |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.

## Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Section 7. Handling and storage

- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                                     | Exposure limits                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| barium sulfate                                      | <b>ACGIH TLV (United States, 1/2025)</b><br>TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable fraction.<br><b>OSHA PEL (United States, 5/2018)</b><br>TWA 8 hours: 15 mg/m <sup>3</sup> . Form: Total dust.<br>TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Respirable fraction.                                                             |
| crystalline silica, respirable powder (<10 microns) | <b>ACGIH TLV (United States, 1/2025) [Silica, crystalline]</b><br>TWA 8 hours: 0.025 mg/m <sup>3</sup> . Form: Respirable fraction.<br><b>OSHA PEL Z3 (United States, 6/2016)</b><br>TWA 8 hours: 250 / (%SiO <sub>2</sub> +5) mppcf. Form: Respirable.<br>TWA 8 hours: 10 / (%SiO <sub>2</sub> +2) mg/m <sup>3</sup> . Form: Respirable. |
| 4-methylpentan-2-one                                | <b>ACGIH TLV (United States, 1/2025)</b><br>TWA 8 hours: 20 ppm.<br>STEL 15 minutes: 75 ppm.<br><b>OSHA PEL (United States, 5/2018)</b><br>TWA 8 hours: 100 ppm.<br>TWA 8 hours: 410 mg/m <sup>3</sup> .                                                                                                                                  |
| titanium dioxide                                    | <b>ACGIH TLV (United States, 1/2025)</b><br>TWA 8 hours: 2.5 mg/m <sup>3</sup> . Form: respirable fraction, finescale particles.                                                                                                                                                                                                          |

## Section 8. Exposure controls/personal protection

Epoxy Resin (700<MW<=1100)  
Epoxy resin (MW ≤ 700)  
butanone

xylene

ethylbenzene

maleic anhydride

### OSHA PEL (United States, 5/2018)

TWA 8 hours: 15 mg/m<sup>3</sup>. Form: Total dust.  
None.

None.

### ACGIH TLV (United States, 1/2025)

Absorbed through skin.

TWA 8 hours: 75 ppm.

STEL 15 minutes: 150 ppm.

### OSHA PEL (United States, 5/2018)

TWA 8 hours: 200 ppm.

TWA 8 hours: 590 mg/m<sup>3</sup>.

### ACGIH TLV (United States, 1/2025) [p-xylene and mixtures containing p-xylene]

Ototoxicant.

TWA 8 hours: 20 ppm.

### OSHA PEL (United States, 5/2018) [Xylenes]

TWA 8 hours: 100 ppm.

TWA 8 hours: 435 mg/m<sup>3</sup>.

### ACGIH TLV (United States, 1/2025)

Ototoxicant.

TWA 8 hours: 20 ppm.

### OSHA PEL (United States, 5/2018)

TWA 8 hours: 100 ppm.

TWA 8 hours: 435 mg/m<sup>3</sup>.

### ACGIH TLV (United States, 1/2025) Skin sensitizer, Inhalation sensitizer.

TWA 8 hours: 0.01 mg/m<sup>3</sup>. Form: Inhalable fraction and vapor.

### OSHA PEL (United States, 5/2018)

TWA 8 hours: 0.25 ppm.

TWA 8 hours: 1 mg/m<sup>3</sup>.

#### Key to abbreviations

A = Acceptable Maximum Peak  
ACGIH = American Conference of Governmental Industrial Hygienists.  
C = Ceiling Limit  
F = Fume  
IPEL = Internal Permissible Exposure Limit  
OSHA = Occupational Safety and Health Administration.  
R = Respirable  
Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

S = Potential skin absorption  
SR = Respiratory sensitization  
SS = Skin sensitization  
STEL = Short term Exposure limit values  
TD = Total dust  
TLV = Threshold Limit Value  
TWA = Time Weighted Average

#### Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## Section 8. Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

## Section 9. Physical and chemical properties

### Appearance

**Physical state** : Liquid.

**Color** : White.

**Odor** : Characteristic.

**pH** : Not applicable.

**Melting point** : Not available.

**Boiling point** : >37.78°C (>100°F)

**Flash point** : Closed cup: 28°C (82.4°F)

**Auto-ignition temperature** : Not available.

## Section 9. Physical and chemical properties

**Decomposition temperature** : Not available.

**Flammability** : Not available.

**Lower and upper explosive (flammable) limits** : Not available.

**Vapor pressure** : Not available.

**Vapor density** : Not available.

**Relative density** : 1.86

**Density ( lbs / gal )** : 15.52

**Solubility(ies)**

| Media | Result |
|-------|--------|
|-------|--------|

|            |             |
|------------|-------------|
| cold water | Not soluble |
|------------|-------------|

**Partition coefficient: n-octanol/water** : Not applicable.

**Viscosity** :  Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

**% Solid. (w/w)** : 82.428

### Particle characteristics

**Median particle size** : Not applicable.

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:  
oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials:  
carbon oxides sulfur oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name   | Result                                  | Dose                 |
|---------------------------|-----------------------------------------|----------------------|
| Barium sulfate            | Rat - Oral - LD50                       | >5000 mg/kg          |
| 4-methylpentan-2-one      | Rat - Dermal - LD50                     | >2000 mg/kg          |
|                           | Rat - Oral - LD50                       | 2.08 g/kg            |
|                           | Rabbit - Dermal - LD50                  | >5000 mg/kg          |
| titanium dioxide          | Rat - Inhalation - LC50 Vapor           | 11 mg/l [4 hours]    |
|                           | Rat - Oral - LD50                       | >5000 mg/kg          |
|                           | Rabbit - Dermal - LD50                  | >5000 mg/kg          |
|                           | Rat - Inhalation - LC50 Dusts and mists | >6.82 mg/l [4 hours] |
| Epoxy Resin (700<MW≤1100) | Rat - Oral - LD50                       | >2000 mg/kg          |
| Epoxy resin (MW ≤ 700)    | Rat - Dermal - LD50                     | >2000 mg/kg          |
|                           | Rat - Oral - LD50                       | >2 g/kg              |
|                           | Rabbit - Dermal - LD50                  | >2 g/kg              |
| butanone                  | Rabbit - Dermal - LD50                  | 6480 mg/kg           |
|                           | Rat - Oral - LD50                       | 2737 mg/kg           |
| xylene                    | Rat - Oral - LD50                       | 4.3 g/kg             |
|                           | Rabbit - Dermal - LD50                  | 1.7 g/kg             |
| ethylbenzene              | Rat - Oral - LD50                       | 3.5 g/kg             |
|                           | Rabbit - Dermal - LD50                  | 17.8 g/kg            |
|                           | Rat - Inhalation - LC50 Vapor           | 17.8 mg/l [4 hours]  |
| maleic anhydride          | Rabbit - Dermal - LD50                  | 2620 mg/kg           |
|                           | Rat - Oral - LD50                       | 400 mg/kg            |

**Product Conclusion** : There are no data available on the mixture itself.

#### Skin corrosion/irritation

| Product/ingredient name | Species                           | Dose                                                                                   | Score |
|-------------------------|-----------------------------------|----------------------------------------------------------------------------------------|-------|
| Epoxy resin (MW ≤ 700)  | Rabbit - Skin - Mild irritant     | -                                                                                      | -     |
| xylene                  | Rabbit - Skin - Moderate irritant | Amount/concentration applied:<br>500 mg<br>Duration of treatment/exposure:<br>24 hours | -     |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Serious eye damage/eye irritation

| Product/ingredient name | Species                       | Dose | Score |
|-------------------------|-------------------------------|------|-------|
| Epoxy resin (MW ≤ 700)  | Rabbit - Eyes - Mild irritant | -    | -     |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Respiratory corrosion/irritation

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Sensitization

| Product/ingredient name | Species                  | Result              |
|-------------------------|--------------------------|---------------------|
| Epoxy resin (MW ≤ 700)  | Mouse - skin<br>OECD 429 | Result: Sensitizing |

#### Skin

**Conclusion/Summary** : There are no data available on the mixture itself.

## Section 11. Toxicological information

### Respiratory

**Conclusion/Summary** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Classification

| Product/ingredient name                             | OSHA | IARC | NTP                             |
|-----------------------------------------------------|------|------|---------------------------------|
| crystalline silica, respirable powder (<10 microns) | +    | 1    | Known to be a human carcinogen. |
| 4-methylpentan-2-one                                | -    | 2B   | -                               |
| titanium dioxide                                    | -    | 2B   | -                               |
| xylene                                              | -    | 3    | -                               |
| ethylbenzene                                        | -    | 2B   | -                               |

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Result                                                                                       |
|-------------------------|----------------------------------------------------------------------------------------------|
| 4-methylpentan-2-one    | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| butanone                | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3             |
| xylene                  | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name                             | Result                                                                                            |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------|
| crystalline silica, respirable powder (<10 microns) | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (inhalation) - Category 1                      |
| ethylbenzene                                        | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2                  |
| maleic anhydride                                    | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory system) (inhalation) - Category 1 |

### Target organs

: Contains material which causes damage to the following organs: liver, spleen, brain, bone marrow, central nervous system (CNS).

Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, the reproductive system, upper respiratory tract, immune system, skin, eye, lens or cornea.

### Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

## Section 11. Toxicological information

### Information on the likely routes of exposure

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. This product contains TiO<sub>2</sub> which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO<sub>2</sub> is utilized as a raw material in a liquid coating formulation. In this case, the TiO<sub>2</sub> particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO<sub>2</sub> when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Short term exposure

- Potential immediate effects** : There are no data available on the mixture itself.

## Section 11. Toxicological information

**Potential delayed effects** : There are no data available on the mixture itself.

### Long term exposure

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

**Conclusion/Summary** : There are no data available on the mixture itself.

**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Product/ingredient name             | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| AMERCOAT 370 DEEP TINT RESIN CANADA | 6531.6       | 3884.3         | N/A                      | 41.6                       | 5.7                                 |
| barium sulfate                      | N/A          | 2500           | N/A                      | N/A                        | N/A                                 |
| 4-methylpentan-2-one                | 2080         | N/A            | N/A                      | 11                         | 1.5                                 |
| Epoxy Resin (700<MW<=1100)          | 2500         | 2500           | N/A                      | N/A                        | N/A                                 |
| Epoxy resin (MW ≤ 700)              | 2500         | 2500           | N/A                      | N/A                        | N/A                                 |
| butanone                            | 2737         | 6480           | N/A                      | N/A                        | N/A                                 |
| xylene                              | 4300         | 1700           | N/A                      | 11                         | 1.5                                 |
| ethylbenzene                        | 3500         | 17800          | N/A                      | 17.8                       | 1.5                                 |
| maleic anhydride                    | 400          | 2620           | N/A                      | N/A                        | N/A                                 |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name | Result                                             | Species                             |
|-------------------------|----------------------------------------------------|-------------------------------------|
| 4-methylpentan-2-one    | Acute - LC50<br>>179 mg/l [96 hours]               | Fish                                |
| titanium dioxide        | Acute - LC50 - Fresh water<br>>100 mg/l [48 hours] | Daphnia - <i>Daphnia magna</i>      |
| Epoxy resin (MW ≤ 700)  | Chronic - NOEC<br>0.3 mg/l [21 days]               | Daphnia                             |
|                         | Acute - LC50<br>1.8 mg/l [48 hours]                | Daphnia                             |
| ethylbenzene            | Acute - EC50 - Fresh water<br>1.8 mg/l [48 hours]  | Daphnia                             |
|                         | Chronic - NOEC - Fresh water<br>1 mg/l             | Daphnia - <i>Ceriodaphnia dubia</i> |

## Section 12. Ecological information

**Conclusion/Summary** : Not available.

### Persistence and degradability

| Product/ingredient name | Result                               |
|-------------------------|--------------------------------------|
| 4-methylpentan-2-one    | OECD 301F<br>83% [28 days] - Readily |
| Epoxy resin (MW ≤ 700)  | OECD 301F<br>5% [28 days]            |
| ethylbenzene            | 79% [10 days] - Readily              |

**Conclusion/Summary** : Not available.

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| 4-methylpentan-2-one    | 1.9                | -           | Low       |
| Epoxy resin (MW ≤ 700)  | 3                  | 31          | Low       |
| butanone                | 0.3                | -           | Low       |
| xylene                  | 3.12               | 7.4 to 18.5 | Low       |
| ethylbenzene            | 3.6                | 79.43       | Low       |
| maleic anhydride        | -2.78              | -           | Low       |

### Mobility in soil

**Soil/Water partition coefficient** : Not available.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

**Product code** 00371593

**Date of issue** 18 December 2025 **Version** 10

**Product name** AMERCOAT 370 DEEP TINT RESIN CANADA

## 14. Transport information

|                             | DOT                            | IMDG            | IATA            |
|-----------------------------|--------------------------------|-----------------|-----------------|
| UN number                   | UN1263                         | UN1263          | UN1263          |
| UN proper shipping name     | PAINT                          | PAINT           | PAINT           |
| Transport hazard class (es) | 3                              | 3               | 3               |
| Packing group               | III                            | III             | III             |
| Environmental hazards       | No.                            | No.             | No.             |
| Marine pollutant substances | Not applicable.                | Not applicable. | Not applicable. |
| Product RQ (lbs)            | 3838.3                         | Not applicable. | Not applicable. |
| RQ substances               | (xylene, 4-methylpentan-2-one) | Not applicable. | Not applicable. |

### Additional information

**DOT** : Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**IMDG** : None identified.

**IATA** : None identified.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

## Section 15. Regulatory information

### United States

**United States inventory (TSCA 8b)** : All components are active or exempted.

### SARA 302/304

**SARA 304 RQ** : Not applicable.

### Composition/information on ingredients

No products were found.

### SARA 311/312

**Classification** :  **FLAMMABLE LIQUIDS** - Category 3  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1A  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
HNOC - Defatting irritant

## Section 15. Regulatory information

Composition/information on ingredients

| Name                                                | %            | Classification                                                                                                                                                                                                                                                                                                       |
|-----------------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| crystalline silica, respirable powder (<10 microns) | ≥20 - ≤50    | CARCINOGENICITY - Category 1A<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1                                                                                                                                                                                                                     |
| 4-methylpentan-2-one                                | ≥10 - ≤12    | FLAMMABLE LIQUIDS - Category 2<br>ACUTE TOXICITY (inhalation) - Category 4<br>EYE IRRITATION - Category 2A<br>CARCINOGENICITY - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>HNOC - Defatting irritant                                                          |
| titanium dioxide                                    | ≥5.0 - ≤10   | CARCINOGENICITY - Category 2                                                                                                                                                                                                                                                                                         |
| Epoxy Resin (700<MW≤1100)                           | ≥5.0 - ≤10   | COMBUSTIBLE DUSTS<br>SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1B                                                                                                                                                                                                |
| Epoxy resin (MW ≤ 700)                              | ≥1.0 - ≤4.3  | SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1B                                                                                                                                                                                                                     |
| butanone                                            | ≥1.0 - ≤4.0  | FLAMMABLE LIQUIDS - Category 2<br>EYE IRRITATION - Category 2A<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>HNOC - Defatting irritant                                                                                                                                      |
| xylene                                              | ≥0.10 - ≤2.9 | FLAMMABLE LIQUIDS - Category 3<br>ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>ASPIRATION HAZARD - Category 1 |
| ethylbenzene                                        | <1.0         | FLAMMABLE LIQUIDS - Category 2<br>ACUTE TOXICITY (inhalation) - Category 4<br>CARCINOGENICITY - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>ASPIRATION HAZARD - Category 1<br>HNOC - Defatting irritant                                                                         |
| maleic anhydride                                    | <0.10        | COMBUSTIBLE DUSTS<br>ACUTE TOXICITY (oral) - Category 4<br>SKIN CORROSION - Category 1B<br>SERIOUS EYE DAMAGE - Category 1<br>RESPIRATORY SENSITIZATION - Category 1A<br>SKIN SENSITIZATION - Category 1A<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1                                         |

SARA 313

Chemical nameCAS numberConcentration

United States

Page: 16/17

## Section 15. Regulatory information

|                       |                                                                                                      |           |         |
|-----------------------|------------------------------------------------------------------------------------------------------|-----------|---------|
| Supplier notification |  methylpentan-2-one | 108-10-1  | 7 - 13  |
|                       | xylene                                                                                               | 1330-20-7 | 1 - 5   |
|                       | ethylbenzene                                                                                         | 100-41-4  | 0.1 - 1 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.**

### California Prop. 65

 **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications.  
The customer is responsible for determining the PPE code for this material.

Date of previous issue : 2/6/2024

Organization that prepared the SDS : EHS

Key to abbreviations : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

 Indicates information that has changed from previously issued version.

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*