

SAFETY DATA SHEET

Date of issue/Date of revision

: 18 December 2025

Version

: 1.01



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMA SAILADVANCE NX BROWN

Product code : 000010024034

Other means of identification

00444627; 00444629 ; 00482020 ; 00482039 ; 30013528

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Antifouling products

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Acute Tox. 4, H302
Acute Tox. 4, H332
Skin Irrit. 2, H315
Eye Dam. 1, H318
Skin Sens. 1, H317
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Code : 000010024034

Date of issue/Date of revision

: 18 December 2025

SIGMA SAILADVANCE NX BROWN

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Flammable liquid and vapor.
Harmful if swallowed or if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Very toxic to aquatic life with long lasting effects.

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

Response

: Collect spillage. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P210, P273, P391, P305 + P351 + P338, P501

Hazardous ingredients

: dicopper oxide; rosin; bis(1-hydroxy-1H-pyridine-2-thionato-O,S)copper; 4,5-dichloro-2-octyl-2H-isothiazol-3-one and octhiline (ISO)

Supplemental label elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 2: Hazards identification

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. : Based on available data, the classification criteria are not met.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
 copper oxide	REACH #: 01-2119513794-36 EC: 215-270-7 CAS: 1317-39-1 Index: 029-002-00-X	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 3.34 mg/l M [Acute] = 100 M [Chronic] = 10	[1] [2]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤17	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
rosin	REACH #: 01-2119480418-32 EC: 232-475-7 CAS: 8050-09-7 Index: 650-015-00-7	≥5.0 - ≤10	Skin Sens. 1, H317	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≥1.0 - ≤5.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Hydrocarbons, C9, aromatics > 0.1% cumene	REACH #: 01-2119455851-35	≥0.10 - ≤2.2	Flam. Liq. 3, H226 Carc. 1B, H350	Carc. 1B, H350: C ≥ 10%	[1] [2]

Code : 000010024034 Date of issue/Date of revision : 18 December 2025
SIGMA SAILADVANCE NX BROWN

SECTION 3: Composition/information on ingredients

	EC: 918-668-5 CAS: 128601-23-0		STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066		
bis(1-hydroxy-1H-pyridine-2-thionato-O,S)copper	EC: 238-984-0 CAS: 14915-37-8	≥1.0 - ≤4.5	Acute Tox. 4, H302 Acute Tox. 2, H330 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1075 mg/kg ATE [Inhalation (dusts and mists)] = 0.07 mg/l M [Acute] = 100 M [Chronic] = 100	[1]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	<1.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 567 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (dusts and mists)] = 0.16 mg/l Skin Corr. 1, H314: C ≥ 5% Skin Irrit. 2, H315: 0.025% ≤ C < 5% Eye Dam. 1, H318: C ≥ 3% Eye Irrit. 2, H319: 0.025% ≤ C < 3% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
copper(II) oxide	REACH #: 01-2119502447-44 EC: 215-269-1 CAS: 1317-38-0 Index: 029-016-00-6	≤1.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 100 M [Chronic] = 10	[1]
copper	REACH #: 01-2119480154-42 EC: 231-159-6 CAS: 7440-50-8	<1.0	Aquatic Acute 1, H400 Aquatic Chronic 3, H412	M [Acute] = 1	[1]
octhilinone (ISO)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.0010	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: Harmful if inhaled.
Skin contact	: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 4: First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
sulfur oxides
carbonyl halides
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up

- Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- 6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
dicopper oxide	ACGIH TLV (United States, 1/2025) [copper fume] TWA 8 hours: 0.2 mg/m³. Form: Fume.
xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.
rosin	ACGIH TLV (United States, 1/2025) [resin acids] Skin sensitizer , Inhalation sensitizer. TWA 8 hours: 0.001 mg/m³ (as total Resin acids). Form: Inhalable fraction.
ethylbenzene	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m³. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m³.
1-methoxy-2-propanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³.
Hydrocarbons, C9, aromatics > 0.1% cumene	EU OEL (Europe) TWA: 19 ppm. TWA: 100 mg/m³.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
dicopper oxide	DNEL - Workers - Long term - Inhalation DNEL - Workers - Long term - Inhalation DNEL - Workers - Long term - Dermal DNEL - General population - Long term - Oral DNEL - General population - Short term - Oral DNEL - General population - Long term - Oral DNEL - General population - Long term - Inhalation DNEL - General population - Long term - Inhalation	Local Systemic Systemic Systemic Systemic Systemic Local Systemic
xylene		1 mg/m³ 1 mg/m³ 137 mg/kg bw/day 0.041 mg/kg bw/day 0.082 mg/kg bw/day 5 mg/kg bw/day 65.3 mg/m³ 65.3 mg/m³
English (US)		Europe 8/21

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 8: Exposure controls/personal protection

ethylbenzene	DNEL - General population - Long term - Dermal	Systemic	125 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	212 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Local	221 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	221 mg/m³
	DNEL - General population - Short term - Inhalation	Local	260 mg/m³
	DNEL - General population - Short term - Inhalation	Systemic	260 mg/m³
	DNEL - Workers - Short term - Inhalation	Local	442 mg/m³
	DNEL - Workers - Short term - Inhalation	Systemic	442 mg/m³
	DMEL - Workers - Long term - Inhalation	Local	442 mg/m³
	DMEL - Workers - Short term - Inhalation	Systemic	884 mg/m³
1-methoxy-2-propanol	DNEL - General population - Long term - Oral	Systemic	1.6 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	15 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	77 mg/m³
	DNEL - Workers - Long term - Dermal	Systemic	180 mg/kg bw/day
	DNEL - Workers - Short term - Inhalation	Local	293 mg/m³
	DNEL - General population - Long term - Oral	Systemic	33 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	43.9 mg/m³
	DNEL - General population - Long term - Dermal	Systemic	78 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	183 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Systemic	369 mg/m³
Hydrocarbons, C9, aromatics > 0.1% cumene	DNEL - Workers - Short term - Inhalation	Local	553.5 mg/m³
	DNEL - Workers - Short term - Inhalation	Systemic	553.5 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	150 mg/m³
	DNEL - Workers - Long term - Dermal	Systemic	25 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	32 mg/m³
	DNEL - General population - Long term - Dermal	Systemic	11 mg/kg bw/day
	DNEL - General population - Long term - Oral	Systemic	11 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Local	1 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	1 mg/m³
	DNEL - Workers - Long term - Dermal	Systemic	137 mg/kg bw/day
copper(II) oxide	DNEL - General population - Long term - Oral	Systemic	0.041 mg/kg bw/day
	DNEL - General population - Short term - Oral	Systemic	0.082 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic	137 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	137 mg/kg bw/day
	DNEL - General population - Short term - Dermal	Systemic	273 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	Systemic	273 mg/kg bw/day
copper			

PNECs

Product/ingredient name	Compartment Detail - Method	Value
dicopper oxide	Fresh water	0.0078 mg/l
	Fresh water sediment	87.1 mg/kg dw
	Marine water	0.0056 mg/l
	Marine water sediment	676 mg/kg dw
	Soil	64.6 mg/kg dw
	Sewage Treatment Plant	0.23 mg/l
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage Treatment Plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dw
	Marine water sediment	12.46 mg/kg dw

Code : 000010024034 Date of issue/Date of revision : 18 December 2025
SIGMA SAILADVANCE NX BROWN

SECTION 8: Exposure controls/personal protection

rosin	Soil	2.31 mg/kg
	Fresh water - Assessment Factors	0.002 mg/l
	Marine water - Assessment Factors	0 mg/l
	Sewage Treatment Plant - Assessment Factors	1000 mg/l
	Fresh water sediment - Equilibrium Partitioning	0.007 mg/kg dwt
ethylbenzene	Marine water sediment - Equilibrium Partitioning	0.001 mg/kg dwt
	Soil - Equilibrium Partitioning	0 mg/kg dwt
	Fresh water - Assessment Factors	0.1 mg/l
	Marine water - Assessment Factors	0.01 mg/l
	Sewage Treatment Plant - Assessment Factors	9.6 mg/l
zinc oxide	Fresh water sediment - Equilibrium Partitioning	13.7 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	1.37 mg/kg dwt
	Soil - Equilibrium Partitioning	2.68 mg/kg dwt
	Secondary Poisoning	20 mg/kg
	Fresh water - Sensitivity Distribution	20.6 µg/l
1-methoxy-2-propanol	Marine water - Sensitivity Distribution	6.1 µg/l
	Fresh water sediment - Sensitivity Distribution	117 mg/kg dwt
	Sewage Treatment Plant - Assessment Factors	52 µg/l
	Marine water sediment - Assessment Factors	56.5 mg/kg dwt
	Soil - Sensitivity Distribution	35.6 mg/kg dwt
	Fresh water - Assessment Factors	10 mg/l
	Marine water - Assessment Factors	1 mg/l
	Sewage Treatment Plant - Assessment Factors	100 mg/l
	Fresh water sediment - Equilibrium Partitioning	41.6 mg/kg
	Marine water sediment - Equilibrium Partitioning	4.17 mg/kg
	Soil - Equilibrium Partitioning	2.47 mg/kg

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use,

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 8: Exposure controls/personal protection

as included in the user's risk assessment.

Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapor (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Color

Odor

Melting point/freezing point

Boiling point or initial boiling point and boiling range

Flammability

Lower and upper explosion limit

Flash point

Auto-ignition temperature

Decomposition temperature

pH

Viscosity

Solubility

: Liquid.

: Not available.

: Characteristic.

: Not determined.

: >37.78°C

: Not determined. There are no data available on the mixture itself.

: Not available.

: Closed cup: 25°C

:

Ingredient name	°C	°F	Method
 methoxy-2-propanol	270	518	

: Stable under recommended storage and handling conditions (see Section 7).

: Not applicable. insoluble in water.

: Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s

:

Code : 000010024034 Date of issue/Date of revision : 18 December 2025
SIGMA SAILADVANCE NX BROWN

SECTION 11: Toxicological information

Product/ingredient name	Result	Dose / Exposure
copper oxide	Rat - Oral - LD50 Rat - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists	500 mg/kg >2000 mg/kg 3.34 mg/l [4 hours]
xylene	Rat - Oral - LD50 Rabbit - Dermal - LD50	4.3 g/kg 1.7 g/kg
rosin	Rat - Oral - LD50 Rat - Dermal - LD50	7600 mg/kg >2000 mg/kg
ethylbenzene	Rat - Oral - LD50 Rabbit - Dermal - LD50	3.5 g/kg 17.8 g/kg
zinc oxide	Rat - Inhalation - LC50 Vapor Rat - Oral - LD50 Rat - Dermal - LD50	17.8 mg/l [4 hours] >5000 mg/kg >2000 mg/kg
1-methoxy-2-propanol	Rat - Inhalation - LC50 Dusts and mists Rabbit - Dermal - LD50 Rat - Oral - LD50	>5700 mg/m ³ [4 hours] 13 g/kg 5.2 g/kg
Hydrocarbons, C9, aromatics > 0.1% cumene	Rat - Inhalation - LC50 Vapor Rat - Female - Oral - LD50	>7000 ppm [6 hours] 3492 mg/kg
bis(1-hydroxy-1H-pyridine-2-thionato-O,S)copper	Rabbit - Dermal - LD50 Rat - Oral - LD50	>3160 mg/kg 1075 mg/kg
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Rat - Inhalation - LC50 Dusts and mists <i>Toxic effects:</i> Eye - Lacrimation Lung, Thorax, or Respiration - Dyspnea Lung, Thorax, or Respiration - Respiratory stimulation Rat - Oral - LD50	70 mg/m ³ [4 hours] 567 mg/kg
copper(II) oxide	Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists Rat - Oral - LD50	3.9 g/kg 0.16 mg/l [4 hours] >2000 mg/kg
copper	Rat - Inhalation - LC50 Dusts and mists Rat - Oral - LD50	>5.11 mg/l [4 hours] 125 mg/kg
octhilinone (ISO)	Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists	311 mg/kg 0.27 mg/l [4 hours]

Acute toxicity estimates

Route	ATE value
Oral	1617.57 mg/kg
Dermal	10274.46 mg/kg
Inhalation (vapors)	57.52 mg/l
Inhalation (dusts and mists)	2.38 mg/l

Conclusion/Summary : Harmful if swallowed or if inhaled.

Irritation/Corrosion

Product/ingredient name	Result
xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

Skin : Causes skin irritation.

Eyes : Causes serious eye damage.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 11: Toxicological information

Product/ingredient name	Test	Result
octhilinone (ISO)	Mouse - skin OECD 429	Sensitizing

Conclusion/Summary

Skin : May cause an allergic skin reaction.
Respiratory : Based on available data, the classification criteria are not met.
Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
1-methoxy-2-propanol	Category 3	-	Narcotic effects
Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Category 3	-	Respiratory tract irritation

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9, aromatics > 0.1% cumene	ASPIRATION HAZARD - Category 1

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Harmful if inhaled.
Ingestion : Harmful if swallowed.
Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Eye contact : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 11: Toxicological information

- Ingestion** : Adverse symptoms may include the following:
stomach pains
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

Potential chronic health effects

- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.
- Other information** : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Dose / Exposure
dicopper oxide ethylbenzene	LC50	Fish	0.003 mg/l [96 hours]
	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
zinc oxide	Chronic - NOEC - Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	1 mg/l
	Acute - EC50 - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	0.481 mg/l [48 hours]
1-methoxy-2-propanol	Acute - EC50	Algae	0.17 mg/l [72 hours]
	Chronic - NOEC - Fresh water	Algae	0.017 mg/l [72 hours]
Hydrocarbons, C9, aromatics > 0.1% cumene	Acute - LC50 - Fresh water	Fish - Goldfish	>4500 mg/l [96 hours]
	Acute - LC50	Daphnia - Daphnia	23300 mg/l [48 hours]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	EC50	Daphnia	3.2 mg/l [48 hours]
	LC50	Fish	9.2 mg/l [96 hours]
	Acute - EC50 - Marine water	Algae - Diatom - <i>Nitzschia pungens</i>	267.368 µg/l [96 hours]
	Chronic - NOEC - Marine water	Algae - Diatom - <i>Nitzschia pungens</i>	19.789 µg/l [96 hours]
	Acute - LC50 - Marine water	Crustaceans - Brine shrimp - <i>Artemia sp.</i>	0.318 mg/l [48 hours]
	Acute - LC50 - Fresh water	Fish	0.0027 mg/l [96 hours]
copper	Chronic - NOEC - Fresh water	Fish	0.00056 mg/l [97 days]
	Acute - LC50	Fish	810 ppb [96 hours]
	Chronic - EC10	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	8.1 µg/l [21 days]

Conclusion/Summary : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
ethylbenzene	-	79% [10 days] - Readily	
Hydrocarbons, C9, aromatics > 0.1% cumene	-	75% [28 days] - Readily	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
ethylbenzene	-	-	Readily
Hydrocarbons, C9, aromatics > 0.1% cumene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
rosin	1.9 to 7.7	-	High
ethylbenzene	3.6	79.43	Low
1-methoxy-2-propanol	<1	-	Low
octhilinone (ISO)	2.45	-	Low

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/Water partition coefficient

Product/ingredient name	logKoc	Koc
ethylbenzene	2.2	170.406
1-methoxy-2-propanol	1	10.447
4,5-dichloro-2-octyl-2H-isothiazol-3-one	3.4	2562.01
octhillinone (ISO)	2.8	706.605

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste :

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 13: Disposal considerations

Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
---------------------	--

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(dicopper oxide)	Not applicable.

Additional information

ADR/RID	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (D/E)
ADN	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user	: Transport within user’s premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
-----------------------------------	---

14.7 Maritime transport in bulk according to IMO instruments	: Not applicable.
--	-------------------

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
SIGMA SAILADVANCE NX BROWN	3

Labeling : Not applicable.

Other EU regulations

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c E1

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- IMDG = International Maritime Dangerous Goods
- IATA = International Air Transport Association

Full text of abbreviated H statements

Code : 000010024034	Date of issue/Date of revision : 18 December 2025
SIGMA SAILADVANCE NX BROWN	

SECTION 16: Other information

H225 H226 H301 H302 H304 H311 H312 H314 H315 H317 H318 H319 H330 H332 H335 H336 H350 H373 H400 H410 H411 H412 EUH066 EUH071	Highly flammable liquid and vapor. Flammable liquid and vapor. Toxic if swallowed. Harmful if swallowed. May be fatal if swallowed and enters airways. Toxic in contact with skin. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Corrosive to the respiratory tract.
--	---

Full text of classifications [CLP/GHS]

Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Carc. 1B Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Skin Corr. 1 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT RE 2 STOT SE 3	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
---	---

History

Date of issue/ Date of revision	: 18 December 2025
Date of previous issue	: 2 October 2025
Prepared by	: EHS
Version	: 1.01

Disclaimer

Code	: 000010024034	Date of issue/Date of revision	: 18 December 2025
SIGMA SAILADVANCE NX BROWN			

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.