

# SAFETY DATA SHEET

Date of issue/Date of revision

: 2 January 2026

Version

: 4.09



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : SIGMAFAST 20 REDBROWN

Product code : 000001103669

### Other means of identification

00178249; 00199088 ; 00392641 ; 00429234

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Varossieau Suriname NV,  
Mastanaweg 4, Paramaribo,  
SURINAME

Tel: 00597 484447

Fax: 00597 483785

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number : 0031 (0)20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 3, H335

Aquatic Chronic 3, H412


The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms :



Signal word : Warning

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 2: Hazards identification**

<b>Hazard statements</b>	: Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
<b><u>Precautionary statements</u></b>	
<b>Prevention</b>	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.
<b>Response</b>	: IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
<b>Storage</b>	: Store in a well-ventilated place. Keep container tightly closed.
<b>Disposal</b>	: Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P210, P273, P304 + P312, P403 + P233, P501
<b>Hazardous ingredients</b>	: xylene
<b>Supplemental label elements</b>	: Contains Octadecanamide, N,N'-1,6-hexanediylibis[12-hydroxy- and maleic anhydride]. May produce an allergic reaction.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Not applicable.
<b><u>Special packaging requirements</u></b>	
<b>Containers to be fitted with child-resistant fastenings</b>	: Not applicable.
<b>Tactile warning of danger</b>	: Not applicable.

**2.3 Other hazards**

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: Prolonged or repeated contact may dry skin and cause irritation.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]

Code : 000001103669

Date of issue/Date of revision

: 2 January 2026

SIGMAFAST 20 REDBROWN

**SECTION 3: Composition/information on ingredients**

ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤1.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	REACH #: 01-2119977130-42 EC: 939-607-9 CAS: 1474044-65-9	≤0.94	Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 570 mg/kg ATE [Dermal] = 528 mg/kg M [Acute] = 10 M [Chronic] = 1	[1]
Octadecanamide, N, N'-1,6-hexanediylibis [12-hydroxy-	CAS: 55349-01-4	<1.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	-	[1] [2]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	<0.0010	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : May cause respiratory irritation.

**Skin contact** : Causes skin irritation. Defatting to the skin.

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 5: Firefighting measures

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

#### Protective measures

- Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Advice on general occupational hygiene

- Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	<b>EU OEL (Europe, 1/2022) [xylene, mixed isomers]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m <sup>3</sup> .
ethylbenzene	<b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m <sup>3</sup> .

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 8: Exposure controls/personal protection**

toluene	STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m <sup>3</sup> . <b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 192 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. STEL 15 minutes: 384 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm.
maleic anhydride	<b>ACGIH TLV (United States, 1/2025)</b> A4. Skin sensitiser , Inhalation sensitiser. TWA 8 hours: 0.01 mg/m <sup>3</sup> . Form: Inhalable fraction and vapor.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles.

**Skin protection****Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves**

: For prolonged or repeated handling, use the following type of gloves:

Not recommended: nitrile rubber

Recommended: polyvinyl alcohol (PVA), Viton®

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 8: Exposure controls/personal protection**

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

**Physical state** : Liquid.

**Colour** : Brownish-red.

**Odour** : Aromatic.

**Odour threshold** : Not available.

**Melting point/freezing point** : Not determined.

**Initial boiling point and boiling range** : >37.78°C

**Flammability** : Not determined. There are no data available on the mixture itself.

**Upper/lower flammability or explosive limits** : Not available.

**Flash point****Auto-ignition temperature**

Ingredient name	°C	°F	Method
xylene	432	809.6	

**Decomposition temperature**

**pH** : Not applicable. insoluble in water.

**Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm<sup>2</sup>/s

**Solubility(ies)**

Media	Result
cold water	Not soluble

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure**

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 9: Physical and chemical properties**

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.30076	1.2				

<b>Relative density</b>	: 1.48
<b>Explosive properties</b>	: The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.
<b>Oxidising properties</b>	: Product does not present an oxidizing hazard.
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

**9.2 Other information**

<b>Explosive properties</b>	: The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.
<b>Oxidising properties</b>	: Product does not present an oxidizing hazard.

No additional information.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Causes serious eye irritation.  
 Causes skin irritation.  
 May cause respiratory irritation.

**Acute toxicity**

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 11: Toxicological information**

Product/ingredient name	Result	Dose / Exposure
XYLEMES	Rat - Oral - LD50	4.3 g/kg
ethylbenzene	Rabbit - Dermal - LD50	1.7 g/kg
	Rat - Oral - LD50	3.5 g/kg
	Rabbit - Dermal - LD50	17.8 g/kg
trizinc bis(orthophosphate)	Rat - Inhalation - LC50 Vapour	17.8 mg/l [4 hours]
	Rat - Oral - LD50	>5000 mg/kg
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethylidimethyl, ethyl sulphates	Rat - Inhalation - LC50 Dusts and mists	>5.7 mg/l [4 hours]
	Rat - Oral - LD50	570 mg/kg
toluene	Rabbit - Dermal - LD50	528 mg/kg
	Rat - Oral - LD50	5580 mg/kg
	Rat - Inhalation - LC50 Vapour	49 g/m <sup>3</sup> [4 hours]
maleic anhydride	Rabbit - Dermal - LD50	2620 mg/kg
	Rat - Oral - LD50	400 mg/kg

Acute toxicity estimates

Route	ATE value
Dermal	7423.03 mg/kg
Inhalation (vapours)	46.76 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

Skin : Causes skin irritation.

Eyes : Causes serious eye irritation.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitizationConclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene toluene	Category 3 Category 3	- -	Respiratory tract irritation Narcotic effects

Conclusion/Summary (Product) :

May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene toluene maleic anhydride	Category 2 Category 2 Category 1	- - inhalation	hearing organs - respiratory system

### Conclusion/Summary (Product) :

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

Conclusion/Summary (Product) : Based on available data, the classification criteria are not met.

**Information on likely routes of exposure** : Not available.

#### Potential acute health effects

- Inhalation** : May cause respiratory irritation.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Eye contact** : Causes serious eye irritation.

#### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Ingestion** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

##### Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

##### Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

#### Potential chronic health effects

- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 11: Toxicological information

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
ethylbenzene	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	1 mg/l
	Acute - LC50	Fish	0.112 mg/l [96 hours]
		Fish	0.026 mg/l [30 days]
	LC50	Fish	13.8 mg/l [96 hours]
		Fish	3.2 mg/m <sup>3</sup> [28 days]
		Daphnia	0.036 mg/l [48 hours]
		Daphnia	7 mg/m <sup>3</sup> [21 days]
		Algae	0.14 mg/l [72 hours]
	NOEC	Algae	10 mg/m <sup>3</sup> [72 hours]
		Daphnia	3.78 mg/l [48 hours]
		Fish	5.5 mg/l [96 hours]
toluene	EC50		
	LC50		

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79% [10 days] - Readily		
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	-	67.77% [28 days] - Readily		

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
ethylbenzene	-	-	Readily
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	-	-	Readily
toluene	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
ethylbenzene	3.6	79.43	Low
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	3.2	-	Low
toluene	2.73	90	Low
maleic anhydride	-2.78	-	Low

**12.4 Mobility in soil****Soil/water partition coefficient**

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
ethylbenzene	2.2	170.406
Octadecanamide, N,N'-1,6-hexanediylibis	4.3	20556.9
[12-hydroxy-toluene	2.1	117.115
maleic anhydride	1.1	11.4841

**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties**

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

**12.7 Other adverse effects**

No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

**SECTION 13: Disposal considerations**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**European waste catalogue (EWC)**

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

**Additional information**

**ADR/RID** : None identified.

**Tunnel code** : (D/E)

**IMDG** : None identified.

**IATA** : None identified.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 14: Transport information

14.7 Transport in bulk according to IMO instruments : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

None of the components are listed.

##### Other national and international regulations.

Explosive precursors : Not applicable.

##### Ozone depleting substances (EU 2024/590)

Not listed.

##### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

###### Category

P5c

### 15.2 Chemical safety assessment

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

##### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
Aquatic Chronic 3, H412	Calculation method

Code : 000001103669	Date of issue/Date of revision : 2 January 2026
SIGMAFAST 20 REDBROWN	

## SECTION 16: Other information

Full text of abbreviated H statements	: <table> <tr><td>H225</td><td>Highly flammable liquid and vapour.</td></tr> <tr><td>H226</td><td>Flammable liquid and vapour.</td></tr> <tr><td>H302</td><td>Harmful if swallowed.</td></tr> <tr><td>H304</td><td>May be fatal if swallowed and enters airways.</td></tr> <tr><td>H311</td><td>Toxic in contact with skin.</td></tr> <tr><td>H312</td><td>Harmful in contact with skin.</td></tr> <tr><td>H314</td><td>Causes severe skin burns and eye damage.</td></tr> <tr><td>H315</td><td>Causes skin irritation.</td></tr> <tr><td>H317</td><td>May cause an allergic skin reaction.</td></tr> <tr><td>H318</td><td>Causes serious eye damage.</td></tr> <tr><td>H319</td><td>Causes serious eye irritation.</td></tr> <tr><td>H332</td><td>Harmful if inhaled.</td></tr> <tr><td>H334</td><td>May cause allergy or asthma symptoms or breathing difficulties if inhaled.</td></tr> <tr><td>H335</td><td>May cause respiratory irritation.</td></tr> <tr><td>H336</td><td>May cause drowsiness or dizziness.</td></tr> <tr><td>H361d</td><td>Suspected of damaging the unborn child.</td></tr> <tr><td>H372</td><td>Causes damage to organs through prolonged or repeated exposure.</td></tr> <tr><td>H373</td><td>May cause damage to organs through prolonged or repeated exposure.</td></tr> <tr><td>H400</td><td>Very toxic to aquatic life.</td></tr> <tr><td>H410</td><td>Very toxic to aquatic life with long lasting effects.</td></tr> <tr><td>H412</td><td>Harmful to aquatic life with long lasting effects.</td></tr> <tr><td>H413</td><td>May cause long lasting harmful effects to aquatic life.</td></tr> <tr><td>EUH071</td><td>Corrosive to the respiratory tract.</td></tr> </table>	H225	Highly flammable liquid and vapour.	H226	Flammable liquid and vapour.	H302	Harmful if swallowed.	H304	May be fatal if swallowed and enters airways.	H311	Toxic in contact with skin.	H312	Harmful in contact with skin.	H314	Causes severe skin burns and eye damage.	H315	Causes skin irritation.	H317	May cause an allergic skin reaction.	H318	Causes serious eye damage.	H319	Causes serious eye irritation.	H332	Harmful if inhaled.	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	H335	May cause respiratory irritation.	H336	May cause drowsiness or dizziness.	H361d	Suspected of damaging the unborn child.	H372	Causes damage to organs through prolonged or repeated exposure.	H373	May cause damage to organs through prolonged or repeated exposure.	H400	Very toxic to aquatic life.	H410	Very toxic to aquatic life with long lasting effects.	H412	Harmful to aquatic life with long lasting effects.	H413	May cause long lasting harmful effects to aquatic life.	EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.																																														
H226	Flammable liquid and vapour.																																														
H302	Harmful if swallowed.																																														
H304	May be fatal if swallowed and enters airways.																																														
H311	Toxic in contact with skin.																																														
H312	Harmful in contact with skin.																																														
H314	Causes severe skin burns and eye damage.																																														
H315	Causes skin irritation.																																														
H317	May cause an allergic skin reaction.																																														
H318	Causes serious eye damage.																																														
H319	Causes serious eye irritation.																																														
H332	Harmful if inhaled.																																														
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.																																														
H335	May cause respiratory irritation.																																														
H336	May cause drowsiness or dizziness.																																														
H361d	Suspected of damaging the unborn child.																																														
H372	Causes damage to organs through prolonged or repeated exposure.																																														
H373	May cause damage to organs through prolonged or repeated exposure.																																														
H400	Very toxic to aquatic life.																																														
H410	Very toxic to aquatic life with long lasting effects.																																														
H412	Harmful to aquatic life with long lasting effects.																																														
H413	May cause long lasting harmful effects to aquatic life.																																														
EUH071	Corrosive to the respiratory tract.																																														
Full text of classifications [CLP/GHS]	: <table> <tr><td>Acute Tox. 3</td><td>ACUTE TOXICITY - Category 3</td></tr> <tr><td>Acute Tox. 4</td><td>ACUTE TOXICITY - Category 4</td></tr> <tr><td>Aquatic Acute 1</td><td>SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1</td></tr> <tr><td>Aquatic Chronic 1</td><td>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1</td></tr> <tr><td>Aquatic Chronic 3</td><td>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3</td></tr> <tr><td>Aquatic Chronic 4</td><td>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4</td></tr> <tr><td>Asp. Tox. 1</td><td>ASPIRATION HAZARD - Category 1</td></tr> <tr><td>Eye Dam. 1</td><td>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1</td></tr> <tr><td>Eye Irrit. 2</td><td>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2</td></tr> <tr><td>Flam. Liq. 2</td><td>FLAMMABLE LIQUIDS - Category 2</td></tr> <tr><td>Flam. Liq. 3</td><td>FLAMMABLE LIQUIDS - Category 3</td></tr> <tr><td>Repr. 2</td><td>REPRODUCTIVE TOXICITY - Category 2</td></tr> <tr><td>Resp. Sens. 1</td><td>RESPIRATORY SENSITISATION - Category 1</td></tr> <tr><td>Skin Corr. 1B</td><td>SKIN CORROSION/IRRITATION - Category 1B</td></tr> <tr><td>Skin Corr. 1C</td><td>SKIN CORROSION/IRRITATION - Category 1C</td></tr> <tr><td>Skin Irrit. 2</td><td>SKIN CORROSION/IRRITATION - Category 2</td></tr> <tr><td>Skin Sens. 1</td><td>SKIN SENSITISATION - Category 1</td></tr> <tr><td>Skin Sens. 1A</td><td>SKIN SENSITISATION - Category 1A</td></tr> <tr><td>STOT RE 1</td><td>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1</td></tr> <tr><td>STOT RE 2</td><td>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2</td></tr> <tr><td>STOT SE 3</td><td>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3</td></tr> </table>	Acute Tox. 3	ACUTE TOXICITY - Category 3	Acute Tox. 4	ACUTE TOXICITY - Category 4	Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4	Asp. Tox. 1	ASPIRATION HAZARD - Category 1	Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3	Repr. 2	REPRODUCTIVE TOXICITY - Category 2	Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1	Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	Skin Sens. 1	SKIN SENSITISATION - Category 1	Skin Sens. 1A	SKIN SENSITISATION - Category 1A	STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1	STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3				
Acute Tox. 3	ACUTE TOXICITY - Category 3																																														
Acute Tox. 4	ACUTE TOXICITY - Category 4																																														
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1																																														
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1																																														
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3																																														
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4																																														
Asp. Tox. 1	ASPIRATION HAZARD - Category 1																																														
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1																																														
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2																																														
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2																																														
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3																																														
Repr. 2	REPRODUCTIVE TOXICITY - Category 2																																														
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1																																														
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B																																														
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C																																														
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2																																														
Skin Sens. 1	SKIN SENSITISATION - Category 1																																														
Skin Sens. 1A	SKIN SENSITISATION - Category 1A																																														
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1																																														
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2																																														
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3																																														

### History

Date of issue/ Date of revision : 2 January 2026

Date of previous issue : 20 August 2025

Prepared by : EHS

Version : 4.09

### Disclaimer

Code : 000001103669  
SIGMAFAST 20 REDBROWN

Date of issue/Date of revision : 2 January 2026

## SECTION 16: Other information

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*