

SAFETY DATA SHEET

Date of issue/Date of revision

: 26 February 2026

Version

: 4.01



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMAPRIME 700 BAS YEL/GREEN

Product code : 000001202286

Other means of identification

00477460

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.
PO Box 7509, Dammam 31472
Saudi Arabia
Tel: 00966 138 47 31 00
Fax: 00966 138 47 17 34

**e-mail address of person
responsible for this SDS** : PS.ACEMEA@ppg.com

**1.4 Emergency telephone
number** : 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Repr. 1B, H360F

STOT RE 2, H373

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

:



: Danger

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 2: Hazards identification

- Hazard statements** : Flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May damage fertility.
May cause damage to organs through prolonged or repeated exposure.
Harmful to aquatic life with long lasting effects.
- Precautionary statements**
- Prevention** : Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour.
- Response** : IF exposed or concerned: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
P202, P280, P210, P260, P308 + P313, P501
- Hazardous ingredients** : Epoxy Resin (700<MW<=1100); Phenol, methylstyrenated; oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Quartz (SiO₂); Cashew, nutshell liq. and formaldehyde
- Supplemental label elements** : Not applicable.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Restricted to professional users.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.
- 2.3 Other hazards**
- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.
- Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Code : 000001202286

Date of issue/Date of revision

: 26 February 2026

SIGMAPRIME 700 BAS YEL/GREEN

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Epoxy Resin (700<MW <=1100)	REACH #: Exempt CAS: 25036-25-3	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤18	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Phenol, methylstyrenated	REACH #: 01-2119555274-38 EC: 270-966-8 CAS: 68512-30-1	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1] [3]
Solvent naphtha (petroleum), heavy arom. Nota(s) P	REACH #: 01-2119451097-39 EC: 265-198-5 CAS: 64742-94-5 Index: 649-424-00-3	≥1.0 - ≤5.0	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Repr. 1B, H360F	-	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
crystalline silica, respirable powder (<10 microns)	EC: 238-878-4 CAS: 14808-60-7	≥1.0 - ≤5.0	STOT RE 1, H372 (inhalation)	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	REACH #: 01-0000017900-73 EC: 432-840-2 CAS: 220926-97-6 Index: 616-201-00-7	≥1.0 - ≤5.0	Acute Tox. 4, H332 STOT RE 2, H373 (lungs) (inhalation) Aquatic Chronic 4, H413	ATE [Inhalation (dusts and mists)] = 3.56 mg/l	[1] [2]
Urea, polymer with formaldehyde, butylated	CAS: 68002-19-7	≥1.0 - ≤5.0	Aquatic Chronic 4, H413	-	[1]
Cashew, nutshell liq.	REACH #: 01-2119502450-57	≤1.6	Acute Tox. 4, H302 Acute Tox. 4, H312	ATE [Oral] = 500 mg/kg	[1]

Code : 000001202286 Date of issue/Date of revision : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 3: Composition/information on ingredients

	EC: 700-991-6 CAS: 8007-24-7		Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	ATE [Dermal] = 1100 mg/kg	
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤1.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
formaldehyde	REACH #: 01-2119488953-20 EC: 200-001-8 CAS: 50-00-0 Index: 605-001-00-5	<0.10	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg ATE [Inhalation (gases)] = 100 ppm Skin Corr. 1B, H314: C ≥ 25% Skin Irrit. 2, H315: 5% ≤ C < 25% Eye Dam. 1, H318: C ≥ 25% Eye Irrit. 2, H319: 5% ≤ C < 25% STOT SE 3, H335: C ≥ 5% EUH071: C ≥ 25%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Code : 000001202286

Date of issue/Date of revision

: 26 February 2026

SIGMAPRIME 700 BAS YEL/GREEN

SECTION 4: First aid measures

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
halogenated compounds
metal oxide/oxides
Formaldehyde.

5.3 Advice for firefighters

Code : 000001202286

Date of issue/Date of revision

: 26 February 2026

SIGMAPRIME 700 BAS YEL/GREEN

SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original

Code	: 000001202286	Date of issue/Date of revision	: 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN			

SECTION 7: Handling and storage

	container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)
See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters
Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.
1-methoxy-2-propanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³.
crystalline silica, respirable powder (<10 microns)	ACGIH TLV (United States, 1/2025) [Silica, crystalline] A2. TWA 8 hours: 0.025 mg/m³. Form: Respirable fraction.
ethylbenzene	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m³. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m³.
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	ACGIH TLV (United States) TWA: 10 mg/m³. Form: Inhalable particle. TWA: 3 mg/m³ (inhalable dust). Form: Respirable particle.
2-methylpropan-1-ol	ACGIH TLV (United States, 1/2025)

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 8: Exposure controls/personal protection

formaldehyde	TWA 8 hours: 50 ppm. TWA 8 hours: 152 mg/m³. EU OEL (Europe, 3/2024) Skin sensitiser. STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m³. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m³.
--------------	--

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 8: Exposure controls/personal protection

Respiratory protection :
Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Yellow.
Odour : Aromatic. [Strong]
Odour threshold : Not available.
Melting point/freezing point : Not determined.
Initial boiling point and boiling range : >37.78°C
Flammability : Not determined. There are no data available on the mixture itself.
Upper/lower flammability or explosive limits : Not available.
Flash point : Closed cup: 31°C
Auto-ignition temperature :

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), heavy arom. Nota(s) P	220 to 250	428 to 482	ASTM E 659

Decomposition temperature : Stable under recommended storage and handling conditions (see Section 7).
pH : Not applicable. insoluble in water.
Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): >400 mm²/s
Kinematic (40°C): >21 mm²/s
Viscosity : 60 - 100 s (ISO 6mm)
Solubility(ies) :

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/ water : Not applicable.

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
2-methylpropan-1-ol	<12.00102	<1.6	DIN EN 13016-2			

Relative density : 1.49
Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties : Product does not present an oxidizing hazard.
Particle characteristics
Median particle size : Not applicable.

Code	: 000001202286	Date of issue/Date of revision	: 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN			

SECTION 9: Physical and chemical properties

9.2 Other information

Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
No additional information.	

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds Formaldehyde. metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May damage fertility.
May cause damage to organs through prolonged or repeated exposure.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
EPOXY RESIN (AVERAGE MOLECULAR WEIGHT >700 - <1100)	Rat - Oral - LD50	>2000 mg/kg
XYLENES	Rat - Dermal - LD50 Rat - Oral - LD50	>2000 mg/kg 4.3 g/kg
Phenol, methylstyrenated	Rabbit - Dermal - LD50 Rat - Oral - LD50	1.7 g/kg >2000 mg/kg
Solvent naphtha (petroleum), heavy arom. Nota(s) P	Rabbit - Dermal - LD50 Rat - Oral - LD50	>2000 mg/kg >5 g/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Rat - Inhalation - LC50 Dusts and mists Rat - Oral - LD50	>5.2 mg/l [4 hours] 17100 mg/kg
1-methoxy-2-propanol	Rabbit - Dermal - LD50 Rabbit - Dermal - LD50 Rat - Oral - LD50 Rat - Inhalation - LC50 Vapour	>4000 mg/kg 13 g/kg 5.2 g/kg >7000 ppm [6 hours]

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 11: Toxicological information

ethylbenzene	Rat - Oral - LD50 Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Vapour Rat - Oral - LD50	3.5 g/kg 17.8 g/kg 17.8 mg/l [4 hours] >2000 mg/kg
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Rat - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists Rat - Oral - LD50 Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Vapour Rat - Oral - LD50	>2000 mg/kg 3.56 mg/l [4 hours] 2830 mg/kg 2460 mg/kg 24.6 mg/l [4 hours] 0.5 g/kg
2-methylpropan-1-ol		
formaldehyde		

Acute toxicity estimates

Route	ATE value
Oral	39062.5 mg/kg
Dermal	13790.37 mg/kg
Inhalation (vapours)	95.75 mg/l
Inhalation (dusts and mists)	256.91 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

Skin : Causes skin irritation.
Eyes : Causes serious eye irritation.
Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Conclusion/Summary

Skin : May cause an allergic skin reaction.
Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
Solvent naphtha (petroleum), heavy arom. Nota(s) P	Category 3	-	Narcotic effects
1-methoxy-2-propanol	Category 3	-	Narcotic effects
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
formaldehyde	Category 3	-	Respiratory tract irritation

Conclusion/Summary (Product) :

Based on available data, the classification criteria are not met.

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 11: Toxicological information

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns) ethylbenzene 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Category 1 Category 2 Category 2	inhalation - inhalation	- hearing organs lungs

Conclusion/Summary (Product) :

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Product/ingredient name	Result
xylene Solvent naphtha (petroleum), heavy arom. Nota(s) P ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Conclusion/Summary (Product) : Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Code : 000001202286 Date of issue/Date of revision : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 11: Toxicological information

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
Solvent naphtha (petroleum), heavy arom. Nota(s) P	NOEL - Fresh water	Daphnia	0.48 mg/l [21 days]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LC50	Fish	>1.8 mg/l [96 hours]
	EC50	Daphnia	7.2 mg/l [48 hours]
	EC50	Algae	844 mg/l [72 hours]
1-methoxy-2-propanol	Acute - LC50 - Fresh water	Fish - Goldfish	>4500 mg/l [96 hours]
	Acute - LC50	Daphnia - Daphnia	23300 mg/l [48 hours]
ethylbenzene	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	1 mg/l
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Acute - LC50	Fish - <i>Oncorhynchus mykiss</i> (rainbow trout)	>100 mg/l [96 hours]

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 12: Ecological information

2-methylpropan-1-ol formaldehyde	Acute - EC50	Daphnia - <i>Daphnia magna</i> (Water flea)	>100 mg/l [48 hours]
	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i> (microalgae)	>100 mg/l [72 hours]
	Chronic - NOEC	Daphnia - <i>Daphnia magna</i> (Water flea)	≥50 mg/l [21 days]
	Chronic - NOEC	Algae - <i>Pseudokirchneriella subcapitata</i>	100 mg/l [72 hours]
	Acute - EC50	Daphnia	1100 mg/l [48 hours]
	Acute - EC50 - Fresh water	Algae - Green algae - <i>Desmodesmus subspicatus</i>	3.48 mg/l [72 hours]
	Acute - EC50 - Fresh water	Daphnia - Water flea - <i>Daphnia pulex</i> - Neonate	5.8 mg/l [48 hours]
	Chronic - NOEC	Daphnia - Water flea - <i>Daphnia magna</i>	0.81 to 1.07 mg/l [21 days]

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	OECD [Ready Biodegradability - Manometric Respirometry Test]	87% [28 days] - Readily		
ethylbenzene	-	79% [10 days] - Readily		
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	OECD [Ready Biodegradability - Closed Bottle Test]	9% [29 days] - Not readily		

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	-	Readily
ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

Code : 000001202286

Date of issue/Date of revision

: 26 February 2026

SIGMAPRIME 700 BAS YEL/GREEN

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
Phenol, methylstyrenated	3.627	-	Low
Solvent naphtha (petroleum), heavy arom. Nota(s) P	2.8 to 6.5	-	High
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	Low
1-methoxy-2-propanol	<1	-	Low
ethylbenzene	3.6	79.43	Low
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	>6	-	High
Cashew, nutshell liq.	>4.78	-	High
2-methylpropan-1-ol	1	-	Low
formaldehyde	0.35	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
1-methoxy-2-propanol	1	10.447
ethylbenzene	2.2	170.406
2-methylpropan-1-ol	1.1	12.0246
formaldehyde	0.44	2.72646

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Epoxy Resin (700<MW <=1100)	No	N/A	N/A	No	N/A	N/A	N/A
xylene	No	N/A	No	No	No	N/A	No
Phenol, methylstyrenated	No	N/A	N/A	No	SVHC (Candidate)	Specified	Specified
Solvent naphtha (petroleum), heavy arom. Nota(s) P	No	N/A	N/A	No	N/A	N/A	N/A
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	No	N/A	No	Yes	No	N/A	No
1-methoxy-2-propanol	No	N/A	N/A	No	N/A	N/A	N/A
ethylbenzene	No	N/A	No	Yes	No	N/A	No
Urea, polymer with formaldehyde, butylated	No	N/A	N/A	No	N/A	N/A	N/A
Cashew, nutshell liq.	No	N/A	N/A	No	N/A	N/A	N/A
2-methylpropan-1-ol	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 000001202286 **Date of issue/Date of revision** : 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Tunnel code : (D/E)

Code	: 000001202286	Date of issue/Date of revision	: 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN			

SECTION 14: Transport information

IMDG : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.
IATA : None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
vPvB	Phenol, methylstyrenated	Candidate	D(2023) 8585-DC	1/23/2024

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#) : Restricted to professional users.

[Other national and international regulations.](#)

Explosive precursors : This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

[Ozone depleting substances \(EU 2024/590\)](#)

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

Full text of abbreviated H statements

Code : 000001202286

Date of issue/Date of revision

: 26 February 2026

SIGMAPRIME 700 BAS YEL/GREEN

SECTION 16: Other information

: H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H360F May damage fertility.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH071 Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

: Acute Tox. 2 ACUTE TOXICITY - Category 2
Acute Tox. 4 ACUTE TOXICITY - Category 4
Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1 ASPIRATION HAZARD - Category 1
Carc. 1B CARCINOGENICITY - Category 1B
Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3
Muta. 2 GERM CELL MUTAGENICITY - Category 2
Repr. 1B REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1A SKIN SENSITISATION - Category 1A
Skin Sens. 1B SKIN SENSITISATION - Category 1B
STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 26 February 2026

Date of previous issue : 26 February 2026

Prepared by : EHS

Version : 4.01

Disclaimer

Code	: 000001202286	Date of issue/Date of revision	: 26 February 2026
SIGMAPRIME 700 BAS YEL/GREEN			

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.