

HELAIAN DATA KESELAMATAN SAFETY DATA SHEET



Tarikh keluaran : 7 Mei 2026
Date of issue : 7 May 2026

Versi : 1.05
Version : 1.05

Bahagian 1: Pengenalan bahan kimia berbahaya dan pembekal

Pengecam produk : PPG AQUACOVER ONE 625 BUFF
Kod Produk : 000001192153
Cara pengenalpastian yang lain : 00463631
Jenis Produk : Cecair.

Kegunaan relevan yang dikenal pasti bagi zat atau campuran serta kegunaan yang tidak dinasihatkan

Kegunaan Produk : Penyalutan.
Aplikasi profesional, Guna dengan Menyembur.

Dinasihatkan tidak digunakan pada	Sebab
Tidak berkenaan.	

Butir-butir pembekal : PPG Performance Coatings (M) Sdn. Bhd.
No 3, Jalan 205, P.O.Box 388,
46700 Petaling Jaya,
Selangor Darul Ehsan, Malaysia

Nombor telefon kecemasan : CHEMTREC +(60)-327884561 (CCN 17704)
Titik hubungan : Tel: +603 7787 7881
PMC.Safety@PPG.com

Section 1. Identification of the hazardous chemical and of the supplier

Product name : PPG AQUACOVER ONE 625 BUFF
Product code : 000001192153
Other means of identification : 00463631
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.
Professional applications, Used by spraying.

Uses advised against	Reason
Not applicable.	

Supplier's details : PPG Performance Coatings (M) Sdn. Bhd.
No 3, Jalan 205, P.O.Box 388,
46700 Petaling Jaya,
Selangor Darul Ehsan, Malaysia

Emergency phone: : CHEMTREC +(60)-327884561 (CCN 17704)
Contact person : Tel: +603 7787 7881
PMC.Safety@PPG.com

Bahagian 2: Pengenalan bahaya

Klasifikasi bahan atau campuran : BERBAHAYA KEPADA PERSEKITARAN AKUATIK - BAHAYA KRONIK - Kategori 2

Peratus campuran yang mengandungi bahan-bahan yang tidak diketahui bahayanya terhadap persekitaran akuatik: 31.4 %

Unsur label GHS

Piktogram bahaya :



Kata isyarat : Tiada kata isyarat.

Pernyataan bahaya : Toksik kepada hidupan akuatik dengan kesan kekal berpanjangan.

Pernyataan berjaga-jaga

Pencegahan : Elakkan pelepasan bahan ke persekitaran.

Tindakan : Pungut kumpul tumpahan.

Penyimpanan : Tidak berkenaan.

Pelupusan : Lupuskan kandungan dan bekas mengikut semua peraturan tempatan, serantau, nasional dan antarabangsa.

Bahaya lain yang tidak menyebabkan ia diklasifikasikan : Mengandungi isotiazolinon (isothiazolinones). Boleh menyebabkan tindak balas alergi.

Section 2. Hazards identification

Classification of the substance or mixture : HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 31.4%

GHS label elements

Hazard pictograms :



Signal word : No signal word.

Hazard statements : Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Avoid release to the environment.

Response : Collect spillage.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : Contains isothiazolinones. May cause allergic reaction.

Bahagian 3: Komposisi dan maklumat mengenai ramuan bahan kimia berbahaya

Bahan/Penyediaan : Campuran

Nombor CAS/pengenal pasti lain

Nombor CAS : Tidak berkenaan.

Nombor EC : Campuran.

Nama Ramuan	%	Nombor CAS
zink bis(ortofosfat)	≥5.0 - ≤7.1	7779-90-0
Batu sabun	≥3.0 - ≤5.0	14807-96-6
butil karbitol (dietilena glikol monobutil eter)	≥1.0 - ≤3.0	112-34-5
zink oksida	≤0.80	1314-13-2
ammonia larutan akues	≤0.19	1336-21-6
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8- tridecafluorooctyl)	≤0.10	SUB141402
phosphates, ammonium salt		
pyrithione zinc	≤0.016	13463-41-7

sub-kod mewakili bahan-bahan tanpa nombor CAS yang terdaftar.

Tidak ada ramuan tambahan, setakat yang diketahui pembekal dan dalam pemekatan yang boleh didapati, diklasifikasikan sebagai berbahaya kepada kesihatan atau persekitaran sehingga perlu dilaporkan dalam seksyen ini.

Had pendedahan pekerjaan, jika tersedia, disenaraikan dalam seksyen 8.

Section 3. Composition and information of the ingredients of the hazardous chemical

Substance/mixture : Mixture

CAS number/other identifiers

CAS number : Not applicable.

EC number : Mixture.

Ingredient name	%	CAS number
zinc bis(orthophosphate)	≥5.0 - ≤7.1	7779-90-0
Talc , not containing asbestiform fibres	≥3.0 - ≤5.0	14807-96-6
butyl carbitol (diethylene glycol monobutyl ether)	≥1.0 - ≤3.0	112-34-5
Zinc oxide	≤0.80	1314-13-2
ammonia aqueous solution	≤0.19	1336-21-6
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8- tridecafluorooctyl)	≤0.10	SUB141402
phosphates, ammonium salt		
pyrithione zinc	≤0.016	13463-41-7

SUB codes represent substances without registered CAS Numbers.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Bahagian 4: Langkah-langkah pertolongan cemas

Perihalan langkah pertolongan cemas yang perlu

- Sentuhan mata** : Periksa jika memakai kanta mata dan keluarkan jika ada. Segera cuci dengan air yang banyak selama 15 minit dengan kelopak mata terbuka. Dapatkan rawatan perubatan segera.
- Penyedutan** : Pindah ke kawasan udara segar. Biarkan orang tersebut hangat dan berehat. Jika tidak bernafas, jika bernafas tak menentu atau henti pernafasan berlaku, berikan pernafasan pemulihan atau oksigen oleh kakitangan terlatih.
- Sentuhan kulit** : Tanggalkan pakaian dan kasut yang tercemar. Cuci kulit sehingga bersih dengan sabun dan air atau gunakan pencuci kulit yang dibenarkan. Jangan guna pelarut atau pencair.
- Pengingesan** : Jika tertelan, dapatkan nasihat perubatan segera dan tunjukkan bekas atau label tersebut. Biarkan orang tersebut hangat dan berehat. JANGAN paksa muntah.

Simptom/kesan paling penting, akut dan tertunda

Kesan Kesihatan Akut Berpotensi

- Sentuhan mata** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Penyedutan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Sentuhan kulit** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.
- Pengingesan** : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Gejala-gejala/tanda-tanda lampau terdedah

- Sentuhan mata** : Tiada data spesifik.
- Penyedutan** : Tiada data spesifik.
- Sentuhan kulit** : Tiada data spesifik.
- Pengingesan** : Tiada data spesifik.

Tanda rawatan perubatan segera dan rawatan khas diperlukan, jika perlu

- Nota kepada doktor** : Rawat mengikut gejala. Hubungi pakar rawatan keracunan segera jika tertelan atau tersedut dalam kuantiti yang besar.
- Rawatan spesifik** : Tiada rawatan spesifik.
- Perlindungan untuk pemberi pertolongan cemas** : Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya.

Lihat Maklumat Toksikologi (Seksyen 11)

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Section 4. First aid measures

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments : No specific treatment.
Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Bahagian 5: Langkah-langkah pemadaman kebakaran

Kod Hazchem : •3Z

Media pemadam kebakaran

- Media pemadam yang sesuai** : Guna agen pemadaman sesuai untuk lingkungan api.
Media pemadam yang tidak sesuai : Tiada yang diketahui.

Bahaya khusus yang timbul daripada bahan kimia ini : Ketika kebakaran atau jika dipanaskan, peningkatan tekanan akan berlaku dan bekas boleh pecah. Bahan ini toksik pada hidupan akuatik dengan kesan yang berkekalan. Air pemadaman kebakaran yang tercemar dengan bahan ini mesti dibendung dan dielakkan daripada memasuki jalan air, pembetung atau longkang.

Hasil penguraian terma yang berbahaya : Produk penguraian mungkin termasuk bahan berikut:
karbon oksida
oksida fosforus
oksida logam

Tindakan perlindungan khas untuk ahli bomba : Kosongkan kawasan serta-merta dengan mengeluarkan semua orang daripada kawasan sekeliling jika kebakaran berlaku. Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya.

Alat perlindungan khas untuk ahli bomba : Ahli bomba perlulah memakai peralatan perlindungan bersesuaian dan peralatan pernafasan serba lengkap dengan penutup muka penuh dalam operasi mod tekanan positif.

Section 5. Firefighting measures

Hazchem code : •3Z

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media : None known.

Section 5. Firefighting measures

Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides phosphorus oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Bahagian 6: Langkah-langkah pelepasan tidak sengaja

Langkah berjaga-jaga peribadi, peralatan pelindung dan prosedur kecemasan

Untuk kakitangan bukan kecemasan	: Jangan lakukan sebarang tindakan yang membabitkan risiko peribadi atau tanpa latihan yang sewajarnya. Kosongkan kawasan persekitaran. Halang kakitangan tidak berkaitan dan tidak dilindungi daripada masuk. Jangan sentuh atau jalan melalui bahan tertumpah. Pakai peralatan perlindungan diri yang sesuai.
Untuk pasukan tindak balas kecemasan	: Jika pakaian khas diperlukan bagi mengendalikan tumpahan, perhatikan apa jua maklumat dalam Seksyen 8 tentang bahan yang sesuai dan tidak sesuai. Lihat juga maklumat dalam bahagian "Untuk kakitangan bukan kecemasan".
Peringatan alam sekitar	: Elakkan penyebaran bahan tertumpah dan aliran dan bersentuh dengan tanah, jalan air, longkang dan pemetung. Beritahu pihak berkuasa yang berkaitan jika produk menyebabkan pencemaran persekitaran (pemetung, aliran air, tanah atau udara). Bahan mencemar air. Boleh memudaratkan alam sekitar jika terlepas dalam jumlah yang banyak. Pungut kumpul tumpahan.

Kaedah dan bahan bagi pembendungan dan pembersihan

Tumpahan kecil	: Hentikan kebocoran jika tidak berisiko. Alih bekas daripada kawasan tumpahan. Cairkan dengan air dan seka bersih jika terlarut air. Sebagai alternatif, atau jika tidak terlarut air, serap dengan bahan kering yang lengai dan isikan dalam bekas pelupusan bahan buangan yang wajar. Buang melalui kontraktor pelupusan sisa yang berlesen.
Tumpahan besar	: Hentikan kebocoran jika tidak berisiko. Alih bekas daripada kawasan tumpahan. Pendekatan lepas dari arah angin bertiup jauh dari kamu, bukan ke arah kamu. Cegah kemasukan ke dalam pemetung, aliran air, basemen atau ruang terbatas. Siram tumpahan ke dalam loji perawatan efluen atau teruskan seperti berikut. Bendung dan kumpul tumpahan dengan bahan serap tidak mampu bakar seperti pasir, tanah, vermikulit dan tanah diatom, dan letakkan dalam bekas untuk pembuangan mengikut peraturan tempatan (lihat Seksyen 13). Buang melalui kontraktor pelupusan sisa yang berlesen. Bahan penyerap yang tercemar boleh mendatangkan bahaya yang sama seperti produk tertumpah. Nota: Lihat Seksyen 1 untuk maklumat hubungan kecemasan dan Seksyen 13 untuk pelupusan sisa.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Section 6. Accidental release measures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Bahagian 7: Pengendalian dan penyimpanan

Langkah berjaga-jaga bagi mengendalikan dengan selamat

- Langkah perlindungan** : Pakai kelengkapan perlindungan peribadi bersesuaian (Lihat Seksyen 8). Jangan inges. Elakkan tersentuh mata, kulit dan pakaian. Elakkan menyedut wap atau kabus. Elakkan pelepasan bahan ke persekitaran. Simpan di dalam bekas asal atau bekas lain yang diluluskan yang diperbuat daripada bahan yang sesuai, tutup ketat apabila tidak digunakan. Bekas kosong mengandungi sisa produk dan boleh menjadi berbahaya. Jangan guna semula bekas.
- Nasihat tentang aturan kebersihan pekerjaan umum** : Makan, minum dan menghisap rokok harus dilarang dalam kawasan di mana bahan ini dikendalikan, disimpan dan diproses. Para pekerja harus membasuh tangan dan muka sebelum makan, minum dan menghisap rokok. Tanggalkan pakaian yang tercemar dan peralatan perlindungan sebelum masuk tempat makan. Lihat juga Seksyen 8 untuk maklumat tambahan tentang langkah kebersihan.
- Syarat-syarat bagi penyimpanan yang selamat, termasuk apa-apa ketakserasian** : Simpan pada suhu berikut: 5 hingga 35°C (41 hingga 95°F). Simpan mengikut peraturan tempatan. Simpan di dalam bekas asal yang terlindung dari pancaran terus cahaya matahari dalam kawasan kering, sejuk dan pengudaraan yang baik, jauh daripada bahan tidak sesuai (lihat Seksyen 10) dan makanan dan minuman. Simpan bekas tertutup rapat dan terkedap sehingga sedia untuk diguna. Bekas yang telah dibuka mesti dikedap semula dengan teliti dan disimpan menegak untuk mencegah kebocoran. Jangan simpan dalam bekas tidak berlabel. Gunakan kaedah pengurangan yang sesuai untuk mengelakkan pencemaran alam sekitar. Lihat Bahagian 10 untuk bahan yang tidak serasi sebelum mengendali atau mengguna.

Bahagian 7: Pengendalian dan penyimpanan**Section 7. Handling and storage****Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Bahagian 8: Kawalan pendedahan dan perlindungan diri**Parameter kawalan****Had Pendedahan Pekerjaan**

Nama Ramuan	Had-Had Pendedahan
Zn zink bis(ortofosfat) Batu sabun butil karbitol (dietilena glikol monobutil eter) Zink oksida ammonia	DFG MAC-values list (Jerman, 7/2024) [Zinc and its inorganic compounds] Develop C. PEAK 15 minit: 0.4 mg/m ³ 4 kali per syif [Interval: 1 hour]. Borang: nisbah ternafas. TWA 8 jam: 2 mg/m ³ . Borang: pecahan tersedutkan. TWA 8 jam: 0.1 mg/m ³ . Borang: nisbah ternafas. PEAK 15 minit: 4 mg/m ³ 4 kali per syif [Interval: 1 hour]. Borang: pecahan tersedutkan. Jadual I USECHH 2000 (Malaysia, 4/2000) [Talkum (tidak mengandungi gentian asbestos)] Purata berpemberat lapan jam 8 jam: 2 mg/m ³ . Borang: pecahan ternafaskan. ACGIH TLV (Amerika Syarikat, 1/2025) TWA 8 jam: 10 ppm. Borang: Pecahan boleh disedut dan pecahan wap. Jadual I USECHH 2000 (Malaysia, 4/2000) Purata berpemberat lapan jam 8 jam: 10 mg/m ³ . Borang: habuk. Purata berpemberat lapan jam 8 jam: 5 mg/m ³ . Borang: wasap. Jadual I USECHH 2000 (Malaysia, 4/2000) [Ammonia]

Bahagian 8: Kawalan pendedahan dan perlindungan diri

pyrithione zinc

Purata berpemberat lapan jam 8 jam: 25 ppm.

Purata berpemberat lapan jam 8 jam: 17 mg/m³.**DFG MAC-values list (Jerman, 7/2024)**

Diserap melalui kulit.

- Langkah pemantauan yang disyorkan** : Rujukan harus dibuat atas piawai pemantauan yang berkenaan. Rujukan kepada dokumen panduan negara bagi kaedah penentuan zat berbahaya juga dikehendaki.
- Kawalan kejuruteraan yang wajar** : Pengalihudaraan am yang baik hendaklah mencukupi untuk mengawal bahan cemar bawaan udara yang terdedah kepada pekerja.
- Kawalan pendedahan alam sekitar** : Pengeluaran daripada pengudaraan atau peralatan proses kerja hendaklah diperiksa untuk memastikan ianya mematuhi keperluan perundangan perlindungan alam sekitar. Bagi sesetengah kes, penyental wasap, penuras atau pengubahsuaian kejuruteraan terhadap peralatan proses adalah perlu bagi mengurangkan pengeluaran ke tahap yang dibenarkan.

Langkah-langkah perlindungan individu

- Langkah-langkah kebersihan** : Basuh kedua tangan, lengan dan muka sehingga bersih setelah mengendalikan produk kimia, sebelum makan, merokok dan menggunakan tandas dan pada akhir waktu kerja. Teknik yang sesuai harus digunakan apabila menanggalkan pakaian yang mungkin tercemar. Basuh pakaian tercemar sebelum memakai semula. Pastikan tempat mencuci mata dan pancuran air keselamatan berdekatan dengan lokasi tempat kerja.
- Perlindungan mata/muka** : Cermin mata keselamatan dengan pelindung sisi.
- Perlindungan kulit**
- Perlindungan tangan** : Sarung tangan kedap penentang bahan kimia, yang mematuhi piawaian yang diluluskan hendaklah dipakai pada setiap masa apabila mengendalikan produk kimia jika penilaian risiko menunjukkan ini adalah perlu. Dengan mempertimbangkan parameter yang ditetapkan oleh pengilang sarung tangan, pastikan semasa digunakan bahawa sarung tangan masih mengekalkan ciri-ciri perlindungannya. Harus diperhatikan bahawa jangka masa hingga terobos untuk mana-mana bahan sarung tangan mungkin berbeza mengikut pengilang sarung tangan. Bagi kes campuran, yang terdiri daripada beberapa zat, jangka masa perlindungan sarung tangan tidak dapat dianggarkan dengan tepat.
- sarung tangan** : Bagi pengendalian berpanjangan dan berulang, guna jenis sarung tangan seperti berikut:
Disyorkan: Getah nitril, Kloroprena, getah butil
- Perlindungan tubuh** : Peralatan perlindungan peribadi untuk badan perlu dipilih berdasarkan tugas yang dilakukan dan risiko yang terlibat dan perlulah diluluskan oleh pakar sebelum mengendalikan produk ini.
- Perlindungan kulit yang lain** : Kasut yang wajar dan apa jua langkah tambahan bagi perlindungan kulit harus dipilih berdasarkan tugas yang dilakukan dan risiko yang terbabit, dan harus diluluskan oleh seorang pakar sebelum mengendalikan produk ini.
- Perlindungan respiratori** : Berdasarkan bahaya dan kemungkinan pendedahan, pilih respirator yang memenuhi standard atau pensijilan yang sewajarnya. Respirator harus digunakan mengikut program pelindung pernafasan bagi memastikan pemakaian dan latihan yang betul, serta aspek penggunaan lain yang penting.

Section 8. Exposure controls/personal protection

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Zinc bis(orthophosphate) Talc , not containing asbestiform fibres 2-(2-butoxyethoxy)ethanol zinc oxide ammonia pyrrithione zinc	<p>DFG MAC-values list (Germany, 7/2024) [Zinc and its inorganic compounds] Develop C. PEAK 15 minutes: 0.4 mg/m³ 4 times per shift [Interval: 1 hour]. Form: respirable fraction. TWA 8 hours: 2 mg/m³. Form: inhalable fraction. TWA 8 hours: 0.1 mg/m³. Form: respirable fraction. PEAK 15 minutes: 4 mg/m³ 4 times per shift [Interval: 1 hour]. Form: inhalable fraction.</p> <p>Schedule I USECHH 2000 (Malaysia, 4/2000) [Talc (containing no asbestos fibres)] TWA 8 hours: 2 mg/m³. Form: Respirable fraction.</p> <p>ACGIH TLV (United States, 1/2025) TWA 8 hours: 10 ppm. Form: Inhalable fraction and vapor.</p> <p>Schedule I USECHH 2000 (Malaysia, 4/2000) TWA 8 hours: 10 mg/m³. Form: Dust. TWA 8 hours: 5 mg/m³. Form: Fume.</p> <p>Schedule I USECHH 2000 (Malaysia, 4/2000) [Ammonia] TWA 8 hours: 25 ppm. TWA 8 hours: 17 mg/m³.</p> <p>DFG MAC-values list (Germany, 7/2024) Absorbed through skin.</p>

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:
Recommended: nitrile rubber, Chloroprene, butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Bahagian 9: Sifat fizikal dan kimia

Rupa

- Keadaan fizikal** : Cecair.
- Warna** : Kuning air.
- Bau** : Tidak berbau.
- Ambang Bau** : Tidak tersedia.
- pH** : 8.5
- Takat Lebur** : Tidak tersedia.
- Takat Didih** : >37.78°C (>100°F)
- Takat kilat** : Cawan tertutup: Tidak berkenaan.
- Kadar Penyejatan** : Tidak tersedia.
- Kemudahbakaran (pepejal, gas)** : Tidak tersedia.
- Had mudah meletup (mudah menyala) bawah dan atas** : Tidak tersedia.
- Tekanan Wap** : Tidak tersedia.
- Ketumpatan Wap** : Tidak tersedia.
- Ketumpatan bandingan** : 1.2
- | Keterlarutan | Media | Keputusan |
|--------------|-----------|--------------|
| | air sejuk | Separa larut |
- Pekali sekatan: n-oktanol/air** : Tidak berkenaan.
- Suhu pengautocucuhan** : Tidak tersedia.
- Suhu penguraian** : Tidak tersedia.
- Kelikatan** : Dinamik (suhu bilik): Tidak tersedia.
Kinematik (suhu bilik): Tidak tersedia.
Kinematik (40°C): >21 mm²/s

Bahagian 9: Sifat fizikal dan kimia

Kelikatan : > 100 s (ISO 6mm)

Section 9. Physical and chemical propertiesAppearance

Physical state : Liquid.
 Colour : Beige.
 Odour : Odourless.
 Odour threshold : Not available.
 pH : 8.5
 Melting point : Not available.
 Boiling point : >37.78°C (>100°F)
 Flash point : Closed cup: Not applicable.
 Evaporation rate : Not available.
 Flammability (solid, gas) : Not available.
 Lower and upper explosive (flammable) limits : Not available.
 Vapour pressure : Not available.
 Vapour density : Not available.
 Relative density : 1.2

Solubility(ies) :

Media	Result
cold water	Partially soluble

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm²/s

Viscosity : > 100 s (ISO 6mm)

Bahagian 10: Kestabilan dan kereaktifan

Kereaktifan : Tiada data ujian khusus berkaitan dengan kereaktifan bagi produk ini atau ramuannya.

Kestabilan bahan : Produk ini stabil.

Kemungkinan berlakunya tindak balas berbahaya : Dalam keadaan penyimpanan dan penggunaan yang normal, tindak balas berbahaya tidak akan terjadi.

Keadaan yang perlu dielak : Apabila terdedah kepada suhu tinggi, boleh mengeluarkan hasil penguraian berbahaya.

Bahan tidak serasi : Jauhkan daripada bahan berikut untuk mencegah tindakbalas eksotermik kuat: agen pengoksidaan, alkali kuat, asid kuat.

Produk penguraian berbahaya : Bergantung pada keadaan, produk pereputan mungkin termasuk bahan berikut: karbon oksida oksida fosforus oksida logam

Bahagian 10: Kestabilan dan kereaktifan**Section 10. Stability and reactivity**

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides metal oxide/oxides

Bahagian 11: Maklumat toksikologi**Maklumat tentang kesan toksikologi****Ketoksikan akut**

Nama produk/bahan	Keputusan	Spesis	Dos	Pendedahan
zink bis(ortofosfat)	LC50 Penyedutan Debu dan Kabus	Tikus	>5.7 mg/l	4 jam
butil karbitol (dietilena glikol monobutil eter)	LD50 Oral	Tikus	>5000 mg/kg	-
	LD50 Kulit	Arnab	2700 mg/kg	-
zink oksida	LD50 Oral	Tikus	4500 mg/kg	-
	LC50 Penyedutan Debu dan Kabus	Tikus	>5700 mg/m ³	4 jam
	LD50 Kulit	Tikus	>2000 mg/kg	-
ammonia larutan akues reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt pyriithione zinc	LD50 Oral	Tikus	>5000 mg/kg	-
	LD50 Oral	Tikus	350 mg/kg	-
	LC50 Penyedutan Debu dan Kabus	Tikus	0.047 mg/l	4 jam
	LC50 Penyedutan Debu dan Kabus	Tikus	0.14 mg/l	4 jam
	LD50 Kulit	Arnab	>2 g/kg	-
	LD50 Oral	Tikus	177 mg/kg	-

Kesimpulan/Ringkasan : Tiada data tentang campuran itu sendiri.

Kerengsaan/Kakistan

Nama produk/bahan	Keputusan	Spesis	Skor	Pendedahan	Pencerapan
pyriithione zinc	Mata - Kelegapan kornea	Arnab	4	24 jam	24 jam

Kesimpulan/Ringkasan

Kulit : Tiada data tentang campuran itu sendiri.

Mata : Tiada data tentang campuran itu sendiri.

Pernafasan : Tiada data tentang campuran itu sendiri.

Pemekaan**Kesimpulan/Ringkasan**

Bahagian 11: Maklumat toksikologi

Kulit : Tiada data tentang campuran itu sendiri.

Pernafasan : Tiada data tentang campuran itu sendiri.

Mutagenisiti

Kesimpulan/Ringkasan : Tiada data tentang campuran itu sendiri.

Karsinogenisiti

Kesimpulan/Ringkasan : Tiada data tentang campuran itu sendiri.

Toksisiti reproduktif

Kesimpulan/Ringkasan : Tiada data tentang campuran itu sendiri.

Keteratogenikan

Kesimpulan/Ringkasan : Tiada data tentang campuran itu sendiri.

Ketoksikan organ sasaran khusus (pendedahan tunggal)

Nama	Kategori	Laluan pendedahan	Organ Sasaran
Batu sabun	Kategori 3	-	Kerengsaan saluran pernafasan
ammonia larutan akues	Kategori 3	-	Kerengsaan saluran pernafasan

Ketoksikan organ sasaran khusus (pendedahan berulang)

Nama	Kategori	Laluan pendedahan	Organ Sasaran
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	Kategori 2	-	hati
pyrithione zinc	Kategori 1	-	-

Bahaya penyedutan

Tidak tersedia.

Maklumat tentang laluan pendedahan yang berkemungkinan : Tidak tersedia.

Kesan Kesihatan Akut Berpotensi

Sentuhan mata : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Penyedutan : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Sentuhan kulit : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Pengingesan : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Gejala yang berkaitan dengan ciri fizikal, kimia dan toksikologi

Sentuhan mata : Tiada data spesifik.

Penyedutan : Tiada data spesifik.

Sentuhan kulit : Tiada data spesifik.

Pengingesan : Tiada data spesifik.

Kesan tertunda dan serta merta, dan juga kesan kronik akibat pendedahan jangka pendek dan panjang**Pendedahan jangka pendek**

Kesan serta merta yang berpotensi : Tiada data tentang campuran itu sendiri.

Bahagian 11: Maklumat toksikologi

Kesan tertunda yang berpotensi : Tiada data tentang campuran itu sendiri.

Pendedahan jangka panjang

Kesan serta merta yang berpotensi : Tiada data tentang campuran itu sendiri.

Kesan tertunda yang berpotensi : Tiada data tentang campuran itu sendiri.

Kesan Kesihatan Kronik Berpotensi

Am : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Karsinogenisiti : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Mutagenisiti : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Toksisiti reproduktif : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Ukuran ketoksikan secara angka**Anggaran ketoksikan akut**

Tidak tersedia.

Maklumat lain :

Mengempelas dan mengisar debu mungkin berbahaya jika tersedut. Mengandungi isotiazolinon (isothiazolinones). Boleh menyebabkan tindak balas alergi.

Section 11. Toxicological information**Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Zinc bis(orthophosphate)	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	2700 mg/kg	-
butyl carbitol (diethylene glycol monobutyl ether)	LD50 Oral	Rat	4500 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
Zinc oxide	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	350 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	0.047 mg/l	4 hours
ammonia aqueous solution reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
pyrithione zinc	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Section 11. Toxicological information

Respiratory : There are no data available on the mixture itself.

Sensitisation

Not available.

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation
ammonia aqueous solution	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
reaction mass of mixed (3,3,4,4,5,5,6,6,7,7, 8,8,8-tridecafluorooctyl) phosphates, ammonium salt	Category 2	-	liver
pyrithione zinc	Category 1	-	-

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Section 11. Toxicological information

Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure**

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.

Long term exposure

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.

Potential chronic health effects

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

Not available.

Other information :

Sanding and grinding dusts may be harmful if inhaled. Contains isothiazolinones. May cause allergic reaction.

Bahagian 12: Maklumat ekologi**Ketoksikan**

Nama produk/bahan	Keputusan	Spesis	Pendedahan
zink bis(ortofosfat)	Akut LC50 0.112 mg/l	Ikan	96 jam
zink oksida	Kronik NOEC 0.026 mg/l	Ikan	30 hari
	Akut EC50 0.17 mg/l	Alga	72 jam
	Akut EC50 0.481 mg/l Air tawar	Dafnia - <i>Daphnia magna</i> - Neonat	48 jam
pyrithione zinc	Kronik NOEC 0.017 mg/l Air tawar	Alga	72 jam
	Akut EC50 5.513 µg/l Air laut	Alga - <i>Nitzschia pungens</i>	96 jam
	Akut LC50 0.0082 mg/l	Dafnia	48 jam
	Kronik NOEC 1.889 µg/l Air laut	Alga - <i>Nitzschia pungens</i>	96 jam
	Kronik NOEC 0.0027 mg/l	Dafnia	21 hari

Kegigihan dan degradasi

Nama produk/bahan	Ujian	Keputusan	Dos	Inokulum
pyrithione zinc	-	39 % - 28 hari	-	-
Nama produk/bahan	Separuh hayat Akuatik		Fotolisis	Sifat biosot
pyrithione zinc	-		50%; < 28 hari	Tidak mudah

Bahagian 12: Maklumat ekologi**Potensi bioakumulasi**

Nama produk/bahan	LogP _{ow}	BCF	Berpotensi
butil karbitol (diethylene glycol monobutyl ether)	1	-	Rendah
pyrithione zinc	0.9	0.9 [OECD 305 E]	Rendah

Mobiliti tanah

Pekali Sekatan Tanah/Air : Tidak tersedia.

Kesan-kesan buruk lain : Tiada kesan yang penting atau bahaya kritikal yang diketahui.

Section 12. Ecological information**Toxicity**

Product/ingredient name	Result	Species	Exposure
zinc bis(orthophosphate)	Acute LC50 0.112 mg/l	Fish	96 hours
	Chronic NOEC 0.026 mg/l	Fish	30 days
Zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
pyrithione zinc	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
	Acute EC50 5.513 µg/l Marine water	Algae - <i>Nitzschia pungens</i>	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - <i>Nitzschia pungens</i>	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
pyrithione zinc	-	39 % - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
pyrithione zinc	-	50%; < 28 day(s)	Not readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
butyl carbitol (diethylene glycol monobutyl ether)	1	-	Low
pyrithione zinc	0.9	0.9 [OECD 305 E]	Low

Mobility in soil

Soil/water partition coefficient : Not available.

Other adverse effects : No known significant effects or critical hazards.

Bahagian 13: Maklumat pelupusan**Kaedah pelupusan**

: Penghasilan sisa perlulah dielakkan atau diminimumkan sekiranya boleh. Pelupusan produk ini, larutan dan sebarang produk sampingan perlulah pada setiap masa mematuhi keperluan perlindungan alam sekitar dan perundangan pelupusan sisa dan sebarang keperluan pihak berkuasa serantau tempatan. Pembuangan lebihan dan hasilan yang tidak boleh dikitar semula melalui kontraktor pelupusan sisa yang berlesen. Bahan buangan tidak harus dibuang secara tidak dirawat ke pembentung kecuali patuh sepenuhnya kepada keperluan semua pihak berkuasa dengan kuasa undang-undang. Bungkusuan buangan harus dikitar semula. Penunuan atau kambus tanah hanya harus dipertimbangkan apabila tidak mungkin dikitar semula. Bahan ini dan bekasnya hendaklah dilupuskan dengan cara yang selamat. Hati-hati apabila mengendalikan bekas yang telah dikosongkan tetapi belum dibersihkan atau dibilas. Bekas atau pelapik kosong mungkin mengandungi sisa-sisa produk. Elakkan penyebaran bahan tertumpah dan aliran dan bersentuh dengan tanah, jalan air, longkang dan pemetung.

Section 13. Disposal information**Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Bahagian 14: Maklumat pengangkutan

	UN	IMDG	IATA
Nombor UN	UN3082	UN3082	UN3082
Nama penghantaran sah PBB	☑ ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	☑ ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	☑ ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
Kelas bahaya pengangkutan	9	9	9
Kumpulan Pembungkusan	III	III	III
Bahaya Alam Sekitar	Ya.	Yes.	Yes.

Maklumat Tambahan

UN : Produk ini tidak dikawal selia sebagai barang berbahaya apabila dihantar dalam saiz ≤5 L atau ≤5 kg, dengan syarat pembungkusan memenuhi peruntukan am 4.1.1.1, 4.1.1.2 dan 4.1.1.4 hingga 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Bahagian 14: Maklumat pengangkutan

IATA : Produk ini tidak dikawal selia sebagai barang berbahaya apabila dihantar dalam saiz ≤5 L atau ≤5 kg, dengan syarat pembungkusan memenuhi peruntukan am 5.0.2.4.1, 5.0.2.6.1.1 dan 5.0.2.8.

Langkah pencegah istimewa untuk pengguna : "Pengangkutan dalam premis pemilik:" sentiasa mengangkut dalam bekas bertutup yang tegak dan selamat. Pastikan orang yang mengangkut produk tahu apa yang perlu dilakukan sekiranya berlaku kemalangan atau tumpahan.

Angkut secara pukal menurut alatan IMO : Tidak berkenaan.

Section 14. Transport information

	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.

Additional information

UN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Bahagian 15: Maklumat pengawalseliaan**Peraturan Antarabangsa****Bahan Kimia Jadual I, II & III Senarai Konvensyen Senjata Kimia**

Tidak tersenarai.

Protokol Montreal

Tidak tersenarai.

Konvensyen Stockholm tentang zat pencemar organik gigih

Bahagian 15: Maklumat pengawalseliaan

Tidak tersenarai.

[Protokol UNECE Aarhus tentang POP dan Logam Berat](#)

Tidak tersenarai.

Section 15. Regulatory information

[International regulations](#)

[Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

[Montreal Protocol](#)

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

Bahagian 16: Maklumat lain

[Sejarah](#)

Tarikh keluaran/Tarikh semakan : 7 Mei 2026

Tarikh Keluaran Terdahulu : 11/5/2025

Versi : 1.05
EHS

Petunjuk untuk Singkatan : ATE = Anggaran Keracunan Teruk
BCF = Faktor Biokepekatan
GHS = Sistem Global Berharmoni bagi Pengelasan dan Pelabelan Kimia
IATA = Persatuan Pengangkutan Udara Antarabangsa
IBC = Bekas Pukul Sederhana
IMDG = Barang-barang Berbahaya Laut Antarabangsa
LogPow = Logaritma pekali sekatan bagi oktanol/air
MARPOL = Persidangan Antarabangsa bagi Pencegahan Pencemaran Daripada Kapal-kapal, 1973 seperti yang diubah oleh Protokol 1978. ("Marpol" = pencemaran laut)
UN = Pertubuhan Bangsa-bangsa Bersatu

Rujukan : Tidak tersedia.

✓ **Menunjukkan maklumat yang telah berubah daripada versi isu terdahulu.**

[Penafian](#)

Maklumat yang terkandung dalam risalah data ini berdasarkan maklumat saintifik dan maklumat teknikal terkini. Maklumat ini bertujuan untuk memberikan penekanan terhadap aspek kesihatan dan keselamatan bagi produk yang dihasilkan oleh PPG, dan untuk mengesyorkan langkah berjaga-jaga untuk penyimpanan dan pengendalian produk. Tiada waranti atau jaminan diberikan berkenaan dengan sifat produk. Pihak PPG tidak akan menanggung keatas apa-apa kegagalan untuk mematuhi langkah berjaga-jaga seperti yang dinyatakan dalam risalah data keselamatan ini atau bagi apa-apa penyalahgunaan.

Section 16. Other information

[History](#)

Date of issue/Date of revision : 7 May 2026

Section 16. Other information

Date of previous issue : 11/5/2025

Version : 1.05

EHS

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships,
1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

✔ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.