

# SAFETY DATA SHEET

Date of issue/Date of revision

: 14 June 2026

Version

: 2



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PPG FLR 912 LV EPOXY PRIMER CLEAR - A

**Product code** : 00482510

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

☑ Skin Irrit. 2, H315

Eye Dam. 1, H318

Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 2: Hazards identification

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Toxic to aquatic life with long lasting effects.

Prevention

: Wear protective gloves. Wear eye or face protection. Avoid release to the environment.

Response

: Collect spillage. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P280, P273, P391, P305 + P351 + P338, P310, P501

Hazardous ingredients

: bis-[4-(2,3-epoxipropoxy)phenyl]propane; benzyl alcohol and [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Supplemental label elements

: Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.

: Based on available data, the classification criteria are not met.

Other hazards which do not result in classification

: None known.

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name                      | Identifiers  | % by weight | Classification   | Specific Conc. Limits, M-factors and ATEs                 | Type    |
|--|--|-------------|--|---|---------|
| 1,4-bis-[4-(2,3-epoxypropoxy)phenyl]propane  | REACH #:<br>01-2119456619-26<br>EC: 216-823-5<br>CAS: 1675-54-3<br>Index: 603-073-00-2 | ≥75 - ≤90   | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                                     | Skin Irrit. 2, H315: C ≥ 5%<br>Eye Irrit. 2, H319: C ≥ 5% | [1]     |
| benzyl alcohol                               | REACH #:<br>01-2119492630-38<br>EC: 202-859-9<br>CAS: 100-51-6<br>Index: 603-057-00-5  | ≥5.0 - ≤10  | Acute Tox. 4, H302<br>Eye Irrit. 2, H319<br>Skin Sens. 1B, H317  | ATE [Oral] = 1200 mg/kg                                   | [1] [2] |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | REACH #:<br>01-2119513212-58<br>EC: 219-784-2<br>CAS: 2530-83-8                        | ≥1.0 - ≤5.0 | Eye Dam. 1, H318<br>Aquatic Chronic 3, H412<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | -   | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Code : 00482510 Date of issue/Date of revision : 14 June 2026  
PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 4: First aid measures

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name | Exposure limit values                           |
|-------------------------|---|
| Benzyl alcohol          | <b>IPEL (-)</b><br>TWA: 5 ppm.<br>STEL: 10 ppm. |

#### Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

| Product/ingredient name                 | Exposure  | Value                                   |
|---|---|---|
| bis-[4-(2,3-epoxypropoxy)phenyl]propane | DNEL - Workers - Long term - Inhalation                     | <i>Systemic</i> 12.25 mg/m <sup>3</sup> |
|   | DNEL - Workers - Short term - Inhalation                    | <i>Systemic</i> 12.25 mg/m <sup>3</sup> |
|   | DNEL - Workers - Long term - Dermal                         | <i>Systemic</i> 8.33 mg/kg bw/day       |
|   | DNEL - Workers - Short term - Dermal                        | <i>Systemic</i> 8.33 mg/kg bw/day       |
|   | DNEL - General population - Consumers - Long term - Dermal  | <i>Systemic</i> 3.571 mg/kg bw/day      |
|   | DNEL - General population - Consumers - Short term - Dermal | <i>Systemic</i> 3.571 mg/kg bw/day      |
|   | DNEL - General population - Consumers - Long term - Oral    | <i>Systemic</i> 0.75 mg/kg bw/day       |
|   | DNEL - General population - Consumers - Short term - Oral   | <i>Systemic</i> 0.75 mg/kg bw/day       |
|   | DNEL - General population - Long term - Dermal              | <i>Systemic</i> 89.3 µg/kg bw/day       |
|   | DNEL - General population - Long term - Oral                | <i>Systemic</i> 0.5 mg/kg bw/day        |
|   | DNEL - Workers - Long term - Dermal                         | <i>Systemic</i> 0.75 mg/kg bw/day       |
|   | DNEL - General population - Long term -                     | <i>Systemic</i> 0.87 mg/m <sup>3</sup>  |

|  |  |
|--|--|
| <b>Code</b> : 00482510                       | <b>Date of issue/Date of revision</b> : 14 June 2026 |
| <b>PPG FLR 912 LV EPOXY PRIMER CLEAR - A</b> |  |

**SECTION 8: Exposure controls/personal protection**

|  |   |          |                         |
|--|---|----------|-------------------------|
| benzyl alcohol                               | Inhalation  |          |                         |
|  | DNEL - Workers - Long term - Inhalation             | Systemic | 4.93 mg/m <sup>3</sup>  |
|  | DNEL - General population - Long term - Oral        | Systemic | 4 mg/kg bw/day          |
|  | DNEL - General population - Long term - Dermal      | Systemic | 4 mg/kg bw/day          |
|  | DNEL - General population - Long term - Inhalation  | Systemic | 5.4 mg/m <sup>3</sup>   |
|  | DNEL - Workers - Long term - Dermal                 | Systemic | 8 mg/kg bw/day          |
|  | DNEL - General population - Short term - Oral       | Systemic | 20 mg/kg bw/day         |
|  | DNEL - General population - Short term - Dermal     | Systemic | 20 mg/kg bw/day         |
|  | DNEL - Workers - Long term - Inhalation             | Systemic | 22 mg/m <sup>3</sup>    |
|  | DNEL - General population - Short term - Inhalation | Systemic | 27 mg/m <sup>3</sup>    |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | DNEL - Workers - Short term - Dermal                | Systemic | 40 mg/kg bw/day         |
|  | DNEL - Workers - Short term - Inhalation            | Systemic | 110 mg/m <sup>3</sup>   |
|  | DNEL - Workers - Short term - Inhalation            | Systemic | 147 mg/m <sup>3</sup>   |
|  | DNEL - Workers - Short term - Dermal                | Systemic | 21 mg/kg bw/day         |
|  | DNEL - General population - Long term - Oral        | Systemic | 5 mg/kg bw/day          |
|  | DNEL - General population - Long term - Dermal      | Systemic | 5 mg/kg bw/day          |
|  | DNEL - Workers - Long term - Dermal                 | Systemic | 10 mg/kg bw/day         |
|  | DNEL - General population - Long term - Inhalation  | Systemic | 17 mg/m <sup>3</sup>    |
|  | DNEL - Workers - Long term - Inhalation             | Systemic | 70.5 mg/m <sup>3</sup>  |
|  | DNEL - General population - Short term - Inhalation | Systemic | 26400 mg/m <sup>3</sup> |

**PNECs**

| Product/ingredient name                      | Compartment Detail - Method                      | Value           |
|--|--|-----------------|
| bis-[4-(2,3-epoxypropoxy)phenyl]propane      | Fresh water - Assessment Factors                 | 0.006 mg/l      |
|  | Marine water - Assessment Factors                | 0.001 mg/l      |
|  | Fresh water sediment - Equilibrium Partitioning  | 0.996 mg/kg dwt |
|  | Marine water sediment - Equilibrium Partitioning | 0.1 mg/kg dwt   |
|  | Soil - Equilibrium Partitioning                  | 0.196 mg/kg dwt |
|  | Sewage Treatment Plant - Assessment Factors      | 10 mg/l         |
|  | Secondary Poisoning - Assessment Factors         | 11 mg/kg        |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Fresh water - Assessment Factors                 | 1 mg/l          |
|  | Marine water - Assessment Factors                | 0.1 mg/l        |
|  | Sewage Treatment Plant - Assessment Factors      | 10 mg/l         |
|  | Fresh water sediment - Equilibrium Partitioning  | 3.6 mg/kg dwt   |
|  | Marine water sediment - Equilibrium Partitioning | 0.36 mg/kg dwt  |
|  | Soil - Equilibrium Partitioning                  | 0.14 mg/kg dwt  |

**8.2 Exposure controls**

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Chemical splash goggles and face shield. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapor (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Color** : Clear.
- Odor** : Odorless.
- Melting point/freezing point** : Not determined.
- Boiling point or initial boiling point and boiling range** : >37.78°C
- Flammability** : Not determined. There are no data available on the mixture itself.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: 180°C

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 9: Physical and chemical properties

Auto-ignition temperature :

| Ingredient name                             | °C  | °F  | Method    |
|---|-----|-----|-----------|
| γ-(2,3-epoxypropoxy)propyl trimethoxysilane | 400 | 752 | DIN 51794 |

Decomposition temperature : Stable under recommended storage and handling conditions (see Section 7).

pH : Not applicable. insoluble in water.

Viscosity : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm<sup>2</sup>/s

Solubility :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

Partition coefficient n-octanol/water (log Pow) : Not applicable.

Vapor pressure :

| Ingredient name | Vapor Pressure at 20°C |        |        | Vapor pressure at 50°C |     |        |
|-----------------|------------------------|--------|--------|------------------------|-----|--------|
|                 | mm Hg                  | kPa    | Method | mm Hg                  | kPa | Method |
| benzyl alcohol  | 0.05                   | 0.0067 |        |                        |     |        |

Relative density : 1.14

Particle characteristics

Median particle size : Not applicable.

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapor or dust with air is possible.

**Oxidizing properties** : Product does not present an oxidizing hazard.

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Code : 00482510 Date of issue/Date of revision : 14 June 2026  
 PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- Causes serious eye damage.
- Causes skin irritation.
- May cause an allergic skin reaction.

#### Acute toxicity

| Product/ingredient name                       | Result  | Dose / Exposure     |
|---|---|---------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl] propane      | Rabbit - Dermal - LD50  | 23000 mg/kg         |
| benzyl alcohol                                | Rat - Oral - LD50   | 15000 mg/kg         |
|   | Rabbit - Dermal - LD50  | >2000 mg/kg         |
| [3-(2,3-epoxypropoxy)propyl] trimethoxysilane | Rat - Oral - LD50   | 1200 mg/kg          |
|   | Rat - Inhalation - LC50 Dusts and mists   | >5 mg/l [4 hours]   |
|   | Rat - Oral - LD50   | 7.01 g/kg           |
|   | <i>Toxic effects:</i> Behavioral - Somnolence (general depressed activity) Behavioral - Coma<br>Rat - Inhalation - LC50 Dusts and mists | >5.3 mg/l [4 hours] |

#### Acute toxicity estimates

| Route | ATE value      |
|-------|----------------|
| Oral  | 14495.73 mg/kg |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Irritation/Corrosion

| Product/ingredient name                  | Result  |
|--|---|
| bis-[4-(2,3-epoxipropoxy)phenyl] propane | <u>Rabbit - Eyes - Redness of the conjunctivae</u><br>Duration of treatment/exposure: 24 hours<br>Irritation score: 0.4 |
| -  | <u>Rabbit - Eyes - Mild irritant</u><br>Duration of treatment/exposure: 24 hours<br>Fully reversible in 7 days or less  |
| -  | <u>Rabbit - Skin - Erythema/Eschar</u><br>Duration of treatment/exposure: 4 hours<br>Irritation score: 0.8              |
| -  | <u>Rabbit - Skin - Edema</u><br>Duration of treatment/exposure: 4 hours<br>Irritation score: 0.5                        |
| -  | <u>Rabbit - Skin - Mild irritant</u><br>Duration of treatment/exposure: 4 hours   |

#### Conclusion/Summary

- Skin** : Causes skin irritation.
- Eyes** : Causes serious eye damage.
- Respiratory** : Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitization

| Product/ingredient name                  | Test         | Result      |
|--|--------------|-------------|
| bis-[4-(2,3-epoxipropoxy)phenyl] propane | Mouse - skin | Sensitizing |

Code : 00482510

Date of issue/Date of revision

: 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 11: Toxicological information

### Conclusion/Summary

**Skin** : May cause an allergic skin reaction.

**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

### Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : No specific data.

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

**Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur

**Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure

**Potential immediate effects** : No known significant effects or critical hazards.

**Potential delayed effects** : No known significant effects or critical hazards.

### Potential chronic health effects

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Code : 00482510 Date of issue/Date of revision : 14 June 2026  
 PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 11: Toxicological information

- Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.  
**Other information** : Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

There are no data available on the mixture itself.  
 Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

### 12.1 Toxicity

| Product/ingredient name                      | Result                     | Species                        | Dose / Exposure     |
|--|----------------------------|--------------------------------|---------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane      | Chronic - NOEC             | Daphnia                        | 0.3 mg/l [21 days]  |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | Acute - LC50 - Fresh water | Daphnia - <i>daphnia magna</i> | 1.8 mg/l [48 hours] |
|  | Acute - EC50 - Fresh water | Algae                          | 255 mg/l [72 hours] |
|  | Acute - EC50               | Daphnia                        | 473 mg/l [48 hours] |
|  | Acute - LC50               | Fish                           | 55 mg/l [96 hours]  |

**Conclusion/Summary** : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

| Product/ingredient name                      | Test | Result                      | Dose / Inoculum |
|--|------|-----------------------------|-----------------|
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | -    | 37% [28 days] - Not readily |                 |

| Product/ingredient name                      | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane      | -                 | -          | Not readily      |
| benzyl alcohol                               | -                 | -          | Readily          |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | -                 | -          | Not readily      |

### 12.3 Bioaccumulative potential

Code : 00482510 Date of issue/Date of revision : 14 June 2026  
PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 12: Ecological information

| Product/ingredient name | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| benzyl alcohol          | 0.87               | -   | Low       |

### 12.4 Mobility in soil

#### Soil/Water partition coefficient

| Product/ingredient name                      | logK <sub>oc</sub> | K <sub>oc</sub> |
|--|--------------------|-----------------|
| 1,4-bis-[4-(2,3-epoxypropoxy)phenyl]propane  | 4                  | 10465.7         |
| benzyl alcohol                               | 1.1                | 12.6442         |
| [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 2.4                | 266.308         |

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** :

#### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

Code : 00482510 Date of issue/Date of revision : 14 June 2026

PPG FLR 912 LV EPOXY PRIMER CLEAR - A

## SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                 | ADR/RID  | ADN  | IMDG   | IATA   |
|---------------------------------|--|--|--|--|
| 14.1 UN number or ID number     | UN3082   | UN3082   | UN3082   | UN3082   |
| 14.2 UN proper shipping name    | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(PAINT) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(PAINT) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.<br>(PAINT) | Environmentally hazardous substance, liquid, n.o.s.<br>(PAINT) |
| 14.3 Transport hazard class(es) | 9  | 9  | 9  | 9  |
| 14.4 Packing group              | III  | III  | III  | III  |
| 14.5 Environmental hazards      | Yes.   | Yes.   | Yes.   | Yes.   |
| Marine pollutant substances     | Not applicable.  | Not applicable.  | (bis-[4-(2,3-epoxipropoxy)phenyl]propane)                      | Not applicable.  |

### Additional information

**ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Tunnel code** : (-)

**ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

|                                       |   |
|---------------------------------------|---|
| Code : 00482510                       | Date of issue/Date of revision : 14 June 2026 |
| PPG FLR 912 LV EPOXY PRIMER CLEAR - A |   |

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorization

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name               | Entry Number ( REACH ) |
|---------------------------------------|------------------------|
| PPG FLR 912 LV EPOXY PRIMER CLEAR - A | 3                      |

**Labeling** : Not applicable.

#### Other EU regulations

**Explosive precursors** : Not applicable.

##### Ozone depleting substances (EU 2024/590)

Not listed.

##### Persistent Organic Pollutants

Not listed.

#### Seveso Directive


This product is controlled under the Seveso Directive.

##### Danger criteria

| Category |
|----------|
| E2       |

**15.2 Chemical Safety Assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

 Indicates information that has changed from previously issued version.

#### **Abbreviations and acronyms**

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

#### Full text of abbreviated H statements

|                                       |  |
|---------------------------------------|--|
| <b>Code</b> : 00482510                | <b>Date of issue/Date of revision</b> : 14 June 2026 |
| PPG FLR 912 LV EPOXY PRIMER CLEAR - A |  |

**SECTION 16: Other information**

|  |  |
|--|--|
| H302<br>H315<br>H317<br>H318<br>H319<br>H411<br>H412 | Harmful if swallowed.<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye damage.<br>Causes serious eye irritation.<br>Toxic to aquatic life with long lasting effects.<br>Harmful to aquatic life with long lasting effects. |
|--|--|

**Full text of classifications [CLP/GHS]**

|  |  |
|--|--|
| Acute Tox. 4<br>Aquatic Chronic 2<br>Aquatic Chronic 3<br>Eye Dam. 1<br>Eye Irrit. 2<br>Skin Irrit. 2<br>Skin Sens. 1<br>Skin Sens. 1B | ACUTE TOXICITY - Category 4<br>AQUATIC HAZARD (LONG-TERM) - Category 2<br>AQUATIC HAZARD (LONG-TERM) - Category 3<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2<br>SKIN CORROSION/IRRITATION - Category 2<br>SKIN SENSITIZATION - Category 1<br>SKIN SENSITIZATION - Category 1B |
|--|--|

**History**

**Date of issue/ Date of revision** : 14 June 2026  
**Date of previous issue** : 5 May 2026  
**Prepared by** : EHS  
**Version** : 2

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*