

SAFETY DATA SHEET



Date of issue/Date of revision

: 19 June 2026

Version

: 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PITT-CHAR XP BASE WHITE
Product code : 00393292
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier
+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture
Classification according to UK CLP/GHS
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Repr. 2, H361d
Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.
See Section 16 for the full text of the H statements declared above.
See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms : 

Signal word : Warning

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 2: Hazards identification

Hazard statements : Causes skin irritation.
 May cause an allergic skin reaction.
 Causes serious eye irritation.
 Suspected of damaging the unborn child.
 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Avoid breathing vapour.

Response : Collect spillage.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
 P202, P280, P273, P261, P391, P501

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Type |
|---|--|-----------|---|------|
| Hexaboron dizinc undecaoxide | REACH #: 01-2119691658-19 EC: 235-804-2 CAS: 12767-90-7 | ≥10 - <25 | Eye Irrit. 2, H319 Repr. 2, H361d (oral) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 | [1] |
| Dodecanedioic acid, polymer with 2,2'-[1,4-butanediylbis (oxymethylene)]bis[oxirane], (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol], nonanedioic acid and 2,2'-oxybis [ethanol] | CAS: 139651-91-5 | ≥10 - ≤25 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 | [1] |
| Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)- | REACH #: 01-2119970312-43 EC: 234-521-1 CAS: 12046-04-7 | ≥10 - ≤25 | Repr. 2, H361d | [1] |
| Phosphoric trichloride, reaction products with propylene oxide | REACH #: 01-2119486772-26 | ≥10 - <25 | Acute Tox. 4, H302 Aquatic Chronic 3, | [1] |

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 3: Composition/information on ingredients

| | | | | |
|--|--|------------|---|-----|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | EC: 807-935-0 CAS: 1244733-77-4 REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2 | ≥5.0 - ≤10 | H412 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 | [1] |
| N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) | REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2 | <1.0 | Skin Sens. 1B, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above. | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

| | |
|--------------------------------|--|
| Code : 00393292 | Date of issue/Date of revision : 19 June 2026 |
| PITT-CHAR XP BASE WHITE | |

SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
 carbon oxides
 phosphorus oxides
 halogenated compounds
 metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

| | |
|--------------------------------|--|
| Code : 00393292 | Date of issue/Date of revision : 19 June 2026 |
| PITT-CHAR XP BASE WHITE | |

SECTION 6: Accidental release measures

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

| | |
|--------------------------------|--|
| Code : 00393292 | Date of issue/Date of revision : 19 June 2026 |
| PITT-CHAR XP BASE WHITE | |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

No exposure limit value known.

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| | | | | |
|--|--|---|-------------------------|-------------------------|
| Hexaboron dizinc undecaoxide | DNEL - General population - Long term - Inhalation | <i>Local</i> | 0.12 mg/m ³ | |
| | DNEL - General population - Long term - Oral | <i>Systemic</i> | 0.507 mg/kg bw/day | |
| | DNEL - Workers - Long term - Inhalation | <i>Local</i> | 0.69 mg/m ³ | |
| | DNEL - General population - Long term - Inhalation | <i>Systemic</i> | 0.88 mg/m ³ | |
| | DNEL - Workers - Long term - Inhalation | <i>Systemic</i> | 2.48 mg/m ³ | |
| | DNEL - General population - Long term - Dermal | <i>Systemic</i> | 25.35 mg/kg bw/day | |
| | DNEL - Workers - Long term - Dermal | <i>Systemic</i> | 35.49 mg/kg bw/day | |
| | DNEL - General population - Long term - Oral | <i>Systemic</i> | 0.52 mg/kg bw/day | |
| | Phosphoric trichloride, reaction products with propylene oxide | DNEL - General population - Long term - Dermal | <i>Systemic</i> | 1.04 mg/kg bw/day |
| | | DNEL - General population - Long term - Inhalation | <i>Systemic</i> | 1.45 mg/m ³ |
| | | DNEL - General population - Short term - Oral | <i>Systemic</i> | 2 mg/kg bw/day |
| | | DNEL - Workers - Long term - Dermal | <i>Systemic</i> | 2.91 mg/kg bw/day |
| | | DNEL - General population - Short term - Inhalation | <i>Systemic</i> | 5.6 mg/m ³ |
| | | DNEL - Workers - Long term - Inhalation | <i>Systemic</i> | 8.2 mg/m ³ |
| DNEL - Workers - Short term - Inhalation | | <i>Systemic</i> | 22.6 mg/m ³ | |
| DNEL - Workers - Long term - Inhalation | | <i>Systemic</i> | 12.25 mg/m ³ | |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | | DNEL - Workers - Short term - Inhalation | <i>Systemic</i> | 12.25 mg/m ³ |
| | | DNEL - Workers - Long term - Dermal | <i>Systemic</i> | 8.33 mg/kg bw/day |
| | DNEL - Workers - Short term - Dermal | <i>Systemic</i> | 8.33 mg/kg bw/day | |
| | DNEL - General population - Consumers - Long term - Dermal | <i>Systemic</i> | 3.571 mg/kg bw/day | |
| | DNEL - General population - Consumers - Short term - Dermal | <i>Systemic</i> | 3.571 mg/kg bw/day | |
| | DNEL - General population - Consumers - Long term - Oral | <i>Systemic</i> | 0.75 mg/kg bw/day | |
| | DNEL - General population - Consumers - Short term - Oral | <i>Systemic</i> | 0.75 mg/kg bw/day | |
| | DNEL - General population - Long term - Dermal | <i>Systemic</i> | 89.3 µg/kg bw/day | |
| | DNEL - General population - Long term - Oral | <i>Systemic</i> | 0.5 mg/kg bw/day | |
| | DNEL - Workers - Long term - Dermal | <i>Systemic</i> | 0.75 mg/kg bw/day | |
| DNEL - General population - Long term - Inhalation | <i>Systemic</i> | 0.87 mg/m ³ | | |
| DNEL - Workers - Long term - Inhalation | <i>Systemic</i> | 4.93 mg/m ³ | | |

PNECs

| | |
|--------------------------------|--|
| Code : 00393292 | Date of issue/Date of revision : 19 June 2026 |
| PITT-CHAR XP BASE WHITE | |

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Compartment Detail - Method | Value |
|---|--|-----------------|
| trans-[4-(2,3-epoxipropoxy)phenyl]propane | Fresh water - Assessment Factors | 0.006 mg/l |
| | Marine water - Assessment Factors | 0.001 mg/l |
| | Fresh water sediment - Equilibrium Partitioning | 0.996 mg/kg dwt |
| | Marine water sediment - Equilibrium Partitioning | 0.1 mg/kg dwt |
| | Soil - Equilibrium Partitioning | 0.196 mg/kg dwt |
| | Sewage Treatment Plant - Assessment Factors | 10 mg/l |
| | Secondary Poisoning - Assessment Factors | 11 mg/kg |

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
Colour : Off-white.
Odour : Characteristic.
Odour threshold : Not available.
Melting point/freezing point :
Initial boiling point and boiling range : >37.78°C (>100°F)
Flammability (solid, gas) : liquid
Upper/lower flammability or explosive limits : Not available.
Flash point : Closed cup: Not applicable.
Auto-ignition temperature : Not available.
pH : Not applicable.
 Not applicable. insoluble in water.
Viscosity : Dynamic (room temperature): Not available.
 Kinematic (room temperature): Not available.
 Kinematic (40°C): >21 mm²/s

Solubility(ies)

| Media | Result |
|------------|-------------|
| cold water | Not soluble |

- Miscible with water** : No.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|---|-------------------------|----------|--------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| is-[4-(2,3-epoxipropoxy)phenyl] propane | <0.000075006 | <0.00001 | | | | |

- Relative density** : 1.47
Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties : Product does not present an oxidizing hazard.
Particle characteristics
Median particle size : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability : The product is stable.
10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

| | |
|--------------------------------|--|
| Code : 00393292 | Date of issue/Date of revision : 19 June 2026 |
| PITT-CHAR XP BASE WHITE | |

SECTION 10: Stability and reactivity

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Dose / Exposure |
|--|--|--|
| Hexaboron dizinc undecaoxide | Rabbit - Dermal - LD50 Rat - Oral - LD50 Rat - Inhalation - LC50 Dusts and mists Rabbit - Dermal - LD50 | >5000 mg/kg >5000 mg/kg >5 mg/l [4 hours] >2000 mg/kg |
| Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)- | Rat - Oral - LD50 Rat - Oral - LD50 | 4200 mg/kg 630 to 2000 mg/kg |
| Phosphoric trichloride, reaction products with propylene oxide | Rabbit - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists Rabbit - Dermal - LD50 | >2000 mg/kg >7 mg/l [4 hours] 23000 mg/kg |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Rat - Oral - LD50 Rat - Oral - LD50 | 15000 mg/kg >2000 mg/kg |
| N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | Rat - Dermal - LD50 Rat - Inhalation - LC50 Dusts and mists | >2000 mg/kg >5.11 mg/l [4 hours] |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| PITT-CHAR XP BASE WHITE | 3963.9 | N/A | N/A | N/A | N/A |
| Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)- | 4200 | N/A | N/A | N/A | N/A |
| Phosphoric trichloride, reaction products with propylene oxide | 500 | N/A | N/A | N/A | N/A |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | 15000 | 23000 | N/A | N/A | N/A |

Irritation/Corrosion

| Product/ingredient name | Result |
|---|---|
| Hexaboron dizinc undecaoxide | <u>Rabbit - Eyes - Cornea opacity</u> Amount/concentration applied: 0.083g Duration of treatment/exposure: 24 hours Observation period: 74 hours Irritation score: 33 Fully reversible in more than 7 days |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | <u>Rabbit - Eyes - Redness of the conjunctivae</u> Duration of treatment/exposure: 24 hours Irritation score: 0.4 |
| - | <u>Rabbit - Eyes - Mild irritant</u> Duration of treatment/exposure: 24 hours |

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 11: Toxicological information

| | |
|---|--|
| - | Fully reversible in 7 days or less |
| - | <u>Rabbit - Skin - Erythema/Eschar</u> Duration of treatment/exposure: 4 hours Irritation score: 0.8 |
| - | <u>Rabbit - Skin - Oedema</u> Duration of treatment/exposure: 4 hours Irritation score: 0.5 |
| - | <u>Rabbit - Skin - Mild irritant</u> Duration of treatment/exposure: 4 hours |

Conclusion/Summary : Not available.
Skin : There are no data available on the mixture itself.
Eyes : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

Sensitisation

| Product/ingredient name | Test | Result |
|---|--------------|-------------|
| Bis-[4-(2,3-epoxipropoxy)phenyl]propane | Mouse - skin | Sensitising |

Conclusion/Summary
Skin : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

| Product/ingredient name | Test | Result |
|------------------------------|---|---|
| Hexaboron dizinc undecaoxide | Rat - Oral OECD 408 375 mg/kg [7 days per week] [90 days] | Developmental: Positive Maternal toxicity: Positive Fertility effects: Positive |

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Code : 00393292
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 19 June 2026

SECTION 11: Toxicological information

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Long term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Potential chronic health effects****Conclusion/Summary** : Not available.**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Reproductive toxicity** : Suspected of damaging the unborn child.**Other information**

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

| Product/ingredient name | Result | Species | Dose / Exposure |
|--|--------------|--------------------------------|----------------------|
| Hexaboron dizinc undecaoxide Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-Phosphoric trichloride, reaction products with propylene oxide | Acute - EC50 | Daphnia - <i>Daphnia magna</i> | 76 mg/l [48 hours] |
| | Acute - LC50 | Fish - <i>Salmo gairdneri</i> | 2.17 mg/l [96 hours] |
| | Acute - LC50 | Fish | >100 mg/l [96 hours] |
| | EC50 | Algae | 82 mg/l [72 hours] |
| | LC50 | Fish | 51 mg/l [96 hours] |
| | EC50 | Daphnia | 131 mg/l [48 hours] |
| | NOEC | Daphnia | 32 mg/l [48 hours] |

| | |
|--------------------------------|--|
| Code : 00393292 | Date of issue/Date of revision : 19 June 2026 |
| PITT-CHAR XP BASE WHITE | |

SECTION 12: Ecological information

| | | | |
|--|----------------------------|--|--------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | Chronic - NOEC | Daphnia | 0.3 mg/l [21 days] |
| N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | Acute - LC50 - Fresh water | Daphnia - <i>daphnia magna</i> | 1.8 mg/l [48 hours] |
| | Acute - EC50 | Daphnia - <i>Daphnia magna</i> | 94 mg/l [48 hours] |
| | Acute - EC50 | Algae - <i>Pseudokirchneriella subcapitata</i> | 29 to 43 mg/l [72 hours] |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose / Inoculum |
|--|------|---------------|-----------------|
| <input checked="" type="checkbox"/> N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | - | 63% [28 days] | |

Conclusion/Summary : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| <input checked="" type="checkbox"/> bis-[4-(2,3-epoxipropoxy)phenyl]propane | - | - | Not readily |
| <input checked="" type="checkbox"/> N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|-----------|-----------|
| <input checked="" type="checkbox"/> hexaboron dizinc undecaoxide | - | 60960 | High |
| Phosphoric trichloride, reaction products with propylene oxide | 2.68 | 0.8 to 14 | Low |
| <input checked="" type="checkbox"/> N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | >6 | - | High |

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|---|-----|-----|-----|----|------|-----|-----|
| <input checked="" type="checkbox"/> hexaboron dizinc undecaoxide | No | No | No | No | No | No | No |
| Dodecanedioic acid, polymer with 2,2'-[1,4-butanediylbis(oxymethylene)]bis[oxirane], (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol], nonanedioic acid and 2,2'-oxybis[ethanol] | No | N/A | N/A | No | N/A | N/A | N/A |
| Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)- | No | No | No | No | No | No | No |
| Phosphoric trichloride, reaction products with propylene oxide | No | N/A | No | No | No | N/A | No |
| <input checked="" type="checkbox"/> bis-[4-(2,3-epoxipropoxy) | No | N/A | N/A | No | N/A | N/A | N/A |

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 12: Ecological information

| | | | | | | | |
|--|----|-----|-----|----|-----|-----|-----|
| phenyl]propane N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide) | No | N/A | N/A | No | N/A | N/A | N/A |
|--|----|-----|-----|----|-----|-----|-----|

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Waste catalogue

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue |
|-------------------|--------------------------|
| Container | 15 01 06 mixed packaging |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|--|--|--|--|
| 14.1 UN number | UN3082 | UN3082 | UN3082 | UN3082 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT) |
| 14.3 Transport hazard class(es) | 9 | 9 | 9 | 9 |
| 14.4 Packing group | III | III | III | III |
| 14.5 Environmental hazards | Yes. | Yes. | Yes. | Yes. |
| Marine pollutant substances | Not applicable. | Not applicable. | ☑ (hexaboron dizinc undecaoxide) | Not applicable. |

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 14: Transport information

Additional information

- ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- Tunnel code** : (-)
- ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern


None of the components are listed.

Explosive precursors : Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles


| Product/ingredient name | Entry Number (REACH) |
|---|----------------------|
|  PITT-CHAR XP BASE WHITE | 3 |

Labelling : Not applicable.


Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|---|
|  |

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = GB CLP-specific Hazard statement
 N/A = Not available

Code : 00393292 **Date of issue/Date of revision** : 19 June 2026
PITT-CHAR XP BASE WHITE

SECTION 16: Other information

PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

| Classification | Justification |
|--|--|
| Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361d Aquatic Chronic 2, H411 | Calculation method Calculation method Calculation method Calculation method Calculation method |

Full text of abbreviated H statements

| | |
|-------|--|
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H361d | Suspected of damaging the unborn child. |
| H400 | Very toxic to aquatic life. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Full text of classifications

| | |
|-------------------|---|
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Repr. 2 | REPRODUCTIVE TOXICITY - Category 2 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1B | SKIN SENSITISATION - Category 1B |

History

Date of issue/ Date of revision : 19 June 2026
Date of previous issue : 9 November 2022
Prepared by : EHS
Version : 1.01

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.