

SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 19 June 2026

Date of issue 19 June 2026

Version 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : PSX 700A CLEAR COAT RESIN

Product code : 00336125

Other means of identification : Not applicable.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

Use of the substance/
mixture : Coating.

Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture : SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 2
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:
88.5% (oral), 91.9% (dermal), 93.6% (inhalation)

GHS label elements

Hazard pictograms :



SECTION 2: Hazards identification

Signal word : Danger

Hazard statements : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H341 - Suspected of causing genetic defects.
H351 - Suspected of causing cancer.
H360 - May damage fertility or the unborn child.
H370 - Causes damage to organs. (thymus)
H372 - Causes damage to organs through prolonged or repeated exposure. (immune system)

Precautionary statements

Prevention : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing and eye or face protection.
P260 - Do not breathe vapor.
P270 - Do not eat, drink or smoke when using this product.
P264 - Wash thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.

Response : P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.

See toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture
Product name : PSX 700A CLEAR COAT RESIN
Other means of identification : Not applicable.

Ingredient name	%	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with	≥10 - ≤20	30583-72-3
1-chloro-2,3-epoxypropane	≥1.0 - ≤5.0	41556-26-7
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤1.8	1067-33-0
dibutyltin di(acetate)	≤1.4	1330-20-7
xylene	<1.0	100-41-4
ethylbenzene	<1.0	82919-37-7
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		

SECTION 3: Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

- | | |
|---------------------|--|
| Eye contact | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |

Most important symptoms/effects, acute and delayed

Potential acute health effects

- | | |
|---------------------|--|
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : Causes damage to organs following a single exposure in contact with skin. Causes skin irritation. May cause an allergic skin reaction. |
| Ingestion | : Causes damage to organs following a single exposure if swallowed. |

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary

- | | |
|-----------------------------------|---|
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

SECTION 5: Firefighting measures

Extinguishing media

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |

- | | |
|---|---|
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
|---|---|

SECTION 5: Firefighting measures

Hazardous thermal decomposition products

- : Decomposition products may include the following materials:
 - carbon oxides
 - nitrogen oxides
 - halogenated compounds
 - metal oxide/oxides

Special protective actions for fire-fighters

- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor. Put on appropriate personal protective equipment.

For emergency responders

- : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

- : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

- : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible

SECTION 7: Handling and storage

material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate dibutyltin di(acetate)	None.
xylene	None. NOM-010-STPS-2014 (Mexico, 4/2016) [Estaño, compuestos orgánicos] Absorbed through skin. TWA 8 hours: 0.1 mg/m ³ (as Sn). STEL 15 minutes: 0.2 mg/m ³ (as Sn). NOM-010-STPS-2014 (Mexico, 4/2016) [Xileno, mezcla] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.
ethylbenzene	NOM-010-STPS-2014 (Mexico, 4/2016) TWA 8 hours: 20 ppm.
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	None.

Key to abbreviations

C = Ceiling Limit
IPEL = Internal Permissible Exposure Limit

STEL = Short term exposure limit
TLV = Threshold Limit Value
TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Clear.

Odor : Characteristic.

Odor threshold : Not available.

Molecular weight : Not applicable.

pH : Not applicable.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 97.22°C (207°F)

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability : Not available.

SECTION 9: Physical and chemical properties

Lower and upper explosive (flammable) limits : Not available.

Evaporation rate : 0.98 (butyl acetate = 1)

Vapor pressure : 3.3 kPa (24.9 mm Hg)

Vapor density : Not available.

Relative density : 1.12

Density (lbs / gal) : 9.35

Media	Result
cold water	Not soluble

Solubility in water : 0.4 g/l

Partition coefficient: n-octanol/water : Not applicable.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

% Solid. (w/w) : 96.982

SECTION 10: Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.
Refer to protective measures listed in sections 7 and 8.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose
Diis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Rat - Oral - LD50	3.125 g/kg
dibutyltin di(acetate)	Rabbit - Dermal - LD50	2318 mg/kg
xylene	Rat - Oral - LD50	4.3 g/kg
	Rabbit - Dermal - LD50	1.7 g/kg
ethylbenzene	Rat - Oral - LD50	3.5 g/kg
	Rabbit - Dermal - LD50	17.8 g/kg
	Rat - Inhalation - LC50 Vapor	17.8 mg/l [4 hours]
methyl 1,2,2,6,6-pentamethyl-4-piperidyl	Rat - Oral - LD50	3.125 g/kg

SECTION 11: Toxicological information

sebacate

Product Conclusion : There are no data available on the mixture itself.**Skin corrosion/irritation**

Product/ingredient name	Species	Dose	Score
xylene	Rabbit - Skin - Moderate irritant	Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours	-

Conclusion/Summary : There are no data available on the mixture itself.**Serious eye damage/eye irritation****Conclusion/Summary** : There are no data available on the mixture itself.**Respiratory corrosion/irritation****Conclusion/Summary** : There are no data available on the mixture itself.**Sensitization****Skin****Conclusion/Summary** : There are no data available on the mixture itself.**Respiratory****Conclusion/Summary** : There are no data available on the mixture itself.**Mutagenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Carcinogenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Classification**

Product/ingredient name	OSHA	IARC	NTP
xylene	-	3	-
ethylbenzene	-	2B	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity**Conclusion/Summary** : There are no data available on the mixture itself.**Specific target organ toxicity (single exposure)**

Product/ingredient name	Result
dibutyltin di(acetate)	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (thymus) (oral) - Category 1
xylene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
dibutyltin di(acetate)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (immune system) - Category 1
ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2

SECTION 11: Toxicological information

Target organs : Contains material which causes damage to the following organs: brain, upper respiratory tract, skin.
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, bladder, immune system, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure**Potential acute health effects**

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes damage to organs following a single exposure in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Ingestion : Causes damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 11: Toxicological information**Short term exposure**

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Conclusion/Summary : There are no data available on the mixture itself.

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : Suspected of causing genetic defects.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700A CLEAR COAT RESIN	8491.3	5168.7	N/A	51.6	7.0
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3125	N/A	N/A	N/A	N/A
dibutyltin di(acetate)	N/A	2318	N/A	N/A	N/A
xylene	4300	1700	N/A	11	1.5
ethylbenzene	3500	17800	N/A	17.8	1.5
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3125	N/A	N/A	N/A	N/A

SECTION 12: Ecological information**Toxicity**

Product/ingredient name	Result	Species
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50 11.5 mg/l [96 hours]	Fish - Trout
dibutyltin di(acetate)	Acute - EC10 3.1 mg/l [72 hours] Acute - EC50 0.5 mg/l [72 hours]	Fish Algae
ethylbenzene	Acute - EC50 - Fresh water 1.8 mg/l [48 hours] Chronic - NOEC - Fresh water 1 mg/l	Daphnia Daphnia - <i>Ceriodaphnia dubia</i>

Persistence and degradability

SECTION 12: Ecological information

Product/ingredient name	Result
ethylbenzene	79% [10 days] - Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
ethylbenzene	3.6	79.43	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

	Mexico Classification	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.

SECTION 14: Transport information

Marine pollutant substances	Not applicable.	(bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)	Not applicable.
Product RQ (lbs)	Not applicable.	Not applicable.	Not applicable.
RQ substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- Mexico** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

SECTION 16: Other information

Please refer to Section 2 of this document for GHS hazard classifications.
The customer is responsible for determining the PPE code for this material.

Date of previous issue : 3/3/2025

Organization that prepared the SDS : EHS

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient

SECTION 16: Other information

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.