

SAFETY DATA SHEET

Date of issue/Date of revision

: 9 July 2026

Version

: 1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMARINE 48 LF GREY

Product code : 30013447

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Repr. 1B, H360FD

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Flammable liquid and vapour. Causes skin irritation. May damage fertility. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Prevention	:	Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour.
Response	:	IF exposed or concerned: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P202, P280, P210, P260, P308 + P313, P501
Hazardous ingredients	:	naphtha (petroleum), hydrodesulphurized heavy Note P and 2-ethylhexanoic acid, zirconium salt
Supplemental label elements	:	Contains octanoic acid, cobalt salt. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	:	Based on available data, the classification criteria are not met.
Other hazards which do not result in classification	:	None known.

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), hydro- treated light	EC: 265-149-8 CAS: 64742-47-8 Index: 649-422-00-2	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]
naphtha (petroleum), hydrodesulphurized heavy Note P	EC: 265-185-4 CAS: 64742-82-1 Index: 649-330-00-2	≥10 - <20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	-	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 Index: 607-230-00-6	≥1.0 - ≤5.0	Repr. 1B, H360D	-	[1] [2]
octanoic acid, cobalt salt	EC: 229-744-6 CAS: 6700-85-2	<1.0	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code : 30013447
SIGMARINE 48 LF GREY

Date of issue/Date of revision : 9 July 2026

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Code : 30013447
SIGMARINE 48 LF GREY

Date of issue/Date of revision : 9 July 2026

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.
2-ethylhexanoic acid, zirconium salt	ACGIH TLV (United States, 1/2025) [Zirconium and compounds] A4. TWA 8 hours: 5 mg/m³ (as Zr). STEL 15 minutes: 10 mg/m³ (as Zr).
octanoic acid, cobalt salt	ACGIH TLV (United States, 1/2025) [cobalt and inorganic compounds] A3. Skin sensitiser , Inhalation sensitiser. TWA 8 hours: 0.02 mg/m³ (as Co).

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
naphtha (petroleum), hydrodesulphurized heavy Note P	DNEL - Workers - Long term - Inhalation	Systemic 1286 mg/m³
	DNEL - General population - Long term - Inhalation	Systemic 0.41 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic 1.9 mg/m³
	DNEL - General population - Long term - Inhalation	Local 178.57 mg/m³
	DNEL - General population - Short term - Inhalation	Local 640 mg/m³
	DNEL - Workers - Long term - Inhalation	Local 837.5 mg/m³
	DNEL - Workers - Short term - Inhalation	Local 1066.67 mg/m³
	DNEL - General population - Short term - Inhalation	Systemic 570 mg/m³
	DNEL - Workers - Short term - Inhalation	Systemic 570 mg/m³
	DNEL - General population - Long term - Dermal	Systemic 12 mg/kg bw/day
	DNEL - General population - Long term - Oral	Systemic 21 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic 21 mg/kg bw/day
	DNEL - General population - Long term - Oral	Systemic 5 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Local 65.3 mg/m³
	DNEL - General population - Long term -	Systemic 65.3 mg/m³
xylene		

Code : 30013447

Date of issue/Date of revision

: 9 July 2026

SIGMARINE 48 LF GREY

SECTION 8: Exposure controls/personal protection

2-ethylhexanoic acid, zirconium salt	Inhalation		
	DNEL - General population - Long term - Dermal	Systemic	125 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	212 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Local	221 mg/m ³
	DNEL - Workers - Long term - Inhalation	Systemic	221 mg/m ³
	DNEL - General population - Short term - Inhalation	Local	260 mg/m ³
	DNEL - General population - Short term - Inhalation	Systemic	260 mg/m ³
	DNEL - Workers - Short term - Inhalation	Local	442 mg/m ³
	DNEL - Workers - Short term - Inhalation	Systemic	442 mg/m ³
	DNEL - General population - Long term - Inhalation	Systemic	0.58 mg/m ³
	DNEL - Workers - Long term - Inhalation	Systemic	2.351 mg/m ³
	DNEL - General population - Long term - Oral	Systemic	0.167 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic	0.167 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	0.333 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Local	0.7 mg/m ³
	DNEL - Workers - Long term - Inhalation	Local	2.82 mg/m ³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
xylene	Fresh water	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage Treatment Plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dwt
	Marine water sediment	12.46 mg/kg dwt
	Soil	2.31 mg/kg

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 8: Exposure controls/personal protection

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves	: For prolonged or repeated handling, use the following type of gloves: Recommended: neoprene, polyvinyl alcohol (PVA), Viton® Not recommended: nitrile rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Colour

Odour

Melting point/freezing point

Boiling point or initial boiling point and boiling range

Flammability

Lower and upper explosion limit

Flash point

Auto-ignition temperature

Decomposition temperature

: Liquid.

: Not available.

: Not available.

: Not determined.

: >37.78°C

: Not determined. There are no data available on the mixture itself.

: Not available.

: Closed cup: 44°C

:

: Stable under recommended storage and handling conditions (see Section 7).

Ingredient name	°C	°F	Method
Distillates (petroleum), hydro- treated light	>220	>428	

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

- Causes skin irritation.
- May damage fertility.
- May damage the unborn child.
- Causes damage to organs through prolonged or repeated exposure.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
naphtha (petroleum), hydrodesulphurized heavy Note P	Rat - Oral - LD50	>5000 mg/kg
xylene	Rabbit - Dermal - LD50	>2000 mg/kg
	Rat - Oral - LD50	4.3 g/kg
	Rabbit - Dermal - LD50	1.7 g/kg
2-ethylhexanoic acid, zirconium salt	Rabbit - Dermal - LD50	>5 g/kg
	Rat - Oral - LD50	>5 g/kg
	<i>Toxic effects:</i> Behavioral - Somnolence (general depressed activity)	

Acute toxicity estimates

Route	ATE value
Dermal	66203.42 mg/kg
Inhalation (vapours)	428.38 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

- Skin : Causes skin irritation.
- Eyes : Based on available data, the classification criteria are not met.
- Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Conclusion/Summary

- Skin : Based on available data, the classification criteria are not met.
- Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

- May damage fertility.
- May damage the unborn child.

Specific target organ toxicity (single exposure)

Code : 30013447
SIGMARINE 48 LF GREY

Date of issue/Date of revision : 9 July 2026

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
naphtha (petroleum), hydrodesulphurized heavy Note P xylene	Category 3 Category 3	- -	Narcotic effects Respiratory tract irritation

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
naphtha (petroleum), hydrodesulphurized heavy Note P	Category 1	-	-

Conclusion/Summary :

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydro- treated light naphtha (petroleum), hydrodesulphurized heavy Note P xylene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Eye contact** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 11: Toxicological information

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility. May damage the unborn child.

Other information : Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
2-ethylhexanoic acid, zirconium salt	Acute - LC50	Fish	>100 mg/l [96 hours]

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydro-treated light xylene	-	-	Readily
	-	-	Readily

12.3 Bioaccumulative potential

Code : 30013447	Date of issue/Date of revision : 9 July 2026
SIGMARINE 48 LF GREY	

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Distillates (petroleum), hydro- treated light naphtha (petroleum), hydrodesulphurized heavy	-	159	Low
Note P	-	10 to 2500	High
xylene	3.12	7.4 to 18.5	Low

12.4 Mobility in soil

Soil/water partition coefficient		
Product/ingredient name	logK _{oc}	K _{oc}
octanoic acid, cobalt salt	2	110.089

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
Tunnel code	: (D/E)
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)
None of the components are listed.
[Substances of very high concern](#)
None of the components are listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	Entry Number (REACH)
SIGMARINE 48 LF GREY	3
2-ethylhexanoic acid, zirconium salt	30
octanoic acid, cobalt salt	30

Code	: 30013447	Date of issue/Date of revision	: 9 July 2026
SIGMARINE 48 LF GREY			

SECTION 15: Regulatory information

Labelling : Restricted to professional users.

Other EU regulations

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H360F	May damage fertility.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Code : 30013447	Date of issue/Date of revision : 9 July 2026
SIGMARINE 48 LF GREY	

SECTION 16: Other information

H412	Harmful to aquatic life with long lasting effects.
------	--

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Repr. 1B Skin Irrit. 2 Skin Sens. 1B STOT RE 1 STOT SE 3	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 REPRODUCTIVE TOXICITY - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
--	--

History

Date of issue/ Date of revision	: 9 July 2026
Date of previous issue	: No previous validation
Prepared by	: EHS
Version	: 1

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.