

Date of issue 7/10/2026 (month/day/year)

Version 4

## Section 1. Chemical product and company identification

A. Product name : SIGMAWELD 199 PASTE REDBROWN  
Product code : 000001099082

### Other means of identification

00156917; 00158331 ; 00160925 ; 00174027 ; 00422011 ; 00477594 ; 40199-C2008/6L

### B. Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.  
Use of the substance/  
mixture : Coating.  
Uses advised against : Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's  
information : PPG SSC  
(44714)  
19, Yeocheon-ro 217beon-gil, Nam-gu,  
Ulsan, Korea  
Tel: +82-52-210-8222

Email Address : Korea.MSDS@PPG.COM

Emergency telephone  
number: : +82-52-210-8331

## Section 2. Hazards identification

A. Hazard classification :  FLAMMABLE LIQUIDS - Category 2  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
GERM CELL MUTAGENICITY - Category 1B  
CARCINOGENICITY - Category 1A  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract  
irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -  
Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
AQUATIC HAZARD (ACUTE) - Category 1  
AQUATIC HAZARD (LONG-TERM) - Category 1  
This product is classified in accordance with the Industrial Safety and Health Act and  
the Chemical Control Act.

### B. GHS label elements, including precautionary statements

## Section 2. Hazards identification

**Symbol**

:

**Signal word**

:

Danger

**Hazard statements**

:

H225 - Highly flammable liquid and vapor.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H361 - Suspected of damaging fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H400 - Very toxic to aquatic life.  
H410 - Very toxic to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

:

P202 - Do not handle until all safety precautions have been read and understood.  
P280 - Wear protective gloves, protective clothing and eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 - Use explosion-proof electrical, ventilating or lighting equipment.  
P241 - Use explosion-proof electrical, ventilating or lighting equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P240 - Ground and bond container and receiving equipment.  
P273 - Avoid release to the environment.  
P260 - Do not breathe vapor.  
P264 - Wash thoroughly after handling.

**Response**

:

P391 - Collect spillage.  
P370 + P378 - In case of fire: Never use water to extinguish.  
P308 + P313 - IF exposed or concerned: Get medical advice or attention.  
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.  
P321 - Specific treatment (see the label).

**Storage**

:

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 - Keep cool.

**Disposal**

:

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**C. Other hazards which do not result in classification**

:

Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

### CAS number/other identifiers

CAS number : Not applicable.

| Chemical name                                                                                                                                                                                 | Common name                                  | Identifiers                                      | %        |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|--------------------------------------------------|----------|
| Zinc powder - zinc dust (stabilized)                                                                                                                                                          | ZINC                                         | CAS: 7440-66-6                                   | 30 - <40 |
| xylene                                                                                                                                                                                        | XYLENES                                      | EC: 231-175-3<br>CAS: 1330-20-7                  | 10 - <20 |
| Iron oxide                                                                                                                                                                                    | Diiron trioxide                              | EC: 215-535-7<br>CAS: 1309-37-1                  | 5 - <10  |
| propylene glycol methyl ether                                                                                                                                                                 | PROPYLENE GLYCOL MONOMETHYL ETHER            | EC: 215-168-2<br>CAS: 107-98-2                   | 5 - <10  |
| zinc oxide                                                                                                                                                                                    | ZINC OXIDE                                   | EC: 203-539-1<br>CAS: 1314-13-2                  | 5 - <10  |
| ethylbenzene                                                                                                                                                                                  | ETHYLBENZENE                                 | EC: 215-222-5<br>CAS: 100-41-4                   | 1 - <5   |
| 2-propanol                                                                                                                                                                                    | ISOPROPYL ALCOHOL                            | EC: 202-849-4<br>CAS: 67-63-0                    | 1 - <5   |
| Aluminum                                                                                                                                                                                      | ALUMINUM POWDER                              | EC: 200-661-7<br>CAS: 7429-90-5                  | 0.1 - <1 |
| Quaternary ammonium compounds, benzyl (hydrogenated tallow alkyl) dimethyl, stearates, salts with bentonite; Bentonite, benzyl(hydrogenated tallow alkyl) dimethylammonium stearate complex - | ORGANIC DERIVATIVE OF A MONTMORILLONITE CLAY | EC: 231-072-3<br>CAS: 121888-68-4                | 0.1 - <1 |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC                                                                                                                                                   | SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC  | CAS: 64742-95-6                                  | 0.1 - <1 |
| cadmium                                                                                                                                                                                       | CADMIUM                                      | EC: 265-199-0<br>CAS: 7440-43-9<br>EC: 231-152-8 | <0.1     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

- A. Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- B. Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- C. Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

## Section 4. First aid measures

- D. Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- E. Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

- A. Extinguishing media**
- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- B. Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides
- C. Special equipment for fire-fighting** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire-fighting procedures** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

## Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures** :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- B. Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

## Section 6. Accidental release measures

### C. Methods and materials for containment and cleaning up

#### Small spill

- : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

- : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### A. Precautions for safe handling

- : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

### B. Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### A. Occupational exposure limits

## Section 8. Exposure controls/personal protection

| Ingredient name               | Exposure limits                                                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| xylene                        | <b>ISHA Article 42 (Republic of Korea, 1/2020) [Xylene]</b><br>STEL 15 minutes: 150 ppm.<br>TWA 8 hours: 100 ppm.                                                                                      |
| Iron oxide                    | <b>ISHA Article 42 (Republic of Korea, 1/2020) [Iron oxide]</b><br>TWA 8 hours: 5 mg/m <sup>3</sup> (as Fe). Form: Fume.<br>TWA 8 hours: 5 mg/m <sup>3</sup> (as Fe).                                  |
| propylene glycol methyl ether | <b>ISHA Article 42 (Republic of Korea, 1/2020)</b><br>STEL 15 minutes: 150 ppm.<br>TWA 8 hours: 100 ppm.                                                                                               |
| zinc oxide                    | <b>ISHA Article 42 (Republic of Korea, 1/2020)</b><br>STEL 15 minutes: 10 mg/m <sup>3</sup> .<br>TWA 8 hours: 5 mg/m <sup>3</sup> .<br>TWA 8 hours: 2 mg/m <sup>3</sup> . Form: Respirable dust.       |
| ethylbenzene                  | <b>ISHA Article 42 (Republic of Korea, 1/2020)</b><br>STEL 15 minutes: 125 ppm.<br>TWA 8 hours: 100 ppm.                                                                                               |
| 2-propanol                    | <b>ISHA Article 42 (Republic of Korea, 1/2020)</b><br>STEL 15 minutes: 400 ppm.<br>TWA 8 hours: 200 ppm.                                                                                               |
| Aluminum                      | <b>ISHA Article 42 (Republic of Korea, 1/2020)</b><br>TWA 8 hours: 10 mg/m <sup>3</sup> . Form: Dust.                                                                                                  |
| cadmium                       | <b>ISHA Article 42 (Republic of Korea, 1/2020) [Cadmium and compounds]</b><br>TWA 8 hours: 0.01 mg/m <sup>3</sup> (as Cd).<br>TWA 8 hours: 0.002 mg/m <sup>3</sup> (as Cd). Form: Respirable fraction. |

### Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### B. Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### C. Personal protective equipment

## Section 8. Exposure controls/personal protection

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Eye protection** : Chemical splash goggles.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### A. Appearance

**Physical state** : Liquid.

**Color** : Brownish-red.

**B. Odor** : Aromatic.

**C. Odor threshold** : Not available.

**D. pH** : Not applicable.

**E. Melting/freezing point** : Not available.

**F. Boiling point/boiling range** : >37.78°C (>100°F)

**G. Flash point** : Closed cup: 20.4°C (68.7°F)

**H. Evaporation rate** : Not available.

**I. Flammability (solid, gas)** : Not available.

**J. Lower and upper explosive (flammable) limits** : Not available.

**K. Vapor pressure** :



## Section 9. Physical and chemical properties

|                    | Ingredient name                        | Vapor Pressure at 20°C                                                                                                                                     |     |        | Vapor pressure at 50°C |     |        |
|--------------------|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--------|------------------------|-----|--------|
|                    |                                        | mm Hg                                                                                                                                                      | kPa | Method | mm Hg                  | kPa | Method |
|                    | Isopropyl alcohol                      | 33.00268                                                                                                                                                   | 4.4 |        |                        |     |        |
| L. Solubility(ies) | Media                                  | Result                                                                                                                                                     |     |        |                        |     |        |
|                    | cold water                             | Not soluble                                                                                                                                                |     |        |                        |     |        |
|                    | Solubility in water                    | : Not available.                                                                                                                                           |     |        |                        |     |        |
| M.                 | Vapor density                          | : Not available.                                                                                                                                           |     |        |                        |     |        |
| N.                 | Relative density                       | : 2.13                                                                                                                                                     |     |        |                        |     |        |
| O.                 | Partition coefficient: n-octanol/water | : Not applicable.                                                                                                                                          |     |        |                        |     |        |
| P.                 | Auto-ignition temperature              | : 287°C (548.6°F)                                                                                                                                          |     |        |                        |     |        |
| Q.                 | Decomposition temperature              | : Not available.                                                                                                                                           |     |        |                        |     |        |
| R.                 | Viscosity                              | : Dynamic (room temperature): Not available.<br>Kinematic (room temperature): Not available.<br>Kinematic (40°C (104°F)): >21 mm <sup>2</sup> /s (>21 cSt) |     |        |                        |     |        |
|                    | Flow time (ISO 2431)                   | : Not available.                                                                                                                                           |     |        |                        |     |        |
| S.                 | Molecular weight                       | : Not applicable.                                                                                                                                          |     |        |                        |     |        |

## Section 10. Stability and reactivity

- A. Chemical stability : The product is stable.
- Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
- B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.
- C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- D. Hazardous decomposition products : Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

## Section 11. Toxicological information

- A. Information on the likely routes of exposure : Not available.

### Potential acute health effects

- Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Ingestion : Can cause central nervous system (CNS) depression.
- Skin contact : Causes skin irritation. Defatting to the skin.



## Section 11. Toxicological information

**Eye contact** : Causes serious eye irritation.

### Over-exposure signs/symptoms

**Inhalation** : ☒ Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Ingestion** : ☒ Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Skin contact** : ☒ Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

## B. Health hazards

### Acute toxicity

| Product/ingredient name                                                  | Result                          | Species | Dose                    | Exposure |
|--------------------------------------------------------------------------|---------------------------------|---------|-------------------------|----------|
| <input checked="" type="checkbox"/> Zinc powder - zinc dust (stabilized) | LC50 Inhalation Dusts and mists | Rat     | >5.4 mg/l               | 4 hours  |
| xylene                                                                   | LD50 Oral                       | Rat     | >2000 mg/kg             | -        |
|                                                                          | LD50 Dermal                     | Rabbit  | 1.7 g/kg                | -        |
|                                                                          | LD50 Oral                       | Rat     | 4.3 g/kg                | -        |
| Iron oxide                                                               | LC50 Inhalation Dusts and mists | Rat     | >5 mg/l                 | 4 hours  |
|                                                                          | LD50 Oral                       | Rat     | 10 g/kg                 | -        |
| propylene glycol methyl ether                                            | LC50 Inhalation Vapor           | Rat     | >7000 ppm               | 6 hours  |
|                                                                          | LD50 Dermal                     | Rabbit  | 13 g/kg                 | -        |
|                                                                          | LD50 Oral                       | Rat     | 5.2 g/kg                | -        |
| zinc oxide                                                               | LC50 Inhalation Dusts and mists | Rat     | >5700 mg/m <sup>3</sup> | 4 hours  |
|                                                                          | LD50 Dermal                     | Rat     | >2000 mg/kg             | -        |
|                                                                          | LD50 Oral                       | Rat     | >5000 mg/kg             | -        |
| ethylbenzene                                                             | LC50 Inhalation Vapor           | Rat     | 17.8 mg/l               | 4 hours  |
|                                                                          | LD50 Dermal                     | Rabbit  | 17.8 g/kg               | -        |
|                                                                          | LD50 Oral                       | Rat     | 3.5 g/kg                | -        |
| 2-propanol                                                               | LC50 Inhalation Vapor           | Rat     | 72600 mg/m <sup>3</sup> | 4 hours  |

## Section 11. Toxicological information

|                                                |                                                             |                      |                                      |                   |
|------------------------------------------------|-------------------------------------------------------------|----------------------|--------------------------------------|-------------------|
| Aluminum                                       | LD50 Dermal<br>LD50 Oral<br>LC50 Inhalation Dusts and mists | Rabbit<br>Rat<br>Rat | 12800 mg/kg<br>5045 mg/kg<br>>5 mg/l | -<br>-<br>4 hours |
| SOLVENT NAPHTHA (PETROLEUM),<br>LIGHT AROMATIC | LD50 Oral<br>LD50 Dermal                                    | Rat<br>Rabbit        | >15900 mg/kg<br>3.48 g/kg            | -<br>-            |
| cadmium                                        | LD50 Oral<br>LD50 Oral                                      | Rat<br>Rat           | 8400 mg/kg<br>0.225 g/kg             | -<br>-            |

**Conclusion/Summary** : There are no data available on the mixture itself.

### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| xylene                  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name                          | Classification | Route of exposure | Target organs                |
|-------------------------------|----------------|-------------------|------------------------------|
| xylene                        | Category 3     | -                 | Respiratory tract irritation |
| -                             | Category 3     | -                 | Narcotic effects             |
| Iron oxide                    | Category 3     | -                 | Respiratory tract irritation |
| propylene glycol methyl ether | Category 3     | -                 | Narcotic effects             |
| 2-propanol                    | Category 3     | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

## Section 11. Toxicological information

| Name         | Classification | Route of exposure | Target organs |
|--------------|----------------|-------------------|---------------|
| xylene       | Category 2     | -                 | -             |
| Iron oxide   | Category 1     | -                 | -             |
| ethylbenzene | Category 2     | -                 | -             |
| Aluminum     | Category 2     | -                 | -             |
| cadmium      | Category 1     | -                 | -             |

### Aspiration hazard

| Name                                        | Result                         |
|---------------------------------------------|--------------------------------|
| xylene                                      | ASPIRATION HAZARD - Category 1 |
| ethylbenzene                                | ASPIRATION HAZARD - Category 1 |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC | ASPIRATION HAZARD - Category 1 |

### Potential chronic health effects

- General** : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : May cause genetic defects.
- Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

### Additional information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

| Chemical name                        | Identifiers                                      | GHS Classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Zinc powder - zinc dust (stabilized) | CAS: 7440-66-6                                   | SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 3<br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1<br>FLAMMABLE LIQUIDS - Category 3<br>ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>TOXIC TO REPRODUCTION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>ASPIRATION HAZARD - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - |
| xylene                               | EC: 231-175-3<br>CAS: 1330-20-7<br>EC: 215-535-7 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Iron oxide                           | CAS: 1309-37-1                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

## Section 11. Toxicological information

|                                                                                                                                                                                                                                           |                                                                   |                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| propylene glycol methyl ether                                                                                                                                                                                                             | EC: 215-168-2                                                     | Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1<br>FLAMMABLE LIQUIDS - Category 3                                                                                                                                                                                                                                  |
| zinc oxide                                                                                                                                                                                                                                | CAS: 107-98-2<br>EC: 203-539-1                                    | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1                                                                                                                                                                               |
| ethylbenzene                                                                                                                                                                                                                              | CAS: 1314-13-2<br>EC: 215-222-5<br>CAS: 100-41-4<br>EC: 202-849-4 | FLAMMABLE LIQUIDS - Category 2<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>CARCINOGENICITY - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>ASPIRATION HAZARD - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 3                       |
| 2-propanol                                                                                                                                                                                                                                | CAS: 67-63-0<br>EC: 200-661-7                                     | FLAMMABLE LIQUIDS - Category 2<br>EYE IRRITATION - Category 2B<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3                                                                                                                                                                                               |
| Aluminum                                                                                                                                                                                                                                  | CAS: 7429-90-5<br>EC: 231-072-3                                   | FLAMMABLE SOLIDS - Category 1<br>PYROPHORIC SOLIDS - Category 1<br>SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>AQUATIC HAZARD (LONG-TERM) - Category 1                                                                         |
| Quaternary ammonium compounds, benzyl (hydrogenated tallow alkyl) dimethyl, stearates, salts with bentonite; Bentonite, benzyl(hydrogenated tallow alkyl) dimethylammonium stearate complex - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC | CAS: 121888-68-4                                                  | CARCINOGENICITY - Category 1A                                                                                                                                                                                                                                                                                                                    |
|                                                                                                                                                                                                                                           | CAS: 64742-95-6<br>EC: 265-199-0                                  | FLAMMABLE LIQUIDS - Category 3<br>SKIN IRRITATION - Category 2<br>GERM CELL MUTAGENICITY - Category 1B<br>CARCINOGENICITY - Category 1B<br>ASPIRATION HAZARD - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 2                                                                                                                             |
| cadmium                                                                                                                                                                                                                                   | CAS: 7440-43-9<br>EC: 231-152-8                                   | ACUTE TOXICITY (oral) - Category 3<br>ACUTE TOXICITY (inhalation) - Category 2<br>GERM CELL MUTAGENICITY - Category 2<br>CARCINOGENICITY - Category 1<br>TOXIC TO REPRODUCTION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1<br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1 |

## Section 12. Ecological information

### A. Ecotoxicity

| Product/ingredient name                                   | Result                                        | Species                                                                       | Exposure             |
|-----------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------|----------------------|
| Zinc powder - zinc dust (stabilized)                      | Acute EC50 0.106 mg/l Fresh water             | Algae - <i>Pseudokirchneriella subcapitata</i>                                | 72 hours             |
|                                                           | Acute EC50 354 µg/l Fresh water               | Daphnia - <i>Daphnia magna</i>                                                | 48 hours             |
|                                                           | Chronic EC10 27.3 µg/l Fresh water            | Algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase            | 72 hours             |
|                                                           | Chronic EC10 6.3 µg/l                         | Daphnia - <i>Daphnia magna</i> - Neonate                                      | 21 days              |
| Iron oxide<br>propylene glycol methyl ether               | Chronic LC10 185 µg/l Fresh water             | Fish - <i>Oncorhynchus mykiss</i> - Juvenile (Fledgling, Hatchling, Weanling) | 30 days              |
|                                                           | Acute EC50 >100 mg/l<br>Acute LC50 23300 mg/l | Daphnia<br>Daphnia                                                            | 48 hours<br>48 hours |
| zinc oxide                                                | Acute LC50 >4500 mg/l Fresh water             | Fish                                                                          | 96 hours             |
|                                                           | Acute EC50 0.17 mg/l                          | Algae                                                                         | 72 hours             |
|                                                           | Acute EC50 0.481 mg/l Fresh water             | Daphnia - <i>Daphnia magna</i> - Neonate                                      | 48 hours             |
| ethylbenzene                                              | Chronic NOEC 0.017 mg/l Fresh water           | Algae                                                                         | 72 hours             |
|                                                           | Acute EC50 1.8 mg/l Fresh water               | Daphnia                                                                       | 48 hours             |
|                                                           | Chronic NOEC 1 mg/l Fresh water               | Daphnia - <i>Ceriodaphnia dubia</i>                                           | -                    |
| 2-propanol<br>SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC | Acute EC50 10.1 g/L Fresh water               | Daphnia - <i>Daphnia magna</i>                                                | 48 hours             |
|                                                           | Acute LC50 8.2 mg/l                           | Fish                                                                          | 96 hours             |
| cadmium                                                   | Acute LC50 1500 ppb                           | Fish                                                                          | 96 hours             |

### B. Persistence and degradability

| Product/ingredient name | Test              | Result                   | Dose             | Inoculum |
|-------------------------|-------------------|--------------------------|------------------|----------|
| ethylbenzene            | -                 | 79 % - Readily - 10 days | -                | -        |
| Product/ingredient name | Aquatic half-life | Photolysis               | Biodegradability |          |
| xylene                  | -                 | -                        | Readily          |          |
| ethylbenzene            | -                 | -                        | Readily          |          |

### C. Bioaccumulative potential

| Product/ingredient name       | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------------|--------------------|-------------|-----------|
| xylene                        | 3.12               | 7.4 to 18.5 | Low       |
| propylene glycol methyl ether | <1                 | -           | Low       |
| ethylbenzene                  | 3.6                | 79.43       | Low       |
| 2-propanol                    | 0.05               | -           | Low       |

### D. Mobility in soil

Soil/Water partition coefficient : Not available.

## Section 12. Ecological information

**E. Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**A. Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**B. Disposal precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                       | UN                                                                 | IMDG                                   | IATA                                                               |
|---------------------------------------|--------------------------------------------------------------------|----------------------------------------|--------------------------------------------------------------------|
| <b>A. UN number</b>                   | UN1263                                                             | UN1263                                 | UN1263                                                             |
| <b>B. UN proper shipping name</b>     | PAINT                                                              | PAINT                                  | PAINT                                                              |
| <b>C. Transport hazard class(es)</b>  | 3                                                                  | 3                                      | 3                                                                  |
| <b>D. Packing group</b>               | II                                                                 | II                                     | II                                                                 |
| <b>Environmental hazards</b>          | Yes. The environmentally hazardous substance mark is not required. | Yes.                                   | Yes. The environmentally hazardous substance mark is not required. |
| <b>E. Marine pollutant substances</b> | Not applicable.                                                    | (Zinc powder - zinc dust (stabilized)) | Not applicable.                                                    |

### Additional information

**UN** : None identified.

**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

### F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 14. Transport information

Transport in bulk according to IMO instruments : Not applicable.

## Section 15. Regulatory information

### A. Regulation according to ISHA

ISHA article 117 (Harmful substances prohibited from manufacture) : None of the components are listed.

ISHA article 118 (Harmful substances requiring permission) : None of the components are listed.

Article 2 of Youth Protection Act on Substances Hazardous to Youth : It is not allowed to sell to persons under the age of 19.

### Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

☒ xylene  
Iron oxide  
propylene glycol methyl ether  
zinc oxide  
ethylbenzene  
2-propanol  
Aluminum  
cadmium

ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors) : ☒ The following components are listed: toluene, Lead and its inorganic compounds, Cadmium and its compounds, benzene, methanol

ISHA Enforcement Regs Annex 11-5 (Harmful factors subject to Work Environment Measurement) : The following components are listed: xylene, iron oxide, zinc oxide, ethyl benzene, isopropyl alcohol, aluminum and its compounds

ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check-up) : The following components are listed: Xylene, Iron oxide (dust, fume), Zinc oxide, Ethyl benzene, Isopropyl alcohol, Aluminum and its compounds

Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control) : The following components are listed: zinc and its compounds, xylene, iron and its compounds, zinc and its compounds, ethyl benzene, isopropyl alcohol, aluminum and its compounds

### B. Regulation according to Chemicals Control Act

Article 11 (TRI) : The following components are listed: Zinc and its compounds, Xylene including o-,m-,p- isomer, Zinc and its compounds, Ethylbenzene, 2-Propanol, Aluminium and its compounds



## Section 15. Regulatory information

**Article 18 Prohibited (K-Reach Article 27)** : None of the components are listed.

**Article 19 Candidate substances subject to authorization (K-Reach Article 25)** : The following components are listed: Benzene, Lead monoxide

**Article 19 Subject to authorization (K-Reach Article 25)** : None of the components are listed.

**Article 20 Restricted (K-Reach Article 27)** : None of the components are listed.

**Korea inventory** : All components are listed or exempted.

**Article 39 (Accident Precaution Chemicals)** : The following components are listed: xylene

**Substances Harmful to Human Health Acute/Chronic and Ecologically Hazardous Substances (K-REACH Article 20)**

| Ingredient name                                         | Acute human toxicity | Chronic human toxicity | Ecotoxicity | Reference number |
|---------------------------------------------------------|----------------------|------------------------|-------------|------------------|
| Zinc, except for particles larger than or equal to 1 mm | Not applicable       | Not applicable         | Applicable  | 2025-1-1263      |

**Existing Chemical Substances Subject to Registration** : The following components are listed: Xylene, Zinc oxide, Toluene, Quartz, Quartz, Cadmium, Lead, Benzene, Methanol, Lead monoxide, Triphenyl phosphite, Naphthalene, Phenol

### C. Regulations under the Act on Registration and Evaluation of Chemical Substances

No unconfirmed hazards apply.

**D. Dangerous Materials Safety Management Act** : **Class:** Class 4 - Flammable Liquid  
**Item:** 2. Class 1 petroleums - Water-insoluble liquid  
**Threshold:** 200 L

**Danger category:** II

**Signal word:** Contact with sources of ignition prohibited

**E. Wastes regulation** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

### F. Regulation according to other foreign laws

**Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

## Section 16. Other information

**A. References** : Korean Ministry of Environment; Chemical Control Act  
Korean Ministry of Labor; Industrial Safety and Health Act  
NIER Notice  
Registry of Toxic Effects of Chemical Substances (RTECS)  
U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.

**B. First issue date** : 1/13/2021

**C. Date of issue/Date of revision** : 7/10/2026

## Section 16. Other information

D. Version : 4  
Prepared by : EHS

### E. Other

Indicates information that has changed from previously issued version.

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*