

Date of issue 7/10/2026 (month/day/year)

Version 12

Section 1. Chemical product and company identification

- A. Product name** : SIGMAZINC 158 HS BINDER OFFWHITE
Product code : 00383730
- B. Relevant identified uses of the substance or mixture and uses advised against**
Product use : Professional applications, Used by spraying.
Use of the substance/ mixture : Coating.
Uses advised against : Product is not intended, labelled or packaged for consumer use.
- C. Supplier's or Importer's information** : PPG SSC
 (44714)
 19, Yeocheon-ro 217beon-gil, Nam-gu,
 Ulsan, Korea
 Tel: +82-52-210-8222
Email Address : Korea.MSDS@PPG.COM
Emergency telephone number: : +82-52-210-8331

Section 2. Hazards identification

- A. Hazard classification** :  FLAMMABLE LIQUIDS - Category 3
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A
 CARCINOGENICITY - Category 1A
 TOXIC TO REPRODUCTION - Category 1B
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 AQUATIC HAZARD (LONG-TERM) - Category 3
 This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.
- B. GHS label elements, including precautionary statements**
Symbol :   
- Signal word** : Danger

Section 2. Hazards identification

Hazard statements : H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H350 - May cause cancer.
H360 - May damage fertility or the unborn child.
H371 - May cause damage to organs.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing and eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P240 - Ground and bond container and receiving equipment.
P273 - Avoid release to the environment.
P260 - Do not breathe vapor.
P270 - Do not eat, drink or smoke when using this product.
P264 - Wash thoroughly after handling.

Response : P370 + P378 - In case of fire: Never use water to extinguish.
P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor.
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.
P321 - Specific treatment (see the label).

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number : Not applicable.

Section 3. Composition/information on ingredients

Chemical name	Common name	Identifiers	%
Silicic acid, ethyl ester	ETHYL SILICATE POLYMER	CAS: 11099-06-2 EC: 234-324-0	20 - <30
propylene glycol methyl ether	PROPYLENE GLYCOL MONOMETHYL ETHER	CAS: 107-98-2 EC: 203-539-1	20 - <30
Silicon oxide (crystalline quartz)	QUARTZ (<10 microns)	CAS: 14808-60-7 EC: 238-878-4	10 - <20
2-Butoxyethanol, EGBE	2-BUTOXY ETHANOL	CAS: 111-76-2 EC: 203-905-0	5 - <10
xylene	XYLENES	CAS: 1330-20-7 EC: 215-535-7	5 - <10
ethanol	ETHYL ALCOHOL	CAS: 64-17-5 EC: 200-578-6	5 - <10
2-propanol	ISOPROPYL ALCOHOL	CAS: 67-63-0 EC: 200-661-7	1 - <5
ethylbenzene	ETHYLBENZENE	CAS: 100-41-4 EC: 202-849-4	1 - <5
ETHYLCELLULOSE	ETHYL CELLULOSE	CAS: 9004-57-3	1 - <5
Methyl alcohol	METHYL ALCOHOL	CAS: 67-56-1 EC: 200-659-6	1 - <5
Silicon oxide (crystalline quartz)	QUARTZ (>10 microns)	CAS: 14808-60-7 EC: 238-878-4	1 - <5
TRIMETHYL BORATE	trimethyl borate	CAS: 121-43-7 EC: 204-468-9	0.1 - <1
Sulfuric acid	SULFURIC ACID	CAS: 7664-93-9 EC: 231-639-5	0.1 - <1
Zinc chloride	ZINC CHLORIDE	CAS: 7646-85-7 EC: 231-592-0	<0.1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

- A. Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- B. Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- C. Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- D. Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- E. Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 4. First aid measures

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

B. Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

C. Special equipment for fire-fighting : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighting procedures : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

B. Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

C. Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

- A. Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- B. Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
propylene glycol methyl ether	ISHA Article 42 (Republic of Korea, 1/2020)
Silicon oxide (crystalline quartz)	STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.
2-Butoxyethanol, EGBE	ISHA Article 42 (Republic of Korea, 1/2020)
	TWA 8 hours: 0.05 mg/m ³ . Form: Respirable fraction.
	ISHA Article 42 (Republic of Korea,

Section 8. Exposure controls/personal protection

xylene	1/2020) Absorbed through skin. TWA 8 hours: 20 ppm. ISHA Article 42 (Republic of Korea, 1/2020) [Xylene] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.
ethanol	ISHA Article 42 (Republic of Korea, 1/2020) TWA 8 hours: 1000 ppm.
2-propanol	ISHA Article 42 (Republic of Korea, 1/2020) STEL 15 minutes: 400 ppm. TWA 8 hours: 200 ppm.
ethylbenzene	ISHA Article 42 (Republic of Korea, 1/2020) STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm.
Methyl alcohol	ISHA Article 42 (Republic of Korea, 1/2020) Absorbed through skin. STEL 15 minutes: 250 ppm. TWA 8 hours: 200 ppm.
Silicon oxide (crystalline quartz)	ISHA Article 42 (Republic of Korea, 1/2020) TWA 8 hours: 0.05 mg/m ³ . Form: Respirable fraction.
TRIMETHYL BORATE	ACGIH TLV (United States) STEL: 6 mg/m ³ . TWA: 2 mg/m ³ .
Sulfuric acid	ISHA Article 42 (Republic of Korea, 1/2020) TWA 8 hours: 0.2 mg/m ³ . Form: Thoracic fraction. STEL 15 minutes: 0.6 mg/m ³ . Form: Thoracic fraction.
Zinc chloride	ISHA Article 42 (Republic of Korea, 1/2020) STEL 15 minutes: 2 mg/m ³ . Form: Fume. TWA 8 hours: 1 mg/m ³ . Form: Fume.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

B. Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 8. Exposure controls/personal protection

C. Personal protective equipment

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Eye protection** : Chemical splash goggles.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:
- Recommended: polyvinyl alcohol (PVA), Viton®, butyl rubber, nitrile rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

Physical state : Liquid.

Color : Off-white.

B. Odor : Aromatic.

C. Odor threshold : Not available.

D. pH : Not applicable.

E. Melting/freezing point : Not available.

F. Boiling point/boiling range : >37.78°C (>100°F)

G. Flash point : Closed cup: 25°C (77°F)

H. Evaporation rate : Not available.

I. Flammability (solid, gas) : Not available.

J. Lower and upper explosive (flammable) limits : Not available.

Section 9. Physical and chemical properties

K. Vapor pressure

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
methanol	126.96329	16.9				

L. Solubility(ies)

Media	Result
cold water	Not soluble

Solubility in water

: Not available.

Vapor density

: Not available.

M.

Relative density

: 1.06

N.

Partition coefficient: n-octanol/water

: Not applicable.

O.

P. Auto-ignition temperature

:

Ingredient name	°C	°F	Method
2-butoxyethanol	230	446	DIN 51794

Q. Decomposition temperature

: Not available.

R. Viscosity

: Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Flow time (ISO 2431)

: Not available.

S. Molecular weight

: Not applicable.

Section 10. Stability and reactivity

A. Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

C. Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

D. Hazardous decomposition products

: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : ☒ Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Ingestion** : May cause damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression.
- Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin.
- Eye contact** : Causes serious eye irritation.

Over-exposure signs/symptoms

- Inhalation** : ☒ Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : ☒ Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : ☒ Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Silicic acid, ethyl ester propylene glycol methyl ether	LD50 Oral	Rat	6270 mg/kg	-
	LC50 Inhalation Vapor	Rat	>7000 ppm	6 hours
	LD50 Dermal	Rabbit	13 g/kg	-
2-Butoxyethanol, EGBE	LD50 Oral	Rat	5.2 g/kg	-
	LC50 Inhalation Vapor	Rat	3 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
xylene	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-

Section 11. Toxicological information

ethanol	LD50 Oral	Rat	4.3 g/kg	-
	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Dermal	Rat	17100 mg/kg	-
2-propanol	LD50 Oral	Rat	7 g/kg	-
	LC50 Inhalation Vapor	Rat	72600 mg/m ³	4 hours
	LD50 Dermal	Rabbit	12800 mg/kg	-
ethylbenzene	LD50 Oral	Rat	5045 mg/kg	-
	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
ETHYLCELLULOSE	LD50 Oral	Rat	3.5 g/kg	-
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
Methyl alcohol	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
TRIMETHYL BORATE	LD50 Dermal	Rabbit	1.98 g/kg	-
	LD50 Oral	Rat	6140 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
Sulfuric acid	LD50 Oral	Rat	0.35 g/kg	-
Zinc chloride	LD50 Oral	Rat		

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Butoxyethanol, EGBE	Eyes - Irritant	Rabbit	-	24 hours	21 days
xylene	Skin - Moderate irritant	Rabbit	-	4 hours	28 days
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

Name	Classification	Route of exposure	Target organs
propylene glycol methyl ether	Category 3	-	Narcotic effects
Silicon oxide (crystalline quartz)	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
2-propanol	Category 3	-	Narcotic effects
Methyl alcohol	Category 1	-	-
Silicon oxide (crystalline quartz)	Category 3	-	Respiratory tract irritation
TRIMETHYL BORATE	Category 1	-	-

Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
xylene	Category 2	-	-
ethylbenzene	Category 2	-	-

Aspiration hazard

Name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Potential chronic health effects

- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage fertility or the unborn child.

Additional information

Prolonged or repeated contact may dry skin and cause irritation. Contains . methanol . Cannot be made nonpoisonous. May be fatal or cause blindness if swallowed. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Chemical name	Identifiers	GHS Classification
Silicic acid, ethyl ester	CAS: 11099-06-2 EC: 234-324-0	EYE IRRITATION - Category 2A
propylene glycol methyl ether	CAS: 107-98-2 EC: 203-539-1	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Silicon oxide (crystalline quartz)	CAS: 14808-60-7 EC: 238-878-4	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Section 11. Toxicological information

2-Butoxyethanol, EGBE	CAS: 111-76-2 EC: 203-905-0	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2
xylene	CAS: 1330-20-7 EC: 215-535-7	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1
ethanol	CAS: 64-17-5 EC: 200-578-6	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2
2-propanol	CAS: 67-63-0 EC: 200-661-7	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
ethylbenzene	CAS: 100-41-4 EC: 202-849-4	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3
ETHYLCELLULOSE	CAS: 9004-57-3	EYE IRRITATION - Category 2A AQUATIC HAZARD (LONG-TERM) - Category 4
Methyl alcohol	CAS: 67-56-1 EC: 200-659-6	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3
Silicon oxide (crystalline quartz)	CAS: 14808-60-7 EC: 238-878-4	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
TRIMETHYL BORATE	CAS: 121-43-7 EC: 204-468-9	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 3 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE

Section 11. Toxicological information

Sulfuric acid	CAS: 7664-93-9 EC: 231-639-5	EXPOSURE) - Category 1 CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (inhalation) - Category 2 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A
Zinc chloride	CAS: 7646-85-7 EC: 231-592-0	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
propylene glycol methyl ether	Acute LC50 23300 mg/l	Daphnia	48 hours
2-Butoxyethanol, EGBE	Acute LC50 >4500 mg/l Fresh water	Fish	96 hours
	Acute LC50 1474 mg/l	Fish	96 hours
	Chronic NOEC >100 mg/l	Fish	21 days
ethanol	Acute EC50 7640 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
2-propanol	Acute EC50 10.1 g/L Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - <i>Ceriodaphnia dubia</i>	-
Methyl alcohol	Acute LC50 13 mg/l Fresh water	Fish	96 hours
Zinc chloride	Acute EC50 22 µg/l Fresh water	Algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase	72 hours
	Acute EC50 5.64 mg/l Fresh water	Aquatic plants - <i>Lemna minor</i>	4 days
	Acute EC50 0.2 mg/l	Crustaceans	48 hours
	Acute LC50 0.14 mg/l Fresh water	Daphnia - <i>Daphnia galeata</i> - Neonate	48 hours
	Acute LC50 0.4 to 2.2 mg/l	Fish	96 hours
	Chronic EC10 10 µg/l Fresh water	Algae - <i>Raphidocelis subcapitata</i> - Exponential growth phase	72 hours
	Chronic EC10 58 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Juvenile (Fledgling, Hatchling, Weanling)	21 days

B. Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-Butoxyethanol, EGBE	-	-	Readily
xylene	-	-	Readily
ethanol	-	-	Readily
ethylbenzene	-	-	Readily

Section 12. Ecological information

C. Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
propylene glycol methyl ether	<1	-	Low
2-Butoxyethanol, EGBE	0.81	-	Low
xylene	3.12	7.4 to 18.5	Low
ethanol	-0.35	-	Low
2-propanol	0.05	-	Low
ethylbenzene	3.6	79.43	Low
ETHYLCELLULOSE	5.5	-	High
Methyl alcohol	-0.77	-	Low
TRIMETHYL BORATE	-1.9	-	Low

D. Mobility in soil

Soil/Water partition coefficient : Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	UN1263	UN1263	UN1263
B. UN proper shipping name	PAINT	PAINT	PAINT
C. Transport hazard class(es)	3	3	3
D. Packing group	III	III	III
Environmental hazards	No.	No.	No.

Section 14. Transport information

E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.
--------------------------------	-----------------	-----------------	-----------------

Additional information

UN : None identified.

IMDG : None identified.

IATA : None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 117 : None of the components are listed.

(Harmful substances prohibited from manufacture)

ISHA article 118 : None of the components are listed.

(Harmful substances requiring permission)

Article 2 of Youth Protection Act on Substances Hazardous to Youth : It is not allowed to sell to persons under the age of 19.

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

propylene glycol methyl ether
Silicon oxide (crystalline quartz)
2-Butoxyethanol, EGBE
xylene
ethanol
2-propanol
ethylbenzene
Methyl alcohol
Silicon oxide (crystalline quartz)
TRIMETHYL BORATE
Sulfuric acid
Zinc chloride

ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors) : The following components are listed: methanol, sulfuric acid, toluene

Section 15. Regulatory information

ISHA Enforcement Regs Annex 11-5 (Harmful factors subject to Work Environment Measurement) : The following components are listed: silicates, quartz, 2-butoxyethanol / EGBE, xylene, isopropyl alcohol, mica, ethyl benzene, methanol, quartz

ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check-up) : The following components are listed: 2-Butoxyethanol, Xylene, Isopropyl alcohol, Ethyl benzene, Methanol

Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control) : The following components are listed: 2-butoxyethanol, xylene, isopropyl alcohol, ethyl benzene, methanol, sulfuric acid

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : The following components are listed: Xylene including o-,m-,p- isomer, 2-Propanol, Ethylbenzene, Methyl alcohol

Article 18 Prohibited (K-Reach Article 27) : None of the components are listed.

Article 19 Candidate substances subject to authorization (K-Reach Article 25) : None of the components are listed.

Article 19 Subject to authorization (K-Reach Article 25) : None of the components are listed.

Article 20 Restricted (K-Reach Article 27) : None of the components are listed.

Korea inventory : All components are listed or exempted.

Article 39 (Accident Precaution Chemicals) : The following components are listed: xylene

Substances Harmful to Human Health Acute/Chronic and Ecologically Hazardous Substances (K-REACH Article 20)

Not applicable.

Existing Chemical Substances Subject to Registration : The following components are listed: Quartz, Xylene, Methanol, Quartz, Sulfuric acid, Zinc chloride, Toluene, Sodium nitrate, Zinc oxide, Hydrogen chloride

C. Regulations under the Act on Registration and Evaluation of Chemical Substances

No unconfirmed hazards apply.

D. Dangerous Materials Safety Management Act : **Class:** Class 4 - Flammable Liquid
Item: 4. Class 2 petroleums - Water-insoluble liquid
Threshold: 1000 L
Danger category: III
Signal word: Contact with sources of ignition prohibited

E. Wastes regulation : Dispose of contents and container in accordance with all local, regional, national and international regulations.

F. Regulation according to other foreign laws

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

- A. References** : Korean Ministry of Environment; Chemical Control Act
Korean Ministry of Labor; Industrial Safety and Health Act
NIER Notice
Registry of Toxic Effects of Chemical Substances (RTECS)
U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
- B. First issue date** : 3/29/2018
- C. Date of issue/Date of revision** : 7/10/2026
- D. Version** : 12
- Prepared by** : EHS

E. Other

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.