

# SAFETY DATA SHEET

Date of issue/Date of revision

: 11 July 2026

Version

: 14



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMAGLIDE 890 BASE WHITE

**Product code** : 00276264

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person  
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

 **STOT RE 1, H372**

**Aquatic Chronic 3, H412**

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Code : 00276264  
SIGMAGLIDE 890 BASE WHITE

Date of issue/Date of revision : 11 July 2026

## SECTION 2: Hazards identification

Hazard pictograms :



Signal word : Danger

Hazard statements : Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

### Precautionary statements

Prevention : Avoid release to the environment. Do not breathe vapour.

Response : Get medical advice/attention if you feel unwell.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P273, P260, P314, P501

Hazardous ingredients : Cristobalite

Supplemental label elements : Contains 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. : Based on available data, the classification criteria are not met.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                              | Identifiers                                                                            | % by weight | Classification                                                                                                                                                                 | Specific Conc. Limits, M-factors and ATEs                         | Type               |
|------------------------------------------------------|----------------------------------------------------------------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|--------------------|
| Cristobalite (<10 microns)                           | EC: 238-455-4<br>CAS: 14464-46-1                                                       | ≥10 - ≤25   | STOT RE 1, H372<br>(inhalation)                                                                                                                                                | -                                                                 | [1] [2]            |
| xylene                                               | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | ≥1.0 - ≤5.0 | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | ATE [Dermal] = 1700 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1] [2]            |
| dodecamethylcyclohexasiloxane                        | REACH #:<br>01-2119517435-42<br>EC: 208-762-8<br>CAS: 540-97-6                         | ≤1.0        | Not classified.                                                                                                                                                                | -                                                                 | [3] [4]            |
| Cyclosiloxanes, di-Me                                | CAS: 69430-24-6                                                                        | <1.0        | Flam. Liq. 3, H226<br>Repr. 2, H361f<br>Aquatic Chronic 4, H413                                                                                                                | -                                                                 | [1]                |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | REACH #:<br>01-2119962189-26<br>CAS: 911674-82-3<br>Index: 616-198-00-2                | <1.0        | Skin Sens. 1, H317<br>Aquatic Chronic 4, H413                                                                                                                                  | -                                                                 | [1] [2]            |
| octamethylcyclotetrasiloxane                         | REACH #:<br>01-2119529238-36<br>EC: 209-136-7<br>CAS: 556-67-2<br>Index: 014-018-00-1  | ≤0.10       | Flam. Liq. 3, H226<br>Repr. 2, H361f<br>Aquatic Chronic 1, H410<br><br><b>See Section 16 for the full text of the H statements declared above.</b>                             | M [Chronic] = 10                                                  | [1] [2]<br>[3] [4] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code : 00276264  
SIGMAGLIDE 890 BASE WHITE

Date of issue/Date of revision : 11 July 2026

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides  
Formaldehyde.

Code : 00276264  
SIGMAGLIDE 890 BASE WHITE

Date of issue/Date of revision : 11 July 2026

## SECTION 5: Firefighting measures

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

|                                               |                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Advice on general occupational hygiene</b> | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

| Product/ingredient name                              | Exposure limit values                                                                                                                                                                                                  |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| crystobalite (<10 microns)                           | <b>ACGIH TLV (United States, 1/2025) [Silica, crystalline] A2.</b><br>TWA 8 hours: 0.025 mg/m <sup>3</sup> . Form: Respirable fraction.                                                                                |
| xylene                                               | <b>EU OEL (Europe, 1/2022) [xylene, mixed isomers]</b> Absorbed through skin.<br>TWA 8 hours: 50 ppm.<br>TWA 8 hours: 221 mg/m <sup>3</sup> .<br>STEL 15 minutes: 100 ppm.<br>STEL 15 minutes: 442 mg/m <sup>3</sup> . |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | <b>ACGIH TLV (United States)</b><br>TWA: 3 mg/m <sup>3</sup> (Respirable fraction).<br>TWA: 10 mg/m <sup>3</sup> (Total dust).                                                                                         |
| octamethylcyclotetrasiloxane                         | <b>IPEL (-, 10/2017)</b><br>TWA: 10 ppm.                                                                                                                                                                               |

## DNELs/DMELs

Code : 00276264

Date of issue/Date of revision

: 11 July 2026

SIGMAGLIDE 890 BASE WHITE

## SECTION 8: Exposure controls/personal protection

| Product/ingredient name        | Exposure                                            | Value                              |
|--------------------------------|-----------------------------------------------------|------------------------------------|
| Xylene                         | DNEL - General population - Long term - Oral        | Systemic<br>5 mg/kg bw/day         |
|                                | DNEL - General population - Long term - Inhalation  | Local<br>65.3 mg/m <sup>3</sup>    |
|                                | DNEL - General population - Long term - Inhalation  | Systemic<br>65.3 mg/m <sup>3</sup> |
|                                | DNEL - General population - Long term - Dermal      | Systemic<br>125 mg/kg bw/day       |
|                                | DNEL - Workers - Long term - Dermal                 | Systemic<br>212 mg/kg bw/day       |
|                                | DNEL - Workers - Long term - Inhalation             | Local<br>221 mg/m <sup>3</sup>     |
|                                | DNEL - Workers - Long term - Inhalation             | Systemic<br>221 mg/m <sup>3</sup>  |
|                                | DNEL - General population - Short term - Inhalation | Local<br>260 mg/m <sup>3</sup>     |
|                                | DNEL - General population - Short term - Inhalation | Systemic<br>260 mg/m <sup>3</sup>  |
|                                | DNEL - Workers - Short term - Inhalation            | Local<br>442 mg/m <sup>3</sup>     |
|                                | DNEL - Workers - Short term - Inhalation            | Systemic<br>442 mg/m <sup>3</sup>  |
|                                | DNEL - General population - Long term - Inhalation  | Local<br>0.3 mg/m <sup>3</sup>     |
|                                | DNEL - Workers - Long term - Inhalation             | Local<br>1.22 mg/m <sup>3</sup>    |
|                                | DNEL - General population - Short term - Inhalation | Local<br>1.5 mg/m <sup>3</sup>     |
|                                | DNEL - Workers - Short term - Inhalation            | Local<br>6.1 mg/m <sup>3</sup>     |
|                                | DNEL - General population - Long term - Oral        | Systemic<br>3.7 mg/kg bw/day       |
|                                | DNEL - General population - Long term - Inhalation  | Local<br>13 mg/m <sup>3</sup>      |
|                                | DNEL - General population - Long term - Inhalation  | Systemic<br>13 mg/m <sup>3</sup>   |
| dodecamethylcyclotetrasiloxane | DNEL - Workers - Long term - Inhalation             | Local<br>73 mg/m <sup>3</sup>      |
| octamethylcyclotetrasiloxane   | DNEL - Workers - Long term - Inhalation             | Systemic<br>73 mg/m <sup>3</sup>   |

### PNECs

| Product/ingredient name | Compartment Detail - Method | Value           |
|-------------------------|-----------------------------|-----------------|
| Xylene                  | Fresh water                 | 0.327 mg/l      |
|                         | Marine water                | 0.327 mg/l      |
|                         | Sewage Treatment Plant      | 6.58 mg/l       |
|                         | Fresh water sediment        | 12.46 mg/kg dwt |
|                         | Marine water sediment       | 12.46 mg/kg dwt |
|                         | Soil                        | 2.31 mg/kg      |

### 8.2 Exposure controls

#### Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Individual protection measures

##### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### Eye/face protection

: Safety glasses with side shields. Use eye protection according to EN 166.

##### Skin protection

##### Hand protection

:



Code : 00276264  
SIGMAGLIDE 890 BASE WHITE

Date of issue/Date of revision : 11 July 2026

## SECTION 8: Exposure controls/personal protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: polyvinyl alcohol (PVA), Viton®  
Not recommended: nitrile rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.  
**Colour** : White.  
**Odour** : Aromatic.  
**Melting point/freezing point** : Not determined.  
**Boiling point or initial boiling point and boiling range** : >37.78°C  
**Flammability** : Not determined. There are no data available on the mixture itself.  
**Lower and upper explosion limit** : Not available.



|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 9: Physical and chemical properties

Flash point

: Closed cup: Not applicable.

Auto-ignition temperature

:

| Ingredient name                                                                         | °C  | °F    | Method |
|-----------------------------------------------------------------------------------------|-----|-------|--------|
|  ylene | 432 | 809.6 |        |

Decomposition temperature

: Stable under recommended storage and handling conditions (see Section 7).

pH

: Not applicable. insoluble in water.

Viscosity

: ynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm²/s

Solubility

:

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

Partition coefficient n-octanol/ water (log Pow)

: Not applicable.

Vapour pressure

:

| Ingredient name                                                                         | Vapour Pressure at 20°C |      |        | Vapour pressure at 50°C |     |        |
|-----------------------------------------------------------------------------------------|-------------------------|------|--------|-------------------------|-----|--------|
|                                                                                         | mm Hg                   | kPa  | Method | mm Hg                   | kPa | Method |
|  ylene | 6.7                     | 0.89 |        |                         |     |        |

Relative density

: 1.14

Particle characteristics

Median particle size

: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties

: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties

: Product does not present an oxidizing hazard.

No additional information.

SECTION 10: Stability and reactivity

|                                         |                                                                                                                                               |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.                                                  |
| 10.2 Chemical stability                 | : The product is stable.                                                                                                                      |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                                                             |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions:<br>oxidising agents, strong alkalis, strong acids.           |
| 10.6 Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials:<br>carbon oxides Formaldehyde. metal oxide/oxides      |

|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Causes damage to organs through prolonged or repeated exposure.

Acute toxicity

| Product/ingredient name                              | Result                                                                                                                                                                  | Dose / Exposure      |
|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| Xylene                                               | Rat - Oral - LD50                                                                                                                                                       | 4.3 g/kg             |
| dodecamethylcyclohexasiloxane                        | Rabbit - Dermal - LD50                                                                                                                                                  | 1.7 g/kg             |
|                                                      | Rat - Oral - LD50                                                                                                                                                       | >50 g/kg             |
|                                                      | Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Respiratory stimulation Lung, Thorax, or Respiration - Other changes |                      |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | Rat - Inhalation - LC50 Dusts and mists                                                                                                                                 | >5.08 mg/l [4 hours] |
| octamethylcyclotetrasiloxane                         | Rat - Oral - LD50                                                                                                                                                       | >4800 mg/kg          |
|                                                      | Rat - Dermal - LD50                                                                                                                                                     | >2375 mg/kg          |
|                                                      | Rabbit - Dermal - LD50                                                                                                                                                  | >2400 mg/kg          |
|                                                      | Rat - Inhalation - LC50 Vapour                                                                                                                                          | 36 g/m³ [4 hours]    |
|                                                      | Toxic effects: Behavioral - Excitement Lung, Thorax, or Respiration - Dyspnea Other - Hair                                                                              |                      |
|                                                      | Rat - Inhalation - LC50 Dusts and mists                                                                                                                                 | 36 mg/l [4 hours]    |

Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Dermal               | 46848.78 mg/kg |
| Inhalation (vapours) | 303.14 mg/l    |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

| Product/ingredient name | Result                                                                                                                |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Xylene                  | Rabbit - Skin - Moderate irritant<br>Amount/concentration applied: 500 mg<br>Duration of treatment/exposure: 24 hours |

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 11: Toxicological information

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| Xylene                  | Category 3 | -                 | Respiratory tract irritation |

Conclusion/Summary :  
Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name  | Category   | Route of exposure | Target organs |
|--------------------------|------------|-------------------|---------------|
| crystalite (<10 microns) | Category 1 | inhalation        | -             |

Conclusion/Summary :  
Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| Xylene                  | ASPIRATION HAZARD - Category 1 |

Conclusion/Summary :  
Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

- Potential acute health effects
- Inhalation : No known significant effects or critical hazards.
  - Ingestion : No known significant effects or critical hazards.
  - Skin contact : Defatting to the skin. May cause skin dryness and irritation.
  - Eye contact : No known significant effects or critical hazards.
- Symptoms related to the physical, chemical and toxicological characteristics
- Inhalation : No specific data.
  - Ingestion : No specific data.
  - Skin contact : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
  - Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Short term exposure
- Potential immediate effects : No known significant effects or critical hazards.
  - Potential delayed effects : No known significant effects or critical hazards.
- Long term exposure
- Potential immediate effects : No known significant effects or critical hazards.
  - Potential delayed effects : No known significant effects or critical hazards.

- Potential chronic health effects
- General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
  - Carcinogenicity : No known significant effects or critical hazards.

|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 11: Toxicological information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mutagenicity          | : No known significant effects or critical hazards.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Reproductive toxicity | : No known significant effects or critical hazards.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Other information     | : Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Avoid contact with skin and clothing. |

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

| Product/ingredient name                                                         | Result         | Species | Dose / Exposure       |
|---------------------------------------------------------------------------------|----------------|---------|-----------------------|
| 3-bis[12-hydroxy-octadecamide-N-methylene]-benzene octamethylcyclotetrasiloxane | Acute - LC50   | Fish    | >100 mg/l [96 hours]  |
|                                                                                 | Chronic - NOEC | Algae   | ≥0.044 mg/l [93 days] |
|                                                                                 | Chronic - NOEC | Daphnia | 0.0079 mg/l [21 days] |

Conclusion/Summary : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

| Product/ingredient name      | Test     | Result                       | Dose / Inoculum |
|------------------------------|----------|------------------------------|-----------------|
| octamethylcyclotetrasiloxane | OECD 310 | 3.7% [29 days] - Not readily |                 |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name       | LogP <sub>ow</sub> | BCF                      | Potential |
|-------------------------------|--------------------|--------------------------|-----------|
| xylene                        | 3.12               | 7.4 to 18.5              | Low       |
| dodecamethylcyclohexasiloxane | 8.87               | 1660 [OECD 305]          | High      |
| octamethylcyclotetrasiloxane  | 6.488              | 13400 [EPA OTS 797.1520] | High      |

|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient

| Product/ingredient name      | logKoc | Koc     |
|------------------------------|--------|---------|
| Decamethylcyclohexasiloxane  | 4.4    | 25167.8 |
| octamethylcyclotetrasiloxane | 3.5    | 3064.9  |

12.5 Results of PBT and vPvB assessment

| Product/ingredient name                              | PBT                   | P         | B         | T         | vPvB                  | vP        | vB        |
|------------------------------------------------------|-----------------------|-----------|-----------|-----------|-----------------------|-----------|-----------|
| Xylene                                               | No                    | N/A       | No        | No        | No                    | N/A       | No        |
| dodecamethylcyclohexasiloxane                        | SVHC<br>(Recommended) | Specified | Specified | Specified | SVHC<br>(Recommended) | Specified | Specified |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene | No                    | N/A       | N/A       | No        | N/A                   | N/A       | N/A       |
| octamethylcyclotetrasiloxane                         | SVHC<br>(Recommended) | Specified | Specified | Specified | SVHC<br>(Recommended) | Specified | Specified |

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste :  
European waste catalogue (EWC)

| Waste code | Waste designation                                                                 |
|------------|-----------------------------------------------------------------------------------|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Code : 00276264 Date of issue/Date of revision : 11 July 2026  
SIGMAGLIDE 890 BASE WHITE

## SECTION 13: Disposal considerations

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                        | ADR/RID         | ADN                                                 | IMDG            | IATA            |
|----------------------------------------|-----------------|-----------------------------------------------------|-----------------|-----------------|
| <b>14.1 UN number or ID number</b>     | Not regulated.  | 9006                                                | Not regulated.  | Not regulated.  |
| <b>14.2 UN proper shipping name</b>    | -               | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | -               | -               |
| <b>14.3 Transport hazard class(es)</b> | -               | 9                                                   | -               | -               |
| <b>14.4 Packing group</b>              | -               | -                                                   | -               | -               |
| <b>14.5 Environmental hazards</b>      | No.             | Yes.                                                | No.             | No.             |
| <b>Marine pollutant substances</b>     | Not applicable. | Not applicable.                                     | Not applicable. | Not applicable. |

### Additional information

**ADR/RID** : None identified.  
**ADN** : The product is only regulated as a dangerous good when transported in tank vessels.  
**IMDG** : None identified.  
**IATA** : None identified.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

|                           |            |                                |                |
|---------------------------|------------|--------------------------------|----------------|
| Code                      | : 00276264 | Date of issue/Date of revision | : 11 July 2026 |
| SIGMAGLIDE 890 BASE WHITE |            |                                |                |

SECTION 15: Regulatory information

| Intrinsic property                                                                    | Ingredient name               | Status      | Reference number    | Date of revision |
|---------------------------------------------------------------------------------------|-------------------------------|-------------|---------------------|------------------|
|  PBT | dodecamethylcyclohexasiloxane | Recommended | 10th recommendation | 4/14/2021        |
|                                                                                       | octamethylcyclotetrasiloxane  | Recommended | 10th recommendation | 4/14/2021        |
|                                                                                       | vPvB                          | Recommended | 10th recommendation | 4/14/2021        |
|                                                                                       | octamethylcyclotetrasiloxane  | Recommended | 10th recommendation | 4/14/2021        |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name                                                                                     | Entry Number ( REACH ) |
|-------------------------------------------------------------------------------------------------------------|------------------------|
|  SIGMAGLIDE 890 BASE WHITE | 3                      |
| dodecamethylcyclohexasiloxane                                                                               | 70                     |
| octamethylcyclotetrasiloxane                                                                                | 70                     |

Labelling : Not applicable.

Other EU regulations

Explosive precursors :  Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- IMDG = International Maritime Dangerous Goods
- IATA = International Air Transport Association

Full text of abbreviated H statements



|                                  |                                                      |
|----------------------------------|------------------------------------------------------|
| <b>Code</b> : 00276264           | <b>Date of issue/Date of revision</b> : 11 July 2026 |
| <b>SIGMAGLIDE 890 BASE WHITE</b> |                                                      |

**SECTION 16: Other information**

|                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H226<br>H304<br>H312<br>H315<br>H317<br>H319<br>H332<br>H335<br>H361f<br>H372<br>H410<br>H412<br>H413 | Flammable liquid and vapour.<br>May be fatal if swallowed and enters airways.<br>Harmful in contact with skin.<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>Harmful if inhaled.<br>May cause respiratory irritation.<br>Suspected of damaging fertility.<br>Causes damage to organs through prolonged or repeated exposure.<br>Very toxic to aquatic life with long lasting effects.<br>Harmful to aquatic life with long lasting effects.<br>May cause long lasting harmful effects to aquatic life. |
|-------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Full text of classifications [CLP/GHS]

|                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute Tox. 4<br>Aquatic Chronic 1<br>Aquatic Chronic 3<br>Aquatic Chronic 4<br>Asp. Tox. 1<br>Eye Irrit. 2<br>Flam. Liq. 3<br>Repr. 2<br>Skin Irrit. 2<br>Skin Sens. 1<br>STOT RE 1<br><br>STOT SE 3 | ACUTE TOXICITY - Category 4<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3<br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4<br>ASPIRATION HAZARD - Category 1<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2<br>FLAMMABLE LIQUIDS - Category 3<br>REPRODUCTIVE TOXICITY - Category 2<br>SKIN CORROSION/IRRITATION - Category 2<br>SKIN SENSITISATION - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**History**

|                                        |                   |
|----------------------------------------|-------------------|
| <b>Date of issue/ Date of revision</b> | : 11 July 2026    |
| <b>Date of previous issue</b>          | : 31 October 2022 |
| <b>Prepared by</b>                     | : EHS             |
| <b>Version</b>                         | : 14              |

**Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.