

# SAFETY DATA SHEET

Date of issue/Date of revision

: 31 July 2026

Version

: 2



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMARINE ONE 648 GREY 517705

**Product code** : 000010026013

**Other means of identification**

30013596; 30013597

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Professional painting, indoor brush/roller  
Professional spray painting, outdoor (with or without respiratory protection)  
Professional painting, outdoor brush/roller  
Professional spray painting, near-industrial setting  
Professional non-spray painting, near-industrial setting  
Professional spray painting, indoor (with or without respiratory protection)

**Product use** : Professional applications, Used by spraying, Application by non spray methods..

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

 Flam. Liq. 3, H226  
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

|                                                                                                                                    |   |                                                                                                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms                                                                                                                  | : |   |
| Signal word                                                                                                                        | : | Warning                                                                                                                                                             |
| Hazard statements                                                                                                                  | : | Flammable liquid and vapour.<br>May cause drowsiness or dizziness.                                                                                                  |
| Prevention                                                                                                                         | : | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour.                                              |
| Response                                                                                                                           | : | IF INHALED: Call a POISON CENTER or doctor if you feel unwell.                                                                                                      |
| Storage                                                                                                                            | : | Store in a well-ventilated place. Keep container tightly closed.                                                                                                    |
| Disposal                                                                                                                           | : | Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P210, P261, P304 + P312, P403 + P233, P501     |
| Hazardous ingredients                                                                                                              | : | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics                                                                                                 |
| Supplemental label elements                                                                                                        | : | Repeated exposure may cause skin dryness or cracking.                                                                                                               |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable.                                                                                                                                                     |
| Special packaging requirements                                                                                                     |   |                                                                                                                                                                     |
| Containers to be fitted with child-resistant fastenings                                                                            | : | Not applicable.                                                                                                                                                     |
| Tactile warning of danger                                                                                                          | : | Not applicable.                                                                                                                                                     |

2.3 Other hazards

|                                                                                                            |   |                                                                                       |
|------------------------------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII          | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. | : | Based on available data, the classification criteria are not met.                     |
| Other hazards which do not result in classification                                                        | : | Prolonged or repeated contact may dry skin and cause irritation.                      |

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                                             | Identifiers                                                      | % by weight | Classification                                                                                                                                      | Specific Conc. Limits, M-factors and ATEs | Type |
|---------------------------------------------------------------------|------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | REACH #:<br>01-2119463258-33<br>EC: 919-857-5<br>CAS: 64742-48-9 | ≥25 - ≤50   | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>EUH066<br><b>See Section 16 for the full text of the H statements declared above.</b> | EUH066: C ≥ 20%                           | [1]  |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard  
Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

|                            |                                                                                                                                                                                                                                                                                                                |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact                | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.                                                                                                                                                      |
| Inhalation                 | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.                                                                                                               |
| Skin contact               | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.                                                                                                                                                           |
| Ingestion                  | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.                                                                                                                                                                         |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

|              |                                                                                         |
|--------------|-----------------------------------------------------------------------------------------|
| Eye contact  | : No known significant effects or critical hazards.                                     |
| Inhalation   | : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. |
| Skin contact | : Defatting to the skin. May cause skin dryness and irritation.                         |
| Ingestion    | : Can cause central nervous system (CNS) depression.                                    |

Over-exposure signs/symptoms

|             |                     |
|-------------|---------------------|
| Eye contact | : No specific data. |
|-------------|---------------------|

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| <b>Code</b> : 000010026013    | <b>Date of issue/Date of revision</b> : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                                                      |

## SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

|                               |                                                      |
|-------------------------------|------------------------------------------------------|
| <b>Code</b> : 000010026013    | <b>Date of issue/Date of revision</b> : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                                                      |

## SECTION 6: Accidental release measures

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 7: Handling and storage

**7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**7.3 Specific end use(s)**  
See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters**  
**Occupational exposure limits**  
No exposure limit value known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name                                             | Exposure                                                                          | Value            |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | DNEL - Workers - Long term - Dermal<br><i>Systemic</i>                            | 208 mg/kg bw/day |
|                                                                     | DNEL - Workers - Long term - Inhalation<br><i>Systemic</i>                        | 871 mg/m³        |
|                                                                     | DNEL - General population - Consumers - Long term - Dermal<br><i>Systemic</i>     | 125 mg/kg bw/day |
|                                                                     | DNEL - General population - Consumers - Long term - Inhalation<br><i>Systemic</i> | 185 mg/m³        |
|                                                                     | DNEL - General population - Consumers - Long term - Oral<br><i>Systemic</i>       | 125 mg/kg bw/day |

**PNECs**  
Not available.

**8.2 Exposure controls**

Code : 000010026013

Date of issue/Date of revision

: 31 July 2026

SIGMARINE ONE 648 GREY 517705

## SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:  
  
Recommended: nitrile rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Colour

Odour

Melting point/freezing point

Boiling point or initial boiling point and boiling range

Flammability

Lower and upper explosion limit

Flash point

Auto-ignition temperature

Decomposition temperature

pH

Viscosity

Viscosity

Solubility

Partition coefficient n-octanol/ water (log Pow)

Vapour pressure

Relative density

Particle characteristics

Median particle size

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties

Oxidising properties

No additional information.

: Liquid.

: Grey.

: Aromatic. [Slight]

: Not determined.

: >37.78°C

: Not determined. There are no data available on the mixture itself.

: Not available.

: Closed cup: 43°C

:

| Ingredient name                                                     | °C  | °F  | Method |
|---------------------------------------------------------------------|-----|-----|--------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 270 | 518 |        |

: Stable under recommended storage and handling conditions (see Section 7).

: Not applicable. insoluble in water.

: Dynamic (room temperature): Not available.  
Kinematic (room temperature): >400 mm²/s  
Kinematic (40°C): >21 mm²/s

: > 100 s (ISO 6mm)

:

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

: Not applicable.

:

| Ingredient name                                                     | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|---------------------------------------------------------------------|-------------------------|-----|--------|-------------------------|-----|--------|
|                                                                     | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | 2.25                    | 0.3 |        |                         |     |        |

: 0.98

: Not applicable.

: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

: Product does not present an oxidizing hazard.



|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 10: Stability and reactivity

|                                         |                                                                                                                                               |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.                                                  |
| 10.2 Chemical stability                 | : The product is stable.                                                                                                                      |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                                                             |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions:<br>oxidising agents, strong alkalis, strong acids.           |
| 10.6 Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials:<br>carbon oxides metal oxide/oxides                    |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

May cause drowsiness or dizziness.

Acute toxicity

| Product/ingredient name                                                                                                                                | Result              | Dose / Exposure |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-----------------|
|  Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | Rat - Oral - LD50   | >5000 mg/kg     |
|                                                                                                                                                        | Rat - Dermal - LD50 | >5000 mg/kg     |

Acute toxicity estimates

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Code : 000010026013 Date of issue/Date of revision : 31 July 2026  
SIGMARINE ONE 648 GREY 517705

## SECTION 11: Toxicological information

| Product/ingredient name                                             | Category   | Route of exposure | Target organs    |
|---------------------------------------------------------------------|------------|-------------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | Category 3 | -                 | Narcotic effects |

### Conclusion/Summary :

May cause drowsiness or dizziness.

### Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

### Aspiration hazard

| Product/ingredient name                                             | Result                         |
|---------------------------------------------------------------------|--------------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | ASPIRATION HAZARD - Category 1 |

### Conclusion/Summary :

Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

### Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Ingestion** : Can cause central nervous system (CNS) depression.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Eye contact** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Ingestion** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Eye contact** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

#### Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

### Potential chronic health effects

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 11: Toxicological information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General               | : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.                                                                                                                                                                                                                                                                                                                    |
| Carcinogenicity       | : No known significant effects or critical hazards.                                                                                                                                                                                                                                                                                                                                                                       |
| Mutagenicity          | : No known significant effects or critical hazards.                                                                                                                                                                                                                                                                                                                                                                       |
| Reproductive toxicity | : No known significant effects or critical hazards.                                                                                                                                                                                                                                                                                                                                                                       |
| Other information     | : Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. |

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

12.1 Toxicity

| Product/ingredient name                                             | Result | Species | Dose / Exposure       |
|---------------------------------------------------------------------|--------|---------|-----------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | LC50   | Algae   | >1000 mg/l [72 hours] |

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

| Product/ingredient name                                             | Test | Result                  | Dose / Inoculum |
|---------------------------------------------------------------------|------|-------------------------|-----------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | -    | 80% [28 days] - Readily |                 |

| Product/ingredient name                                             | Aquatic half-life | Photolysis | Biodegradability |
|---------------------------------------------------------------------|-------------------|------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name                                             | LogP <sub>ow</sub> | BCF        | Potential |
|---------------------------------------------------------------------|--------------------|------------|-----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | -                  | 10 to 2500 | High      |

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition coefficient

Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Hazardous waste :  
[European waste catalogue \(EWC\)](#)

| Waste code | Waste designation                                                                 |
|------------|-----------------------------------------------------------------------------------|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

|                     |                                                                                                                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special precautions | : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 14: Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number or ID number     | UN1263          | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               | 3               |
| 14.4 Packing group              | III             | III             | III             | III             |
| 14.5 Environmental hazards      | No.             | No.             | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

Additional information

|             |                                                                                                                |
|-------------|----------------------------------------------------------------------------------------------------------------|
| ADR/RID     | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1. |
| Tunnel code | : (D/E)                                                                                                        |
| ADN         | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1. |
| IMDG        | : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.     |
| IATA        | : None identified.                                                                                             |

|                                   |                                                                                                                                                                                                                     |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 14.6 Special precautions for user | : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                              |                   |
|--------------------------------------------------------------|-------------------|
| 14.7 Maritime transport in bulk according to IMO instruments | : Not applicable. |
|--------------------------------------------------------------|-------------------|

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

| Product/ingredient name       | Entry Number ( REACH ) |
|-------------------------------|------------------------|
| SIGMARINE ONE 648 GREY 517705 | 3                      |

|           |                   |
|-----------|-------------------|
| Labelling | : Not applicable. |
|-----------|-------------------|

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 15: Regulatory information

|                                                        |                   |
|--------------------------------------------------------|-------------------|
| <u>Other EU regulations</u>                            |                   |
| Explosive precursors                                   | : Not applicable. |
| <u>Ozone depleting substances (EU 2024/590)</u>        |                   |
| Not listed.                                            |                   |
| <u>Persistent Organic Pollutants</u>                   |                   |
| Not listed.                                            |                   |
| <u>Seveso Directive</u>                                |                   |
| This product is controlled under the Seveso Directive. |                   |
| <u>Danger criteria</u>                                 |                   |
| Category                                               |                   |
| P5c                                                    |                   |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
PBT = Persistent, Bioaccumulative and Toxic  
vPvB = Very Persistent and Very Bioaccumulative  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
IMDG = International Maritime Dangerous Goods  
IATA = International Air Transport Association

Full text of abbreviated H statements

|                                |                                                                                                                                                                              |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H226<br>H304<br>H336<br>EUH066 | Flammable liquid and vapour.<br>May be fatal if swallowed and enters airways.<br>May cause drowsiness or dizziness.<br>Repeated exposure may cause skin dryness or cracking. |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Full text of classifications [CLP/GHS]

|                                          |                                                                                                                                   |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Asp. Tox. 1<br>Flam. Liq. 3<br>STOT SE 3 | ASPIRATION HAZARD - Category 1<br>FLAMMABLE LIQUIDS - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|

History

Date of issue/ Date of revision : 31 July 2026  
Date of previous issue : 5 February 2026  
Prepared by : EHS  
Version : 2

|                               |                |                                |                |
|-------------------------------|----------------|--------------------------------|----------------|
| Code                          | : 000010026013 | Date of issue/Date of revision | : 31 July 2026 |
| SIGMARINE ONE 648 GREY 517705 |                |                                |                |

SECTION 16: Other information

Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*



# Safe Use of Mixtures Information for end-users

**Title** : Professional painting, indoor brush/roller

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Indoor painting by professionals with brush or roller, with good general room ventilation (open doors/windows)

**This safe use information is linked to SWED no.** : CEPE\_PW\_04

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Maximum duration  | Ventilation                   |                            | Respiratory                                                 | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|-------------------|-------------------------------|----------------------------|-------------------------------------------------------------|-----------------------------------------|---------------------------------------|
|                                                                             |                   | Type                          | ach (air changes per hour) |                                                             |                                         |                                       |
| Preparation of material for application                                     | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by brush or roller            | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | None                                    | None                                  |
| Cleaning                                                                    | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# Safe Use of Mixtures Information for end-users

**Title** : Professional spray painting, outdoor (without respiratory protection)

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Outdoor spray painting by professionals for general applications (e.g. decorative)

**This safe use information is linked to SWED no.** : CEPE\_PW\_05a

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Outdoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Maximum duration  | Ventilation |                            | Respiratory                                                 | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|-------------------|-------------|----------------------------|-------------------------------------------------------------|-----------------------------------------|---------------------------------------|
|                                                                             |                   | Type        | ach (air changes per hour) |                                                             |                                         |                                       |
| Preparation of material for application                                     | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by spraying                   | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | None                                    | None                                  |
| Cleaning                                                                    | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# Safe Use of Mixtures Information for end-users

**Title** : Professional painting, outdoor brush/roller

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Outdoor painting by professionals with brush or roller

**This safe use information is linked to SWED no.** : CEPE\_PW\_06

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Outdoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Maximum duration  | Ventilation |                            | Respiratory                                                 | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|-------------------|-------------|----------------------------|-------------------------------------------------------------|-----------------------------------------|---------------------------------------|
|                                                                             |                   | Type        | ach (air changes per hour) |                                                             |                                         |                                       |
| Preparation of material for application                                     | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by brush or roller            | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | None                                    | None                                  |
| Cleaning                                                                    | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | More than 4 hours | Outdoors    | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# Safe Use of Mixtures Information for end-users

**Title** : Professional spray painting, near-industrial setting

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Indoor spray painting by professionals with efficient ventilation such as spray booth or local exhaust ventilation

**This safe use information is linked to SWED no.** : CEPE\_PW\_01

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Maximum duration  | Ventilation                            |                                       | Respiratory                                                                              | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|-------------------|----------------------------------------|---------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------|
|                                                                             |                   | Type                                   | ach (air changes per hour)            |                                                                                          |                                         |                                       |
| Preparation of material for application                                     | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by spraying                   | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | None                                    | None                                  |
| Cleaning                                                                    | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# Safe Use of Mixtures Information for end-users

**Title** : Professional application by non spray methods, near-industrial setting

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Indoor painting by professionals with brush, roller, putty knife etc. with enhanced ventilation or local exhaust ventilation.

**This safe use information is linked to SWED no.** : CEPE\_PW\_02

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Maximum duration  | Ventilation                            |                                       | Respiratory                                                                              | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|-------------------|----------------------------------------|---------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------|
|                                                                             |                   | Type                                   | ach (air changes per hour)            |                                                                                          |                                         |                                       |
| Preparation of material for application                                     | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by brush or roller            | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - air drying                                                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | None                                    | None                                  |
| Cleaning                                                                    | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# Safe Use of Mixtures Information for end-users

**Title** : Professional spray painting, indoor (with respiratory protection)

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Indoor spray painting by professionals for specialist applications, with good general room ventilation plus respiratory protection

**This safe use information is linked to SWED no.** : CEPE\_PW\_03b

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Maximum duration  | Ventilation                   |                            | Respiratory                                                                              | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|-------------------|-------------------------------|----------------------------|------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------|
|                                                                             |                   | Type                          | ach (air changes per hour) |                                                                                          |                                         |                                       |
| Preparation of material for application                                     | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by spraying                   | More than 4 hours | Good general room ventilation | 3 - 5                      | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications.                              | None                                    | None                                  |
| Cleaning                                                                    | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | More than 4 hours | Good general room ventilation | 3 - 5                      | See section 8 of this Safety Data Sheet for specifications.                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.