

Date of issue

5 August 2026

Version 5

Section 1. Product and company identification

Product name : AMERLOCK/SIGMACOVER 400 HARDENER
Product code : 000001194604
Other means of identification : 00437439; 00466371 ; 00466891
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against**Identified uses**

Coating. Paints. Painting-related materials.

Uses advised against

Not applicable.

Reason**Supplier's details:****Supplier**

: PPG Industrial do Brasil – Tintas e Vernizes Ltda
Via Anhanguera KM 106, Bairro Sao Judas Tadeu
Sumare / SP, Brasil
Teléfono: 55 19 2103-6000 (Recepción)

Email address:

: HazComLatam@ppg.com

Emergency telephone number : Centro de intoxicaciones 0800-333-0160 /CIQUIME 0800-222-2933

Section 2. Hazards identification**Classification of the substance or mixture**

: FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (oral) - Category 5
ACUTE TOXICITY (dermal) - Category 5
ACUTE TOXICITY (inhalation) - Category 4
SKIN CORROSION - Category 1
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1B
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
AQUATIC HAZARD (ACUTE) - Category 1
AQUATIC HAZARD (LONG-TERM) - Category 1

Section 2. Hazards identification

Target organs : Contains material which causes damage to the following organs: blood, liver, heart, brain, skin, central nervous system (CNS).
Contains material which may cause damage to the following organs: kidneys, lungs, the reproductive system, cardiovascular system, upper respiratory tract, bones, eye, lens or cornea.

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 14.1%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 59.8%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 70.6%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 69.9%

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Flammable liquid and vapor.
May be harmful if swallowed or in contact with skin.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapor.

Response

: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification

: Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of identification : 00437439; 00466371 ; 00466891

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
Isocyanate, not containing asbestiform fibres	30 - <60	14807-96-6
4-methylpentan-2-one	10 - <12.5	108-10-1
Polyaminoamide	7 - <10	68082-29-1
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	5 - <7	68515-49-1
benzyl alcohol	3 - <5	100-51-6
cyclohexanone	3 - <5	108-94-1
3-aminomethyl-3,5,5-trimethylcyclohexylamine	3 - <5	2855-13-2
4-nonylphenol, branched	3 - <5	84852-15-3
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-	3 - <5	38294-64-3
2,3-epoxypropane, reaction products with 3-aminomethyl-		
3,5,5-trimethylcyclohexylamine		
2-methylpropan-1-ol	2 - <3	78-83-1
2,4,6-tris(dimethylaminomethyl)phenol	1 - <2	90-72-2
Fatty acids, tall-oil, reaction products with diethylenetriamine	0.5 - <1	61790-69-0
Amines, polyethylenepoly-, triethylenetetramine fraction	0.5 - <1	90640-67-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

Specific treatments : The exposed person may need to be kept under medical surveillance for 48 hours.
No specific treatment.

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Potential acute health effects

Eye contact : Causes serious eye damage.
Inhalation : Harmful if inhaled. May cause respiratory irritation.
Skin contact : Causes severe burns. May be harmful in contact with skin. Defatting to the skin. May cause an allergic skin reaction.
Ingestion : May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

- Small spill :** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill :** Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Talc , not containing asbestiform fibres	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina, 11/2003) TWA 8 hours: 2 mg/m ³ . Form: Respirable fibers: length> 5 .mu.m; Length / diameter ratio (aspect) ³ 3: 1, determined by the membrane filter method at 400 - 450 x magnification (4mm objective) using illumination of phase contrast – Respirable fraction..
4-methylpentan-2-one	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina, 11/2003) TWA 8 hours: 50 ppm. STEL 15 minutes: 75 ppm.
cyclohexanone	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina, 11/2003) Absorbed through skin. TWA 8 hours: 25 ppm.
2-methylpropan-1-ol	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina, 11/2003) TWA 8 hours: 50 ppm.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection : Chemical splash goggles and face shield.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Clear.
- Odor** : Amine-like. [Strong]
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 37°C (98.6°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.36

	Solubility(ies)	
	Media	Result
	cold water	Not soluble

- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.

Section 9. Physical and chemical properties

Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): >21 mm ² /s (>21 cSt)
Viscosity	: 40 - <60 s (ISO 6mm)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4-methylpentan-2-one	LC50 Inhalation Vapor	Rat	11 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	2.08 g/kg	-
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	LD50 Dermal	Rabbit	16000 mg/kg	-
	LD50 Oral	Rat	>60000 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
cyclohexanone	LC50 Inhalation Gas.	Rat	8000 ppm	4 hours
	LD50 Dermal	Rabbit	1100 mg/kg	-
	LD50 Oral	Rat	1800 mg/kg	-
3-aminomethyl-3,5,5-trimethylcyclohexylamine	LC50 Inhalation Dusts and mists	Rat	>5.01 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
4-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
2-methylpropan-1-ol	LC50 Inhalation Vapor	Rat	24.6 mg/l	4 hours
	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rat	1280 mg/kg	-

Section 11. Toxicological information

Amines, polyethylenepoly-, triethylenetetramine fraction	LD50 Oral	Rat	1200 mg/kg	-
	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4-nonylphenol, branched	Skin - Erythema/Eschar	Rabbit	4	-	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl-3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitizing

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
alc , not containing asbestiform fibres	-	2A	-
4-methylpentan-2-one	-	2B	-
cyclohexanone	-	3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Not available.

Section 11. Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
alc , not containing asbestiform fibres 4-methylpentan-2-one Polyaminoamide 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich benzyl alcohol cyclohexanone 3-aminomethyl-3,5,5-trimethylcyclohexylamine 4-nonylphenol, branched 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine 2-methylpropan-1-ol - 2,4,6-tris(dimethylaminomethyl)phenol Fatty acids, tall-oil, reaction products with diethylenetriamine Amines, polyethylenepoly-, triethylenetetramine fraction	Category 3 Category 3 None. None. None. Category 3 None. None. None. Category 3 Category 3 None. None. Category 1	- - None. None. - None. None. None. - - None. None. -	Respiratory tract irritation Narcotic effects None. None. Respiratory tract irritation None. None. None. Respiratory tract irritation Narcotic effects None. None. respiratory tract

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
alc , not containing asbestiform fibres 4-methylpentan-2-one Polyaminoamide 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich benzyl alcohol cyclohexanone 3-aminomethyl-3,5,5-trimethylcyclohexylamine 4-nonylphenol, branched 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine 2-methylpropan-1-ol 2,4,6-tris(dimethylaminomethyl)phenol Fatty acids, tall-oil, reaction products with diethylenetriamine Amines, polyethylenepoly-, triethylenetetramine fraction	None. None. None. None. None. None. None. None. None. None. None. None. Category 2 None.	None. None. None. None. None. None. None. None. None. None. None. oral None.	None. None. None. None. None. None. None. None. None. None. - None.

Target organs : Contains material which causes damage to the following organs: blood, liver, heart, brain, skin, central nervous system (CNS).
Contains material which may cause damage to the following organs: kidneys, lungs, the reproductive system, cardiovascular system, upper respiratory tract, bones, eye, lens or cornea.

Section 11. Toxicological information

Aspiration hazard

Name	Result
Talc , not containing asbestiform fibres	None.
4-methylpentan-2-one	ASPIRATION HAZARD - Category 2
4-methylpentan-2-one	None.
Polyaminoamide	None.
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	None.
benzyl alcohol	ASPIRATION HAZARD - Category 2
benzyl alcohol	None.
cyclohexanone	None.
3-aminomethyl-3,5,5-trimethylcyclohexylamine	None.
4-nonylphenol, branched	None.
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-	None.
2,3-epoxypropane, reaction products with 3-aminomethyl-	
3,5,5-trimethylcyclohexylamine	
2-methylpropan-1-ol	ASPIRATION HAZARD - Category 2
2-methylpropan-1-ol	None.
2,4,6-tris(dimethylaminomethyl)phenol	None.
Fatty acids, tall-oil, reaction products with diethylenetriamine	None.
Amines, polyethylenepoly-, triethylenetetramine fraction	None.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Harmful if inhaled. May cause respiratory irritation.
- Skin contact** : Causes severe burns. May be harmful in contact with skin. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 - pain
 - watering
 - redness
- Inhalation** : Adverse symptoms may include the following:
 - respiratory tract irritation
 - coughing
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 - pain or irritation
 - redness
 - dryness
 - cracking
 - blistering may occur
 - reduced fetal weight
 - increase in fetal deaths
 - skeletal malformations

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:
 stomach pains
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
AMERLOCK/SIGMACOVER 400 HARDENER	4256.2	3550.0	54807.5	31.5	4.3
Talc , not containing asbestiform fibres	Not available	Not available	Not available	Not available	Not available
4-methylpentan-2-one	2080	Not available	Not available	11	1.5
Polyaminoamide	Not available	Not available	Not available	Not available	Not available
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	Not available	16000	Not available	Not available	Not available
benzyl alcohol	1200	2500	Not available	Not available	Not available
cyclohexanone	1800	1100	8000	Not available	Not available
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	2500	Not available	Not available	Not available
4-nonylphenol, branched	1300	2140	Not available	Not available	Not available
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	Not available	Not available	Not available	Not available	Not available
2-methylpropan-1-ol	2830	2460	Not available	24.6	Not available
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	Not available	Not available	Not available
Fatty acids, tall-oil, reaction products with diethylenetriamine	500	Not available	Not available	Not available	Not available
Amines, polyethylenepoly-, triethylenetetramine fraction	1716	1465	Not available	Not available	Not available

Other information : Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
4-methylpentan-2-one	Acute LC50 >179 mg/l	Fish	96 hours
4-nonylphenol, branched	Acute EC50 0.04 mg/l	Algae - <i>Raphidocelis subcapitata</i>	72 hours
	Acute EC50 0.044 mg/l	Crustaceans - <i>Moina macrocopa</i>	48 hours
	Acute LC50 0.221 mg/l	Fish	96 hours
	Chronic EC10 0.37 mg/l Fresh water	Algae - <i>Desmodesmus subspicatus</i>	72 hours
2-methylpropan-1-ol	Acute EC50 1100 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Amines, polyethylenepoly-, triethylenetetramine fraction	Acute EC50 20 mg/l	Aquatic plants - <i>Daphnia magna</i>	72 hours

Section 12. Ecological information

	Acute EC50 31.1 mg/l Acute LC50 330 mg/l Acute NOEC 2.5 mg/l	Daphnia - <i>Daphnia magna</i> Fish - <i>Pimephales promelas</i> Crustaceans	48 hours 96 hours 72 hours
--	--	--	----------------------------------

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
4-methylpentan-2-one 2,4,6-tris (dimethylaminomethyl)phenol	OECD 301F OECD Ready Biodegradability - Closed Bottle Test	83 % - Readily - 28 days 4 % - Not readily - 28 days	- -	- -

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
4-methylpentan-2-one benzyl alcohol 2,4,6-tris (dimethylaminomethyl)phenol	- - -	- - -	Readily Readily Not readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
alc , not containing asbestiform fibres	None.	None.	None.
4-methylpentan-2-one	1.9	None.	Low
Polyaminoamide	None.	None.	None.
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	8.8	None.	High
benzyl alcohol	0.87	None.	Low
cyclohexanone	0.86	None.	Low
3-aminomethyl-	0.99	None.	Low
3,5,5-trimethylcyclohexylamine			
4-nonylphenol, branched	5.4	251.19 [ASTM E 1022-84]	Low
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-	None.	5.13	Low
2,3-epoxypropane, reaction products with 3-aminomethyl-			
3,5,5-trimethylcyclohexylamine			
2-methylpropan-1-ol	1	None.	Low
2,4,6-tris (dimethylaminomethyl)phenol	0.219	None.	Low
Fatty acids, tall-oil, reaction products with diethylenetriamine	None.	None.	None.
Amines, polyethylenepoly-, triethylenetetramine fraction	-2.65	None.	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Section 12. Ecological information

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	IATA
UN number	UN2920	UN2920	UN2920	UN2920
UN proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-nonylphenol, branched, 4-methylpentan-2-one)	LÍQUIDO CORROSIVO, INFLAMÁVEL, N.E. (4-nonylphenol, branched, 4-methylpentan-2-one)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (4-nonylphenol, branched, 4-methylpentan-2-one)	Corrosive liquid, flammable, n.o.s. (4-nonylphenol, branched, 4-methylpentan-2-one)
Transport hazard class(es)	8 (3)	8 (3)	8 (3)	8 (3)
Packing group	II	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(4-nonylphenol, branched)	Not applicable.

Additional information

UN : None identified.
Brazil : None identified.
Risk number : 83
IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Code	000001194604	Date of issue	5 August 2026	Version	5
Product name	AMERLOCK/SIGMACOVER 400 HARDENER				

Section 14. Transport information

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

History

Date of previous issue : 3/30/2026

Version : 5

EHS

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 UN = United Nations

References : ABNT NBR 14725: 2023 (April 2025)
 ANTT - National Land Transportation Agency

 Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.