

SAFETY DATA SHEET

Date of issue/Date of revision

: 7 August 2026

Version

: 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : HYDROCENTRIFUGON PEINTURE NF DURCISSEUR

Product code : 000001180560

Other means of identification

00434976

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.


See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 2: Hazards identification

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Prevention	:	Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P261, P264, P391, P501
Hazardous ingredients	:	epoxy resin (MW ≤ 700) and Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
Supplemental label elements	:	Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
<u>Special packaging requirements</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	:	Based on available data, the classification criteria are not met.
Other hazards which do not result in classification	:	Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
epoxy resin (MW ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6	≥50 - ≤75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 9003-36-5	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Castor oil, ethoxylated	EC: 500-151-7 CAS: 61791-12-6	≥1.0 - ≤5.0	Eye Irrit. 2, H319 See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard
Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Code : 000001180560 Date of issue/Date of revision : 7 August 2026

HYDROCENTRIFUGON PEINTURE NF DURCISSEUR

SECTION 4: First aid measures

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
halogenated compounds
Formaldehyde.

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour. Put on appropriate personal protective equipment.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 6: Accidental release measures

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- 6.3 Methods and material for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling**
- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- 7.3 Specific end use(s)**

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 7: Handling and storage

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Exposure	Value
Epoxy resin (MW ≤ 700)	DNEL - Workers - Long term - Inhalation	Systemic 12.25 mg/m³
	DNEL - Workers - Short term - Inhalation	Systemic 12.25 mg/m³
	DNEL - Workers - Long term - Dermal	Systemic 8.33 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	Systemic 8.33 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Dermal	Systemic 3.571 mg/kg bw/day
	DNEL - General population - Consumers - Short term - Dermal	Systemic 3.571 mg/kg bw/day
	DNEL - General population - Consumers - Long term - Oral	Systemic 0.75 mg/kg bw/day
	DNEL - General population - Consumers - Short term - Oral	Systemic 0.75 mg/kg bw/day
	DMEL - Workers - Short term - Dermal	Local 8.3 µg/cm²
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	DNEL - General population - Long term - Oral	Systemic 6.25 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic 8.7 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic 29.39 mg/m³
	DNEL - General population - Long term - Dermal	Systemic 62.5 mg/kg bw/day
Castor oil, ethoxylated	DNEL - Workers - Long term - Dermal	Systemic 104.15 mg/kg bw/day
	DNEL - General population - Long term - Oral	Systemic 1.67 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic 1.67 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic 2.9 mg/m³
	DNEL - Workers - Long term - Dermal	Systemic 4.67 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Systemic 16.4 mg/m³

PNECs

Code : 000001180560 Date of issue/Date of revision : 7 August 2026

HYDROCENTRIFUGON PEINTURE NF DURCISSEUR

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail - Method	Value
epoxy resin (MW ≤ 700)	Fresh water - Assessment Factors	0.006 mg/l
	Marine water - Assessment Factors	0.001 mg/l
	Sewage Treatment Plant - Assessment Factors	10 mg/l
	Fresh water sediment - Equilibrium Partitioning	0.996 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.1 mg/kg dwt

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds Formaldehyde.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
epoxy resin (MW ≤ 700)	Rat - Oral - LD50	>2 g/kg
	Rabbit - Dermal - LD50	>2 g/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Rat - Oral - LD50	>10000 mg/kg

Acute toxicity estimates

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
epoxy resin (MW ≤ 700)	<u>Rabbit - Skin - Mild irritant</u>
-	<u>Rabbit - Eyes - Mild irritant</u>

Conclusion/Summary	
Skin	: Causes skin irritation.
Eyes	: Causes serious eye irritation.
Respiratory	: Based on available data, the classification criteria are not met.
<u>Respiratory or skin sensitization</u>	

Product/ingredient name	Test	Result
epoxy resin (MW ≤ 700)	Mouse - skin OECD 429	Sensitising

Conclusion/Summary	
Skin	: May cause an allergic skin reaction.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 11: Toxicological information

Respiratory	: Based on available data, the classification criteria are not met.
Mutagenicity	
Based on available data, the classification criteria are not met.	
Carcinogenicity	
Based on available data, the classification criteria are not met.	
Reproductive toxicity	
Based on available data, the classification criteria are not met.	
Specific target organ toxicity (single exposure)	
Based on available data, the classification criteria are not met.	
Specific target organ toxicity (repeated exposure)	
Based on available data, the classification criteria are not met.	
Aspiration hazard	
Based on available data, the classification criteria are not met.	
Information on likely routes of exposure	: Not available.
Potential acute health effects	
Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Eye contact	: Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Short term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Long term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health effects	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 11: Toxicological information

Other information : Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
epoxy resin (MW ≤ 700)	Chronic - NOEC	Daphnia	0.3 mg/l [21 days]
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute - LC50	Daphnia	1.8 mg/l [48 hours]
	Acute - LC50	Fish	2.54 mg/l [96 hours]

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose / Inoculum
epoxy resin (MW ≤ 700)	OECD 301F	5% [28 days]	

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
epoxy resin (MW ≤ 700)	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
epoxy resin (MW ≤ 700)	3	31	Low
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
epoxy resin (MW ≤ 700)	2.6	445

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste :

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  (PAINT)
English (GB) Europe 12/15				

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 14: Transport information

14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(Epoxy resin (MW ≤ 700))	Not applicable.

Additional information

- ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- Tunnel code** : (-)
- ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV
None of the components are listed.

Substances of very high concern
None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR	3

Labelling : Not applicable.

Other EU regulations

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)
Not listed.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 15: Regulatory information

<u>Persistent Organic Pollutants</u>
Not listed.
<u>Seveso Directive</u>
This product is controlled under the Seveso Directive.
<u>Danger criteria</u>
Category
E2

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
PBT = Persistent, Bioaccumulative and Toxic
vPvB = Very Persistent and Very Bioaccumulative
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
IMDG = International Maritime Dangerous Goods
IATA = International Air Transport Association

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1

History

Date of issue/ Date of revision : 7 August 2026
Date of previous issue : 7 May 2025
Prepared by : EHS
Version : 2

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Code	: 000001180560	Date of issue/Date of revision	: 7 August 2026
HYDROCENTRIFUGON PEINTURE NF DURCISSEUR			

SECTION 16: Other information