

Date of issue

19 August 2026

Version 1.05

Section 1. Product and company identification

Product name : SIGMA SAILADVANCE RX BROWN
Product code : 000010023380
Other means of identification : 00373744; 30015292 ; 30088274
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against**Identified uses**

Coating. Paints. Painting-related materials.

Uses advised against

Not applicable.

Reason**Supplier's details:**

Supplier : PPG INDUSTRIES CHILE S.A.
Puerto Madero 9710, Of. 23
Pudahuel - Chile
Teléfono: +56 (2) 2571 0750
Fax: +56 (2) 2571 0752

Email address: : HazComLatam@ppg.com

Emergency telephone number : +56 (2) 2777 1994 (RITA CHILE)

Section 2. Hazards identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (oral) - Category 4
ACUTE TOXICITY (dermal) - Category 5
ACUTE TOXICITY (inhalation) - Category 4
SKIN IRRITATION - Category 2
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1B
AQUATIC HAZARD (ACUTE) - Category 1
AQUATIC HAZARD (LONG-TERM) - Category 1

Target organs : Contains material which causes damage to the following organs: brain, central nervous system (CNS).
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, eye, lens or cornea.

Section 2. Hazards identification

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 8.4%

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 21.3%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 32%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 12.8%

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Flammable liquid and vapor.
Harmful if swallowed or if inhaled.
May be harmful in contact with skin.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause cancer.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling.

Response

: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of identification : 00373744; 30015292 ; 30088274

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
dicopper oxide	20 - <30	1317-39-1
rosin	10 - <12.5	8050-09-7
zinc oxide	10 - <12.5	1314-13-2
4-methylpentan-2-one	7 - <10	108-10-1
Solvent naphtha (petroleum), light aromatic	7 - <10	64742-95-6
Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene	3 - <5	25154-85-2
1,2,4-trimethylbenzene	3 - <5	95-63-6
zineb (ISO)	3 - <5	12122-67-7
diiron trioxide	3 - <5	1309-37-1
xylene	1 - <2	1330-20-7
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	1 - <2	220926-97-6
copper oxide	0.5 - <1	1317-38-0
Oils, pine	0.5 - <1	8002-09-3
copper	0.5 - <1	7440-50-8
p-mentha-1,4(8)-diene	0.1 - <0.2	586-62-9
cumene	0.1 - <0.2	98-82-8
zinc sulphide	0.1 - <0.2	1314-98-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

Specific treatments : The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.

Section 4. First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Harmful if inhaled.

Skin contact : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
sulfur oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Section 6. Accidental release measures

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

dicopper oxide

Ministry of Health (Chile, 2/2018) [Cobre]

TWA 8 hours: 0.18 mg/m³. Form: Fume.

TWA 8 hours: 0.88 mg/m³ (expressed as Cu). Form: Dusts and Mists.

rosin

ACGIH TLV (United States, 1/2025) [resin acids]

Skin sensitizer , Inhalation sensitizer.

TWA 8 hours: 0.001 mg/m³ (as total Resin acids). Form: Inhalable fraction.

zinc oxide

Ministry of Health (Chile, 2/2018)

TWA 8 hours: 4.4 mg/m³. Form: Fume.

STEL 15 minutes: 10 mg/m³. Form: Fume.

4-methylpentan-2-one

Ministry of Health (Chile, 2/2018)

TWA 8 hours: 179 mg/m³.

TWA 8 hours: 44 ppm.

STEL 15 minutes: 75 ppm.

STEL 15 minutes: 307 mg/m³.

Solvent naphtha (petroleum), light aromatic
Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene
1,2,4-trimethylbenzene

Not regulated.

Not regulated.

ACGIH TLV (United States, 1/2025)

TWA 8 hours: 10 ppm.

Not regulated.

ACGIH TLV (United States, 1/2025)

TWA 8 hours: 5 mg/m³. Form: Respirable fraction.

zineb (ISO)
diiron trioxide

Ministry of Health (Chile, 2/2018) [Xileno]

TWA 8 hours: 380 mg/m³.

TWA 8 hours: 87 ppm.

STEL 15 minutes: 150 ppm.

STEL 15 minutes: 651 mg/m³.

12-hydroxyoctadecanoic acid, reaction products with
1,3-benzenedimethanamine and hexamethylenediamine

ACGIH TLV (United States)

TWA: 10 mg/m³. Form: Inhalable particle.

TWA: 3 mg/m³ (inhalable dust). Form: Respirable particle.

copper oxide

Ministry of Health (Chile, 2/2018) [Cobre]

TWA 8 hours: 0.18 mg/m³. Form: Fume.

TWA 8 hours: 0.88 mg/m³ (expressed as Cu). Form: Dusts and Mists.

copper

Ministry of Health (Chile, 2/2018) [Cobre]

TWA 8 hours: 0.18 mg/m³. Form: Fume.

TWA 8 hours: 0.88 mg/m³ (expressed as Cu). Form: Dusts and Mists.

p-mentha-1,4(8)-diene

Not regulated.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye protection** : Chemical splash goggles and face shield.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Brown.
- Odor** : Characteristic.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)

Section 9. Physical and chemical properties

Flash point : Closed cup: 31°C (87.8°F)

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive (flammable) limits : Not available.

Vapor pressure : Not available.

Vapor density : Not available.

Relative density : 1.66

Solubility(ies)		Media	Result
		cold water	Not soluble

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
copper oxide	LC50 Inhalation Dusts and mists	Rat	3.34 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	500 mg/kg	-
rosin	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	7600 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
4-methylpentan-2-one	LC50 Inhalation Vapor	Rat	11 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	2.08 g/kg	-
Solvent naphtha (petroleum), light aromatic	LD50 Dermal	Rabbit	3.48 g/kg	-
	LD50 Oral	Rat	8400 mg/kg	-
1,2,4-trimethylbenzene	LC50 Inhalation Vapor	Rat	18000 mg/m ³	4 hours
	LD50 Oral	Rat	5 g/kg	-
zineb (ISO)	LD50 Oral	Rat	>2000 mg/kg	-
diiron trioxide	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Oral	Rat	10 g/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	LC50 Inhalation Dusts and mists	Rat	3.56 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
copper oxide	LD50 Oral	Rat	>2000 mg/kg	-
Oils, pine	LD50 Dermal	Rabbit	5 g/kg	-
	LD50 Oral	Rat	2.1 g/kg	-
copper	LC50 Inhalation Dusts and mists	Rat	>5.11 mg/l	4 hours
p-mentha-1,4(8)-diene	LD50 Oral	Rat	4390 mg/kg	-
cumene	LC50 Inhalation Vapor	Rat	39000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	12.3 g/kg	-
	LD50 Oral	Rat	2260 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
zineb (ISO)	skin	Guinea pig	Sensitizing

Section 11. Toxicological information

Conclusion/Summary

Skin : zineb (ISO): Weakly positive.
Respiratory : There are no data available on the mixture itself.

Mutagenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
4-methylpentan-2-one	-	2B	-
zineb (ISO)	-	3	-
diiron trioxide	-	3	-
xylene	-	3	-
carbon black	-	2B	-
ethylbenzene	-	2B	-
cumene	-	2B	Reasonably anticipated to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
dicopper oxide	None.	None.	None.
rosin	None.	None.	None.
zinc oxide	None.	None.	None.
4-methylpentan-2-one	Category 3	-	Narcotic effects
Solvent naphtha (petroleum), light aromatic	Category 3	-	Narcotic effects
Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene	None.	None.	None.
1,2,4-trimethylbenzene	Category 3	-	Respiratory tract irritation
zineb (ISO)	Category 3	-	Respiratory tract irritation
diiron trioxide	None.	None.	None.
xylene	Category 3	-	Respiratory tract irritation

Section 11. Toxicological information

12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine copper oxide Oils, pine copper p-mentha-1,4(8)-diene cumene	None. None. None. None. None. Category 3	None. None. None. None. None. -	None. None. None. None. None. Respiratory tract irritation None.
zinc sulphide	None.	None.	None.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
dicopper oxide rosin zinc oxide 4-methylpentan-2-one Solvent naphtha (petroleum), light aromatic Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene 1,2,4-trimethylbenzene zineb (ISO) diiron trioxide xylene 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine copper oxide Oils, pine copper p-mentha-1,4(8)-diene cumene zinc sulphide	None. None. None. None. None. None. None. None. None. None. None. Category 2 None. None. None. None. None. Category 2 None.	None. None. None. None. None. None. None. None. None. None. None. inhalation None. None. None. None. None. - None.	None. None. None. None. None. None. None. None. None. None. lungs None. None. None. None. None. - None.

Target organs

- : Contains material which causes damage to the following organs: brain, central nervous system (CNS).
- Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, eye, lens or cornea.

Aspiration hazard

Name	Result
dicopper oxide rosin zinc oxide 4-methylpentan-2-one 4-methylpentan-2-one Solvent naphtha (petroleum), light aromatic Solvent naphtha (petroleum), light aromatic Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene 1,2,4-trimethylbenzene zineb (ISO) diiron trioxide xylene	None. None. None. ASPIRATION HAZARD - Category 2 None. ASPIRATION HAZARD - Category 1 None. None. None. None. None. None. ASPIRATION HAZARD - Category 1

Section 11. Toxicological information

xylene	None.
12-hydroxyoctadecanoic acid, reaction products with	None.
1,3-benzenedimethanamine and hexamethylenediamine	
copper oxide	None.
Oils, pine	ASPIRATION HAZARD - Category 1
Oils, pine	None.
copper	None.
p-mentha-1,4(8)-diene	ASPIRATION HAZARD - Category 1
p-mentha-1,4(8)-diene	None.
cumene	ASPIRATION HAZARD - Category 1
cumene	None.
zinc sulphide	None.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Harmful if inhaled.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 - pain
 - watering
 - redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
 - pain or irritation
 - redness
 - dryness
 - cracking
 - blistering may occur
- Ingestion** : Adverse symptoms may include the following:
 - stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. Carbon black is utilized as a raw material in many liquid coating formulations. In this case, the carbon black particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of carbon black when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Most carbon blacks contain trace quantities of polyaromatic hydrocarbons (PAH). PAHs are not expected to be released in biological fluids and are therefore not likely available for biological activity. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the

Section 11. Toxicological information

kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMA SAILADVANCE RX BROWN	1550.9	3276.1	Not available	57.6	3.7
dicopper oxide	500	2500	Not available	Not available	3.34
rosin	7600	2500	Not available	Not available	Not available
zinc oxide	Not available	2500	Not available	Not available	Not available
4-methylpentan-2-one	2080	Not available	Not available	11	1.5
Solvent naphtha (petroleum), light aromatic	8400	3480	Not available	Not available	Not available
Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene	Not available	Not available	Not available	Not available	Not available
1,2,4-trimethylbenzene	5000	Not available	Not available	18	1.5

Section 11. Toxicological information

zineb (ISO)	2500	Not available	Not available	Not available	Not available
diiron trioxide	10000	Not available	Not available	Not available	Not available
xylene	4300	1700	Not available	11	1.5
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	2500	2500	Not available	Not available	3.56
copper oxide	2500	Not available	Not available	Not available	Not available
Oils, pine	2100	5000	Not available	Not available	Not available
copper	Not available	Not available	Not available	Not available	Not available
p-mentha-1,4(8)-diene	4390	Not available	Not available	Not available	Not available
cumene	2260	12300	Not available	39	Not available
zinc sulphide	Not available	Not available	Not available	Not available	Not available

Other information : Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
dicopper oxide zinc oxide 4-methylpentan-2-one Solvent naphtha (petroleum), light aromatic diiron trioxide 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine copper	LC50 0.003 mg/l	Fish	96 hours
	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
	Acute LC50 >179 mg/l	Fish	96 hours
	Acute LC50 8.2 mg/l	Fish	96 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i> (microalgae)	72 hours
	Acute EC50 >100 mg/l	Daphnia - <i>Daphnia magna</i> (Water flea)	48 hours
	Acute LC50 >100 mg/l	Fish - <i>Oncorhynchus mykiss</i> (rainbow trout)	96 hours
	Chronic NOEC 100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Chronic NOEC ≥50 mg/l	Daphnia - <i>Daphnia magna</i> (Water flea)	21 days
	Acute LC50 810 ppb	Fish	96 hours
	Chronic EC10 8.1 µg/l	Daphnia - <i>Daphnia magna</i> - Neonate	21 days

Section 12. Ecological information

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
4-methylpentan-2-one 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	OECD 301F OECD Ready Biodegradability - Closed Bottle Test	83 % - Readily - 28 days 9 % - Not readily - 29 days	- -	- -
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability	
4-methylpentan-2-one xylene	- -	- -	Readily Readily	

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
copper oxide	None.	None.	None.
rosin	1.9 to 7.7	None.	High
zinc oxide	None.	None.	None.
4-methylpentan-2-one	1.9	None.	Low
Solvent naphtha (petroleum), light aromatic	None.	None.	None.
Propane, 1-(ethenyloxy)-2-methyl-, polymer with chloroethene	None.	None.	None.
1,2,4-trimethylbenzene	3.63	120.23	Low
zineb (ISO)	1.3	None.	Low
diiron trioxide	None.	None.	None.
xylene	3.12	7.4 to 18.5	Low
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	>6	None.	High
copper oxide	None.	None.	None.
Oils, pine	None.	None.	None.
copper	None.	None.	None.
p-mentha-1,4(8)-diene	4.47	None.	High
cumene	3.55	35.48	Low
zinc sulphide	None.	None.	None.

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3	3
Packing group	III	III	III	III
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(dicopper oxide)	Not applicable.

Additional information

UN : None identified.
Brazil : None identified.
Risk number : 30
IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Code	000010023380	Date of issue	19 August 2026	Version	1.05
Product name	SIGMA SAILADVANCE RX BROWN				

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

- : Decree N° 57 of 2021 – Approves the Regulation for the classification, labeling, and notification of hazardous chemical substances and mixtures.
- Supreme Decree N° 148 of 2004 – Approves the Sanitary Regulation on the Management of Hazardous Waste.
- Decree 40 – Amends Supreme Decree N° 298 of 1994 from the Transport and Telecommunications Ministry which "Regulates the Transportation of Dangerous Cargo on Streets and Roads".
- Supreme Decree N° 374 of 1997 – Establishes the maximum permissible limit of lead in paints that it indicates.
- NCh382:2021 – Dangerous Goods – Classification.

Section 16. Other information

History

Date of previous issue : 3/10/2026

Version : 1.05

EHS

Key to abbreviations

- : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- UN = United Nations

References

- : ABNT NBR 14725: 2023 (April 2025)
- ANTT - National Land Transportation Agency



Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.