

SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2023.

Date of issue/Date of revision 28 August 2026

Version 1

Section 1. Identification

Product name : SIGMARINE 48 GREEN 4171
Product code : 000010024382
Other means of identification : 00224097; 00445040 ; 00461214 ; 30014137 ; 445040 ; 224097
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/ mixture : Coating.
Uses advised against : Not applicable.

Supplier : PPG Canada Inc.
5676 Timberlea Blvd
Mississauga ON L4W 4M6
Canada
+1 905-629-7999

PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 888-977-4762

Section 2. Hazard identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1A
CARCINOGENICITY - Category 1B
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Health Hazards Not Otherwise Classified - Category 1

Section 2. Hazard identification

This product contains TiO₂ which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO₂ is utilized as a raw material in a liquid coating formulation. In this case, the TiO₂ particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO₂ when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
Prolonged or repeated contact may dry skin and cause irritation.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS,

Section 2. Hazard identification

STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

33.8% (oral), 44.2% (dermal), 81.6% (inhalation)

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: SIGMARINE 48 GREEN 4171
Other means of identification	: 00224097; 00445040 ; 00461214 ; 30014137 ; 445040 ; 224097

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
Naphtha (petroleum), hydrodesulfurized heavy	naphtha (petroleum), hydrodesulphurized heavy; Low boiling point hydrogen treated naphtha; Naphtha, petroleum, hydrodesulfurized heavy; naphtha (petroleum), hydrodesulfurized heavy, as light oils; low boiling point hydrogen treated naphtha, as light oils; Naphtha, (petroleum), heavy, hydrodesulfurized; ALIPHATIC HYDROCARBON; NAPHTHA (PETROLEUM), HYDROGENSULFURIZED HEAVY; OILS, NAPHTHA, HYDRODESULFURIZED HEAVY; Naphtha (petroleum), hydrodesulfurized heavy, Low boiling point hydrogen treated naphtha; Naphtha (petroleum), hydrodesulfurised heavy	10 - 30*	64742-82-1
Naphtha (petroleum), hydrotreated heavy	Low boiling point hydrogen treated naphtha; Hydrotreated heavy naphtha (petroleum); Hydrotreated light steam cracked naphtha residuum (petroleum); Naphtha, petroleum, hydrotreated heavy; Hydrotreated light, steam cracked naphtha residuum, petroleum; Hydrotreated heavy naphtha; Naphtha, (petroleum), heavy, hydrotreated; NAPHTHA	10 - 30*	64742-48-9
titanium dioxide	Titanium oxide; Titanium oxide (TiO ₂); CI 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide, other than those of heading 3206 11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206 11 00	3 - 7*	13463-67-7
calcium carbonate	Carbonic acid calcium salt (1:1); Carbonic acid, calcium salt (1:1); CI 77220; C.I. Pigment White 18; Sugar refinery carbonatation mud; Limestone; Marble; Whiting; pre-mix, consisting of oxytetracycline hydrochloride (INN) on a base of calcium carbonate; E 170; chalk;	1 - 5*	471-34-1

Section 3. Composition/information on ingredients

	C.I. 77220; aragonite; calcite; limestone; marble; carbonic acid salt (1:1); PIGMENT WHITE 18		
Talc , not containing asbestiform fibres	Talc; magnesium silicate monohydrate (talc) not containing asbestiform fibres	1 - 5*	14807-96-6
xylene	Benzene, dimethyl-; Xylol; Benzene, dimethyl-, mixed isomers; xylene, mixed isomers, pure; xylene, crude; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); Benzene, dimethyl-; Xylene (mixed); xylene (total); Xylenes; Dimethylbenzene	1 - 5*	1330-20-7
2-ethylhexanoic acid	Hexanoic acid, 2-ethyl-; Ethyl hexanoic acid; 2-ETHYLHEXANOIC ACID and its alkyl esters; 3-Heptanecarboxylic acid; 2-Ethylcaproic acid; 2-Ethyl hexoic acid; Alkanoic acid (C4-30); Butylethylacetic acid; 2-Butylbutanoic acid; ETHYL HEXANOIC ACID, 2-; 2-ETHYLHEXANOIC ACID (EHA)	0.5 - 1.5*	149-57-5
ethylbenzene	Benzene, ethyl-; Phenylethane; Ethylbenzol; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); EB; Mono-(or di-) methyl (ethyl,bromoallyl, bromopropylloxycarbonyl benzene	0.1 - 1*	100-41-4
2-ethylhexanoic acid, zirconium salt	Hexanoic acid, 2-ethyl-, zirconium salt (1:?) ; Hexanoic acid, 2-ethyl-, zirconium salt; Zirconium 2-ethylhexanoate; Aliphatic monocarboxylic acid (C6-28) salt (Pb, Cu, Mn, Zn, Zr, Ce, Cd, Sn, Sr, Co); Zirconium salt of 2-ethylhexanoic acid; 2-Ethylhexanoic acid zirconium salt; HEXANOATE, 2-ETHYL-, ZIRCONIUM; ZIRCONIUM OCTOATE; Zirconium 2-ethylhexanoate (component unspecified)	0.1 - 1*	22464-99-9
cobalt bis(2-ethylhexanoate)	Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1); Hexanoic acid, 2-ethyl-, cobalt(2+) salt; Cobalt octoate; Cobalt 2-ethylhexanoate; Aliphatic monocarboxylic acid (C6-28) salt	0.1 - 1*	136-52-7

Section 3. Composition/information on ingredients

calcium bis(2-ethylhexanoate)	(Pb, Cu, Mn, Zn, Zr, Ce, Cd, Sn, Sr, Co); Cobalt(II) 2-ethylhexanoate; 2-Ethylhexanoic acid cobalt(2+) salt; Cobaltous octoate; HEXANOATE, 2-ETHYL-, COBALT (II); HEXANOIC ACID, 2-ETHYL, COBALT(2+)SALT Hexanoic acid, 2-ethyl-, calcium salt (2:1); Hexanoic acid, 2-ethyl-, calcium salt; Calcium 2-ethylhexanoate; calcium 2-ethylhexoate; Hexanoic acid, 2-ethyl-, calcium salt; Aliphatic monocarboxylic acid (C6-28) light metal salt (Na,K,Li,Ba, Mg,Ca); 2-ETHYLHEXANOIC ACID CALCIUM SALT; HEXANOATE, ETHYL-, CALCIUM; HEXANOATE, 2-ETHYL-, CALCIUM; CALCIUM-2-ETHYLHEXOATE	0.1 - 1*	136-51-6
-------------------------------	--	----------	----------

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Section 4. First-aid measures

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Section 5. Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides
Formaldehyde.
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: Ingestion of product or cured coating may be harmful. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Wash hands thoroughly after handling.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Naphtha (petroleum), hydrodesulfurized heavy Naphtha (petroleum), hydrotreated heavy titanium dioxide	None. None. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 10 mg/m ³ . CA British Columbia Provincial (Canada, 8/2025) TWA 8 hours: 10 mg/m ³ . CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 10 mg/m ³ . CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 10 mg/m ³ . Form: total particulate matter. CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 20 mg/m ³ . TWA 8 hours: 10 mg/m ³ .
calcium carbonate	CA Alberta Provincial (Canada, 3/2023) [Calcium carbonate] OEL 8 hours: 10 mg/m ³ . CA Quebec Provincial (Canada, 2/2024) [Calcium carbonate] TWAEV 8 hours: 10 mg/m ³ . Form: total particulate matter.
Talc , not containing asbestiform fibres	CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 2 mg/m ³ . Form: respirable particulate. CA British Columbia Provincial (Canada, 8/2025) TWA 8 hours: 2 mg/m ³ . Form: respirable. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 2 mg/m ³ . Form: respirable aerosol fraction. CA Saskatchewan Provincial (Canada, 4/2021) TWA 8 hours: 2 mg/m ³ . Form: respirable fraction.
xylene	CA Alberta Provincial (Canada, 3/2023) [Dimethylbenzene] OEL 8 hours: 100 ppm. OEL 15 minutes: 651 mg/m ³ . OEL 15 minutes: 150 ppm. OEL 8 hours: 434 mg/m ³ . CA British Columbia Provincial (Canada, 8/2025) [xylene, all isomers] TWA 8 hours: 20 ppm. CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)] STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. CA Quebec Provincial (Canada, 2/2024) [Xylene] TWAEV 8 hours: 100 ppm. TWAEV 8 hours: 434 mg/m ³ .

Section 8. Exposure controls/personal protection

2-ethylhexanoic acid

STEV 15 minutes: 150 ppm.

STEV 15 minutes: 651 mg/m³.

CA Saskatchewan Provincial (Canada, 4/2021) [Xylene]

STEL 15 minutes: 150 ppm.

TWA 8 hours: 100 ppm.

CA Alberta Provincial (Canada, 3/2023)

OEL 8 hours: 5 mg/m³.

CA British Columbia Provincial (Canada, 8/2025)

TWA 8 hours: 5 mg/m³. Form: inhalable vapour and aerosol.

CA Ontario Provincial (Canada, 6/2019)

TWA 8 hours: 5 mg/m³. Form: inhalable fraction and vapour.

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 10 mg/m³. Form: inhalable fraction and vapour.

TWA 8 hours: 5 mg/m³. Form: inhalable fraction and vapour.

ethylbenzene

CA Alberta Provincial (Canada, 3/2023)

OEL 8 hours: 100 ppm.

OEL 8 hours: 434 mg/m³.

OEL 15 minutes: 543 mg/m³.

OEL 15 minutes: 125 ppm.

CA British Columbia Provincial (Canada, 8/2025)

TWA 8 hours: 20 ppm.

CA Ontario Provincial (Canada, 6/2019)

TWA 8 hours: 20 ppm.

CA Quebec Provincial (Canada, 2/2024)

TWAEV 8 hours: 20 ppm.

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 125 ppm.

TWA 8 hours: 100 ppm.

2-ethylhexanoic acid, zirconium salt

CA Alberta Provincial (Canada, 3/2023) [Zirconium and compounds]

OEL 8 hours: 5 mg/m³ (as Zr).

OEL 15 minutes: 10 mg/m³ (as Zr).

CA British Columbia Provincial (Canada, 8/2025) [zirconium and compounds]

TWA 8 hours: 5 mg/m³ (as Zr).

STEL 15 minutes: 10 mg/m³ (as Zr).

CA Ontario Provincial (Canada, 6/2019) [Zirconium and compounds]

STEL 15 minutes: 10 mg/m³ (as Zr).

TWA 8 hours: 5 mg/m³ (as Zr).

CA Quebec Provincial (Canada, 2/2024) [Zirconium and compounds]

TWAEV 8 hours: 5 mg/m³ (as Zr).

STEV 15 minutes: 10 mg/m³ (as Zr).

Section 8. Exposure controls/personal protection

cobalt bis(2-ethylhexanoate)	CA British Columbia Provincial (Canada, 8/2025) [cobalt and inorganic compounds] Skin sensitizer , Inhalation sensitizer. TWA 8 hours: 0.02 mg/m ³ (as Co). Form: inhalable. CA Ontario Provincial (Canada, 6/2019) [Cobalt and inorganic compounds] TWA 8 hours: 0.02 mg/m ³ (as Co). CA Quebec Provincial (Canada, 2/2024) [Cobalt elemental, and inorganic compounds] Skin sensitizer , Inhalation sensitizer. TWAEV 8 hours: 0.02 mg/m ³ (as Co). Form: inhalable aerosol fraction. CA Saskatchewan Provincial (Canada, 4/2021) [Cobalt and inorganic compounds] STEL 15 minutes: 0.06 mg/m ³ (measured as Co). TWA 8 hours: 0.02 mg/m ³ (measured as Co).
calcium bis(2-ethylhexanoate)	None.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Green.
- Odor** : Characteristic.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 46°C (114.8°F)
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Flammability** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1
- Density (lbs / gal)** : 8.35

Solubility(ies) :

Media	Result
cold water	Not soluble

- Partition coefficient: n-octanol/water** : Not applicable.

Section 9. Physical and chemical properties

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

% Solid. (w/w) : 78.431

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.
Refer to protective measures listed in sections 7 and 8.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose
Naphtha (petroleum), hydrodesulfurized heavy	Rat - Oral - LD50	>5000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Rabbit - Dermal - LD50	>2000 mg/kg
titanium dioxide	Rat - Oral - LD50	>6 g/kg
	Rabbit - Dermal - LD50	>5000 mg/kg
	Rat - Oral - LD50	>5000 mg/kg
	Rabbit - Dermal - LD50	>5000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>6.82 mg/l [4 hours]
calcium carbonate	Rat - Oral - LD50	6450 mg/kg
	Rat - Dermal - LD50	>5000 mg/kg
xylene	Rat - Oral - LD50	4.3 g/kg
	Rabbit - Dermal - LD50	1.7 g/kg
2-ethylhexanoic acid	Rat - Oral - LD50	3640 mg/kg
	Rat - Dermal - LD50	>2000 mg/kg
ethylbenzene	Rat - Oral - LD50	3.5 g/kg
	Rabbit - Dermal - LD50	17.8 g/kg
	Rat - Inhalation - LC50 Vapor	17.8 mg/l [4 hours]
2-ethylhexanoic acid, zirconium salt	Rabbit - Dermal - LD50	>5 g/kg
	Rat - Oral - LD50	>5 g/kg
cobalt bis(2-ethylhexanoate)	Rabbit - Dermal - LD50	>5 g/kg

Section 11. Toxicological information

Rat - Oral - LD50

3129 mg/kg

Product Conclusion : There are no data available on the mixture itself.

Skin corrosion/irritation

Product/ingredient name	Species	Dose	Score
xylene	Rabbit - Skin - Moderate irritant	Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours	-

Conclusion/Summary : There are no data available on the mixture itself.

Serious eye damage/eye irritation

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory corrosion/irritation

Conclusion/Summary : There are no data available on the mixture itself.

Sensitization

Skin

Conclusion/Summary : There are no data available on the mixture itself.

Respiratory

Conclusion/Summary : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
Talc , not containing asbestiform fibres	-	2A	-
xylene	-	3	-
ethylbenzene	-	2B	-
cobalt bis(2-ethylhexanoate)	-	2B	Reasonably anticipated to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Naphtha (petroleum), hydrotreated heavy	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Talc , not containing asbestiform fibres	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
xylene	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2

Target organs : Contains material which causes damage to the following organs: brain.
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, the reproductive system, liver, cardiovascular system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrotreated heavy xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. This product contains TiO₂ which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO₂ is utilized as a raw material in a liquid coating formulation. In this case, the TiO₂ particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO₂ when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Conclusion/Summary : There are no data available on the mixture itself.

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product code 000010024382

Date of issue 28 August 2026

Version 1

Product name SIGMARINE 48 GREEN 4171

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMARINE 48 GREEN 4171	86465.3	5701.5	N/A	120.8	16.5
Naphtha (petroleum), hydrodesulfurized heavy	N/A	2500	N/A	N/A	N/A
calcium carbonate	6450	N/A	N/A	N/A	N/A
xylene	4300	1700	N/A	11	1.5
2-ethylhexanoic acid	3640	2500	N/A	N/A	N/A
ethylbenzene	3500	17800	N/A	17.8	1.5
cobalt bis(2-ethylhexanoate)	3129	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species
titanium dioxide	Acute - LC50 - Fresh water >100 mg/l [48 hours]	Daphnia - <i>Daphnia magna</i>
calcium carbonate	Acute - EC10 OECD 201 >14 mg/l [72 hours]	Algae
ethylbenzene	Acute - EC50 - Fresh water 1.8 mg/l [48 hours] Chronic - NOEC - Fresh water 1 mg/l	Daphnia Daphnia - <i>Ceriodaphnia dubia</i>
2-ethylhexanoic acid, zirconium salt	Acute - LC50 >100 mg/l [96 hours]	Fish

Conclusion/Summary : Not available.

Persistence and degradability

Product/ingredient name	Result
ethylbenzene	79% [10 days] - Readily

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Naphtha (petroleum), hydrodesulfurized heavy	-	10 to 2500	High
xylene	3.12	7.4 to 18.5	Low
2-ethylhexanoic acid	2.7	-	Low
ethylbenzene	3.6	79.43	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3
Packing group	III	III	III
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

TDG : This product is not regulated as a dangerous good when packaged in a small means of containment (≤ 450 L) and transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage using TDGR 1.33 (Class 3, Flammable Liquids: General Exemption)

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Proof of classification statement : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

Section 15. Regulatory information

[National Inventory List](#)

Canada inventory (DSL) : At least one component is not listed in DSL but all such components are listed in NDSL.

Section 16. Other information

Please refer to Section 2 of this document for GHS hazard classifications.

The customer is responsible for determining the PPE code for this material.

Date of issue/Date of revision 28 August 2026

Organization that prepared the SDS : EHS

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- N/A = Not available
- SGG = Segregation Group
- UN = United Nations

Indicates information that has changed from previously issued version.

[Disclaimer](#)

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.