

# SAFETY DATA SHEET

Date of issue/Date of revision

: 21 September 2026

Version

: 1.02



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMARINE ONE 648 GREEN 4199

**Product code** : 000010026272

**Other means of identification**

30014060; 30014738 ; 30015570 ; 30088087 ; 30088156 ; 30088189 ; 30098663

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person  
responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

**Supplier**

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 3, H336

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 2: Hazards identification

2.2 Label elements

|                                                                                                                                    |   |                                                                                                                                                                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard pictograms                                                                                                                  | : |                                                                                                                                                                         |
| Signal word                                                                                                                        | : | Danger                                                                                                                                                                                                                                                   |
| Hazard statements                                                                                                                  | : | Flammable liquid and vapour.<br>Causes skin irritation.<br>Causes serious eye irritation.<br>May cause drowsiness or dizziness.<br>Causes damage to organs through prolonged or repeated exposure.<br>Harmful to aquatic life with long lasting effects. |
| Prevention                                                                                                                         | : | Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour.                                                                               |
| Response                                                                                                                           | : | Get medical advice/attention if you feel unwell.                                                                                                                                                                                                         |
| Storage                                                                                                                            | : | Store in a well-ventilated place. Keep container tightly closed.                                                                                                                                                                                         |
| Disposal                                                                                                                           | : | Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P280, P210, P260, P314, P403 + P233, P501                                                                                           |
| Hazardous ingredients                                                                                                              | : | stoddard solvent Nota(s) P; naphtha (petroleum), hydrodesulphurized heavy Note P and Solvent naphtha (petroleum), light arom. Nota(s) P                                                                                                                  |
| Supplemental label elements                                                                                                        | : | Contains Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May produce an allergic reaction.                                                                                                                                       |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable.                                                                                                                                                                                                                                          |
| Special packaging requirements                                                                                                     |   |                                                                                                                                                                                                                                                          |
| Containers to be fitted with child-resistant fastenings                                                                            | : | Not applicable.                                                                                                                                                                                                                                          |
| Tactile warning of danger                                                                                                          | : | Not applicable.                                                                                                                                                                                                                                          |

2.3 Other hazards

|                                                                                                            |   |                                                                                       |
|------------------------------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII          | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. | : | Based on available data, the classification criteria are not met.                     |

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 2: Hazards identification

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name                                                | Identifiers                                                                             | % by weight | Classification                                                                                                                                                                 | Specific Conc. Limits, M-factors and ATEs                         | Type    |
|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------|
| stoddard solvent Nota(s) P                                             | REACH #:<br>01-2120261965-45<br>EC: 232-489-3<br>CAS: 8052-41-3<br>Index: 649-345-00-4  | ≥10 - ≤25   | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT RE 1, H372<br>(central nervous system (CNS)) (inhalation)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412                    | -                                                                 | [1] [2] |
| naphtha (petroleum), hydrodesulphurized heavy Note P                   | EC: 265-185-4<br>CAS: 64742-82-1<br>Index: 649-330-00-2                                 | ≥10 - ≤14   | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>STOT RE 1, H372<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411                                                | -                                                                 | [1]     |
| Solvent naphtha (petroleum), light arom. Nota(s) P                     | REACH #:<br>01-2119486773-24<br>EC: 265-199-0<br>CAS: 64742-95-6<br>Index: 649-356-00-4 | ≥5.0 - ≤10  | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411                                                                   | -                                                                 | [1]     |
| butan-1-ol                                                             | REACH #:<br>01-2119484630-38<br>EC: 200-751-6<br>CAS: 71-36-3<br>Index: 603-004-00-6    | ≥1.0 - <3.0 | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336                                                      | ATE [Oral] = 790 mg/kg                                            | [1] [2] |
| xylene                                                                 | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9  | ≥1.0 - ≤5.0 | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 | ATE [Dermal] = 1700 mg/kg<br>ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | REACH #:<br>01-2119979085-27<br>EC: 309-629-8<br>CAS: 100545-48-0                       | ≤0.30       | Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412<br><br>See Section 16 for the full text of the H statements declared above.                                                     | -                                                                 | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 3: Composition/information on ingredients

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

|                            |                                                                                                                                                                                                                                                                                                                |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact                | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.                                                                                                                                                      |
| Inhalation                 | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.                                                                                                               |
| Skin contact               | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.                                                                                                                                                           |
| Ingestion                  | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.                                                                                                                                                                         |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

|              |                                                                                         |
|--------------|-----------------------------------------------------------------------------------------|
| Eye contact  | : Causes serious eye irritation.                                                        |
| Inhalation   | : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. |
| Skin contact | : Causes skin irritation. Defatting to the skin.                                        |
| Ingestion    | : Can cause central nervous system (CNS) depression.                                    |

Over-exposure signs/symptoms

|              |                                                                                                                                               |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness                                                    |
| Inhalation   | : Adverse symptoms may include the following:<br>nausea or vomiting<br>headache<br>drowsiness/fatigue<br>dizziness/vertigo<br>unconsciousness |
| Skin contact | : Adverse symptoms may include the following:<br>irritation<br>redness<br>dryness<br>cracking                                                 |
| Ingestion    | : No specific data.                                                                                                                           |

4.3 Indication of any immediate medical attention and special treatment needed

|                                     |                                                           |
|-------------------------------------|-----------------------------------------------------------|
| <b>Code</b> : 000010026272          | <b>Date of issue/Date of revision</b> : 21 September 2026 |
| <b>SIGMARINE ONE 648 GREEN 4199</b> |                                                           |

## SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 6: Accidental release measures

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Small spill                     | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.                                                                                                                                                                                                                                                                                 |
| Large spill                     | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information.<br>See Section 8 for information on appropriate personal protective equipment.<br>See Section 13 for additional waste treatment information.                                                                                                                                                                                                                                                                                                                                                                                                                                      |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective measures                    | : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.<br><br>Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name    | Exposure limit values                                                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| stoddard solvent Nota(s) P | ACGIH TLV (United States, 1/2026)<br>TWA 8 hours: 100 ppm.<br>TWA 8 hours: 525 mg/m³.                                                                                                 |
| butan-1-ol                 | ACGIH TLV (United States, 1/2026)<br>TWA 8 hours: 20 ppm.                                                                                                                             |
| xylene                     | EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin.<br>TWA 8 hours: 50 ppm.<br>TWA 8 hours: 221 mg/m³.<br>STEL 15 minutes: 100 ppm.<br>STEL 15 minutes: 442 mg/m³. |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name                              | Exposure                                                     | Value              |
|------------------------------------------------------|--------------------------------------------------------------|--------------------|
| stoddard solvent Nota (s) P                          | DNEL - General population - Long term - Dermal Local         | 3.78 mg/cm²        |
|                                                      | DNEL - Workers - Long term - Dermal Local                    | 7.56 mg/cm²        |
|                                                      | DNEL - General population - Long term - Oral Systemic        | 10.56 mg/kg bw/day |
|                                                      | DNEL - General population - Long term - Inhalation Local     | 22 mg/m³           |
|                                                      | DNEL - General population - Long term - Inhalation Systemic  | 22 mg/m³           |
|                                                      | DNEL - Workers - Short term - Dermal Systemic                | 30 mg/kg bw/day    |
|                                                      | DNEL - General population - Long term - Dermal Systemic      | 40 mg/kg bw/day    |
|                                                      | DNEL - Workers - Long term - Inhalation Local                | 44 mg/m³           |
|                                                      | DNEL - Workers - Long term - Inhalation Systemic             | 44 mg/m³           |
|                                                      | DNEL - General population - Short term - Oral Systemic       | 50 mg/kg bw/day    |
|                                                      | DNEL - General population - Short term - Inhalation Local    | 55 mg/m³           |
|                                                      | DNEL - General population - Short term - Inhalation Systemic | 55 mg/m³           |
|                                                      | DNEL - Workers - Short term - Inhalation Local               | 55 mg/m³           |
|                                                      | DNEL - Workers - Short term - Inhalation Systemic            | 55 mg/m³           |
|                                                      | DNEL - General population - Short term - Dermal Systemic     | 60 mg/kg bw/day    |
|                                                      | DNEL - Workers - Long term - Dermal Systemic                 | 80 mg/kg bw/day    |
|                                                      | DNEL - Workers - Long term - Inhalation Systemic             | 1286 mg/m³         |
| naphtha (petroleum), hydrodesulphurized heavy Note P |                                                              |                    |

Code : 000010026272 Date of issue/Date of revision : 21 September 2026  
SIGMARINE ONE 648 GREEN 4199

## SECTION 8: Exposure controls/personal protection

|                                                    |                                                     |          |                           |
|----------------------------------------------------|-----------------------------------------------------|----------|---------------------------|
| Solvent naphtha (petroleum), light arom. Nota(s) P | DNEL - General population - Long term - Inhalation  | Systemic | 0.41 mg/m <sup>3</sup>    |
|                                                    | DNEL - Workers - Long term - Inhalation             | Systemic | 1.9 mg/m <sup>3</sup>     |
|                                                    | DNEL - General population - Long term - Inhalation  | Local    | 178.57 mg/m <sup>3</sup>  |
|                                                    | DNEL - General population - Short term - Inhalation | Local    | 640 mg/m <sup>3</sup>     |
|                                                    | DNEL - Workers - Long term - Inhalation             | Local    | 837.5 mg/m <sup>3</sup>   |
|                                                    | DNEL - Workers - Short term - Inhalation            | Local    | 1066.67 mg/m <sup>3</sup> |
|                                                    | DNEL - General population - Short term - Inhalation | Systemic | 570 mg/m <sup>3</sup>     |
|                                                    | DNEL - Workers - Short term - Inhalation            | Systemic | 570 mg/m <sup>3</sup>     |
|                                                    | DNEL - General population - Long term - Dermal      | Systemic | 12 mg/kg bw/day           |
|                                                    | DNEL - General population - Long term - Oral        | Systemic | 21 mg/kg bw/day           |
|                                                    | DNEL - Workers - Long term - Dermal                 | Systemic | 21 mg/kg bw/day           |
|                                                    | DNEL - Workers - Long term - Inhalation             | Systemic | 150 mg/m <sup>3</sup>     |
|                                                    | DNEL - Workers - Long term - Dermal                 | Systemic | 25 mg/kg bw/day           |
|                                                    | DNEL - General population - Long term - Inhalation  | Systemic | 32 mg/m <sup>3</sup>      |
|                                                    | DNEL - General population - Long term - Dermal      | Systemic | 11 mg/kg bw/day           |
|                                                    | DNEL - General population - Long term - Oral        | Systemic | 11 mg/kg bw/day           |
|                                                    | DNEL - General population - Long term - Inhalation  | Systemic | 0.41 mg/m <sup>3</sup>    |
|                                                    | DNEL - Workers - Long term - Inhalation             | Systemic | 1.9 mg/m <sup>3</sup>     |
|                                                    | DNEL - General population - Long term - Inhalation  | Local    | 178.57 mg/m <sup>3</sup>  |
|                                                    | DNEL - General population - Short term - Inhalation | Local    | 640 mg/m <sup>3</sup>     |
| butan-1-ol                                         | DNEL - Workers - Long term - Inhalation             | Local    | 837.5 mg/m <sup>3</sup>   |
|                                                    | DNEL - Workers - Short term - Inhalation            | Local    | 1066.67 mg/m <sup>3</sup> |
|                                                    | DNEL - General population - Short term - Inhalation | Systemic | 1152 mg/m <sup>3</sup>    |
|                                                    | DNEL - Workers - Short term - Inhalation            | Systemic | 1286.4 mg/m <sup>3</sup>  |
|                                                    | DNEL - General population - Long term - Oral        | Systemic | 1.5625 mg/kg bw/day       |
|                                                    | DNEL - General population - Long term - Dermal      | Systemic | 3.125 mg/kg bw/day        |
|                                                    | DNEL - General population - Long term - Inhalation  | Systemic | 55.357 mg/m <sup>3</sup>  |
|                                                    | DNEL - General population - Long term - Inhalation  | Local    | 155 mg/m <sup>3</sup>     |
| xylene                                             | DNEL - Workers - Long term - Inhalation             | Local    | 310 mg/m <sup>3</sup>     |
|                                                    | DNEL - General population - Long term - Oral        | Systemic | 5 mg/kg bw/day            |
|                                                    | DNEL - General population - Long term - Inhalation  | Local    | 65.3 mg/m <sup>3</sup>    |
|                                                    | DNEL - General population - Long term - Inhalation  | Systemic | 65.3 mg/m <sup>3</sup>    |
|                                                    | DNEL - General population - Long term - Dermal      | Systemic | 125 mg/kg bw/day          |
|                                                    | DNEL - Workers - Long term - Dermal                 | Systemic | 212 mg/kg bw/day          |
|                                                    | DNEL - Workers - Long term - Inhalation             | Local    | 221 mg/m <sup>3</sup>     |
|                                                    | DNEL - Workers - Long term - Inhalation             | Systemic | 221 mg/m <sup>3</sup>     |
|                                                    | DNEL - General population - Short term - Inhalation | Local    | 260 mg/m <sup>3</sup>     |
|                                                    | DNEL - General population - Short term - Inhalation | Systemic | 260 mg/m <sup>3</sup>     |
|                                                    | DNEL - Workers - Short term - Inhalation            | Local    | 442 mg/m <sup>3</sup>     |
|                                                    | DNEL - Workers - Short term - Inhalation            | Systemic | 442 mg/m <sup>3</sup>     |
| Octadecanoic acid,                                 | DNEL - General population - Long term -             | Local    | 0.055 mg/m <sup>3</sup>   |

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 8: Exposure controls/personal protection

|                                                     |                                         |                   |
|-----------------------------------------------------|-----------------------------------------|-------------------|
| 12-hydroxy-, reaction products with ethylenediamine | Inhalation                              |                   |
|                                                     | DNEL - Workers - Long term - Inhalation | Local 0.308 mg/m³ |

PNECs

| Product/ingredient name | Compartment Detail - Method | Value           |
|-------------------------|-----------------------------|-----------------|
| butan-1-ol              | Fresh water                 | 0.082 mg/l      |
|                         | Marine water                | 0.0082 mg/l     |
|                         | Fresh water sediment        | 0.178 mg/kg     |
|                         | Marine water sediment       | 0.0178 mg/kg    |
|                         | Soil                        | 0.015 mg/kg     |
| xylene                  | Sewage Treatment Plant      | 2476 mg/l       |
|                         | Fresh water                 | 0.327 mg/l      |
|                         | Marine water                | 0.327 mg/l      |
|                         | Sewage Treatment Plant      | 6.58 mg/l       |
|                         | Fresh water sediment        | 12.46 mg/kg dwt |
|                         | Marine water sediment       | 12.46 mg/kg dwt |
|                         | Soil                        | 2.31 mg/kg      |

8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:
- Recommended: butyl rubber, neoprene, polyvinyl alcohol (PVA), Viton®  
May be used: nitrile rubber

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 8: Exposure controls/personal protection

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Body protection                 | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.           |
| Other skin protection           | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.                                                                                                                                                                                                                                                                                                                            |
| Respiratory protection          | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3 |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.                                                                                                                                                                                                                       |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Colour

Odour

Melting point/freezing point

Boiling point or initial boiling point and boiling range

Flammability

Lower and upper explosion limit

Flash point

Auto-ignition temperature

Decomposition temperature

pH

Viscosity

Solubility

: Liquid.

: Various

: Characteristic.

: Not determined.

: >37.78°C

: Not determined. There are no data available on the mixture itself.

: Not available.

: Closed cup: 39°C

:

: Stable under recommended storage and handling conditions (see Section 7).

: Not applicable. insoluble in water.

: Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C): >21 mm²/s

:

| Ingredient name            | °C         | °F         | Method |
|----------------------------|------------|------------|--------|
| stoddard solvent Nota(s) P | 230 to 240 | 446 to 464 |        |

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 9: Physical and chemical properties

Partition coefficient n-octanol/ water (log Pow) : Not applicable.

Vapour pressure : 

| Ingredient name | Vapour Pressure at 20°C |     |                | Vapour pressure at 50°C |     |        |
|-----------------|-------------------------|-----|----------------|-------------------------|-----|--------|
|                 | mm Hg                   | kPa | Method         | mm Hg                   | kPa | Method |
| butan-1-ol      | <7.50064                | <1  | DIN EN 13016-2 |                         |     |        |

Relative density : 0.99

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

No additional information.

SECTION 10: Stability and reactivity

|                                         |                                                                                                                                               |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.                                                  |
| 10.2 Chemical stability                 | : The product is stable.                                                                                                                      |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                                                             |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions:<br>oxidising agents, strong alkalis, strong acids.           |
| 10.6 Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials:<br>carbon oxides metal oxide/oxides                    |

SECTION 11: Toxicological information

|                                                                                                                                                                                                                                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008                                                                                                                                                                                                                                                             |
| The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.<br>Causes serious eye irritation.<br>Causes skin irritation.<br>May cause drowsiness or dizziness.<br>Causes damage to organs through prolonged or repeated exposure. |
| <u>Acute toxicity</u>                                                                                                                                                                                                                                                                                                                     |

Code : 000010026272 Date of issue/Date of revision : 21 September 2026  
SIGMARINE ONE 648 GREEN 4199

## SECTION 11: Toxicological information

| Product/ingredient name                                                | Result                                                                                                                                                                                      | Dose / Exposure                                                          |
|------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| naphtha (petroleum), hydrodesulphurized heavy Note P                   | Rat - Oral - LD50                                                                                                                                                                           | >5000 mg/kg                                                              |
| Solvent naphtha (petroleum), light arom. Nota(s) P                     | Rabbit - Dermal - LD50<br>Rat - Oral - LD50<br><u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Lung, Thorax, or Respiration - Other changes | >2000 mg/kg<br>8400 mg/kg                                                |
| butan-1-ol                                                             | Rabbit - Dermal - LD50<br>Rabbit - Dermal - LD50<br><u>Toxic effects</u> : Eye - Corneal damage Cardiac - Pulse rate Lung, Thorax, or Respiration - Dyspnea                                 | 3.48 g/kg<br>3400 mg/kg                                                  |
| xylene                                                                 | Rat - Oral - LD50<br><u>Toxic effects</u> : Liver - Fatty liver degeneration Kidney, Ureter, and Bladder - Other changes Blood - Other changes                                              | 790 mg/kg                                                                |
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | Rat - Inhalation - LC50 Vapour<br>Rat - Oral - LD50<br>Rabbit - Dermal - LD50<br>Rat - Oral - LD50                                                                                          | 24000 mg/m <sup>3</sup> [4 hours]<br>4.3 g/kg<br>1.7 g/kg<br>>2000 mg/kg |
|                                                                        | Rat - Inhalation - LC50 Dusts and mists                                                                                                                                                     | 5.05 mg/l [4 hours]                                                      |

### Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Oral                 | 40017.26 mg/kg |
| Dermal               | 163120.9 mg/kg |
| Inhalation (vapours) | 1055.49 mg/l   |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Irritation/Corrosion

| Product/ingredient name | Result                                                                                                                |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------|
| butan-1-ol              | Rabbit - Eyes - Cornea opacity<br>Irritation score: 4                                                                 |
| xylene                  | Rabbit - Skin - Moderate irritant<br>Amount/concentration applied: 500 mg<br>Duration of treatment/exposure: 24 hours |

### Conclusion/Summary

**Skin** : Causes skin irritation.

**Eyes** : Causes serious eye irritation.

**Respiratory** : Based on available data, the classification criteria are not met.

### Respiratory or skin sensitization

| Product/ingredient name                                                | Test              | Result      |
|------------------------------------------------------------------------|-------------------|-------------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | Guinea pig - skin | Sensitising |

### Conclusion/Summary

**Skin** : Based on available data, the classification criteria are not met.

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 11: Toxicological information

**Respiratory** : Based on available data, the classification criteria are not met.

**Mutagenicity**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**Specific target organ toxicity (single exposure)**

| Product/ingredient name                              | Category   | Route of exposure | Target organs                |
|------------------------------------------------------|------------|-------------------|------------------------------|
| naphtha (petroleum), hydrodesulphurized heavy Note P | Category 3 | -                 | Narcotic effects             |
| Solvent naphtha (petroleum), light arom. Nota(s) P   | Category 3 | -                 | Narcotic effects             |
| butan-1-ol                                           | Category 3 | -                 | Respiratory tract irritation |
| -                                                    | Category 3 | -                 | Narcotic effects             |
| xylene                                               | Category 3 | -                 | Respiratory tract irritation |

**Conclusion/Summary** :

May cause drowsiness or dizziness.

**Specific target organ toxicity (repeated exposure)**

| Product/ingredient name                              | Category   | Route of exposure | Target organs                |
|------------------------------------------------------|------------|-------------------|------------------------------|
| stoddard solvent Nota(s) P                           | Category 1 | inhalation        | central nervous system (CNS) |
| naphtha (petroleum), hydrodesulphurized heavy Note P | Category 1 | -                 | -                            |

**Conclusion/Summary** :

Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

| Product/ingredient name                              | Result                         |
|------------------------------------------------------|--------------------------------|
| stoddard solvent Nota(s) P                           | ASPIRATION HAZARD - Category 1 |
| naphtha (petroleum), hydrodesulphurized heavy Note P | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), light arom. Nota(s) P   | ASPIRATION HAZARD - Category 1 |
| xylene                                               | ASPIRATION HAZARD - Category 1 |

**Conclusion/Summary** :

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure** : Not available.

**Potential acute health effects**

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Ingestion** : Can cause central nervous system (CNS) depression.

**Skin contact** : Causes skin irritation. Defatting to the skin.

**Eye contact** : Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 11: Toxicological information

- Inhalation : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Ingestion : No specific data.
- Skin contact : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Eye contact : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects : No known significant effects or critical hazards.
- Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects : No known significant effects or critical hazards.
- Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

- General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity : No known significant effects or critical hazards.
- Mutagenicity : No known significant effects or critical hazards.
- Reproductive toxicity : No known significant effects or critical hazards.
- Other information : Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

Code : 000010026272 Date of issue/Date of revision : 21 September 2026  
SIGMARINE ONE 648 GREEN 4199

## SECTION 12: Ecological information

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

### 12.1 Toxicity

| Product/ingredient name                                                | Result       | Species                                        | Dose / Exposure      |
|------------------------------------------------------------------------|--------------|------------------------------------------------|----------------------|
| Solvent naphtha (petroleum), light arom. Nota(s) P                     | Acute - LC50 | Fish                                           | 8.2 mg/l [96 hours]  |
| butan-1-ol                                                             | Acute - LC50 | Fish                                           | 1376 mg/l [96 hours] |
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | Acute - LC50 | Fish - <i>Oncorhynchus mykiss</i>              | >10 mg/l [96 hours]  |
|                                                                        | Acute - EC50 | Daphnia - <i>Daphnia magna</i>                 | >10 mg/l [48 hours]  |
|                                                                        | Acute - EC50 | Algae - <i>Pseudokirchneriella subcapitata</i> | >100 mg/l [72 hours] |

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

| Product/ingredient name                                                | Test                                        | Result        | Dose / Inoculum |
|------------------------------------------------------------------------|---------------------------------------------|---------------|-----------------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | Ready Biodegradability - Closed Bottle Test | 22% [28 days] |                 |

| Product/ingredient name                                                | Aquatic half-life | Photolysis | Biodegradability |
|------------------------------------------------------------------------|-------------------|------------|------------------|
| xylene                                                                 | -                 | -          | Readily          |
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | -                 | -          | Inherent         |

### 12.3 Bioaccumulative potential

| Product/ingredient name                                                | LogP <sub>ow</sub> | BCF         | Potential |
|------------------------------------------------------------------------|--------------------|-------------|-----------|
| stoddard solvent Nota(s) P                                             | 3.16 to 7.06       | -           | High      |
| naphtha (petroleum), hydrodesulphurized heavy                          | -                  | 10 to 2500  | High      |
| Note P                                                                 |                    |             |           |
| butan-1-ol                                                             | 1                  | -           | Low       |
| xylene                                                                 | 3.12               | 7.4 to 18.5 | Low       |
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | >5.86              | -           | High      |

### 12.4 Mobility in soil

#### Soil/water partition coefficient

| Product/ingredient name | logK <sub>oc</sub> | K <sub>oc</sub> |
|-------------------------|--------------------|-----------------|
| butan-1-ol              | 0.51               | 3.22078         |

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

|                                 | ADR/RID | ADN    | IMDG   | IATA   |
|---------------------------------|---------|--------|--------|--------|
| 14.1 UN number or ID number     | UN1263  | UN1263 | UN1263 | UN1263 |
| 14.2 UN proper shipping name    | PAINT   | PAINT  | PAINT  | PAINT  |
| 14.3 Transport hazard class(es) | 3       | 3      | 3      | 3      |
| 14.4 Packing group              | III     | III    | III    | III    |
|                                 |         |        |        |        |

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 14: Transport information

|                                                              |                            |                             |                            |                            |
|--------------------------------------------------------------|----------------------------|-----------------------------|----------------------------|----------------------------|
| 14.5<br>Environmental hazards<br>Marine pollutant substances | No.<br><br>Not applicable. | Yes.<br><br>Not applicable. | No.<br><br>Not applicable. | No.<br><br>Not applicable. |
|--------------------------------------------------------------|----------------------------|-----------------------------|----------------------------|----------------------------|

Additional information

|             |                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------|
| ADR/RID     | : None identified.                                                                                          |
| Tunnel code | : (D/E)                                                                                                     |
| ADN         | : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. |
| IMDG        | : None identified.                                                                                          |
| IATA        | : None identified.                                                                                          |

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)  
None of the components are listed.  
[Substances of very high concern](#)  
None of the components are listed.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

|                              |                        |
|------------------------------|------------------------|
| Product/ingredient name      | Entry Number ( REACH ) |
| SIGMARINE ONE 648 GREEN 4199 | 3                      |

Labelling : Not applicable.

[Other EU regulations](#)

Explosive precursors : Not applicable.  
[Ozone depleting substances \(EU 2024/590\)](#)

Not listed.

[Persistent Organic Pollutants](#)

Not listed.

[Seveso Directive](#)

This product is controlled under the Seveso Directive.

[Danger criteria](#)

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 15: Regulatory information

|          |  |
|----------|--|
| Category |  |
| P5c      |  |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
PBT = Persistent, Bioaccumulative and Toxic  
vPvB = Very Persistent and Very Bioaccumulative  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
IMDG = International Maritime Dangerous Goods  
IATA = International Air Transport Association

Full text of abbreviated H statements

|      |                                                                 |
|------|-----------------------------------------------------------------|
| H225 | Highly flammable liquid and vapour.                             |
| H226 | Flammable liquid and vapour.                                    |
| H302 | Harmful if swallowed.                                           |
| H304 | May be fatal if swallowed and enters airways.                   |
| H312 | Harmful in contact with skin.                                   |
| H315 | Causes skin irritation.                                         |
| H317 | May cause an allergic skin reaction.                            |
| H318 | Causes serious eye damage.                                      |
| H319 | Causes serious eye irritation.                                  |
| H332 | Harmful if inhaled.                                             |
| H335 | May cause respiratory irritation.                               |
| H336 | May cause drowsiness or dizziness.                              |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects.                |
| H412 | Harmful to aquatic life with long lasting effects.              |

Full text of classifications [CLP/GHS]

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1B     | SKIN SENSITISATION - Category 1B                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

|                              |                |                                |                     |
|------------------------------|----------------|--------------------------------|---------------------|
| Code                         | : 000010026272 | Date of issue/Date of revision | : 21 September 2026 |
| SIGMARINE ONE 648 GREEN 4199 |                |                                |                     |

SECTION 16: Other information

History

|                                 |                     |
|---------------------------------|---------------------|
| Date of issue/ Date of revision | : 21 September 2026 |
| Date of previous issue          | : 14 September 2026 |
| Prepared by                     | : EHS               |
| Version                         | : 1.02              |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.