

SAFETY DATA SHEET



Date of issue/Date of revision

: 23 September 2026

Version

: 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMARINE 48 YELLOW 3138

Product code : 00333367

Product type : Liquid.

Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Carc. 1B, H350

Repr. 1B, H360D

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Code : 00333367 **Date of issue/Date of revision** : 23 September 2026
SIGMARINE 48 YELLOW 3138

SECTION 3: Composition/information on ingredients

2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 Index: 607-230-00-6	≥1.0 - ≤5.0	EUH066 Repr. 1B, H360D	[1] [2]
butanone oxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	≤0.30	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 1, H370 (upper respiratory tract) STOT SE 3, H336 STOT RE 2, H373 (blood system) See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : ☒ No known significant effects or critical hazards.
- Inhalation** : ☒ No known significant effects or critical hazards.
- Skin contact** : ☒ Causes skin irritation. Defatting to the skin.
- Ingestion** : ☒ No known significant effects or critical hazards.

Over-exposure signs/symptoms

Code : 00333367	Date of issue/Date of revision : 23 September 2026
SIGMARINE 48 YELLOW 3138	

SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : ☒ Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : ☒ Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : ☒ Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

Code : 00333367	Date of issue/Date of revision : 23 September 2026
SIGMARINE 48 YELLOW 3138	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour. Put on appropriate personal protective equipment. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Code : 00333367	Date of issue/Date of revision : 23 September 2026
SIGMARINE 48 YELLOW 3138	

SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
---	---

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-ethylhexanoic acid, zirconium salt	EH40/2005 WELs (United Kingdom (UK), 1/2020) [zirconium compounds] STEL 15 minutes: 10 mg/m³ (as Zr). TWA 8 hours: 5 mg/m³ (as Zr).

No exposure indices known.

Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
--	---

DNELs/DMELs

Stoddard solvent Nota (s) P	DNEL - General population - Long term - Dermal	Local	3.78 mg/cm²
	DNEL - Workers - Long term - Dermal	Local	7.56 mg/cm²
	DNEL - General population - Long term - Oral	Systemic	10.56 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Local	22 mg/m³
	DNEL - General population - Long term - Inhalation	Systemic	22 mg/m³
	DNEL - Workers - Short term - Dermal	Systemic	30 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic	40 mg/kg bw/day
	DNEL - Workers - Long term - Inhalation	Local	44 mg/m³
	DNEL - Workers - Long term - Inhalation	Systemic	44 mg/m³
	DNEL - General population - Short term - Oral	Systemic	50 mg/kg bw/day
	DNEL - General population - Short term - Inhalation	Local	55 mg/m³

Code : 00333367 **Date of issue/Date of revision** : 23 September 2026
SIGMARINE 48 YELLOW 3138

SECTION 8: Exposure controls/personal protection

2-ethylhexanoic acid, zirconium salt	DNEL - General population - Short term - Inhalation	Systemic	55 mg/m ³
	DNEL - Workers - Short term - Inhalation	Local	55 mg/m ³
	DNEL - Workers - Short term - Inhalation	Systemic	55 mg/m ³
	DNEL - General population - Short term - Dermal	Systemic	60 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	80 mg/kg bw/day
	DNEL - General population - Long term - Inhalation	Systemic	0.58 mg/m ³
	DNEL - Workers - Long term - Inhalation	Systemic	2.351 mg/m ³
	DNEL - General population - Long term - Oral	Systemic	0.167 mg/kg bw/day
	DNEL - General population - Long term - Dermal	Systemic	0.167 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	Systemic	0.333 mg/kg bw/day
butanone oxime	DNEL - General population - Long term - Inhalation	Local	0.7 mg/m ³
	DNEL - Workers - Long term - Inhalation	Local	2.82 mg/m ³
	DMEL - General population - Long term - Oral	Systemic	1.6 µg/kg bw/day
	DMEL - Workers - Long term - Dermal	Systemic	4 µg/kg bw/day
	DMEL - General population - Long term - Inhalation	Systemic	4.82 µg/m ³
	DMEL - Workers - Long term - Inhalation	Systemic	28 µg/m ³
	DNEL - General population - Long term - Inhalation	Local	0.43 mg/m ³
	DNEL - Workers - Long term - Inhalation	Local	0.9 mg/m ³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
butanone oxime	Fresh water - Assessment Factors Sewage Treatment Plant - Assessment Factors	0.256 mg/l 177 mg/l

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Code	: 00333367	Date of issue/Date of revision	: 23 September 2026
SIGMARINE 48 YELLOW 3138			

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: 0.33 kPa (2.5 mm Hg)
Evaporation rate	: 0.16 (butyl acetate = 1)
Relative density	: 1.03
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects		
Acute toxicity		
Product/ingredient name	Result	Dose / Exposure
Solvent naphtha (petroleum), medium aliph.	Rat - Oral - LD50	>5000 mg/kg
2-ethylhexanoic acid, zirconium salt	Rabbit - Dermal - LD50 Rabbit - Dermal - LD50 Rat - Oral - LD50 <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity)	>3000 mg/kg >5 g/kg >5 g/kg
butanone oxime	Rabbit - Dermal - LD50 Rat - Oral - LD50	1100 mg/kg 100 mg/kg

Conclusion/Summary	: There are no data available on the mixture itself.
Acute toxicity estimates	

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMARINE 48 YELLOW 3138 butanone oxime	66267.3 100	N/A 1100	N/A N/A	N/A N/A	N/A N/A

Irritation/Corrosion	
Conclusion/Summary	: Not available.
Skin	: There are no data available on the mixture itself.

Code : 00333367

Date of issue/Date of revision

: 23 September 2026

SIGMARINE 48 YELLOW 3138

SECTION 11: Toxicological information**Eyes** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Sensitisation****Conclusion/Summary****Skin** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Mutagenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Carcinogenicity****Conclusion/Summary** : There are no data available on the mixture itself.**Reproductive toxicity****Conclusion/Summary** : There are no data available on the mixture itself.**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
solvent naphtha (petroleum), medium aliph. butanone oxime	Category 3 Category 1	- -	Narcotic effects upper respiratory tract
-	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
stoddard solvent Nota(s) P	Category 1	inhalation	central nervous system (CNS)
solvent naphtha (petroleum), medium aliph.	Category 1	-	central nervous system (CNS)
butanone oxime	Category 2	-	blood system

Aspiration hazard

Product/ingredient name	Result
stoddard solvent Nota(s) P solvent naphtha (petroleum), medium aliph.	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.**Potential acute health effects****Eye contact** : ☒ No known significant effects or critical hazards.**Inhalation** : No known significant effects or critical hazards.**Skin contact** : ☒ Causes skin irritation. Defatting to the skin.**Ingestion** : No known significant effects or critical hazards.**Symptoms related to the physical, chemical and toxicological characteristics****Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness**Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Code : 00333367

Date of issue/Date of revision

: 23 September 2026

SIGMARINE 48 YELLOW 3138

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Long term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Potential chronic health effects****Conclusion/Summary** : Not available.**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.**Mutagenicity** : No known significant effects or critical hazards.**Reproductive toxicity** : May damage the unborn child.**Other information**

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Result	Species	Dose / Exposure
2-ethylhexanoic acid, zirconium salt	Acute - LC50	Fish	>100 mg/l [96 hours]

Conclusion/Summary : Not available.**12.2 Persistence and degradability****Conclusion/Summary** : Not available.**12.3 Bioaccumulative potential**

Product/ingredient name	LogP _{ow}	BCF	Potential
Stoddard solvent 2-butanone oxime	3.16 to 7.06 0.63	- 5.01 [OECD 305 C]	High Low

12.4 Mobility in soil**Soil/water partition coefficient** : Not available.**Mobility** : Not available.

Code	: 00333367	Date of issue/Date of revision	: 23 September 2026
SIGMARINE 48 YELLOW 3138			
SECTION 12: Ecological information			

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Stoddard solvent Nota(s) P solvent naphtha (petroleum), medium aliph. 2-ethylhexanoic acid, zirconium salt butanone oxime	N/A	N/A	N/A	Yes	N/A	N/A	N/A
	N/A	N/A	N/A	Yes	N/A	N/A	N/A
	N/A	N/A	N/A	Yes	N/A	N/A	N/A
	No	N/A	No	Yes	No	N/A	No

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Waste catalogue

Waste code	Waste designation
08 01 99	wastes not otherwise specified

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3

Code : 00333367	Date of issue/Date of revision : 23 September 2026
SIGMARINE 48 YELLOW 3138	

SECTION 14: Transport information

14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information				
ADR/RID	: None identified.			
Tunnel code	: (D/E)			
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels.			
IMDG	: None identified.			
IATA	: None identified.			

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

Annex XIV - List of substances subject to authorisation	
Annex XIV	
None of the components are listed.	
Substances of very high concern	
None of the components are listed.	
Explosive precursors	: Not applicable.
Ozone depleting substances	
Not listed.	

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
 SIGMARINE 48 YELLOW 3138	3
	28
	30
2-ethylhexanoic acid, zirconium salt	30
butanone oxime	28

Labelling : Restricted to professional users.

Seveso Directive
This product is controlled under the Seveso Directive.

Danger criteria
Category
 5c

Code : 00333367

Date of issue/Date of revision

: 23 September 2026

SIGMARINE 48 YELLOW 3138

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = GB CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Carc. 1B, H350 Repr. 1B, H360D STOT RE 1, H372 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

 H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H360D	May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

 Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Code	: 00333367	Date of issue/Date of revision	: 23 September 2026
SIGMARINE 48 YELLOW 3138			

SECTION 16: Other information

Date of issue/ Date of revision : 23 September 2026

Date of previous issue : 25 October 2023

Prepared by : EHS

Version : 1.02

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.