SAFETY DATA SHEET

Date of issue/Date of revision : 21 November 2026 **Version** : 1.03

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : PSX 700 LIGHT TINT RESIN

Product code : 19A199520

Product type : Liquid.

Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

Use of the substance/ mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG France Business Support SAS, 3, ZAE "Les Dix Muids", B.P. 89, 59583 Marly Cedex, France, 33 (0)3 27 19 35 00

- Technical contact : Product Compliance EMEA
- Tel : +33 (0)3 27 19 35 00

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

National contact

PPG Architectural Coatings UK Ltd, Huddersfield Road, Birstall, West Yorkshire WF17 9XA, Tel: +44 (0) 1924 354000

1.4 Emergency telephone number

Supplier

+33 (0)3 27 19 35 00 (0800-1700)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Skin Sens. 1, H317
Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves. Avoid release to the environment. Avoid breathing vapour.

Response : Collect spillage. Take off contaminated clothing and wash it before reuse.

Storage : Not applicable.

SECTION 2: Hazards identification

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

P280, P273, P261, P391, P362 + P364, P501

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	REACH #: 01-2119959495-22 EC: 500-070-7 CAS: 30583-72-3	≥25 - ≤50	Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
9-Octadecenoic acid, 12-(2-oxiranylmethoxy)-, 1,2,3-propanetriyl ester, homopolymer	CAS: 74398-71-3	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	[1]
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, 3-(dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[(C10-16-alkyloxy)methyl]oxirane-quaternized, benzoates (salts)	CAS: 1431957-88-8	≥1.0 - ≤5.0	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≥1.0 - <3.0	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Imidazolium compounds, 2-(C17 and C17-unsatd. alkyl)-1-[2-(C18 and C18-unsatd. amido)ethyl] -4,5-dihydro-1-methyl, Me sulfates	EC: 276-810-5 CAS: 72749-55-4	<1.0	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6	≤0.30	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311	[1] [2]

SECTION 3: Composition/information on ingredients

	CAS: 67-56-1 Index: 603-001-00-X		Acute Tox. 3, H331 STOT SE 1, H370 **See Section 16 for the full text of the H statements declared above.**	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 6: Accidental release measures

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
methanol	**EH40/2005 WELs (United Kingdom (UK), 1/2020)** Absorbed through skin. STEL 15 minutes: 333 mg/m³. STEL 15 minutes: 250 ppm. TWA 8 hours: 266 mg/m³. TWA 8 hours: 200 ppm.

No exposure indices known.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	DNEL - Workers - Long term - Dermal	*Local*	0.021 mg/cm² skin
	DNEL - Workers - Short term - Dermal	*Local*	0.23 mg/cm² skin
	DNEL - General population - Short term - Dermal	*Local*	21 µg/cm²
	DNEL - General population - Long term - Dermal	*Local*	21 µg/cm²
	DNEL - Workers - Long term - Dermal	*Local*	21 µg/cm²
	DNEL - Workers - Short term - Dermal	*Local*	0.23 mg/cm²
	DNEL - General population - Long term - Oral	*Systemic*	0.5 mg/kg bw/day
	DNEL - General population - Short term - Dermal	*Systemic*	0.5 mg/kg bw/day
	DNEL - General population - Long term - Dermal	*Systemic*	0.5 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	*Systemic*	1 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	*Systemic*	1 mg/kg bw/day
	DNEL - General population - Short term - Inhalation	*Systemic*	1.76 mg/m³
	DNEL - General population - Long term - Inhalation	*Systemic*	1.76 mg/m³
	DNEL - Workers - Long term - Inhalation	*Systemic*	3.25 mg/m³
	DNEL - Workers - Short term - Inhalation	*Systemic*	3.52 mg/m³
methanol	DNEL - General population - Short term - Oral	*Systemic*	4 mg/kg bw/day
	DNEL - General population - Long term - Oral	*Systemic*	4 mg/kg bw/day
	DNEL - General population - Short term - Dermal	*Systemic*	4 mg/kg bw/day
	DNEL - General population - Long term - Dermal	*Systemic*	4 mg/kg bw/day
	DNEL - Workers - Short term - Dermal	*Systemic*	20 mg/kg bw/day
	DNEL - Workers - Long term - Dermal	*Systemic*	20 mg/kg bw/day
	DNEL - General population - Short term - Inhalation	*Local*	26 mg/m³
	DNEL - General population - Long term - Inhalation	*Local*	26 mg/m³
	DNEL - General population - Short term - Inhalation	*Systemic*	26 mg/m³
	DNEL - General population - Long term - Inhalation	*Systemic*	26 mg/m³
	DNEL - Workers - Short term - Inhalation	*Local*	130 mg/m³
	DNEL - Workers - Long term - Inhalation	*Local*	130 mg/m³
	DNEL - Workers - Short term - Inhalation	*Systemic*	130 mg/m³
	DNEL - Workers - Long term - Inhalation	*Systemic*	130 mg/m³

PNECs

Product/ingredient name	Compartment Detail - Method	Value
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Fresh water - Assessment Factors	11.5 µg/l
	Marine water - Assessment Factors	11.5 µg/l
	Sewage Treatment Plant - Assessment Factors	100 mg/l
	Fresh water sediment	0.229 mg/kg dwt
	Marine water sediment - Equilibrium Partitioning	0.023 mg/kg dwt
	Soil - Equilibrium Partitioning	0.099 mg/kg dwt
methanol	Fresh water - Assessment Factors	20.8 mg/l
	Marine water - Assessment Factors	2.08 mg/l

SECTION 8: Exposure controls/personal protection

	Sewage Treatment Plant - Assessment Factors	100 mg/l
	Fresh water sediment - Equilibrium Partitioning	77 mg/kg
	Marine water sediment - Equilibrium Partitioning	7.7 mg/kg
	Soil - Assessment Factors	100 mg/kg

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Not available.

SECTION 9: Physical and chemical properties

Odour : Not available.

Odour threshold : Not available.

Melting point/freezing point :

Initial boiling point and boiling range : >37.78°C (>100°F)

Flammability (solid, gas) : liquid

Upper/lower flammability or explosive limits : Not available.

Flash point : Closed cup: 75°C (167°F)

Auto-ignition temperature : Not available.

pH : Not applicable.

Not applicable. insoluble in water.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm^2/s

Solubility(ies) :

Media	Result
cold water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/water : Not applicable.

Vapour pressure : Not available.

Relative density : 1.23

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
9-Octadecenoic acid, 12-(2-oxiranylmethoxy)-, 1,2,3-propanetriyl ester, homopolymer	Rat - Oral - LD50	>5 g/kg
	Rabbit - Dermal - LD50	>5 g/kg
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl) benzene, 3-(dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[(C10-16-alkyloxy) methyl]oxirane-quaternized, benzoates (salts)	Rat - Female - Oral - LD50	>2000 mg/kg
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rat - Male, Female - Oral - LD50	3230 mg/kg
	Rat - Dermal - LD50	>3170 mg/kg
methanol	Rabbit - Dermal - LD50	15800 mg/kg
	Toxic effects: Eye - Visual field changes	
	Rat - Oral - LD50	5600 mg/kg
	Rat - Inhalation - LC50 Vapour	64000 ppm [4 hours]

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700 LIGHT TINT RESIN	86535.1	259605.4	N/A	2596.1	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
methanol	100	300	64000	3	N/A

Irritation/Corrosion

Conclusion/Summary : Not available.

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
methanol	Category 1	-	-

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50	Fish - Trout	11.5 mg/l [96 hours]
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, 3-(dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[(C10-16-alkyloxy)methyl] oxirane-quaternized, benzoates (salts)	EC50	Algae - *Pseudokirchneriella subcapitata*	0.25 mg/l [72 hours]
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LC50	Fish	0.9 mg/l [96 hours]
	EC50	Algae	1.68 mg/l [72 hours]
methanol	Acute - LC50 - Fresh water	Fish - Trout	13 mg/l [96 hours]

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
methanol	-0.77	-	Low

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	No	N/A	N/A	No	N/A	N/A	N/A
9-Octadecenoic acid, 12-(2-oxiranylmethoxy)-, 1,2,3-propanetriyl ester, homopolymer	No	N/A	N/A	No	N/A	N/A	N/A
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, 3-(dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[	No	N/A	N/A	No	N/A	N/A	N/A

SECTION 12: Ecological information

(C10-16-alkyloxy)methyl] oxirane-quaternized, benzoates (salts)							
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Imidazolium compounds, 2-(C17 and C17-unsatd. alkyl) -1-[2-(C18 and C18-unsatd. amido)ethyl]-4,5-dihydro-1-methyl, Me sulfates	No	N/A	N/A	No	N/A	N/A	N/A
methanol	No	N/A	N/A	No	N/A	N/A	N/A

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	III	III

SECTION 14: Transport information

14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl) benzene, 3-(dimethylamino)propyl imide, imide)	Not applicable.

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Tunnel code : (-)

ADN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Explosive precursors : Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
PSX 700 LIGHT TINT RESIN	3
methanol	69

Labelling : Not applicable.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
E2

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 3	ACUTE TOXICITY - Category 3
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1

History

Date of issue/ Date of revision : 21 November 2026

Date of previous issue : 8 July 2026

Prepared by : EHS

Version : 1.03

Disclaimer

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.