

SAFETY DATA SHEET

Date of issue/Date of revision

: 9 March 2018

Version

: 2.03



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : STEELGUARD 802 WHITE
Product code : 00372935
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.

1.3 Details of the supplier of the safety data sheet

PPG Coatings SPRL/BVBA
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

e-mail address of person responsible for this SDS : PMC.Safety@PPG.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225
Skin Irrit. 2, H315
Repr. 2, H361d (Unborn child)
STOT SE 3, H336
STOT RE 2, H373

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 2: Hazards identification

Hazard pictograms :



Signal word :

Danger

Hazard statements :

Highly flammable liquid and vapour.
Causes skin irritation.
Suspected of damaging the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention :

Wear protective gloves. Wear protective clothing. Wear eye or face protection.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking. Do not breathe vapour.

Response :

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage :

Store in a well-ventilated place. Keep cool.

Disposal :

Not applicable.
P280, P210, P260, P304 + P340, P303 + P361 + P353, P403, P235

Hazardous ingredients :

toluene

Supplemental label elements :

Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles :

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Not applicable.

Tactile warning of danger :

Not applicable.

2.3 Other hazards

Other hazards which do not result in classification :

Prolonged or repeated contact may dry skin and cause irritation. Contains a constituent that may slowly release formaldehyde on storage and at temperatures greater than 60C/140F.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Mixture

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Type

Code : 00372935	Date of issue/Date of revision : 9 March 2018
STEELGUARD 802 WHITE	

SECTION 3: Composition/information on ingredients

toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≥10 - ≤25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d (Unborn child) STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Flam. Liq. 2, H225	[1] [2]
butanone	REACH #: 01-2119457290-43 EC: 201-159-0 CAS: 78-93-3 Index: 606-002-00-3	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1] [2]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	≤0.30	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 4: First aid measures

- Skin contact** : Causes skin irritation. Defatting to the skin.
Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
carbonyl halides
metal oxide/oxides
Formaldehyde.

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Code : 00372935
 STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 7: Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
toluene	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 384 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 191 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
butanone	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 899 mg/m ³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 600 mg/m ³ 8 hours. TWA: 200 ppm 8 hours.

Code : 00372935
 STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
toluene	DNEL	Long term Inhalation	192 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	384 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	192 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	384 mg/m ³	Workers	Local
	DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	56.5 mg/m ³	Consumers	Systemic
	DNEL	Short term Inhalation	226 mg/m ³	Consumers	Systemic
	DNEL	Long term Inhalation	56.5 mg/m ³	Consumers	Local
	DNEL	Short term Inhalation	226 mg/m ³	Consumers	Local
	DNEL	Long term Dermal	226 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	8.13 mg/kg bw/day	Consumers	Systemic
butanone	DNEL	Long term Inhalation	600 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	1161 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	106 mg/m ³	Consumers	Systemic
	DNEL	Long term Dermal	412 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	31 mg/kg bw/day	Consumers	Systemic

PNECs

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
toluene	-	Fresh water	0.68 mg/l	Sensitivity Distribution
	-	Marine water	0.68 mg/l	Sensitivity Distribution
	-	Sewage Treatment Plant	13.61 mg/l	Sensitivity Distribution
butanone	-	Fresh water sediment	16.39 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	16.39 mg/kg dwt	-
	-	Fresh water	55.8 mg/l	Sensitivity Distribution
	-	Marine water	55.8 mg/l	Sensitivity Distribution
	-	Sewage Treatment Plant	709 mg/l	Sensitivity Distribution
	-	Fresh water sediment	284.74 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	284.7 mg/kg dwt	Equilibrium Partitioning
-	Soil	22.5 mg/kg dwt	Equilibrium Partitioning	

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : White.
- Odour** : Aromatic. [Strong]
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: -86.64°C (-124°F) This is based on data for the following ingredient: butanone. Weighted average: -94.13°C (-137.4°F)
- Initial boiling point and boiling range** : >37.78°C
- Flash point** : Closed cup: 3°C
- Evaporation rate** : 2 (toluene) compared with butyl acetate
- Material supports combustion.** : Yes.
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.8% Upper: 11.5% (butanone)
- Vapour pressure** : Highest known value: 10.5 kPa (78.8 mm Hg) (at 20°C) (butanone). Weighted average: 3.87 kPa (29.03 mm Hg) (at 20°C)
- Vapour density** : Highest known value: 3.1 (Air = 1) (toluene). Weighted average: 3.03 (Air = 1)
- Relative density** : 1.35
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Auto-ignition temperature** : Lowest known value: 404°C (759.2°F) (butanone).
- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- Viscosity** : Kinematic (40°C): >0.21 cm²/s
- Viscosity** : > 100 s (ISO 6mm)
- Explosive properties** : Product does not present an explosion hazard.
- Oxidising properties** : Product does not present an oxidizing hazard.

9.2 Other information

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 9: Physical and chemical properties

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. carbonyl halides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
toluene	LC50 Inhalation Vapour	Rat	49 g/m ³	4 hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LD50 Oral	Rat	5580 mg/kg	-
butanone	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 Oral	Rat	2737 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.11 mg/l	4 hours
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Conclusion/Summary

- Skin** : There are no data available on the mixture itself.
- Eyes** : There are no data available on the mixture itself.
- Respiratory** : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

- Skin** : There are no data available on the mixture itself.
- Respiratory** : There are no data available on the mixture itself.

Code : 00372935	Date of issue/Date of revision : 9 March 2018
STEELGUARD 802 WHITE	

SECTION 11: Toxicological information

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
toluene	Category 3	Not applicable.	Narcotic effects
butanone	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
toluene	Category 2	Not determined	Not determined

Aspiration hazard

Product/ingredient name	Result
toluene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Ingestion : Can cause central nervous system (CNS) depression.

Skin contact : Causes skin irritation. Defatting to the skin.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Ingestion : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Code : 00372935
 STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	Acute EC50 29 to 43 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 94 mg/l	Daphnia - Daphnia magna	48 hours

Conclusion/Summary : There are no data available on the mixture itself.**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	-	63 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
toluene	2.73	8.32	low
butanone	0.29	-	low
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	>6	-	high

12.4 Mobility in soil**Soil/water partition coefficient (K_{oc})** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment****PBT** : Not applicable.**vPvB** : Not applicable.**12.6 Other adverse effects** : No known significant effects or critical hazards.**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Code : 00372935	Date of issue/Date of revision : 9 March 2018
STEELGUARD 802 WHITE	

SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.
Tunnel code : (D/E)
ADN : None identified.
IMDG : None identified.
IATA : None identified.

Code : 00372935
STEELGUARD 802 WHITE

Date of issue/Date of revision : 9 March 2018

14. Transport information

14.6 Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

5c

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Code : 00372935 Date of issue/Date of revision : 9 March 2018
 STEELGUARD 802 WHITE

SECTION 16: Other information

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d (Unborn child) STOT SE 3, H336 STOT RE 2, H373	On basis of test data Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Chronic 3, H412 Asp. Tox. 1, H304 EUH066 Eye Irrit. 2, H319 Flam. Liq. 2, H225 Repr. 2, H361d Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT RE 2, H373	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 Repeated exposure may cause skin dryness or cracking. SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 REPRODUCTIVE TOXICITY (Unborn child) - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

History

Date of issue/ Date of revision : 9 March 2018
 Date of previous issue : 17 September 2017
 Prepared by : EHS
 Version : 2.03

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.