

# SAFETY DATA SHEET

Date of issue/Date of revision

: 21 December 2018 Version : 9



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : MEGASEAL WBPC Waterbased Epoxy Primer Comp B  
**Product code** : 00333472  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Used by spraying.  
**Use of the substance/mixture** : Coating.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings SPRL/BVBA  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : PMC.Safety@PPG.com

### 1.4 Emergency telephone number

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1C, H314  
 Eye Dam. 1, H318  
 Skin Sens. 1, H317  
 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

Causes severe skin burns and eye damage.  
 May cause an allergic skin reaction.  
 Toxic to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** :

Wear protective gloves. Wear protective clothing. Wear eye or face protection.  
 Avoid breathing vapour.

**Response** :

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Storage** :

Store locked up.

**Disposal** :

Not applicable.  
 P280, P261, P304 + P340, P301 + P310, P303 + P361 + P353, P305 + P351 + P338, P405

**Hazardous ingredients** :

Anquamine 401(A modified tetraethylenepentamine adduct, curing agent for epoxy resins (Air Products and Chemicals, Inc. )  
 Poly[oxy(methyl-1,2-ethanediyl)],  $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-3,6,9-triazaundecamethylenediamine  
 2,4,7,9-tetramethyldec-5-yne-4,7-diol

**Supplemental label elements** :

Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification** :

Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** :

Mixture

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

### SECTION 3: Composition/information on ingredients

| Product/ingredient name   | Identifiers   | % by weight | Classification<br>Regulation (EC) No.<br>1272/2008 [CLP]  | Type |
|---|---|-------------|---|------|
| Anquamine 401(A modified tetraethylenepentamine adduct, curing agent for epoxy resins (Air Products and Chemicals, Inc.) )<br>Poly[oxy(methyl-1,2-ethanediyl)], α<br>-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-<br>3,6,<br>9-triazaundecamethylenediamine | CAS: 180583-06-6  | ≥25 - ≤50   | Skin Sens. 1B, H317<br>Aquatic Chronic 2, H411  | [1]  |
|   | REACH #: 01-2119557899-12<br>EC: 618-561-0<br>CAS: 9046-10-0 (n = 2-6)<br>EC: 203-986-2<br>CAS: 112-57-2<br>Index: 612-060-00-0 | ≥1.0 - ≤5.0 | Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Aquatic Chronic 3, H412  | [1]  |
|   |   | ≥1.0 - <5.0 | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                  | [1]  |
| 2,4,7,9-tetramethyldec-5-yne-4,<br>7-diol   | REACH #: 01-2119954390-39<br>EC: 204-809-1<br>CAS: 126-86-3   | <1.0        | Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | [1]  |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 4: First aid measures

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** :  In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** :  Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
Formaldehyde.

### 5.3 Advice for firefighters

- Special precautions for firefighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 5: Firefighting measures

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 7: Handling and storage

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs

| Product/ingredient name  | Type | Exposure              | Value                  | Population | Effects  |
|--|------|-----------------------|------------------------|------------|----------|
| Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-<br><br>2,4,7,9-tetramethyldec-5-yne-4,7-diol | DNEL | Long term Inhalation  | 1.36 mg/m <sup>3</sup> | Workers    | Systemic |
|  | DNEL | Long term Dermal      | 2.5 mg/kg bw/day       | Workers    | Systemic |
|  | DNEL | Long term Inhalation  | 1.76 mg/m <sup>3</sup> | Workers    | Systemic |
|  | DNEL | Short term Inhalation | 5.28 mg/m <sup>3</sup> | Workers    | Systemic |
|  | DNEL | Long term Dermal      | 0.5 mg/kg bw/day       | Workers    | Systemic |
|  | DNEL | Short term Dermal     | 1.5 mg/kg bw/day       | Workers    | Systemic |

|  |   |
|--|---|
| Code : 00333472                              | Date of issue/Date of revision : 21 December 2018 |
| MEGASEAL WBPC Waterbased Epoxy Primer Comp B |   |

**SECTION 8: Exposure controls/personal protection**

|  |      |                       |                        |           |          |
|--|------|-----------------------|------------------------|-----------|----------|
|  | DNEL | Long term Inhalation  | 0.43 mg/m <sup>3</sup> | Consumers | Systemic |
|  | DNEL | Short term Inhalation | 1.29 mg/m <sup>3</sup> | Consumers | Systemic |
|  | DNEL | Long term Dermal      | 0.25 mg/kg bw/day      | Consumers | Systemic |
|  | DNEL | Short term Dermal     | 0.75 mg/kg bw/day      | Consumers | Systemic |
|  | DNEL | Long term Oral        | 0.25 mg/kg bw/day      | Consumers | Systemic |
|  | DNEL | Short term Oral       | 0.75 mg/kg bw/day      | Consumers | Systemic |

**PNECs**

| Product/ingredient name  | Type | Compartment Detail     | Value           | Method Detail            |
|--|------|------------------------|-----------------|--------------------------|
| Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-<br><br>2,4,7,9-tetramethyldec-5-yne-4,7-diol | -    | Fresh water            | 0.015 mg/l      | Assessment Factors       |
|  | -    | Marine water           | 0.014 mg/l      | Assessment Factors       |
|  | -    | Sewage Treatment Plant | 7.5 mg/l        | Assessment Factors       |
|  | -    | Fresh water sediment   | 0.132 mg/kg dwt | Equilibrium Partitioning |
|  | -    | Marine water sediment  | 0.125 mg/kg dwt | Equilibrium Partitioning |
|  | -    | Soil                   | 0.018 mg/kg dwt | Equilibrium Partitioning |
|  | -    | Fresh water            | 0.04 mg/l       | Assessment Factors       |
|  | -    | Marine water           | 0.004 mg/l      | Assessment Factors       |
|  | -    | Sewage Treatment Plant | 7 mg/l          | Assessment Factors       |
|  | -    | Fresh water sediment   | 0.32 mg/kg dwt  | Equilibrium Partitioning |
|  | -    | Marine water sediment  | 0.032 mg/kg dwt | Equilibrium Partitioning |
|  | -    | Soil                   | 0.028 mg/kg dwt | Equilibrium Partitioning |

**8.2 Exposure controls**

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles and face shield. Use eye protection according to EN 166.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class



Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 8: Exposure controls/personal protection

of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Gloves** : nitrile neoprene
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Not available.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -2.27°C (27.9°F)
- Initial boiling point and boiling range** : >37.78°C
- Flash point** : Closed cup: 93.33°C
- Evaporation rate** : Not available.
- Material supports combustion.** : Yes.
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Not available.
- Vapour pressure** : Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.99 kPa (22.43 mm Hg) (at 20°C)
- Relative density** : 1.05
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Water Solubility at room temperature** : 0 g/l
- Partition coefficient: n-octanol/ water** : Not applicable.
- Auto-ignition temperature** : Lowest known value: 321°C (609.8°F) (3,6,9-triazaundecamethylenediamine).



Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 9: Physical and chemical properties

- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).  
**Viscosity** : Kinematic (40°C): >0.21 cm<sup>2</sup>/s  
**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.  
**Oxidising properties** : Product does not present an oxidizing hazard.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.  
**10.2 Chemical stability** : The product is stable.  
**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.  
**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
 Refer to protective measures listed in sections 7 and 8.  
**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.  
**10.6 Hazardous decomposition products** :  Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name   | Result                          | Species | Dose        | Exposure |
|---|---------------------------------|---------|-------------|----------|
| <input checked="" type="checkbox"/> Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)- | LD50 Dermal                     | Rat     | 2980 mg/kg  | -        |
| 3,6,9-triazaundecamethylenediamine  | LD50 Oral                       | Rat     | 2885 mg/kg  | -        |
|   | LD50 Dermal                     | Rabbit  | 0.66 g/kg   | -        |
|   | LD50 Oral                       | Rat     | 0.205 g/kg  | -        |
| White mineral oil (petroleum)   | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| 2,4,7,9-tetramethyldec-5-yne-4,7-diol   | LC50 Inhalation Dusts and mists | Rat     | >20 mg/l    | 1 hours  |
|   | LD50 Dermal                     | Rabbit  | >2000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | 4.6 g/kg    | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Acute toxicity estimates

| Route                                    | ATE value     |
|--|---------------|
| <input checked="" type="checkbox"/> Oral | 22442.7 mg/kg |
| Dermal                                   | 49373.9 mg/kg |

#### Irritation/Corrosion

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 11: Toxicological information

| Product/ingredient name   | Result   | Species          | Score  | Exposure                     | Observation |
|---|--|------------------|--------|------------------------------|-------------|
| <input checked="" type="checkbox"/> 2,4,7,9-tetramethyldec-5-yne-4,7-diol | Eyes - Severe irritant<br>Skin - Mild irritant | Rabbit<br>Rabbit | -<br>- | 0.1 Milliliters<br>0.5 Grams | -<br>-      |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitisation

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : No specific data.

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

**Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur

**Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 11: Toxicological information

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Anquamine 401(A modified tetraethylenepentamine adduct, curing agent for epoxy resins (Air Products and Chemicals, Inc.)), 3,6,9-triazaundecamethylenediamine, 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name   | Result       | Species | Exposure |
|---|--------------|---------|----------|
| Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)- | EC50 15 mg/l | Algae   | 72 hours |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

**Conclusion/Summary** : There are no data available on the mixture itself.

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 12: Ecological information

| Product/ingredient name   | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Poly[oxy(methyl-1,2-ethanediyl)], α-(2-aminomethylethyl)-ω-(2-aminomethylethoxy)- | -                 | -          | Not readily      |

### 12.3 Bioaccumulative potential

| Product/ingredient name       | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------------|--------------------|-----|-----------|
| White mineral oil (petroleum) | >6                 | -   | high      |

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

| Waste code | Waste designation              |
|------------|--------------------------------|
| 08 01 99   | wastes not otherwise specified |

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## 14. Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number                  | Not regulated.  | Not regulated.  | Not regulated.  | Not regulated.  |
| 14.2 UN proper shipping name    | -               | -               | -               | -               |
| 14.3 Transport hazard class(es) | -               | -               | -               | -               |
| 14.4 Packing group              | -               | -               | -               | -               |
| 14.5 Environmental hazards      | No.             | No.             | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

### Additional information

ADR/RID : None identified.  
 ADN : None identified.  
 IMDG : None identified.  
 IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

##### Ozone depleting substances (1005/2009/EU)

Not listed.

##### Seveso Directive

This product is controlled under the Seveso Directive.

Code : 00333472 Date of issue/Date of revision : 21 December 2018  
 MEGASEAL WBPC Waterbased Epoxy Primer Comp B

## SECTION 15: Regulatory information

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 PBT = Persistent, Bioaccumulative and Toxic  
 vPvB = Very Persistent and Very Bioaccumulative  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 IMDG = International Maritime Dangerous Goods  
 IATA = International Air Transport Association

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification          | Justification      |
|-------------------------|--------------------|
| ✔ Skin Corr. 1C, H314   | Calculation method |
| Eye Dam. 1, H318        | Calculation method |
| Skin Sens. 1, H317      | Calculation method |
| Aquatic Chronic 2, H411 | Calculation method |

### Full text of abbreviated H statements

|        |  |
|--------|--|
| ✔ H302 | Harmful if swallowed.                              |
| H312   | Harmful in contact with skin.                      |
| H314   | Causes severe skin burns and eye damage.           |
| H317   | May cause an allergic skin reaction.               |
| H318   | Causes serious eye damage.                         |
| H411   | Toxic to aquatic life with long lasting effects.   |
| H412   | Harmful to aquatic life with long lasting effects. |

### Full text of classifications [CLP/GHS]

|                         |   |
|-------------------------|---|
| ✔ Acute Tox. 4, H302    | ACUTE TOXICITY (oral) - Category 4              |
| Acute Tox. 4, H312      | ACUTE TOXICITY (dermal) - Category 4            |
| Aquatic Chronic 2, H411 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Aquatic Chronic 3, H412 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Eye Dam. 1, H318        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  |
| Skin Corr. 1B, H314     | SKIN CORROSION/IRRITATION - Category 1B         |
| Skin Corr. 1C, H314     | SKIN CORROSION/IRRITATION - Category 1C         |
| Skin Sens. 1, H317      | SKIN SENSITISATION - Category 1                 |
| Skin Sens. 1B, H317     | SKIN SENSITISATION - Category 1B                |

### History

**Date of issue/ Date of revision** : 21 December 2018  
**Date of previous issue** : 9 May 2018  
**Prepared by** : EHS  
**Version** : 9

### Disclaimer



**Code** : 00333472 **Date of issue/Date of revision** : 21 December 2018  
**MEGASEAL WBPC Waterbased Epoxy Primer Comp B**

## **SECTION 16: Other information**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*