SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 17 June 2019

Version 3

Date of issue 17 June 2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: AMERCOAT 861 ACCELERATOR
Product code	: AT861/32
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Industrial applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 or + 52 55 5559 1588 (Mexico)
Technical Phone Number	: 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture	 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 13% (Oral), 13% (Dermal), 100% (Inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H302 + H312 - Harmful if swallowed or in contact with skin. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction.
	Maxies Deves 4/44

Mexico Page: 1/11

Product name AMERCOAT 861 ACCELERATOR

SECTION 2: Hazards identification

Precautionary statements		
Prevention	:	P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection. P261 - Avoid breathing vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace.
Response	:	₱304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. P302 + P352 + P312 + P362 + P364 - IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Take off contaminated clothing and wash it before reuse. P333 + P313 - If skin irritation or rash occurs: Get medical attention. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Emits toxic fumes when heated.
See toxicological information	า (S	Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture Product name	- C.	Mixture AMERCOAT 861 ACCELERATOR
Other means of identification	:	Not applicable.

Ingredient name	%	CAS number
₽,4,6-tris(dimethylaminomethyl)phenol	≥75 - ≤90	90-72-2
bis[(dimethylamino)methyl]phenol	≥10 - ≤20	71074-89-0

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name AMERCOAT 861 ACCELERATOR

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health	<u>effects</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed.
Specific treatments	The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

SECTION 5: Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Product name AMERCOAT 861 ACCELERATOR

SECTION 5: Firefighting measures

.....

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

.

.

....

Personal precautions, protec	τιν	e equipment and emergency procedures
For non-emergency personnel For emergency responders		No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Product name AMERCOAT 861 ACCELERATOR

SECTION 7: Handling and storage

Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in dry, cool and well-ventilated area, away from incompatible materials (see Section and food and drink. Store locked up. Keep container tightly closed and sealed up ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.	a 10) ntil

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
2,4,6-tris(dimethylaminomethyl)phenol	None.	
bis[(dimethylamino)methyl]phenol	None.	

		Key to abbreviations
\sim	- Optilizer Lineth	

С	= Ceiling Limit	STEL
IPEL	= Internal Permissible Exposure Limit	TLV

STEL	= Short term exposure limit
TLV	= Threshold Limit Value
TWA	= Time Weighted Average

Consult local authorities for acceptable exposure limits.

procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	Chemical splash goggles and face shield.
Skin protection	

Version 3

Product name AMERCOAT 861 ACCELERATOR

SECTION 8: Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: nitrile neoprene
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	1	Not available.
Odor	1	Characteristic.
Odor threshold	:	Not available.
Molecular weight		Not applicable.
рН		Not available.
Melting point	1	Not available.
Boiling point	1	>37.78°C (>100°F)
Flash point	1	Closed cup: 123.89°C (255°F)
Material supports combustion.	:	Yes.
Auto-ignition temperature	1	Not available.
Decomposition temperature	:	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Evaporation rate	1	Not available.
Vapor pressure	1	Not available.
Vapor density	:	Not available.
Relative density	:	0.97
Density(lbs / gal)	:	8.1
Solubility	:	Insoluble in the following materials: cold water.
Solubility in water	1	80 g/l
Partition coefficient: n- octanol/water	:	Not available.
Viscosity	1	Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

Product code AT861/32	Date of issue 17 June 2019 Version 3				
Product name AMERCOAT 861 ACCELERATOR					
SECTION 9: Phys	SECTION 9: Physical and chemical properties				
Volatility	: 0% (v/v), 0% (w/w)				
% Solid. (w/w)	: 100				
SECTION 10: Sta	bility and reactivity				
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
Chemical stability	: The product is stable.				
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
Conditions to avoid	 When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. 				
Incompatible materials	 Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. 				
Hazardous decomposition products	 Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. 				

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal LD50 Oral	Rat Rat	1280 mg/kg 1200 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
₽,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days
Conclusion/Summary					
Skin	: There are no data available on the mixture itself.				
Eyes	: There are no data available on the mixture itself.				
Respiratory	: There are no data available on the mixture itself.				

Sensitization

Product/ingredient name	Route of exposure	Species	Result
2,4,6-tris (dimethylaminomethyl) phenol	skin	Guinea pig	Sensitizing
Conclusion/Summary			

Page: 7/11 Mexico

Product name AMERCOAT 861 ACCELERATOR

SECTION 11: Toxicological information

Skin	: There are no data available on the mixture itself.	
Respiratory	: There are no data available on the mixture itself.	
<u>Mutagenicity</u>		
Conclusion/Summary	: There are no data available on the mixture itself.	
Carcinogenicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Reproductive toxicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Teratogenicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Specific target organ toxic	<u>(ty (single exposure)</u>	
Not available.		
Specific target organ toxic	ity (repeated exposure)	
Not available.		
Aspiration hazard		
Not available.		
Information on the likely rou	ites of exposure	
Potential acute health effec	•	
Eye contact	: Causes serious eye damage.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skir	
	reaction.	
Ingestion	: Harmful if swallowed.	
Over-exposure signs/sympt	<u>toms</u>	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur	
Ingestion	: Adverse symptoms may include the following: stomach pains	
Delayed and immediate effe	ects and also chronic effects from short and long term exposure	
Conclusion/Summary	: There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where	

Version 3

Product name AMERCOAT 861 ACCELERATOR

SECTION 11: Toxicological information

known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

1280 mg/kg

		······································		
<u>Short term exposure</u>				
Potential immediate	: Th	There are no data available on the mixture itself.		
effects				
Potential delayed effects	: Th	There are no data available on the mixture itself.		
<u>Long term exposure</u>				
Potential immediate	: Th	There are no data available on the mixture itself.		
effects				
Potential delayed effects	: Th	There are no data available on the mixture itself.		
Potential chronic health effects				
General		Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.		
Carcinogenicity	: N	No known significant effects or critical hazards.		
Mutagenicity	: N	No known significant effects or critical hazards.		
Teratogenicity	: N	No known significant effects or critical hazards.		
Developmental effects	: N	No known significant effects or critical hazards.		
Fertility effects	: N	No known significant effects or critical hazards.		
Numerical measures of toxic	<u>ity</u>			
Acute toxicity estimates				
Route		ATE value		
Oral		1200 mg/kg		

SECTION 12: Ecological information

Toxicity

Dermal

Product/ingredient name	Result	Species	Exposure
₽,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Product name AMERCOAT 861 ACCELERATOR

SECTION 13: Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

•				
	Mexico Classification	IMDG	ΙΑΤΑ	
UN number	VN3066	UN3066	UN3066	
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	
Transport hazard class(es)	8	8	8	
Packing group			III	
Environmental hazards	No.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	

Additional information

- Mexico : None identified.
- **IMDG** : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Product name AMERCOAT 861 ACCELERATOR

SECTION 15: Regulatory information

Mexico

Classification

Flammability : 1 Health : 3 Reactivity : 0

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

SECTION 16: Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue	: 9/11/2018
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
— • • • • • • • • • • • • • • • • • • •	

✓ Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.