

SAFETY DATA SHEET

Date of issue/Date of revision

: 15 November 2019 Version : 3.08



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

Product code : 00349272

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings SPRL/BVBA

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

**e-mail address of person
responsible for this SDS** : PMC.Safety@PPG.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 2: Hazards identification

Hazard pictograms :



Signal word :

Danger

Hazard statements :

Causes serious eye irritation.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Causes damage to organs through prolonged or repeated exposure.
 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention :

Wear protective gloves. Wear eye or face protection. Do not breathe dust or mist.

Response :

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage :

Not applicable.

Disposal :

Not applicable.
 P280, P260, P305 + P351 + P338

Hazardous ingredients :

Quartz (SiO₂)
 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
 Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyl)oxymethylene]]bis-
 Oxirane, 2-[(C12-13-alkyloxy)methyl] derivs.

Supplemental label elements :

Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles :

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Not applicable.

Tactile warning of danger :

Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification :

May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

SECTION 3: Composition/information on ingredients

3.2 Mixtures :

Mixture

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Quartz (SiO ₂)	EC: 238-878-4 CAS: 14808-60-7	≥25 - ≤50	STOT RE 1, H372 (inhalation)	[1] [2]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8	≥10 - ≤22	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyloxy)methylene]]bis-	CAS: 41638-13-5	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
Oxirane, 2-[(C12-13-alkyloxy)methyl] derivs.	CAS: 120547-52-6	≤2.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical powder.
- Unsuitable extinguishing media** : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : May form explosible dust-air mixture if dispersed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections : See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 7: Handling and storage

equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
<input checked="" type="checkbox"/> Quartz (SiO ₂) 1-methoxy-2-propanol	EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 0.1 mg/m ³ 8 hours. Form: respirable dust EH40/2005 WELs (United Kingdom (UK), 8/2018). Absorbed through skin. STEL: 560 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 8: Exposure controls/personal protection

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 1-methoxy-2-propanol	DNEL	Long term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Oral	33 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	43.9 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	78 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	183 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	369 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	553.5 mg/m ³	Workers	Local
DNEL	Short term Inhalation	553.5 mg/m ³	Workers	Systemic	


PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 1-methoxy-2-propanol	-	Fresh water	0.006 mg/l	Assessment Factors
	-	Marine water	0.001 mg/l	Assessment Factors
	-	Sewage Treatment Plant	10 mg/l	Assessment Factors
	-	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning
	-	Fresh water	10 mg/l	Assessment Factors
	-	Marine water	1 mg/l	Assessment Factors
	-	Sewage Treatment Plant	100 mg/l	Assessment Factors
	-	Fresh water sediment	41.6 mg/kg	Equilibrium Partitioning
	-	Marine water sediment	4.17 mg/kg	Equilibrium Partitioning
	-	Soil	2.47 mg/kg	Equilibrium Partitioning

8.2 Exposure controls

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** :  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Product type	: Powder.
Colour	: Grey.
Odour	: Odourless.
Odour threshold	: Not available.
pH	: insoluble in water.
Melting point/freezing point	: May start to solidify at the following temperature: -96°C (-140.8°F) This is based on data for the following ingredient: 1-methoxy-2-propanol.
Initial boiling point and boiling range	: >37.78°C
Flash point	: Closed cup: 205°C
Evaporation rate	: 0.814 (1-methoxy-2-propanol) compared with butyl acetate
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1.48% Upper: 13.74% (1-methoxy-2-propanol)
Vapour pressure	: Highest known value: 1.1 kPa (8.5 mm Hg) (at 20°C) (1-methoxy-2-propanol).
Vapour density	: Highest known value: 3.11 (Air = 1) (1-methoxy-2-propanol).
Relative density	: 2.01
Solubility(ies)	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Lowest known value: 270°C (518°F) (1-methoxy-2-propanol).
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
Viscosity	: Kinematic (40°C): >0.21 cm ² /s
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	LD50 Dermal	Rabbit	>2 g/kg	-
Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyl)oxymethylene]]bis-	LD50 Oral	Rat	11.4 g/kg	-
	LD50 Dermal	Rabbit	>2 g/kg	-
Oxirane, 2-[(C12-13-alkyloxy)methyl] derivs.	LD50 Oral	Rat	>2 g/kg	-
	LD50 Dermal	Rabbit	>2 g/kg	-
1-methoxy-2-propanol	LD50 Oral	Rat	>10 g/kg	-
	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	5.2 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Skin - Moderate irritant	Rabbit	-	-	-
	Eyes - Moderate irritant	Rabbit	-	-	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	skin	Mouse	Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 11: Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-methoxy-2-propanol	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	Inhalation	Not determined

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

Ingestion : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing

Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:
 irritation
 redness

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 11: Toxicological information

- General** : Causes damage to organs through prolonged or repeated exposure. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Other information** : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanedyl)oxymethylene]]bis-, Oxirane, 2-[(C12-13-alkyloxy)methyl] derivs.. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 1-methoxy-2-propanol	Chronic NOEC 0.3 mg/l	Daphnia	21 days
	Acute LC50 23300 mg/l Acute LC50 >4500 mg/l Fresh water	Daphnia Fish	48 hours 96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	OECD 301F	5 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	3	31	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.
ADN : The product is only regulated as a dangerous good when transported in tank vessels.
IMDG : None identified.
IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Code : 00349272 Date of issue/Date of revision : 15 November 2019
 MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 15: Regulatory information

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H372 (inhalation)	Causes damage to organs through prolonged or repeated exposure if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Code : 00349272 **Date of issue/Date of revision** : 15 November 2019
MEGASEAL SFT675 Non Slip 100%Solids Gray Kit

SECTION 16: Other information

Aquatic Chronic 2, H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3, H412	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317	SKIN SENSITISATION - Category 1
STOT RE 1, H372 (inhalation)	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (inhalation) - Category 1
STOT RE 1, H372	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

History

Date of issue/ Date of revision : 15 November 2019
Date of previous issue : 17 May 2018
Prepared by : EHS
Version : 3.08

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.