## SAFETY DATA SHEET

Date of issue/Date of revision : 17 December 2019 Version : 1



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMAGUARD CSF 650 (AMERCOAT 2209 ) FILLER

Product code : 00332950

Product type : Powder.

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.

PO Box 7509 Dammam 31472 Saudi Arabia

Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34

e-mail address of person responsible for this SDS

: ndpic@sfda.gov.sa

1.4 Emergency telephone

number

: 00966 138473100 extn 1001

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

English (GB) United Arab Emirates 1/11

Date of issue/Date of revision Code : 00332950 : 17 December 2019

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### SECTION 2: Hazards identification

**Hazardous ingredients** 

: Not applicable.

**Supplemental label** 

elements

: Safety data sheet available on request.

**Annex XVII - Restrictions** on the manufacture,

placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a

Other hazards which do not

result in classification

May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin,

nose and throat.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
Quartz (SiO2)	EC: 238-878-4 CAS: 14808-60-7	≥90	Not classified.	[2]

#### See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### <u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

### SUB codes represent substances without registered CAS Numbers.

### SECTION 4: First aid measures

### 4.1 Description of first aid measures

**Eye contact** 

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

English (GB) **United Arab Emirates** 2/11

Date of issue/Date of revision : 17 December 2019 Code : 00332950

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### SECTION 4: First aid measures

Skin contact Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show the container or label. Keep Ingestion

person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

### Potential acute health effects

**Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contact : No known significant effects or critical hazards. Ingestion No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact No specific data. Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

### SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical powder.

**Unsuitable extinguishing** 

media

: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : May form explosible dust-air mixture if dispersed.

**Hazardous combustion** 

products

: Decomposition products may include the following materials:

metal oxide/oxides

### 5.3 Advice for firefighters

fighters

Special precautions for fire- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

3/11

Code : 00332950 Date of issue/Date of revision : 17 December 2019

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### **SECTION 5: Firefighting measures**

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

English (GB) United Arab Emirates 4/11

Date of issue/Date of revision Code : 00332950 : 17 December 2019

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### SECTION 7: Handling and storage

### 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations : Not available. : Not available. **Industrial sector specific** 

solutions

### SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

### Occupational exposure limits

Product/ingredient name	Exposure limit values	
Quartz (SiO2)	ACGIH TLV (United States, 3/2019). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction	

### **Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### 8.2 Exposure controls

**Appropriate engineering** controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety glasses with side shields.

English (GB) **United Arab Emirates** 5/11

: 00332950 Date of issue/Date of revision : 17 December 2019 Code

SIGMAGUARD CSF 650 (AMERCOAT 2209) FILLER

### SECTION 8: Exposure controls/personal protection

**Skin protection** 

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products if a risk assessment indicates

this is necessary.

**Gloves** : nitrile rubber, butyl rubber, PVC, Viton®

: Personal protective equipment for the body should be selected based on the task **Body protection** 

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection** Respirator selection must be based on known or anticipated exposure levels, the

> hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Solid. Powder. **Product type** Colour : White. Odourless. **Odour** : Not available. **Odour threshold** : insoluble in water. pН : Not available.

Melting point/freezing point Initial boiling point and boiling

range

: Not available.

: Closed cup: Not applicable. Flash point

: Not available. **Evaporation rate** Flammability (solid, gas) : Not available.

Upper/lower flammability or

explosive limits

: 10 g/m<sup>3</sup>

: Highest known value: 0 kPa (0 mm Hg) (at 20°C) (crystalline silica, respirable Vapour pressure

powder (>10 microns)).

: 2.65 **Relative density** 

Solubility(ies) Insoluble in the following materials: cold water.

Partition coefficient: n-octanol/ : Not applicable.

water

**Auto-ignition temperature** : Not available.

**Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

: Kinematic (40°C): Not applicable. **Viscosity** 

**Explosive properties** : Product does not present an explosion hazard. **Oxidising properties** : Product does not present an oxidizing hazard.

> English (GB) **United Arab Emirates** 6/11

Code : 00332950 Date of issue/Date of revision : 17 December 2019

SIGMAGUARD CSF 650 (AMERCOAT 2209) FILLER

### SECTION 9: Physical and chemical properties

#### 9.2 Other information

No additional information.

### **SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

**10.5** Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous : Depending on conditions, decomposition products may include the following

materials: metal oxide/oxides

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

**Acute toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Acute toxicity estimates** 

decomposition products

Not available.

#### **Irritation/Corrosion**

Conclusion/Summary

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitisation** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

English (GB) United Arab Emirates 7/11

Code : 00332950 Date of issue/Date of revision : 17 December 2019

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### **SECTION 11: Toxicological information**

Not available.

**Aspiration hazard** 

Not available.

Information on likely

: Not available.

routes of exposure

Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Ingestion : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

**Eye contact**: Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion: No specific data.Skin contact: No specific data.

**Eye contact**: Adverse symptoms may include the following:

irritation redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not

effects

: Not available.

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Other information : Not available.

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

English (GB) United Arab Emirates 8/11

Code : 00332950 Date of issue/Date of revision : 17 December 2019

SIGMAGUARD CSF 650 (AMERCOAT 2209) FILLER

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

### 12.2 Persistence and degradability

**Conclusion/Summary**: There are no data available on the mixture itself.

### 12.3 Bioaccumulative potential

Not available.

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### **12.6 Other adverse effects**: No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

### **Hazardous waste**

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

### **European waste catalogue (EWC)**

Waste code	Waste designation	
08 02 01	waste coating powders	

#### **Packaging**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging

### **Special precautions**

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

English (GB)	United Arab Emirates	9/11
--------------	----------------------	------

: 00332950 Date of issue/Date of revision : 17 December 2019 Code

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

ADR/RID : None identified. **IMDG** : None identified. **IATA** : None identified.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable.

### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XIV - List of substances subject to authorisation** 

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** : Not applicable.

on the manufacture,

placing on the market and

use of certain dangerous substances, mixtures and

articles

Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

**United Arab Emirates** English (GB) 10/11

Code : 00332950 Date of issue/Date of revision : 17 December 2019

SIGMAGUARD CSF 650 ( AMERCOAT 2209 ) FILLER

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Full text of abbreviated H

statements

: Not applicable.

**Full text of classifications** 

[CLP/GHS]

: Not applicable.

**History** 

Date of issue/ Date of

revision

: 17 December 2019

Date of previous issue : No previous validation

Prepared by : EHS Version : 1

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) United Arab Emirates 11/11