

# SAFETY DATA SHEET



Date of issue/Date of revision : 6 January 2020 Version : 14.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMAFAST 302 HARDENER

**Product code** : 00283313

**Other means of identification**

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** : Hardener.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person responsible for this SDS** : PMC.Safety@PPG.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Poison Information Centre; emergency telephone, public + 45 82 12 12 12 (health sector +45 35 31 55 55)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 2, H225

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms :



Signal word :

Danger

Hazard statements :

Highly flammable liquid and vapour.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

### Precautionary statements

Prevention :

Wear protective gloves. Wear protective clothing. Wear eye or face protection.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking. Do not breathe vapour.

Response :

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage :

Store in a well-ventilated place. Keep cool.

Disposal :

Not applicable.

Hazardous ingredients

Quartz (SiO<sub>2</sub>)  
2,4,6-tris(dimethylaminomethyl)phenol  
ethylenediamine

Supplemental label elements :

Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Not applicable.

Tactile warning of danger :

Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification :

Prolonged or repeated contact may dry skin and cause irritation.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name                | Identifiers  | % by weight  | Classification<br>Regulation (EC) No.<br>1272/2008 [CLP]   | Type        |
|--|--|--------------|--|-------------|
| Quartz (SiO <sub>2</sub> )             | EC: 238-878-4<br>CAS: 14808-60-7   | ≥10 - ≤25    | STOT RE 1, H372<br>(inhalation)  | [1] [2]     |
| propan-2-ol                            | REACH #: 01-2119457558-25<br>EC: 200-661-7<br>CAS: 67-63-0   | ≥5.0 - ≤10   | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336  | [1] [2]     |
| xylene                                 | Index: 603-117-00-0<br>REACH #: 01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | ≥5.0 - ≤10   | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304    | [1] [2]     |
| 2,4,6-tris(dimethylaminomethyl) phenol | REACH #: 01-2119560597-27<br>EC: 202-013-9<br>CAS: 90-72-2<br>Index: 603-069-00-0                          | ≥1.0 - <3.0  | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317   | [1]         |
| zinc oxide                             | REACH #: 01-2119463881-32<br>EC: 215-222-5<br>CAS: 1314-13-2<br>Index: 030-013-00-7                        | ≥0.30 - <2.5 | Aquatic Acute 1, H400<br>(M=1)<br>Aquatic Chronic 1, H410<br>(M=1)   | [1]         |
| ethylbenzene                           | REACH #: 01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4                         | ≥1.0 - ≤5.0  | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373<br>(hearing organs)<br>Asp. Tox. 1, H304   | [1] [2]     |
| ethylenediamine                        | REACH #: 01-2119480383-37<br>EC: 203-468-6<br>CAS: 107-15-3<br>Index: 612-006-00-6                         | ≤0.30        | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1, H334<br>Skin Sens. 1, H317 | [1] [2] [5] |
|  |  |              | <b>See Section 16 for the full text of the H statements declared above.</b>  |             |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

### SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name    | Exposure limit values  |
|----------------------------|--|
| Quartz (SiO <sub>2</sub> ) | <b>Working Environment Authority (Denmark, 5/2018). Carcinogen.</b>  |
| propan-2-ol                | TWA: 0.1 mg/m <sup>3</sup> 8 hours. Form: total respirable fraction<br><b>Working Environment Authority (Denmark, 5/2018). Absorbed through skin.</b>                                |
| xylene                     | TWA: 490 mg/m <sup>3</sup> 8 hours.<br>TWA: 200 ppm 8 hours.<br><b>Working Environment Authority (Denmark, 5/2018). Absorbed through skin.</b>                                       |
| ethylbenzene               | TWA: 109 mg/m <sup>3</sup> 8 hours.<br>TWA: 25 ppm 8 hours.<br><b>Working Environment Authority (Denmark, 5/2018). Absorbed through skin. Carcinogen.</b>                            |
| ethylenediamine            | TWA: 217 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours.<br><b>Working Environment Authority (Denmark, 5/2018).</b><br>TWA: 25 mg/m <sup>3</sup> 8 hours.<br>TWA: 10 ppm 8 hours. |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs

| Product/ingredient name | Type | Exposure              | Value                  | Population         | Effects  |
|-------------------------|------|-----------------------|------------------------|--------------------|----------|
| propan-2-ol             | DNEL | Long term Oral        | 26 mg/kg bw/day        | General population | Systemic |
|                         | DNEL | Long term Inhalation  | 89 mg/m <sup>3</sup>   | General population | Systemic |
|                         | DNEL | Long term Dermal      | 319 mg/kg bw/day       | General population | Systemic |
| xylene                  | DNEL | Long term Inhalation  | 500 mg/m <sup>3</sup>  | Workers            | Systemic |
|                         | DNEL | Long term Dermal      | 888 mg/kg bw/day       | Workers            | Systemic |
|                         | DNEL | Short term Inhalation | 260 mg/m <sup>3</sup>  | General population | Systemic |
|                         | DNEL | Short term Inhalation | 260 mg/m <sup>3</sup>  | General population | Local    |
|                         | DNEL | Long term Dermal      | 125 mg/kg bw/day       | General population | Systemic |
|                         | DNEL | Long term Inhalation  | 65.3 mg/m <sup>3</sup> | General population | Systemic |



Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

### SECTION 8: Exposure controls/personal protection

|                 |                      |                       |                        |                    |          |
|-----------------|----------------------|-----------------------|------------------------|--------------------|----------|
| zinc oxide      | DNEL                 | Long term Oral        | 12.5 mg/kg bw/day      | General population | Systemic |
|                 | DNEL                 | Long term Inhalation  | 221 mg/m <sup>3</sup>  | Workers            | Systemic |
|                 | DNEL                 | Short term Inhalation | 442 mg/m <sup>3</sup>  | Workers            | Systemic |
|                 | DNEL                 | Long term Inhalation  | 221 mg/m <sup>3</sup>  | Workers            | Local    |
|                 | DNEL                 | Short term Inhalation | 442 mg/m <sup>3</sup>  | Workers            | Local    |
|                 | DNEL                 | Long term Dermal      | 212 mg/kg bw/day       | Workers            | Systemic |
|                 | DNEL                 | Long term Inhalation  | 0.5 mg/m <sup>3</sup>  | Workers            | Local    |
|                 | DNEL                 | Long term Oral        | 0.83 mg/kg bw/day      | General population | Systemic |
|                 | DNEL                 | Long term Inhalation  | 2.5 mg/m <sup>3</sup>  | General population | Systemic |
|                 | DNEL                 | Long term Inhalation  | 5 mg/m <sup>3</sup>    | Workers            | Systemic |
| ethylbenzene    | DNEL                 | Long term Dermal      | 83 mg/kg bw/day        | General population | Systemic |
|                 | DNEL                 | Long term Oral        | 1.6 mg/kg bw/day       | Workers            | Systemic |
|                 | DNEL                 | Long term Inhalation  | 15 mg/m <sup>3</sup>   | General population | Systemic |
| ethylenediamine | DNEL                 | Long term Inhalation  | 77 mg/m <sup>3</sup>   | Workers            | Systemic |
|                 | DNEL                 | Long term Dermal      | 180 mg/kg bw/day       | Workers            | Systemic |
|                 | DNEL                 | Short term Inhalation | 293 mg/m <sup>3</sup>  | Workers            | Local    |
|                 | DNEL                 | Long term Oral        | 0.275 mg/kg bw/day     | General population | Systemic |
|                 | DNEL                 | Long term Dermal      | 3.6 mg/kg bw/day       | Workers            | Systemic |
|                 | DNEL                 | Long term Inhalation  | 12.5 mg/m <sup>3</sup> | General population | Systemic |
| DNEL            | Long term Inhalation | 25 mg/m <sup>3</sup>  | Workers                | Systemic           |          |

#### PNECs

| Product/ingredient name | Type | Compartment Detail     | Value           | Method Detail            |
|-------------------------|------|------------------------|-----------------|--------------------------|
| propan-2-ol             | -    | Fresh water            | 140.9 mg/l      | Assessment Factors       |
|                         | -    | Marine water           | 140.9 mg/l      | Assessment Factors       |
|                         | -    | Secondary Poisoning    | 160 mg/kg       | -                        |
|                         | -    | Fresh water sediment   | 552 mg/kg dwt   | -                        |
|                         | -    | Marine water sediment  | 552 mg/kg dwt   | -                        |
|                         | -    | Sewage Treatment Plant | 2251 mg/l       | Assessment Factors       |
| xylene                  | -    | Soil                   | 28 mg/kg dwt    | -                        |
|                         | -    | Fresh water            | 0.327 mg/l      | -                        |
|                         | -    | Marine water           | 0.327 mg/l      | -                        |
|                         | -    | Sewage Treatment Plant | 6.58 mg/l       | -                        |
|                         | -    | Fresh water sediment   | 12.46 mg/kg dwt | -                        |
|                         | -    | Marine water sediment  | 12.46 mg/kg dwt | -                        |
| zinc oxide              | -    | Soil                   | 2.31 mg/kg      | -                        |
|                         | -    | Fresh water            | 20.6 µg/l       | Sensitivity Distribution |
|                         | -    | Marine water           | 6.1 µg/l        | Sensitivity Distribution |
|                         | -    | Fresh water sediment   | 117 mg/kg dwt   | Sensitivity Distribution |
|                         | -    | Sewage Treatment Plant | 52 µg/l         | Assessment Factors       |
|                         | -    | Marine water sediment  | 56.5 mg/kg dwt  | Assessment Factors       |
| ethylbenzene            | -    | Soil                   | 35.6 mg/kg dwt  | Sensitivity Distribution |
|                         | -    | Fresh water            | 0.1 mg/l        | Assessment Factors       |
|                         | -    | Marine water           | 0.01 mg/l       | Assessment Factors       |
|                         | -    | Sewage Treatment Plant | 9.6 mg/l        | Assessment Factors       |



|                        |   |
|------------------------|---|
| Code : 00283313        | Date of issue/Date of revision : 6 January 2020 |
| SIGMAFAST 302 HARDENER |   |

## SECTION 8: Exposure controls/personal protection

|   |                       |                |                          |
|---|-----------------------|----------------|--------------------------|
| - | Fresh water sediment  | 13.7 mg/kg dwt | Equilibrium Partitioning |
| - | Marine water sediment | 1.37 mg/kg dwt | Equilibrium Partitioning |
| - | Soil                  | 2.68 mg/kg dwt | Equilibrium Partitioning |
| - | Secondary Poisoning   | 20 mg/kg       | -                        |

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : By spraying: air-fed respirator. By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Code : 00283313 Date of issue/Date of revision : 6 January 2020  
 SIGMAFAST 302 HARDENER

## SECTION 8: Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.  
**Colour** : Not available.  
**Odour** : Amine-like. [Strong]  
**Odour threshold** : Not available.  
**pH** : insoluble in water.  
**Melting point/freezing point** : May start to solidify at the following temperature: <-20.15°C (<-4.3°F) This is based on data for the following ingredient: 2,4,6-tris(dimethylaminomethyl)phenol. Weighted average: -79.92°C (-111.9°F)  
**Initial boiling point and boiling range** : >37.78°C  
**Flash point** : Closed cup: 16°C  
**Evaporation rate** : Highest known value: 1.7 (Isopropyl alcohol) Weighted average: 1.27 compared with butyl acetate  
**Flammability (solid, gas)** : liquid  
**Upper/lower flammability or explosive limits** : Greatest known range: Lower: 2% Upper: 12% (Isopropyl alcohol)  
**Vapour pressure** : Highest known value: 4.4 kPa (33 mm Hg) (at 20°C) (Isopropyl alcohol). Weighted average: 2.29 kPa (17.18 mm Hg) (at 20°C)  
**Vapour density** : Highest known value: 3.7 (Air = 1) (xylene). Weighted average: 2.85 (Air = 1)  
**Relative density** : 1.64  
**Solubility(ies)** : Insoluble in the following materials: cold water.  
**Partition coefficient: n-octanol/ water** : Not applicable.  
**Auto-ignition temperature** : Lowest known value: 382°C (719.6°F) (2,4,6-tris(dimethylaminomethyl)phenol).  
**Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).  
**Viscosity** : Kinematic (40°C): >0.21 cm<sup>2</sup>/s  
**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.  
**Oxidising properties** : Product does not present an oxidizing hazard.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.  
**10.2 Chemical stability** : The product is stable.  
**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

Code : 00283313 Date of issue/Date of revision : 6 January 2020  
 SIGMAFAST 302 HARDENER

## SECTION 10: Stability and reactivity

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
 Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name               | Result                          | Species | Dose                    | Exposure |
|---------------------------------------|---------------------------------|---------|-------------------------|----------|
| propan-2-ol                           | LC50 Inhalation Vapour          | Rat     | 72600 mg/m <sup>3</sup> | 4 hours  |
|                                       | LD50 Dermal                     | Rabbit  | 12800 mg/kg             | -        |
|                                       | LD50 Oral                       | Rat     | 4.396 g/kg              | -        |
| xylene                                | LD50 Dermal                     | Rabbit  | >1.7 g/kg               | -        |
|                                       | LD50 Oral                       | Rat     | 4.3 g/kg                | -        |
|                                       | LD50 Dermal                     | Rabbit  | 1.28 g/kg               | -        |
| 2,4,6-tris(dimethylaminomethyl)phenol | LD50 Dermal                     | Rat     | 1280 mg/kg              | -        |
|                                       | LD50 Dermal                     | Rat     | 1200 mg/kg              | -        |
|                                       | LD50 Oral                       | Rat     | 1200 mg/kg              | -        |
| zinc oxide                            | LC50 Inhalation Dusts and mists | Rat     | >5700 mg/m <sup>3</sup> | 4 hours  |
|                                       | LD50 Dermal                     | Rat     | >2000 mg/kg             | -        |
|                                       | LD50 Oral                       | Rat     | >5000 mg/kg             | -        |
| ethylbenzene                          | LC50 Inhalation Vapour          | Rat     | 17.8 mg/l               | 4 hours  |
|                                       | LD50 Dermal                     | Rabbit  | 17.8 g/kg               | -        |
|                                       | LD50 Oral                       | Rat     | 3.5 g/kg                | -        |
| ethylenediamine                       | LD50 Dermal                     | Rabbit  | 0.73 g/kg               | -        |
|                                       | LD50 Oral                       | Rat     | 0.5 g/kg                | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Oral                 | 40735.69 mg/kg |
| Dermal               | 13898.97 mg/kg |
| Inhalation (vapours) | 182.1 mg/l     |

#### Irritation/Corrosion

| Product/ingredient name               | Result                   | Species | Score | Exposure        | Observation |
|---------------------------------------|--------------------------|---------|-------|-----------------|-------------|
| xylene                                | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| 2,4,6-tris(dimethylaminomethyl)phenol | Skin - Visible necrosis  | Rabbit  | -     | 4 hours         | 7 days      |

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitisation

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 11: Toxicological information

| Product/ingredient name               | Route of exposure | Species    | Result      |
|---------------------------------------|-------------------|------------|-------------|
| 2,4,6-tris(dimethylaminomethyl)phenol | skin              | Guinea pig | Sensitising |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.  
**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| propan-2-ol             | Category 3 | Not applicable.   | Narcotic effects             |
| xylene                  | Category 3 | Not applicable.   | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name                             | Category   | Route of exposure | Target organs  |
|---|------------|-------------------|----------------|
| crystalline silica, respirable powder (<10 microns) | Category 1 | Inhalation        | Not determined |
| ethylbenzene  | Category 2 | Not determined    | hearing organs |

### Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.  
**Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : No specific data.  
**Ingestion** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 11: Toxicological information

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2,4,6-tris(dimethylaminomethyl)phenol, ethylenediamine. May produce an allergic reaction.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name               | Result  | Species                                    | Exposure             |
|---------------------------------------|---|--|----------------------|
| propan-2-ol                           | Acute EC50 10100 mg/l<br>Fresh water  | Daphnia - Daphnia magna                    | 48 hours             |
| 2,4,6-tris(dimethylaminomethyl)phenol | Acute LC50 175 mg/l   | Fish                                       | 96 hours             |
| zinc oxide                            | Acute EC50 0.17 mg/l<br>Acute EC50 0.481 mg/l<br>Fresh water                        | Algae<br>Daphnia - Daphnia magna - Neonate | 72 hours<br>48 hours |
| ethylbenzene                          | Chronic NOEC 0.017 mg/l<br>Fresh water<br>Acute LC50 150 to 200 mg/l<br>Fresh water | Algae<br>Fish                              | 72 hours<br>96 hours |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

**Conclusion/Summary** : There are no data available on the mixture itself.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |
| ethylbenzene            | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| propan-2-ol             | 0.05               | -           | low       |
| xylene                  | 3.16               | 7.4 to 18.5 | low       |
| ethylbenzene            | 3.15               | 79.43       | low       |
| ethylenediamine         | -2.04              | -           | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number                  | UN1263          | UN1263          | UN1263          | UN1263          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 3               | 3               | 3               | 3               |
| 14.4 Packing group              | II              | II              | II              | II              |
| 14.5 Environmental hazards      | No.             | Yes.            | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

### Additional information

**ADR/RID** : None identified.

**Tunnel code** : (D/E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

**IMDG** : None identified.

**IATA** : None identified.



Code : 00283313 Date of issue/Date of revision : 6 January 2020  
 SIGMAFAST 302 HARDENER

## 14. Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

##### Substances of very high concern

| Ingredient name | Intrinsic property                               | Status    | Reference number | Date of revision |
|-----------------|--|-----------|------------------|------------------|
| ethylenediamine | Substance of equivalent concern for human health | Candidate | ED/61/2018       | 6/27/2018        |

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

##### Ozone depleting substances (1005/2009/EU)

Not listed.

##### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

| Category |
|----------|
| P5c      |

### National regulations

| Product/ingredient name    | List name                            | Name on list                             | Classification | Notes |
|----------------------------|--------------------------------------|--|----------------|-------|
| Quartz (SiO <sub>2</sub> ) | Denmark<br>Carcinogenic<br>Chemicals | Krystallinsk<br>siliciumdioxid; α-Kvarts | Listed         | -     |
| ethylbenzene               | Denmark<br>Carcinogenic<br>Chemicals | Ethylbenzen                              | Listed         | -     |

**Product registration number** : PR-1768653

**Danish fire class** : I-1

**Denmark – Cancer risks** : National Working Environment Authorities Ordinance on Measures to Prevent Cancer Risks during Work with Substances and Preparations is applicable.

**MAL-code** : 3-6

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 15: Regulatory information

**Protection based on MAL** : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, respiratory protection with air supply and arm protectors/apron/coveralls/protective clothing must be worn as appropriate or as instructed.

MAL-code: 3-6

**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask, protective clothing and eye protection must be worn.

When spraying in new\* booths if the operator is outside the spray zone.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone. During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

Code : 00283313  
SIGMAFAST 302 HARDENER

Date of issue/Date of revision : 6 January 2020

## SECTION 15: Regulatory information

\*See Regulations.

- Low-boiling liquids** : This product contains low-boiling point liquids. Any respiratory protective equipment should be air-fed.
- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 PBT = Persistent, Bioaccumulative and Toxic  
 vPvB = Very Persistent and Very Bioaccumulative  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 IMDG = International Maritime Dangerous Goods  
 IATA = International Air Transport Association

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification          | Justification         |
|-------------------------|-----------------------|
| Flam. Liq. 2, H225      | On basis of test data |
| Skin Irrit. 2, H315     | Calculation method    |
| Eye Irrit. 2, H319      | Calculation method    |
| Skin Sens. 1, H317      | Calculation method    |
| STOT RE 1, H372         | Calculation method    |
| Aquatic Chronic 3, H412 | Calculation method    |

### Full text of abbreviated H statements

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.  |
| H226 | Flammable liquid and vapour.   |
| H302 | Harmful if swallowed.  |
| H304 | May be fatal if swallowed and enters airways.                              |
| H312 | Harmful in contact with skin.  |
| H314 | Causes severe skin burns and eye damage.                                   |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.                                       |
| H318 | Causes serious eye damage.   |
| H319 | Causes serious eye irritation.   |
| H332 | Harmful if inhaled.  |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation.  |

|                               |  |
|-------------------------------|--|
| <b>Code</b> : 00283313        | <b>Date of issue/Date of revision</b> : 6 January 2020 |
| <b>SIGMAFAST 302 HARDENER</b> |  |

**SECTION 16: Other information**

|                   |  |
|-------------------|--|
| H336              | May cause drowsiness or dizziness.   |
| H372 (inhalation) | Causes damage to organs through prolonged or repeated exposure if inhaled. |
| H372              | Causes damage to organs through prolonged or repeated exposure.            |
| H373              | May cause damage to organs through prolonged or repeated exposure.         |
| H400              | Very toxic to aquatic life.  |
| H410              | Very toxic to aquatic life with long lasting effects.                      |
| H412              | Harmful to aquatic life with long lasting effects.                         |

**Full text of classifications [CLP/GHS]**

|                              |  |
|------------------------------|--|
| Acute Tox. 4, H302           | ACUTE TOXICITY (oral) - Category 4   |
| Acute Tox. 4, H312           | ACUTE TOXICITY (dermal) - Category 4   |
| Acute Tox. 4, H332           | ACUTE TOXICITY (inhalation) - Category 4   |
| Aquatic Acute 1, H400        | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1   |
| Aquatic Chronic 1, H410      | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1  |
| Aquatic Chronic 3, H412      | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  |
| Asp. Tox. 1, H304            | ASPIRATION HAZARD - Category 1   |
| Eye Dam. 1, H318             | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1   |
| Eye Irrit. 2, H319           | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2   |
| Flam. Liq. 2, H225           | FLAMMABLE LIQUIDS - Category 2   |
| Flam. Liq. 3, H226           | FLAMMABLE LIQUIDS - Category 3   |
| Resp. Sens. 1, H334          | RESPIRATORY SENSITISATION - Category 1   |
| Skin Corr. 1B, H314          | SKIN CORROSION/IRRITATION - Category 1B  |
| Skin Corr. 1C, H314          | SKIN CORROSION/IRRITATION - Category 1C  |
| Skin Irrit. 2, H315          | SKIN CORROSION/IRRITATION - Category 2   |
| Skin Sens. 1, H317           | SKIN SENSITISATION - Category 1  |
| Skin Sens. 1B, H317          | SKIN SENSITISATION - Category 1B   |
| STOT RE 1, H372 (inhalation) | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (inhalation) - Category 1                 |
| STOT RE 1, H372              | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1                              |
| STOT RE 2, H373              | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2                              |
| STOT SE 3, H335              | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3 |
| STOT SE 3, H336              | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3             |

**History**

**Date of issue/ Date of revision** : 6 January 2020

**Date of previous issue** : 12 October 2019

**Prepared by** : EHS

**Version** : 14.01

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*