

Date of issue 1/15/2020 (month/day/year)

Version 6.01

## Section 1. Chemical product and company identification

A. **Product name** : PSX 700 BASE N7.0  
**Product code** : 00350727

B. **Relevant identified uses of the substance or mixture and uses advised against**

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating. Paint. Painting-related materials.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

C. **Supplier's information** : PPG SSC  
(680-090)  
19, Yeocheon-ro 217beon-gil, Nam-gu,  
Ulsan, Korea  
Tel: +82-52-210-8222

**Email Address** : Korea.MSDS@PPG.COM

**Emergency telephone  
number:** : +82-52-210-8222

## Section 2. Hazards identification

A. **Hazard classification** : SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 2  
AQUATIC HAZARD (LONG-TERM) - Category 3

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. **GHS label elements, including precautionary statements**

**Symbol** :



**Signal word** : Warning

**Hazard statements** : H317 - May cause an allergic skin reaction.  
H351 - Suspected of causing cancer.  
H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements**

## Section 2. Hazards identification

- Prevention** : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapor.  
P272 - Contaminated work clothing should not be allowed out of the workplace.
- Response** : P308 + P313 - IF exposed or concerned: Get medical attention.  
P302 + P352 + P362 + P364 - IF ON SKIN: Wash with plenty of soap and water.  
Take off contaminated clothing and wash it before reuse.  
P333 + P313 - If skin irritation or rash occurs: Get medical attention.
- Storage** : P405 - Store locked up.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**C. Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

### CAS number/other identifiers

**CAS number** : Not applicable.

| Chemical name                                                                                  | Common name                                                                      | Identifiers     | %        |
|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|-----------------|----------|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with (chloromethyl)oxirane | CAS: 30583-72-3 | 20 - <30 |
| titanium dioxide                                                                               | TITANIUM DIOXIDE                                                                 | CAS: 13463-67-7 | 10 - <20 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate                                                | BIS(PENTAMETHYLPIPERIDYL) SEBACATE                                               | CAS: 41556-26-7 | 1 - <5   |
| silicon dioxide                                                                                | SILICA                                                                           | CAS: 7631-86-9  | 1 - <5   |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate                                              | METHYL-(1,2,2,6,6-PENTAMETHYL-4-PIPERIDIYL) SEBACATE                             | CAS: 82919-37-7 | 0.1 - <1 |
| Toluene                                                                                        | Toluene                                                                          | CAS: 108-88-3   | 0.1 - <1 |
| carbon black, respirable powder                                                                | CARBON BLACK                                                                     | CAS: 1333-86-4  | 0.1 - <1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

- A. Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- B. Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

## Section 4. First aid measures

- C. Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- D. Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- E. Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

- A. Extinguishing media**
- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.
- B. Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides
- C. Special equipment for fire-fighting** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire-fighting procedures** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

## Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

## Section 6. Accidental release measures

**B. Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### C. Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

**A. Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**B. Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

**A. Occupational exposure limits**

## Section 8. Exposure controls/personal protection

| Ingredient name                 | Exposure limits                                                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| titanium dioxide                | <b>Ministry of Employment and Labor (Republic of Korea, 7/2018).</b><br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: total dust with less than 1% of free SiO <sub>2</sub> |
| Toluene                         | <b>Ministry of Employment and Labor (Republic of Korea, 7/2018).</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 50 ppm 8 hours.                                              |
| carbon black, respirable powder | <b>Ministry of Employment and Labor (Republic of Korea, 7/2018).</b><br>TWA: 3.5 mg/m <sup>3</sup> 8 hours. Form: inhalable fraction                                   |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**B. Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### C. Personal protective equipment

**Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Eye protection** : Safety glasses with side shields.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 9. Physical and chemical properties

- A. Appearance**
- Physical state** : Liquid.
  - Color** : Not available.
- B. Odor** : Characteristic.
- C. Odor threshold** : Not available.
- D. pH** : Not available.
- E. Melting/freezing point** : Not available.
- F. Boiling point/boiling range** : >37.78°C (>100°F)
- G. Flash point** : Closed cup: Not applicable.
- H. Evaporation rate** : Not available.
- I. Flammability (solid, gas)** : Not available.
- J. Lower and upper explosive (flammable) limits** : Not available.
- K. Vapor pressure** : Not available.
- L. Solubility** : Insoluble in the following materials: cold water.
- M. Vapor density** : Not available.
- N. Relative density** : 1.43
- O. Partition coefficient: n-octanol/water** : Not available.
- P. Auto-ignition temperature** : Not available.
- Q. Decomposition temperature** : Not available.
- R. Viscosity** : Kinematic (40°C (104°F)): >0.21 cm<sup>2</sup>/s (>21 cSt)
- S. Molecular weight** : Not applicable.

## Section 10. Stability and reactivity

- A. Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- B. Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

## Section 10. Stability and reactivity

**C. Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**D. Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

**A. Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Eye contact** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Inhalation** : No specific data.

**Ingestion** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**Eye contact** : No specific data.

### B. Health hazards

#### Acute toxicity

| Product/ingredient name                           | Result                          | Species            | Dose                | Exposure |
|---------------------------------------------------|---------------------------------|--------------------|---------------------|----------|
| titanium dioxide                                  | LC50 Inhalation Dusts and mists | Rat                | >6.82 mg/l          | 4 hours  |
|                                                   | LD50 Dermal                     | Rabbit             | >5000 mg/kg         | -        |
|                                                   | LD50 Oral                       | Rat                | >5000 mg/kg         | -        |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   | LD50 Oral                       | Rat                | 3.125 g/kg          | -        |
|                                                   | silicon dioxide                 | Rabbit             | >5000 mg/kg         | -        |
| LD50 Oral                                         |                                 | Rat - Male, Female | >5000 mg/kg         | -        |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | LD50 Oral                       | Rat                | 3.125 g/kg          | -        |
|                                                   | Toluene                         | Rat                | 49 g/m <sup>3</sup> | 4 hours  |
| LD50 Dermal                                       |                                 | Rabbit             | 8.39 g/kg           | -        |
| LD50 Oral                                         |                                 | Rat                | 5580 mg/kg          | -        |
| carbon black, respirable powder                   | LD50 Dermal                     | Rabbit             | >3 g/kg             | -        |
|                                                   | LD50 Oral                       | Rat                | >15400 mg/kg        | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

##### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

## Section 11. Toxicological information

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name    | Classification | Route of exposure | Target organs    |
|---------|----------------|-------------------|------------------|
| Toluene | Category 3     | Not applicable.   | Narcotic effects |

### Specific target organ toxicity (repeated exposure)

| Name    | Classification | Route of exposure | Target organs  |
|---------|----------------|-------------------|----------------|
| Toluene | Category 2     | Not determined    | Not determined |

### Aspiration hazard

| Name    | Result                         |
|---------|--------------------------------|
| Toluene | ASPIRATION HAZARD - Category 1 |

### Potential chronic health effects

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Additional information

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.



## Section 11. Toxicological information

| Chemical name                                                                                  | Common name                                                                      | CAS #                    | GHS Classification                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | cyclohexanol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl) oxirane | 30583-72-3               | SKIN SENSITIZATION - Category 1<br><br>AQUATIC HAZARD (LONG-TERM) - Category 3                                                                                                                                                                                                                                                                                                                           |
| titanium dioxide bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate                               | TITANIUM DIOXIDE BIS (PENTAMETHYLPIPERIDYL) SEBACATE                             | 13463-67-7<br>41556-26-7 | CARCINOGENICITY - Category 2<br>SKIN SENSITIZATION - Category 1<br><br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1                                                                                                                                                                                                                                                    |
| silicon dioxide methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate                              | SILICA METHYL-(1,2,2,6,6-PENTAMETHYL-4-PIPERIDIYL) SEBACATE                      | 7631-86-9<br>82919-37-7  | Not classified.<br>SKIN SENSITIZATION - Category 1<br><br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 1                                                                                                                                                                                                                                                                 |
| Toluene                                                                                        | Toluene                                                                          | 108-88-3                 | FLAMMABLE LIQUIDS - Category 2<br>SKIN CORROSION/IRRITATION - Category 2<br>TOXIC TO REPRODUCTION (Fertility) - Category 2<br>TOXIC TO REPRODUCTION (Unborn child) - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>ASPIRATION HAZARD - Category 1<br>CARCINOGENICITY - Category 2 |
| carbon black, respirable powder                                                                | CARBON BLACK                                                                     | 1333-86-4                | CARCINOGENICITY - Category 2                                                                                                                                                                                                                                                                                                                                                                             |

## Section 12. Ecological information

### A. Ecotoxicity

| Product/ingredient name                                                                        | Result                           | Species                 | Exposure |
|------------------------------------------------------------------------------------------------|----------------------------------|-------------------------|----------|
| 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane | LC50 11.5 mg/l                   | Fish                    | 96 hours |
| titanium dioxide                                                                               | Acute LC50 >100 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| silicon dioxide                                                                                | Acute LC50 >10000 mg/l           | Fish                    | 96 hours |

### B. Persistence and degradability

## Section 12. Ecological information

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Toluene                 | -                 | -          | Readily          |

### C. Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF  | Potential |
|-------------------------|--------------------|------|-----------|
| Toluene                 | 2.73               | 8.32 | low       |

### D. Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

E. Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**A. Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**B. Disposal precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                       | UN              | IMDG            | IATA            |
|---------------------------------------|-----------------|-----------------|-----------------|
| <b>A. UN number</b>                   | Not regulated.  | Not regulated.  | Not regulated.  |
| <b>B. UN proper shipping name</b>     | -               | -               | -               |
| <b>C. Transport hazard class(es)</b>  | -               | -               | -               |
| <b>D. Packing group</b>               | -               | -               | -               |
| <b>Environmental hazards</b>          | No.             | No.             | No.             |
| <b>E. Marine pollutant substances</b> | Not applicable. | Not applicable. | Not applicable. |

### Additional information

UN : None identified.

IMDG : None identified.

## Section 14. Transport information

IATA : None identified.

### F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

### A. Regulation according to ISHA

**ISHA article 37 (Harmful substances prohibited from manufacture)** : None of the components are listed.

**ISHA article 38 (Harmful substances requiring permission)** : None of the components are listed.

**Article 2 of Youth Protection Act on Substances Hazardous to Youth** : It is not allowed to sell to persons under the age of 19.

### Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

titanium dioxide

Toluene

carbon black, respirable powder

**ISHA Enforcement Regs Annex 11-3 (Exposure standards established for harmful factors)** : None of the components are listed.

**ISHA Enforcement Regs Annex 11-5 (Harmful factors subject to Work Environment Measurement)** : The following components are listed: Titanium dioxide Preparations containing material at weight ratio more than 1%, Silica (Mineral dust)

**ISHA Enforcement Regs Annex 12-2 (Harmful Factors Subject to Special Health Check-up)** : None of the components are listed.

**Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)** : The following components are listed: titanium dioxide

### B. Regulation according to Chemicals Control Act

**CCA Article 20 Toxic Chemicals (K-Reach Article 20)** : Not applicable

**CCA Article 18 Prohibited (K-Reach Article 27)** : None of the components are listed.

## Section 15. Regulatory information

- CCA Article 20 Restricted (K-Reach Article 27) : None of the components are listed.
- CCA Article 11 (TRI) : The following components are listed: Barium and its compounds
- Korea inventory : All components are listed or exempted.
- CCA Article 39 (Accident Precaution Chemicals) : None of the components are listed.
- C. Dangerous Materials Safety Management Act : Not applicable.
- D. Wastes regulation : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- E. Regulation according to other foreign laws
- Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

## Section 16. Other information

- A. References : Korean Ministry of Environment; Chemical Control Act  
Korean Ministry of Labor; Industrial Safety and Health Act  
NIER Notice  
Registry of Toxic Effects of Chemical Substances (RTECS)  
U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
- B. Date of issue/Date of revision : 1/15/2020
- C. Version : 6.01
- Prepared by : EHS
- D. Other

### Procedure used to derive the classification

| Classification          | Justification      |
|-------------------------|--------------------|
| Skin Sens. 1, H317      | Calculation method |
| Carc. 2, H351           | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Indicates information that has changed from previously issued version.

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*