
SAFETY DATA SHEET



Date of issue 1/15/2020 (month/day/year)

Version 2.05

Section 1. Chemical product and company identification

: ANTISKID BROWN ALUMINUM GRIT A. Product name

Product code : 00604065

B. Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying. Use of the substance/

mixture

Uses advised against

: Coating. Paint. Painting-related materials.

: Product is not intended, labelled or packaged for consumer use.

C. Supplier's information : PPG SSC

(680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

Emergency telephone

number:

Email Address

: +82-52-210-8222

Section 2. Hazards identification

A. Hazard classification : CARCINOGENICITY - Category 2

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol



Signal word : Warning

Hazard statements : H351 - Suspected of causing cancer.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.

> P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.

Response : P308 + P313 - IF exposed or concerned: Get medical attention.

: P405 - Store locked up. **Storage**

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Korea (GHS) Page: 1/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 2. Hazards identification

C. Other hazards which do : None known. not result in

classification

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number : Not applicable.

Chemical name	Common name	Identifiers	%
aluminium oxide	ALUMINUM OXIDE	CAS: 1344-28-1	90 - 100
titanium dioxide	TITANIUM DIOXIDE	CAS: 13463-67-7	1 - <5
Silicic acid, aluminum sodium salt	SODIUM ALUMINUM SILICATE	CAS: 1344-00-9	1 - <5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

A.	Eye contact	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelid	s
		apart for at least 10 minutes and seek immediate medical advice.	

B. Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and
	water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is
	irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by
	trained personnel.

D. Ingestion	: If swallowed, seek medical advice immediately and show this container or label.
	Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Korea (GHS) Page: 2/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 5. Fire-fighting measures

- B. Specific hazards arising from the chemical
- B. Specific hazards arising : No specific fire or explosion hazard.
 - Hazardous thermal decomposition products
- Decomposition products may include the following materials: metal oxide/oxides
- C. Special equipment for fire-fighting
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighting procedures

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- C. Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

- A. Precautions for safe handling
- Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.
- B. Conditions for safe storage, including any incompatibilities
- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Korea (GHS) Page: 3/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
aluminium oxide	Ministry of Employment and Labor
	(Republic of Korea, 7/2018).
	TWA: 10 mg/m ³ 8 hours. Form: total dust
	with less than 1% of free SiO2
titanium dioxide	Ministry of Employment and Labor
	(Republic of Korea, 7/2018).
	TWA: 10 mg/m ³ 8 hours. Form: total dust
	with less than 1% of free SiO2
Silicic acid, aluminum sodium salt	ACGIH TLV (United States, 3/2019).
	TWA: 1 mg/m ³ 8 hours. Form: Respirable
	fraction
	ACGIH TLV (United States, 1/2007).
	TWA: 2 mg/m³, (as Al) 8 hours. Form:
	Soluble

Recommended monitoring procedures

- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- B. Appropriate engineering controls
- : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Eye protection Hand protection

- : Safety glasses with side shields.
- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: butyl rubber, nitrile rubber, PVC

Korea (GHS) Page: 4/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 8. Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

A. Appearance

Physical state : Solid.

Color : Brown. [Dark]

B. Odor : Odorless.

C. Odor threshold : Not available.

D. pH : Not available.

E. Melting/freezing point : Not available.

F. Boiling point/boiling : Not available.

range

G. Flash point : Closed cup: 1850°C (3362°F) [Product does not sustain combustion.]

H. Evaporation rate : Not available.I. Flammability (solid, gas) : Not available.

J. Lower and upper explosive (flammable)

limits

: Not applicable.

K. Vapor pressure : Not available.

L. Solubility : Insoluble in the following materials: cold water.

M. Vapor density : Not available.

N. Relative density : 0

O. Partition coefficient: n-

octanol/water

: Not available.

P. Auto-ignition : Not available.

temperature

Q. Decomposition temperature

: Not available.

R. Viscosity : Kinematic (40°C (104°F)): Not applicable.

S. Molecular weight : Not applicable.

Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Korea (GHS) Page: 5/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 10. Stability and reactivity

C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

D. Hazardous : Depending on conditions, decomposition products may include the following

decomposition products materials: metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely routes of exposure

: Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Eye contact : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.Skin contact: No specific data.Eye contact: No specific data.

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and	Rat	>6.82 mg/l	4 hours
	mists			
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Silicic acid, aluminum sodium salt	LD50 Oral	Rat	>27 g/kg	-

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Korea (GHS) Page: 6/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 11. Toxicological information

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.

Chemical name	Common name	CAS#	GHS Classification
titanium dioxide Silicic acid, aluminum	TITANIUM DIOXIDE	13463-67-7	Not classified. CARCINOGENICITY - Category 2 Not classified.

Section 12. Ecological information

A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Not available.

Korea (GHS) Page: 7/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 12. Ecological information

D. Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	Not regulated.	Not regulated.	Not regulated.
B. UN proper shipping name	-	-	-
C. Transport hazard class(es)	-	-	-
D. Packing group	-	-	-
Environmental hazards	No.	No.	No.
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified.IMDG : None identified.IATA : None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Korea (GHS) Page: 8/10

Product name ANTISKID BROWN ALUMINUM GRIT

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 37 (Harmful

substances prohibited from manufacture)

: None of the components are listed.

ISHA article 38 (Harmful

: None of the components are listed.

substances requiring permission)

Article 2 of Youth Protection

: It is not allowed to sell to persons under the age of 19.

Act on Substances Hazardous to Youth

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

aluminium oxide titanium dioxide

Silicic acid, aluminum sodium salt

ISHA Enforcement Regs

: None of the components are listed.

Annex 11-3 (Exposure standards established for harmful factors)

ISHA Enforcement Regs Annex 11-5 (Harmful factors subject to Work **Environment**

: The following components are listed: Aluminum compounds (Fume), as Al; Preparations containing material at weight ratio more than 1%, Titanium dioxide Preparations containing material at weight ratio more than 1%, Aluminum compounds (Fume), as AI; Preparations containing material at weight ratio more than

Measurement) ISHA Enforcement Regs

Annex 12-2 (Harmful **Factors Subject to**

Special Health Check-up)

Standard of Industrial **Safety and Health Annex** 12 (Hazardous substances subject to

The following components are listed: Aluminum and compounds as Al, Aluminum and compounds as Al

: The following components are listed: aluminum and its compounds, titanium dioxide, aluminum and its compounds

B. Regulation according to Chemicals Control Act

CCA Article 20 Toxic

Chemicals (K-Reach Article 20)

CCA Article 18

control)

: Not applicable

Prohibited (K-Reach

Article 27)

: None of the components are listed.

CCA Article 20 Restricted (K-Reach

Article 27)

: None of the components are listed.

CCA Article 11 (TRI) : The following components are listed: Aluminium and its compounds, Aluminium and its compounds

: All components are listed or exempted. **Korea inventory CCA Article 39 (Accident** : None of the components are listed.

Precaution Chemicals)

Page: 9/10 Korea (GHS)

Product name ANTISKID BROWN ALUMINUM GRIT

Section 15. Regulatory information

C. <u>Dangerous Materials</u> Safety Management Act : Not applicable.

D. Wastes regulation

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

E. Regulation according to other foreign laws

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

NIER Notice

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 1/15/2020

C. Version : 2.05
Prepared by : EHS

D. Other

Procedure used to derive the classification

Classification	Justification
Carc. 2, H351	Calculation method

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 10/10