

# SAFETY DATA SHEET



Date of issue/Date of revision : 15 January 2020 Version : 1.03

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : SIGMATHERM 175

Product code : 00136664

#### Other means of identification

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/  
mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

e-mail address of person  
responsible for this SDS : PMC.Safety@PPG.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number : National Poison Information Centre at Beaumont Hospital. Tel: +353 1 8092566,  
email: npicdublin@beaumont.ie

#### Supplier

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

STOT SE 3, H336

STOT RE 1, H372

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 2: Hazards identification

### 2.2 Label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : Flammable liquid and vapour.  
May cause drowsiness or dizziness.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

### Precautionary statements

Prevention : Wear protective gloves. Wear protective clothing. Wear eye or face protection.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking. Do not breathe vapour.

Response : IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage : Store in a well-ventilated place. Keep cool.

Disposal : Not applicable.

P280, P210, P260, P304 + P340, P303 + P361 + P353, P403, P235

Hazardous ingredients : Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Supplemental label elements : Repeated exposure may cause skin dryness or cracking.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

## SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

### SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	REACH #: 01-2119458049-33 EC: 919-446-0 CAS: 64742-82-1	≥10 - <25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 (central nervous system (CNS)) (inhalation) Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9 (EC 918-481-9)	≥5.0 - ≤10	Asp. Tox. 1, H304 EUH066	[1]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9	≥5.0 - ≤10	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304  <b>See Section 16 for the full text of the H statements declared above.</b>	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-211955267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 5: Firefighting measures

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
xylene	<b>NAOSH (Ireland, 8/2018). Absorbed through skin.</b> OELV-15min: 442 mg/m <sup>3</sup> 15 minutes. OELV-15min: 100 ppm 15 minutes. OELV-8hr: 221 mg/m <sup>3</sup> 8 hours. OELV-8hr: 50 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	DNEL	Long term Inhalation	330 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	44 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	71 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	26 mg/kg bw/day	General population	Systemic
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	208 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	871 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population [Consumers]	Systemic
xylene	DNEL	Long term Inhalation	185 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Oral	125 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local

<b>Code</b> : 00136664	<b>Date of issue/Date of revision</b> : 15 January 2020
<b>SIGMATHERM 175</b>	

## SECTION 8: Exposure controls/personal protection

	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic

### PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
xylene	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
	-			

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: polyvinyl alcohol (PVA), Viton®  
May be used: nitrile rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.



Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Characteristic.
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: -43.77°C (-46.8°F) This is based on data for the following ingredient: 1,2,4-trimethylbenzene. Weighted average: -64.01°C (-83.2°F)
- Initial boiling point and boiling range** : >37.78°C
- Flash point** : Closed cup: 41.3°C
- Evaporation rate** : Highest known value: 0.77 (xylene) Weighted average: 0.25 compared with butyl acetate
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 0.6% Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics )
- Vapour pressure** : Highest known value: 0.9 kPa (6.7 mm Hg) (at 20°C) (xylene). Weighted average: 0.36 kPa (2.7 mm Hg) (at 20°C)
- Vapour density** : Highest known value: 4.4 (Air = 1) (nonane). Weighted average: 4.04 (Air = 1)
- Relative density** : 1.02
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Auto-ignition temperature** : 210°C
- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- Viscosity** : Kinematic (room temperature): >4 cm<sup>2</sup>/s  
Kinematic (40°C): >0.21 cm<sup>2</sup>/s
- Viscosity** : < 30 s (ISO 6mm)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

**SECTION 9: Physical and chemical properties****9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity****10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.**10.2 Chemical stability** : The product is stable.**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50 Oral	Rat	>6 g/kg	-
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 Dermal	Rat	>5000 mg/kg	-
xylene	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	>1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.**Acute toxicity estimates**

Route	ATE value
Dermal	44038.84 mg/kg
Inhalation (vapours)	440.39 mg/l

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

**Conclusion/Summary****Skin** : There are no data available on the mixture itself.**Eyes** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.**Sensitisation****Conclusion/Summary****Skin** : There are no data available on the mixture itself.

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 11: Toxicological information

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 3	Not applicable.	Narcotic effects
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	Not applicable.	Narcotic effects
xylene	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 1	Inhalation	central nervous system (CNS)

### Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Ingestion** : Can cause central nervous system (CNS) depression.

**Skin contact** : Defatting to the skin. May cause skin dryness and irritation.

**Eye contact** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Ingestion** : No specific data.

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 11: Toxicological information

**Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking

**Eye contact** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Chronic NOEC 0.097 mg/l Fresh water	Daphnia	21 days
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LC50 >1000 mg/l	Algae	72 hours

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

**SECTION 12: Ecological information****Conclusion/Summary** : There are no data available on the mixture itself.**12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	OECD 301 F 301F Ready Biodegradability - Manometric Respirometry Test	75 % - Readily - 28 days	-	-
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	80 % - Readily - 28 days	-	-

**Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	-	-	Readily
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	-	Readily
xylene	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	10 to 2500	high
xylene	3.16	7.4 to 18.5	low

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

### European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

### Additional information

**ADR/RID** : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

**Tunnel code** : (D/E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

**IMDG** : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## 14. Transport information

IATA : None identified.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

##### Ozone depleting substances (1005/2009/EU)

Not listed.

##### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

<b>Category</b>
P5c

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Code : 00136664  
SIGMATHERM 175

Date of issue/Date of revision : 15 January 2020

## SECTION 16: Other information

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372 (inhalation)	Causes damage to organs through prolonged or repeated exposure if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Chronic 2, H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3, H412	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
STOT RE 1, H372 (inhalation)	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (inhalation) - Category 1
STOT RE 1, H372	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

### History

Date of issue/ Date of revision : 15 January 2020

revision

Date of previous issue : 8 October 2019

Prepared by : EHS

Version : 1.03

### Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.