

# SAFETY DATA SHEET

Date of issue/Date of revision : 19 February 2020 Version : 8



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : SIGMASHIELD 880XS HARDENER

**Product code** : 00358679

**Other means of identification**

Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/  
mixture** : Coating.

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL  
Tweemontstraat 104  
B-2100 Deurne  
Belgium  
Telephone +32-33606311  
Fax +32-33606435

**e-mail address of person  
responsible for this SDS** : PMC.Safety@PPG.com

### 1.4 Emergency telephone number

**Supplier**

+31 20 4075210

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Skin Corr. 1B, H314

Eye Dam. 1, H318

Skin Sens. 1, H317

Repr. 1B, H360F (Fertility)

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Code : 00358679

Date of issue/Date of revision

: 19 February 2020

SIGMASHIELD 880XS HARDENER

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May damage fertility.  
Harmful to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention** :

Wear protective gloves. Wear protective clothing. Wear eye or face protection.  
Avoid breathing vapour.

**Response** :

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Storage** :

Store locked up.

**Disposal** :

Not applicable.

P280, P261, P304 + P340, P301 + P310, P303 + P361 + P353, P305 + P351 + P338, P405

**Hazardous ingredients** :

Epoxy Amine Resin  
m-phenylenebis(methylamine)  
4,4'-isopropylidenediphenol  
2,4,6-tris(dimethylaminomethyl)phenol

**Supplemental label elements** :

Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Restricted to professional users.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB** :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** :

None known.

Code : 00358679

Date of issue/Date of revision

: 19 February 2020

SIGMASHIELD 880XS HARDENER

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

: Mixture

| Product/ingredient name  | Identifiers  | % by weight  | Classification  |             |
|--|--|--------------|---|-------------|
|  |  |              | Regulation (EC) No. 1272/2008 [CLP]   | Type        |
| Epoxy Amine Resin  | CAS: SUB127835   | ≥10 - ≤25    | Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317   | [1]         |
| Propylidynetrimethanol, propoxylated, reaction products with ammonia | REACH #: 01-2119556886-20<br>EC: 500-105-6<br>CAS: 39423-51-3                      | ≥10 - ≤15    | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Eye Dam. 1, H318<br>Aquatic Chronic 2, H411   | [1]         |
| benzyl alcohol   | REACH #: 01-2119492630-38<br>EC: 202-859-9<br>CAS: 100-51-6<br>Index: 603-057-00-5 | ≥5.0 - ≤11   | Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Eye Irrit. 2, H319  | [1]         |
| m-phenylenebis(methylamine)  | REACH #: 01-2119480150-50<br>EC: 216-032-5<br>CAS: 1477-55-0                       | ≥5.0 - ≤7.7  | Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412<br>EUH071 | [1]         |
| 4,4'-isopropylidenediphenol  | REACH #: 01-2119457856-23<br>EC: 201-245-8<br>CAS: 80-05-7<br>Index: 604-030-00-0  | ≥1.0 - ≤5.0  | Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Repr. 1B, H360F (Fertility)<br>STOT SE 3, H335<br>Aquatic Chronic 2, H411                             | [1] [2] [5] |
| 2,4,6-tris(dimethylaminomethyl) phenol                               | REACH #: 01-2119560597-27<br>EC: 202-013-9<br>CAS: 90-72-2<br>Index: 603-069-00-0  | ≥0.30 - ≤2.6 | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317                                      | [1]         |
|  |  |              | <b>See Section 16 for the full text of the H statements declared above.</b>   |             |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SUB codes represent substances without registered CAS Numbers.**

|                                   |  |
|-----------------------------------|--|
| <b>Code</b> : 00358679            | <b>Date of issue/Date of revision</b> : 19 February 2020 |
| <b>SIGMASHIELD 880XS HARDENER</b> |  |

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Code : 00358679

Date of issue/Date of revision

: 19 February 2020

SIGMASHIELD 880XS HARDENER

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code : 00358679 Date of issue/Date of revision : 19 February 2020  
 SIGMASHIELD 880XS HARDENER

## SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name   | Exposure limit values  |
|---------------------------|--|
| 4'-isopropylidenediphenol | EH40/2005 WELs (United Kingdom (UK), 8/2018).<br>TWA: 2 mg/m <sup>3</sup> 8 hours. |

Code : 00358679

Date of issue/Date of revision

: 19 February 2020

SIGMASHIELD 880XS HARDENER

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs

| Product/ingredient name     | Type            | Exposure              | Value                 | Population         | Effects  |
|-----------------------------|-----------------|-----------------------|-----------------------|--------------------|----------|
| Benzyl alcohol              | DNEL            | Long term Oral        | 4 mg/kg bw/day        | General population | Systemic |
|                             | DNEL            | Long term Dermal      | 4 mg/kg bw/day        | General population | Systemic |
|                             | DNEL            | Long term Inhalation  | 5.4 mg/m <sup>3</sup> | General population | Systemic |
|                             | DNEL            | Long term Dermal      | 8 mg/kg bw/day        | Workers            | Systemic |
|                             | DNEL            | Short term Oral       | 20 mg/kg bw/day       | General population | Systemic |
|                             | DNEL            | Short term Dermal     | 20 mg/kg bw/day       | General population | Systemic |
|                             | DNEL            | Long term Inhalation  | 22 mg/m <sup>3</sup>  | Workers            | Systemic |
| m-phenylenebis(methylamine) | DNEL            | Short term Inhalation | 27 mg/m <sup>3</sup>  | General population | Systemic |
|                             | DNEL            | Short term Dermal     | 40 mg/kg bw/day       | Workers            | Systemic |
|                             | DNEL            | Short term Inhalation | 110 mg/m <sup>3</sup> | Workers            | Systemic |
|                             | DNEL            | Long term Inhalation  | 0.2 mg/m <sup>3</sup> | Workers            | Local    |
| 4,4'-isopropylidenediphenol | DNEL            | Long term Dermal      | 0.33 mg/kg bw/day     | Workers            | Systemic |
|                             | DNEL            | Long term Inhalation  | 1.2 mg/m <sup>3</sup> | Workers            | Systemic |
|                             | DNEL            | Long term Inhalation  | 2 mg/m <sup>3</sup>   | Workers            | Systemic |
|                             | DNEL            | Short term Inhalation | 2 mg/m <sup>3</sup>   | Workers            | Systemic |
|                             | DNEL            | Long term Inhalation  | 2 mg/m <sup>3</sup>   | Workers            | Local    |
|                             | DNEL            | Short term Inhalation | 2 mg/m <sup>3</sup>   | Workers            | Local    |
|                             | DNEL            | Long term Dermal      | 0.031 mg/kg bw/day    | Workers            | Systemic |
|                             | DNEL            | Short term Dermal     | 0.031 mg/kg bw/day    | Workers            | Systemic |
|                             | DNEL            | Long term Inhalation  | 1 mg/m <sup>3</sup>   | General population | Systemic |
|                             | DNEL            | Short term Inhalation | 1 mg/m <sup>3</sup>   | General population | Systemic |
|                             | DNEL            | Long term Inhalation  | 1 mg/m <sup>3</sup>   | General population | Local    |
|                             | DNEL            | Short term Inhalation | 1 mg/m <sup>3</sup>   | General population | Local    |
|                             | DNEL            | Long term Dermal      | 0.002 mg/kg bw/day    | General population | Systemic |
|                             | DNEL            | Short term Dermal     | 0.002 mg/kg bw/day    | General population | Systemic |
| DNEL                        | Long term Oral  | 0.004 mg/kg bw/day    | General population    | Systemic           |          |
| DNEL                        | Short term Oral | 0.004 mg/kg bw/day    | General population    | Systemic           |          |

|                                   |  |
|-----------------------------------|--|
| <b>Code</b> : 00358679            | <b>Date of issue/Date of revision</b> : 19 February 2020 |
| <b>SIGMASHIELD 880XS HARDENER</b> |  |

**SECTION 8: Exposure controls/personal protection**

|  |  |  |     |            |  |
|--|--|--|-----|------------|--|
|  |  |  | day | population |  |
|--|--|--|-----|------------|--|

**PNECs**

| Product/ingredient name     | Type | Compartment Detail     | Value          | Method Detail            |
|-----------------------------|------|------------------------|----------------|--------------------------|
| 4,4'-isopropylidenediphenol | -    | Fresh water            | 0.018 mg/l     | Sensitivity Distribution |
|                             | -    | Marine water           | 0.018 mg/l     | Sensitivity Distribution |
|                             | -    | Sewage Treatment Plant | 320 mg/l       | Assessment Factors       |
|                             | -    | Fresh water sediment   | 1.2 mg/kg dwt  | Assessment Factors       |
|                             | -    | Marine water sediment  | 0.24 mg/kg dwt | Assessment Factors       |
|                             | -    | Sewage Treatment Plant | 3.7 mg/kg dwt  | Assessment Factors       |

**8.2 Exposure controls**

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Chemical splash goggles and face shield. Use eye protection according to EN 166.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** : nitrile neoprene

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.



Code : 00358679 Date of issue/Date of revision : 19 February 2020  
 SIGMASHIELD 880XS HARDENER

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Not available.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: 14°C (57.2°F) This is based on data for the following ingredient: m-phenylenebis(methylamine). Weighted average: -12.4°C (9.7°F)
- Initial boiling point and boiling range** : >37.78°C
- Flash point** : Closed cup: 132°C
- Evaporation rate** : 0.007 (benzyl alcohol) compared with butyl acetate
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)
- Vapour pressure** : Highest known value: 0.7 kPa (5.1 mm Hg) (at 20°C) (Propylidynetrimethanol, propoxylated, reaction products with ammonia). Weighted average: 0.29 kPa (2.18 mm Hg) (at 20°C)
- Vapour density** : Highest known value: 3.7 (Air = 1) (benzyl alcohol).
- Relative density** : 1.25
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Auto-ignition temperature** : Lowest known value: 320°C (608°F) (Propylidynetrimethanol, propoxylated, reaction products with ammonia).
- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- Viscosity** : Kinematic (40°C): >0.21 cm<sup>2</sup>/s
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.

### 9.2 Other information

No additional information.

Code : 00358679 Date of issue/Date of revision : 19 February 2020  
 SIGMASHIELD 880XS HARDENER

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
 Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name  | Result                          | Species            | Dose                    | Exposure |
|--|---------------------------------|--------------------|-------------------------|----------|
| Propylidynetrimethanol, propoxylated, reaction products with ammonia | LD50 Dermal                     | Rabbit             | 0.4 g/kg                | -        |
| benzyl alcohol   | LD50 Oral                       | Rat                | 0.22 g/kg               | -        |
|  | LC50 Inhalation Dusts and mists | Rat                | >4178 mg/m <sup>3</sup> | 4 hours  |
| m-phenylenebis(methylamine)  | LD50 Dermal                     | Rabbit             | 2000 mg/kg              | -        |
|  | LD50 Oral                       | Rat                | 1.23 g/kg               | -        |
|  | LC50 Inhalation Gas.            | Rat                | 700 ppm                 | 1 hours  |
|  | LD50 Dermal                     | Rat - Male, Female | >3100 mg/kg             | -        |
| bisphenol A  | LD50 Oral                       | Rat                | 930 mg/kg               | -        |
|  | LD50 Dermal                     | Rabbit             | 3600 mg/kg              | -        |
| 2,4,6-tris(dimethylaminomethyl)phenol                                | LD50 Oral                       | Rat                | 3.25 g/kg               | -        |
|  | LD50 Dermal                     | Rabbit             | 1.28 g/kg               | -        |
|  | LD50 Dermal                     | Rat                | 1280 mg/kg              | -        |
|  | LD50 Oral                       | Rat                | 1200 mg/kg              | -        |

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Acute toxicity estimates

| Route                        | ATE value     |
|------------------------------|---------------|
| Oral                         | 2152.96 mg/kg |
| Dermal                       | 6799.07 mg/kg |
| Inhalation (gases)           | 62437.56 ppm  |
| Inhalation (dusts and mists) | 14.33 mg/l    |

#### Irritation/Corrosion

| Product/ingredient name               | Result                  | Species | Score | Exposure | Observation |
|---------------------------------------|-------------------------|---------|-------|----------|-------------|
| m-phenylenebis(methylamine)           | Skin - Severe irritant  | Rat     | -     | 4 hours  | 4 hours     |
| 2,4,6-tris(dimethylaminomethyl)phenol | Skin - Visible necrosis | Rabbit  | -     | 4 hours  | 7 days      |

**Conclusion/Summary**

Code : 00358679

Date of issue/Date of revision

: 19 February 2020

SIGMASHIELD 880XS HARDENER

## SECTION 11: Toxicological information

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitisation

| Product/ingredient name  | Route of exposure | Species             | Result                     |
|--|-------------------|---------------------|----------------------------|
| m-phenylenebis(methylamine)<br>2,4,6-tris(dimethylaminomethyl)phenol | skin<br>skin      | Mouse<br>Guinea pig | Sensitising<br>Sensitising |

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| bisphenol A             | Category 3 | Not applicable.   | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

**Skin contact** : Causes severe burns. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

**Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

Code : 00358679

Date of issue/Date of revision

: 19 February 2020

SIGMASHIELD 880XS HARDENER

## SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:  
 pain or irritation  
 redness  
 blistering may occur  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations
- Eye contact** : Adverse symptoms may include the following:  
 pain  
 watering  
 redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : May damage fertility.

**Other information** : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Epoxy Amine Resin, m-phenylenebis(methylamine), 4,4'-isopropylidenediphenol, 2,4,6-tris(dimethylaminomethyl)phenol. May produce an allergic reaction.

Code : 00358679 Date of issue/Date of revision : 19 February 2020  
 SIGMASHIELD 880XS HARDENER

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name               | Result                                 | Species   | Exposure |
|---------------------------------------|--|---|----------|
| Bisphenol A                           | Chronic EC10 3.47 mg/l<br>Marine water | Algae -<br>Cochlodinium<br>polykrikoides -<br>Exponential growth<br>phase | 72 hours |
|                                       | Chronic NOEC 0.86 mg/l<br>Fresh water  | Daphnia - Daphnia<br>magna - Neonate                                      | 21 days  |
| 2,4,6-tris(dimethylaminomethyl)phenol | Acute LC50 175 mg/l                    | Fish  | 96 hours |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

**Conclusion/Summary** : There are no data available on the mixture itself.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Benzyl alcohol          | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name     | LogP <sub>ow</sub> | BCF   | Potential |
|-----------------------------|--------------------|-------|-----------|
| Benzyl alcohol              | 1.1                | -     | low       |
| m-phenylenebis(methylamine) | 0.18               | 2.69  | low       |
| bisphenol A                 | 3.32               | 43.65 | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

Code : 00358679 Date of issue/Date of revision : 19 February 2020  
 SIGMASHIELD 880XS HARDENER

## SECTION 13: Disposal considerations

### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

|                                 | ADR/RID         | ADN             | IMDG            | IATA            |
|---------------------------------|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number                  | UN3066          | UN3066          | UN3066          | UN3066          |
| 14.2 UN proper shipping name    | PAINT           | PAINT           | PAINT           | PAINT           |
| 14.3 Transport hazard class(es) | 8               | 8               | 8               | 8               |
| 14.4 Packing group              | II              | II              | II              | II              |
| 14.5 Environmental hazards      | No.             | Yes.            | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

### Additional information

**ADR/RID** : None identified.

**Tunnel code** : (E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

**IMDG** : None identified.

**IATA** : None identified.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

Code : 00358679 Date of issue/Date of revision : 19 February 2020  
 SIGMASHIELD 880XS HARDENER

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

##### Substances of very high concern

| Ingredient name                                 | Intrinsic property                               | Status    | Reference number | Date of revision |
|---|--|-----------|------------------|------------------|
| <input checked="" type="checkbox"/> Bisphenol A | Toxic to reproduction                            | Candidate | ED/01/2018       | 1/12/2017        |
| -   | Substance of equivalent concern for human health | Candidate | ED/01/2018       | 1/12/2017        |
| -   | Substance of equivalent concern for environment  | Candidate | ED/01/2018       | 1/12/2017        |

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Restricted to professional users.

##### Ozone depleting substances (1005/2009/EU)

Not listed.

##### Seveso Directive

This product is not controlled under the Seveso Directive.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

### **Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

|                                   |  |
|-----------------------------------|--|
| <b>Code</b> : 00358679            | <b>Date of issue/Date of revision</b> : 19 February 2020 |
| <b>SIGMASHIELD 880XS HARDENER</b> |  |

**SECTION 16: Other information**

| Classification  | Justification  |
|---|--|
| Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Repr. 1B, H360F (Fertility)<br>Aquatic Chronic 3, H412 | Calculation method<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

**Full text of abbreviated H statements**

|       |  |
|-------|--|
| H302  | Harmful if swallowed.                              |
| H312  | Harmful in contact with skin.                      |
| H314  | Causes severe skin burns and eye damage.           |
| H315  | Causes skin irritation.                            |
| H317  | May cause an allergic skin reaction.               |
| H318  | Causes serious eye damage.                         |
| H319  | Causes serious eye irritation.                     |
| H332  | Harmful if inhaled.                                |
| H335  | May cause respiratory irritation.                  |
| H360F | May damage fertility.                              |
| H411  | Toxic to aquatic life with long lasting effects.   |
| H412  | Harmful to aquatic life with long lasting effects. |

**Full text of classifications [CLP/GHS]**

|                         |  |
|-------------------------|--|
| Acute Tox. 4, H302      | ACUTE TOXICITY (oral) - Category 4   |
| Acute Tox. 4, H312      | ACUTE TOXICITY (dermal) - Category 4   |
| Acute Tox. 4, H332      | ACUTE TOXICITY (inhalation) - Category 4   |
| Aquatic Chronic 2, H411 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2  |
| Aquatic Chronic 3, H412 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  |
| EUH071                  | Corrosive to the respiratory tract.  |
| Eye Dam. 1, H318        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1   |
| Eye Irrit. 2, H319      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2   |
| Repr. 1B, H360F         | REPRODUCTIVE TOXICITY (Fertility) - Category 1B  |
| Skin Corr. 1B, H314     | SKIN CORROSION/IRRITATION - Category 1B  |
| Skin Corr. 1C, H314     | SKIN CORROSION/IRRITATION - Category 1C  |
| Skin Irrit. 2, H315     | SKIN CORROSION/IRRITATION - Category 2   |
| Skin Sens. 1, H317      | SKIN SENSITISATION - Category 1  |
| Skin Sens. 1B, H317     | SKIN SENSITISATION - Category 1B   |
| STOT SE 3, H335         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3 |

**History**

**Date of issue/ Date of revision** : 19 February 2020

**revision**

**Date of previous issue** : 20 December 2018

**Prepared by** : EHS

**Version** : 8

**Disclaimer**

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*