



Date of issue/Date of revision 16 March 2020

Vers

Version3.02

Section 1. Identification

Product code	: 00336156
Product name	: PSX 700 LIGHT TINT RESIN
Other means of identification	: Not available.
CAS number	: Not applicable.
EC number	: Mixture.
Product type	: Liquid.
Relevant identified uses of	of the substance or mixture and uses advised against
Product use	: Coating. Paint. Painting-related materials.
Supplier's details	: PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22
Emergency telephone number (with hours of operation)	: CHEMTREC +(84)-444581938 (CCN 17704)

Section 2. Hazards identification

Classification of the substance or mixture	 SKIN IRRITATION - Category 3 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC TOXICITY (ACUTE) - Category 3 AQUATIC TOXICITY (CHRONIC) - Category 3 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 81.1% (Oral), 82.7% (Dermal), 82.7% (Inhalation) Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 48.7%
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 Causes serious eye irritation. Causes mild skin irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements	

Product name PSX 700 LIGHT TINT RESIN

Section 2. Hazards identification

Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Routes of entry	: Not available.
Other hazards which do not result in classification	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

CAS number EC number	Not applicable. Mixture.			
Ingredient name		CAS number	Chemical formula	%
4,4'-Isopropylidenedicyclohexa reaction products with 1-chloro		30583-72-3	(C15H28O2. C3H5ClO)x	25- <50
Poly(oxy-1,2-ethanediyl), α-(nonylphenyl)-ω-hydroxy-, branched, phosphates		68412-53-3	-	1- <3
bis(1,2,2,6,6-pentamethyl-4-pi Polyamide	peridyl) sebacate	41556-26-7 SUB100538	C30H56N2O4 -	1- <3 1- <3

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Product name PSX 700 LIGHT TINT RESIN

Section 4. First aid measures

Potential acute health effects	2	•		
Eye contact	:	Causes serious eye irritation.		
Inhalation	:	No known significant effects or critical hazards.		
Skin contact	:	Causes mild skin irritation. May cause an allergic skin reaction.		
Ingestion	:	No known significant effects or critical hazards.		
Over-exposure signs/sympto	om	<u>s</u>		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness		
Inhalation	:	No specific data.		
Skin contact	:	Adverse symptoms may include the following: irritation redness		
Ingestion	:	No specific data.		
Indication of immediate medical attention and special treatment needed, if necessary				
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Specific treatments	:	No specific treatment.		
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

See toxicological information (Section 11)

Section 5. Fire-fighting measures

from the chemical	This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being
	discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon oxides
	nitrogen oxides
	halogenated compounds metal oxide/oxides
Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if
for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective	: Fire-fighters should wear appropriate protective equipment and self-contained
equipment for fire-fighters	breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Viet Nam Page: 3/11

1 Viet Nam Page: 3/1

Version 3.02

Section 6. Accidental release measures

Personal precautions, protect	ctiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	-	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for co	<u>ont</u>	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures :	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general : occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage,	Do not store above the following temperature: 50°C (122°F). Store in accordance
including any	with local regulations. Store in original container protected from direct sunlight in a
incompatibilities	dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use.
	Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters		
Occupational exposure lim	<u>its</u>	
None.		
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>res</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product name PSX 700 LIGHT TINT RESIN

Section 8. Exposure controls/personal protection

```
Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
```

Section 9. Physical and chemical properties

Appearance		
Physical state	1	Liquid.
Color	1	Not available.
Odor	1	Characteristic.
Odor threshold	1	Not available.
рН	1	Not available.
Melting point	1	Not available.
Boiling point	1	>37.78°C (>100°F)
Flash point	1	Closed cup: 97.22°C (207°F)
Evaporation rate	1	0.7 (butyl acetate = 1)
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	1	1.6 kPa (12 mm Hg) [room temperature]
Vapor density	1	Not available.
Relative density	1	1.34
Solubility	1	Insoluble in the following materials: cold water.
Solubility in water	1	2.6 g/l
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C): >0.21 cm²/s

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Dose

3.125 g/kg

>6.3 mg/l

>2000 mg/kg

>2000 mg/kg

Exposure

4 hours

_

Product name PSX 700 LIGHT TINT RESIN

Section 10. Stability and reactivity

Hazardous decomposition products

Depending on conditions, decomposition products may include the following ÷. materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/ oxides

Species

Rat

Rat

Rat

Rat

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity **Product/ingredient name** Result bis(1,2,2,6,6-pentamethyl-LD50 Oral 4-piperidyl) sebacate Polyamide LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral **Conclusion/Summary** : There are no data available on the mixture itself. Irritation/Corrosion **Conclusion/Summary** Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself. : There are no data available on the mixture itself. Respiratory **Sensitization** : There are no data available on the mixture itself. Skin There are no data available on the mixture itself. Respiratory **Mutagenicity** : There are no data available on the mixture itself. **Conclusion/Summary Carcinogenicity** : There are no data available on the mixture itself. **Conclusion/Summary Reproductive toxicity Conclusion/Summary** : There are no data available on the mixture itself.

Teratogenicity Conclusion/Summary : There are no data available on the mixture itself. Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes mild skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.

Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
Long term exposure		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
Potential chronic health eff	<u>icts</u>	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Teratogenicity	: No known significant effects or critical hazards.	
Developmental effects	: No known significant effects or critical hazards.	
Fertility effects	: No known significant effects or critical hazards.	

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
	19195.75 mg/kg
Dermal	38514.43 mg/kg

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Product code 00336156

Product name PSX 700 LIGHT TINT RESIN

Section 11. Toxicological information

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Section 12. Ecological information

<u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition : coefficient (K_{oc})

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Dis	posa	l met	hods
010	posu	met	1043

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

Circular no. 05/1999/TT-BYT

Ingredient name	Category	Notes	
1-chloro-2,3-epoxypropane	Category 2		
ethylene oxide	Category 2		
1,4-dioxane	Category 2		
chromium	Category 2		
antimony	Category 2		
arsenic	Category 1		
xylene	Category 2		

Toxic classification (TCVN : 4 3164-79)

Section 16. Other information

arch 2020
2020
2

Section 16. Other information

Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.