

SAFETY DATA SHEET

Date of issue/Date of revision

: 18 May 2020

Version

: 9



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PITT-CHAR XP BASE WHITE

Product code : 00352601

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

**e-mail address of person
responsible for this SDS** : PMC.Safety@PPG.com

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Repr. 2, H361

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms :



Signal word :

Warning

Hazard statements :

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention :

Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.

Response :

Collect spillage.

Storage :

Not applicable.

Disposal :

Not applicable.
P202, P280, P273, P261, P264, P391

Hazardous ingredients :

Hexaboron dizinc undecaoxide
Epoxy Resin
bis-[4-(2,3-epoxipropoxy)phenyl]propane
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)

Supplemental label elements :

Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Not applicable.

Tactile warning of danger :

Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification :

None known.

Code : 00352601
 PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % by weight | Classification | |
|--|--|-------------|---|------|
| | | | Regulation (EC) No. 1272/2008 [CLP] | Type |
| Hexaboron dizinc undecaoxide | REACH #: 01-2119691658-19 EC: 235-804-2 CAS: 12767-90-7 | ≥10 - <25 | Eye Irrit. 2, H319 Repr. 2, H361 (oral) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 | [1] |
| Epoxy Resin | CAS: SUB106346 | ≥10 - ≤25 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361d | [1] |
| Borate(5-), bis[μ-oxotetraoxodiborato(4-)], ammonium tetrahydrogen, dihydrate, (T-4)-phosphorous oxychloride, reaction products with propylene oxide | REACH #: 01-2119970312-43 CAS: 12046-04-7 | ≥10 - ≤25 | Repr. 2, H361d | [1] |
| bis-[4-(2,3-epoxipropoxy)phenyl] propane | REACH #: 01-2119486772-26 CAS: 1244733-77-4 | ≥10 - <25 | Acute Tox. 4, H302 | [1] |
| N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) | REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2 REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2 | ≥5.0 - ≤10 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 | [1] |
| | | <1.0 | Skin Sens. 1B, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above. | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 4: First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
phosphorus oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 8: Exposure controls/personal protection

DNELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects | |
|---|---|----------------------|------------------------|--------------------------------|--------------------------------|----------|
| Hexaboron dizinc undecaoxide | DNEL | Long term Oral | 2.4 mg/kg bw/day | General population | Systemic | |
| | DNEL | Long term Inhalation | 8.3 mg/m ³ | General population | Systemic | |
| | DNEL | Long term Inhalation | 22.4 mg/m ³ | Workers | Systemic | |
| | DNEL | Long term Dermal | 1205 mg/kg bw/day | General population | Systemic | |
| | DNEL | Long term Dermal | 1585 mg/kg bw/day | Workers | Systemic | |
| | bis-[4-(2,3-epoxipropoxy)phenyl]propane | DNEL | Long term Inhalation | 12.25 mg/m ³ | Workers | Systemic |
| | | DNEL | Short term Inhalation | 12.25 mg/m ³ | Workers | Systemic |
| | | DNEL | Long term Dermal | 8.33 mg/kg bw/day | Workers | Systemic |
| | | DNEL | Short term Dermal | 8.33 mg/kg bw/day | Workers | Systemic |
| | N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) | DNEL | Long term Dermal | 3.571 mg/kg bw/day | General population [Consumers] | Systemic |
| DNEL | | Short term Dermal | 3.571 mg/kg bw/day | General population [Consumers] | Systemic | |
| DNEL | | Long term Oral | 0.75 mg/kg bw/day | General population [Consumers] | Systemic | |
| DNEL | | Short term Oral | 0.75 mg/kg bw/day | General population [Consumers] | Systemic | |
| N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) | DNEL | Long term Inhalation | 0.83 mg/m ³ | General population | Local | |
| | DNEL | Long term Inhalation | 3.35 mg/m ³ | Workers | Local | |

PNECs

| Product/ingredient name | Type | Compartment Detail | Value | Method Detail |
|---|------|------------------------|-----------------|--------------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | - | Fresh water | 0.006 mg/l | Assessment Factors |
| | - | Marine water | 0.001 mg/l | Assessment Factors |
| | - | Fresh water sediment | 0.996 mg/kg dwt | Equilibrium Partitioning |
| | - | Marine water sediment | 0.1 mg/kg dwt | Equilibrium Partitioning |
| | - | Soil | 0.196 mg/kg dwt | Equilibrium Partitioning |
| | - | Sewage Treatment Plant | 10 mg/l | Assessment Factors |
| | - | Secondary Poisoning | 11 mg/kg | Assessment Factors |

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Off-white.
- Odour** : Aromatic. [Strong]
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: 8 to 12°C (46.4 to 53.6°F) This is based on data for the following ingredient: bis-[4-(2,3-epoxipropoxy)phenyl] propane.

Code : 00352601 Date of issue/Date of revision : 18 May 2020
 PITT-CHAR XP BASE WHITE

SECTION 9: Physical and chemical properties

| | |
|---|---|
| Initial boiling point and boiling range | : >37.78°C |
| Flash point | : Closed cup: Not applicable. |
| Evaporation rate | : Not available. |
| Flammability (solid, gas) | : liquid |
| Upper/lower flammability or explosive limits | : Not available. |
| Vapour pressure | : Highest known value: <0.01 kPa (<0.1 mm Hg) (at 20°C) (bis-[4-(2,3-epoxipropoxy)phenyl]propane). |
| Vapour density | : Highest known value: 11.7 (Air = 1) (bis-[4-(2,3-epoxipropoxy)phenyl]propane). |
| Relative density | : 1.47 |
| Solubility(ies) | : Insoluble in the following materials: cold water. |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Stable under recommended storage and handling conditions (see Section 7). |
| Viscosity | : Kinematic (40°C): >0.21 cm ² /s |
| Viscosity | : > 100 s (ISO 6mm) |
| Explosive properties | : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible. |
| Oxidising properties | : Product does not present an oxidizing hazard. |

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

| | |
|--|---|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| 10.6 Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides |

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|-------------|-------------------|----------|
| Hexaboron dizinc undecaoxide Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)- phosphorous oxychloride, reaction products with propylene oxide bis-[4-(2,3-epoxipropoxy)phenyl]propane N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide) | LC50 Inhalation Dusts and mists | Rat | >5 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | 4200 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | >7 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | 630 to 2000 mg/kg | - |
| | LD50 Dermal | Rabbit | 23000 mg/kg | - |
| | LD50 Oral | Rat | 15000 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | >5.11 mg/l | 4 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| LD50 Oral | Rat | >2000 mg/kg | - | |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Route | ATE value |
|-------|---------------|
| Oral | 3963.88 mg/kg |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|------------------------------------|---------|-------|-----------------|-------------|
| Hexaboron dizinc undecaoxide bis-[4-(2,3-epoxipropoxy)phenyl]propane | Eyes - Cornea opacity | Rabbit | 33 | 24 hours 0.083g | 74 hours |
| | Eyes - Redness of the conjunctivae | Rabbit | 0.4 | 24 hours | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours | - |
| | Skin - Erythema/Eschar | Rabbit | 0.8 | 4 hours | - |
| | Skin - Oedema | Rabbit | 0.5 | 4 hours | - |
| | Skin - Mild irritant | Rabbit | - | 4 hours | - |

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------|---------|-------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | skin | Mouse | Sensitising |

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Code : 00352601 Date of issue/Date of revision : 18 May 2020
 PITT-CHAR XP BASE WHITE

SECTION 11: Toxicological information

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Developmental toxin | Species | Dose | Exposure |
|------------------------------|-------------------|-----------|---------------------|---------|-----------------|--------------------------|
| hexaboron dizinc undecaoxide | Positive | Positive | Positive | Rat | Oral: 375 mg/kg | 90 days; 7 days per week |

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Ingestion : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Code : 00352601
PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.


Fertility effects : Suspected of damaging fertility.

Other information : Not available.

 Sanding and grinding dusts may be harmful if inhaled.


SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|---------------------------------|---|----------|
|  Hexaboron dizinc undecaoxide | Acute EC50 76 mg/l | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 2.17 mg/l | Fish - Salmo gairdneri | 96 hours |
| Borate(5-), bis[μ-oxotetraoxodiborato(4-)]-, ammonium tetrahydrogen, dihydrate, (T-4)-phosphorous oxychloride, reaction products with propylene oxide | Acute LC50 >100 mg/l | Fish | 96 hours |
| | EC50 82 mg/l | Algae | 72 hours |
| bis-[4-(2,3-epoxipropoxy)phenyl]propane | EC50 131 mg/l | Daphnia | 48 hours |
| | LC50 56.2 mg/l | Fish | 96 hours |
| | NOEC 32 mg/l | Daphnia | 48 hours |
| N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | Acute LC50 1.8 mg/l Fresh water | Daphnia - daphnia magna | 48 hours |
| | Chronic NOEC 0.3 mg/l | Daphnia | 21 days |
| | Acute EC50 29 to 43 mg/l | Algae - Pseudokirchneriella subcapitata | 72 hours |
| | Acute EC50 94 mg/l | Daphnia - Daphnia magna | 48 hours |

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|---|------|----------------|------|----------|
|  N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | - | 63 % - 28 days | - | - |

Code : 00352601 Date of issue/Date of revision : 18 May 2020
 PITT-CHAR XP BASE WHITE

SECTION 12: Ecological information

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| bis-[4-(2,3-epoxipropoxy)phenyl]propane N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | - | - | Not readily |
| | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|-------|-----------|
| hexaboron dizinc undecaoxide phosphorous oxychloride, reaction products with propylene oxide N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) | - | 60960 | high |
| | 2.68 | - | low |
| | >6 | - | high |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container | 15 01 06 mixed packaging |

Code : 00352601 Date of issue/Date of revision : 18 May 2020
 PITT-CHAR XP BASE WHITE

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|--|--|--|--|
| 14.1 UN number | UN3082 | UN3082 | UN3082 | UN3082 |
| 14.2 UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Hexaboron dizinc undecaoxide, bis-[4-(2,3-epoxipropoxi) phenyl]propane) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Hexaboron dizinc undecaoxide, bis-[4-(2,3-epoxipropoxi) phenyl]propane) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Hexaboron dizinc undecaoxide, bis-[4-(2,3-epoxipropoxi) phenyl]propane) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Hexaboron dizinc undecaoxide, bis-[4-(2,3-epoxipropoxi) phenyl]propane) |
| 14.3 Transport hazard class(es) | 9 | 9 | 9 | 9 |
| 14.4 Packing group | III | III | III | III |
| 14.5 Environmental hazards | Yes. | Yes. | Yes. | Yes. |
| Marine pollutant substances | Not applicable. | Not applicable. | Hexaboron dizinc undecaoxide, bis-[4-(2,3-epoxipropoxi) phenyl]propane) | Not applicable. |

Additional information

- ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

Code : 00352601
 PITT-CHAR XP BASE WHITE

Date of issue/Date of revision : 18 May 2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.
**on the manufacture,
 placing on the market
 and use of certain
 dangerous substances,
 mixtures and articles**

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| |
|-----------------|
| Category |
| E2 |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|--------------------|
| ✔ Skin Irrit. 2, H315 | Calculation method |
| Eye Irrit. 2, H319 | Calculation method |
| Skin Sens. 1, H317 | Calculation method |
| Repr. 2, H361 | Calculation method |
| Aquatic Chronic 2, H411 | Calculation method |

Full text of abbreviated H statements

| | |
|--------------------------------|---|
| Code : 00352601 | Date of issue/Date of revision : 18 May 2020 |
| PITT-CHAR XP BASE WHITE | |

SECTION 16: Other information

| | |
|---|--|
| H302 H315 H317 H319 H361 H361d H400 H411 H412 | Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. Suspected of damaging the unborn child. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. |
|---|--|

[Full text of classifications \[CLP/GHS\]](#)

| | |
|--|--|
| Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 2 Aquatic Chronic 3 Eye Irrit. 2 Repr. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1B | ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B |
|--|--|

History

| | |
|--|----------------|
| Date of issue/ Date of revision | : 18 May 2020 |
| Date of previous issue | : 6 March 2020 |
| Prepared by | : EHS |
| Version | : 9 |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.