# SAFETY DATA SHEET



Date of issue

6 June 2020

Version 4.01

# Section 1. Product and company identification

Product name : PSX 700 BLACK RESIN

Product code : PX7009
Other means of identification : Not available.

Product type : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

### Supplier's details:

**Supplier** : PPG INDUSTRIES CHILE S.A.

Puerto Madero 9710, Of. 23

Pudahuel - Chile

Teléfono: +56 (2) 2571 0750 Fax: +56 (2) 2571 0752

Email address: : HazComLatam@ppg.com

**Emergency telephone number** 

+56 9 82939315

### Section 2. Hazards identification

Classification of the substance or mixture : SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1A
AQUATIC HAZARD (ACUTE) - Category 3

AQUATIC HAZARD (LONG-TERM) - Category 3

Target organs : Contains material which causes damage to the following organs: upper respiratory

tract, skin, eyes.

Contains material which may cause damage to the following organs: lungs.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 92.4% (Oral), 94.1% (Dermal), 94.1% (Inhalation)

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 58.5%

#### **GHS** label elements

	English (US	) Chile	1/12
--	-------------	---------	------

Code PX7009 Date of issue 6 June 2020 Version 4.01

**Product name PSX 700 BLACK RESIN** 

### Section 2. Hazards identification

**Hazard pictograms** 





Signal word : Danger

**Hazard statements** : May cause an allergic skin reaction.

May cause cancer.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

Prevention : Øbtain special instructions before use. Wear protective gloves. Wear protective

clothing. Wear eye or face protection. Avoid release to the environment. Avoid

breathing vapor.

Response : F exposed or concerned: Get medical advice or attention. Take off contaminated

clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin

irritation or rash occurs: Get medical advice or attention.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Other hazards which do not : None known.

result in classification

Classification according to

NCh382:

: Not regulated.

Label according to

NCh2190:

: Not Regulated as a Dangerous Good.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of : Not available.

identification

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Ingredient name	%	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30 - <60	30583-72-3
Wollastonite bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate carbon black, respirable powder crystalline silica, respirable powder (<10 microns) methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	15 - <20 1 - <2 0.5 - <1 0.5 - <1 0.2 - <0.5	13983-17-0 41556-26-7 1333-86-4 14808-60-7 82919-37-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Code PX7009 Date of issue 6 June 2020 Version 4.01

Product name PSX 700 BLACK RESIN

## Section 3. Composition/information on ingredients

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician
 In case of inhalation of decomposition products in a fire, symptoms may be delayed.
 Specific treatments
 The exposed person may need to be kept under medical surveillance for 48 hours.

No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing media

: None known.

Specific hazards arising

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

: Use an extinguishing agent suitable for the surrounding fire.

carbon oxides nitrogen oxides

halogenated compounds metal oxide/oxides

English (US) Chile 3/12

Code PX7009 Date of issue 6 June 2020 Version 4.01

**Product name PSX 700 BLACK RESIN** 

### Section 5. Fire-fighting measures

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

**Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

English (US) Chile 4/12 Code PX7009 Date of issue 6 June 2020 Version 4.01

**Product name PSX 700 BLACK RESIN** 

# Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
₩ollastonite	ACGIH TLV (United States, 3/2019). TWA: 1 mg/m³ 8 hours. Form: Inhalable fraction

### **Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye protection Skin protection Hand protection**

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

**Gloves** : butyl rubber

English (US) Chile 5/12 Code PX7009 Date of issue 6 June 2020 Version 4.01

Product name PSX 700 BLACK RESIN

### Section 8. Exposure controls/personal protection

**Body protection** : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.

Color : Not available.
Odor : Characteristic.
pH : Not available.
Melting point : Not available.

**Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: 97.22°C (207°F)

**Evaporation rate** : 0.7 (butyl acetate = 1)

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flames also) limits

(flammable) limits

Vapor pressure

: 1.6 kPa (12 mm Hg) [room temperature]

Vapor density : Not available.

Relative density : 1.29

**Solubility** : Insoluble in the following materials: cold water.

Water Solubility at room

temperature

: 0.7 g/l

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

English (US) Chile 6/12

Code PX7009 Date of issue 6 June 2020 Version 4.01 **Product name PSX 700 BLACK RESIN** 

### Section 10. Stability and reactivity

**Conditions to avoid** 

: When exposed to high temperatures may produce hazardous decomposition products.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
s(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
carbon black, respirable powder	LD50 Dermal	Rabbit	>3 g/kg	-
·	LD50 Oral	Rat	>15400 mg/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-

: There are no data available on the mixture itself.

**Conclusion/Summary** 

Irritation/Corrosion

Not available.

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself. **Eyes** There are no data available on the mixture itself. Respiratory : There are no data available on the mixture itself.

**Sensitization** 

Not available.

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself. : There are no data available on the mixture itself. Respiratory

**Mutagenicity** 

Not available.

**Conclusion/Summary** 

Carcinogenicity

Not available.

: There are no data available on the mixture itself.

**Conclusion/Summary** 

**Classification** 

: There are no data available on the mixture itself.

English (US) Chile 7/12 Code PX7009 Date of issue 6 June 2020 Version 4.01
Product name PSX 700 BLACK RESIN

## **Section 11. Toxicological information**

Product/ingredient name	OSHA	IARC	NTP
₩ollastonite carbon black, respirable	-	3 2B	- -
powder crystalline silica, respirable powder (<10 microns)	-	1	Known to be a human carcinogen.

#### Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

#### Reproductive toxicity

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-

<u>Target organs</u>: Contains material which causes damage to the following organs: upper respiratory

tract, skin, eyes.

Contains material which may cause damage to the following organs: lungs.

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data. **Inhalation** : No specific data.

English (US) Chile	8/12
--------------------	------

Code PX7009 Date of issue 6 June 2020 Version 4.01

Product name PSX 700 BLACK RESIN

## Section 11. Toxicological information

**Skin contact**: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary**: There are no data available on the mixture itself. Trimethoxysilanes are capable of

forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Carbon black is utilized as a raw material in many liquid coating formulations. In this case, the carbon black particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of carbon black when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Most carbon blacks contain trace quantities of polyaromatic

hydrocarbons (PAH). PAHs are not expected to be released in biological fluids and are therefore not likely available for biological activity. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-

term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

effects

There are no data available on the mixture itself.

. There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

English (US) Chile 9/12

Code PX7009 Date of issue 6 June 2020 Version 4.01
Product name PSX 700 BLACK RESIN

# **Section 11. Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700 BLACK RESIN	14077	N/A	N/A	N/A	N/A
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3125	N/A	N/A	N/A	N/A
carbon black, respirable powder	N/A	2500	N/A	N/A	N/A
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3125	N/A	N/A	N/A	N/A

Other information : Not available.

# **Section 12. Ecological information**

### **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours

### Persistence/degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

English (US) Chile 10/12

Code PX7009 6 June 2020 Date of issue Version 4.01 **Product name PSX 700 BLACK RESIN** 

# **Section 14. Transport information**

	UN	Brazil (ANTT)	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

: None identified. UN : None identified. **Brazil** Risk number : Not available. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: NCh 382 - Hazardous substances - General terminology and classification.

NCh 2245 - Material Safety Data Sheet for Chemicals - Contents and section order.

D. S. 148 - Sanitary regulations on hazardous waste management.

D. S. 298 - Transport of dangerous goods by road.

D. S. 374 – Limit for Lead content in paints.

D. S. 594 - Regulation on basic sanitary and environmental conditions at workplace.

### Section 16. Other information

### **History**

Date of previous issue 2/18/2020

**Version** : 4.01

**EHS** 

English (US) Chile 11/12 Code Date of issue 6 June 2020 PX7009 Version 4.01

**Product name PSX 700 BLACK RESIN** 

### Section 16. Other information

Key to abbreviations

: ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

**UN = United Nations** 

: ABNT NBR 14725-4: 2014 References

ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or quarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (US) Chile 12/12