SAFETY DATA SHEET



Date of issue	6 August 2020
---------------	---------------

Version 5

Section 1. Product and company identification

Product name	1
Product code	:
Other means of identification	:
Product type	:

PITT-CHAR XP PITT-CHAR XP HARDENER BLACK PLURAL FEED

00333861

Not available.

Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	 PPG Industries Colombia Ltda Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)
Email address:	: HazComLatam@ppg.com
Emergency telephone number	Colombia: 01 8000 916012 (CISPROQUIM) + 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

Section 2. Hazards identification

	English (US) Colombia 1/12
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 61%
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 68.8% (Oral), 88.9% (Dermal), 76.7% (Inhalation)
Target organs	 Contains material which may cause damage to the following organs: kidneys, liver, brain, upper respiratory tract, skin, eyes.
Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 5 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

5

Section 2. Hazards identification

GHS label elements Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	May be harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer.
Precautionary statements		
Prevention	:	Øbtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor.
Response	:	F exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	:	Causes digestive tract burns.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

CAS number : Not applicable.		
Ingredient name	%	CAS number
Polyaminoamide	30 - <60	68082-29-1
melamine	20 - <30	108-78-1
4,4'-Isopropylidenediphenol, ethoxylated	7 - <10	32492-61-8 (EO>
2.4.6 tric/dimethylaminemethyl)phenel	E -7	4.5 moles) 90-72-2
2,4,6-tris(dimethylaminomethyl)phenol	5 - <7	
3,6-diazaoctanethylenediamin	2 - <3	112-24-3
glass, oxide, chemicals	1 - <2	65997-17-3
crystalline silica, respirable powder (>10 microns)	0.5 - <1	14808-60-7

English (US)	Colombia	2/12

Code	00333861	Date of issue	,	6 August 2020	Version	5
Product nam	e	PITT-CHAR XP PITT-CHAR XP HARDENER BLAC	K PLURAL FE	ED		

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary fin	rst a	id measures
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate me	dica	attention and special treatment needed, if necessary
Notes to physician Specific treatments		In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effec	<u>ts</u>	
Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	English (US) Colombia	3/12
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides	
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.	
Unsuitable extinguishing media	: None known.	
Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	

Section 5. Fire-fighting measures

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling
 Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

English (US)	Colombia
--------------	----------

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
--	---

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits		
grass, oxide, chemicals		ACGIH TLV (United States). TWA: 1 f/cc Form: Continuous filament glass fibers TWA: 5 mg/m³, (Inhalable) Form: Continuous filament glass fibers TWA: 3 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total dust ACGIH TLV (United States, 3/2019). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.		
Recommended monitoring procedures	atmosphere or biological monitoring of the ventilation or other control me protective equipment. Reference sh	vith exposure limits, personal, workplace may be required to determine the effectiveness asures and/or the necessity to use respiratory hould be made to appropriate monitoring uidance documents for methods for the ces will also be required.		
Appropriate engineering controls Environmental exposure controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			

Individual protection measures

Section 8. Exposure controls/personal protection

-		
Hygiene measures		Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection Skin protection	1	Chemical splash goggles and face shield.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	nitrile neoprene
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Characteristic.
рН	: Not available.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	:
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.14
Solubility	: Insoluble in the following materials: cold water.

5

Code	00333861	Date of issue	6 August 2020	Version	5
Product nam	ne	PITT-CHAR XP PITT-CHAR XP HARDENER BLACK P	LURAL FEED		

Section 9. Physical and chemical properties

Water Solubility at room temperature	1	13.7 g/l
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m ³	4 hours
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-
(dimethylaminomethyl) phenol				
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	805 mg/kg	-
-	LD50 Oral	Rat	2500 mg/kg	-

Conclusion/Summary

I here are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days
Conclusion/Summary	•		•	-	
Skin	: There are no data avai	able on the mix	ture itself.		
Eyes	: There are no data avai	able on the mix	ture itself.		
		Eng	glish (US)	Colombia	7/1

Code	00333861		·····	Version	5	
Product name		PITT-CHAR XP PITT-CHAR XP HARDENER BLACK PLURAL FEED				
Sectio	n 11.	Toxicological informatio	n			

Respiratory Sonsitization

: There are no data available on the mixture itself.

Sensilization			
Product/ingredient name	Route of exposure	Species	Result
₽,4,6-tris (dimethylaminomethyl) phenol	skin	Guinea pig	Sensitizing
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitizing

<u>conclusion/summary</u>	Conc	lusion	/Summary
---------------------------	------	--------	----------

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

: There are no data available on the mixture itself. Respiratory

Mutagenicity

Skin

Not available.

Conclusion/Summary

Carcinogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itse	elf.
---	------

Classification

Product/ingredient name	OSHA	IARC	NTP
Melamine glass, oxide, chemicals crystalline silica, respirable powder (>10 microns)	-	2B 3 1	- - Known to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which may cause damage to the following organs: kidneys, liver, brain, upper respiratory tract, skin, eyes.

Aspiration hazard

Section 11. Toxicological information

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effo	ects
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	: May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.
	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain
	: Adverse symptoms may include the following:
	: Adverse symptoms may include the following: pain watering
Eye contact	: Adverse symptoms may include the following: pain watering redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	:	There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headached dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solve vapors in combination with constant loud noise can cause greater hearing loss that expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea an vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure to oral, inhalation and dermal routes of exposure and eye contact.	e he e, f ent an
<u>Short term exposure</u>			
Potential immediate effects	:	There are no data available on the mixture itself.	
Potential delayed effects	1	There are no data available on the mixture itself.	
Long term exposure			
Potential immediate effects	:	There are no data available on the mixture itself.	
		English (US) Colombia	9/12

Code00333861Product namePlane	ITT-CHAR XP PITT-CHAR X	Date of issue XP HARDENER BLACK PLU	6 August 2020 RAL FEED	Version	5
Section 11. T	oxicological	information			
Potential delayed e	ffects : There are	no data available on the	e mixture itself.		
Potential chronic he	alth effects				
Not available.					
General	: Once sens to very low		reaction may occur whe	n subsequently	exposed
Carcinogenicity	: May cause	e cancer. Risk of cance	r depends on duration ar	nd level of expo	sure.

Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
TT-CHAR XP PITT-CHAR XP HARDENER	2654	1714.2	N/A	N/A	N/A
melamine	3161	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin	1200 2500	1280 1100	N/A N/A	N/A N/A	N/A N/A

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
	Acute EC50 200 mg/l	Daphnia	48 hours
	Acute LC50 175 mg/l	Fish	96 hours

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
melamine	-1.37	3.8	low
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group		Ш	III	III
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

UN	: None identified.		
Brazil	: None identified.		
Risk number	: 80		
IMDG	: None identified.		
ΙΑΤΑ	: None identified.		

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Code	00333861	Date of issue	•	6 August 2020	Version	5
Product nam	e	PITT-CHAR XP PITT-CHAR XP HARDENER BLAC	CK PLURAL FE	ED		

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

History

Date of previous issue	: 10/24/2019
Version	: 5
	EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods
	UN = United Nations
References	: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.