# **SAFETY DATA SHEET**



### Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 12 August 2020

Version 1

Date of issue 12 August 2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: SL UC TINT GRAY PIGMENT POWDER
Product code	: 00440249
Other means of identification	: Not applicable.
Product type	: Solid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

# **SECTION 2: Hazards identification**

Classification of the substance or mixture	:	CARCINOGENICITY - Category 1A
		Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 71% (Oral), 75% (Dermal), 71% (Inhalation)
GHS label elements		
Hazard pictograms	:	
Circuit would		
Signal word	1	Danger
Hazard statements	1	H350 - May cause cancer.
Precautionary statements		
Prevention	:	P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection.

### Product name SL UC TINT GRAY PIGMENT POWDER

### **SECTION 2: Hazards identification**

Response	:	P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	;	Not applicable.
Other hazards which do not result in classification	:	Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits toxic fumes when heated.

See toxicological information (Section 11)

# **SECTION 3: Composition/information on ingredients**

Substance/mixture	: Mixture
Product name	: SL UC TINT GRAY PIGMENT POWDER
Other means of identification	: Not applicable.

Ingredient name	%	CAS number
crystalline silica, respirable powder (>10 microns)	≥50 - ≤75	14808-60-7
titanium dioxide	≥20 - ≤50	13463-67-7
diiron trioxide	≥1.0 - ≤5.0	1309-37-1

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

#### **Description of necessary first aid measures**

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

#### **Over-exposure signs/symptoms**

See toxicological information (Section 11)

### Product name SL UC TINT GRAY PIGMENT POWDER

# SECTION 4: First aid measures

Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>		
Specific treatments	: No specific treatment.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

# **SECTION 5: Firefighting measures**

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: No specific fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for co	ont	ainment and cleaning up	
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.	

### **SECTION 6: Accidental release measures**

#### Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# **SECTION 7: Handling and storage**

Precautions for safe handling	1	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
crystalline silica, respirable powder (>10 microns) titanium dioxide diiron trioxide		NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m <sup>3</sup> 8 hours. NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction
C = Ceiling Limit IPEL = Internal Permissible Exposure Limit	STEL TLV	= Short term exposure limit = Threshold Limit Value

### Product name SL UC TINT GRAY PIGMENT POWDER

# **SECTION 8: Exposure controls/personal protection**

TWA = Time Weighted Average

#### Consult local authorities for acceptable exposure limits.

procedures		If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	4	Safety glasses with side shields.
Skin protection Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# **SECTION 9: Physical and chemical properties**

#### Appearance

Physical state	:	Solid.
Color	:	Gray.
Odor	:	Characteristic.
Odor threshold	:	Not available.
Molecular weight	:	Not applicable.
рН	1	Not available.
Melting point	1	Not available.
Boiling point	:	Not available.
Flash point	:	Closed cup: Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Flammability (solid, gas)	4	Not available.
Lower and upper explosive (flammable) limits	1	Not available.
Evaporation rate	1	Not available.
Vapor pressure	1	Not available.
Vapor density	1	Not available.
Relative density	:	2.65
Density(lbs / gal)	:	22.12
Solubility	:	Insoluble in the following materials: cold water.
Solubility in water	1	Not available.
Partition coefficient: n- octanol/water	1	Not available.
Viscosity	:	Kinematic (40°C (104°F)): Not applicable.
Volatility	1	0% (v/v), 0% (w/w)
% Solid. (w/w)	1	100

# **SECTION 10: Stability and reactivity**

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

# **SECTION 11: Toxicological information**

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result			Species	Dose	Exposure
titanium dioxide	LC50 Inha	lation Dus	ts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Derr	nal		Rabbit	>5000 mg/kg	-
	LD50 Oral			Rat	>5000 mg/kg	-
diiron trioxide			ts and mists		>5 mg/l	4 hours
	LD50 Oral			Rat	10 g/kg	-
Conclusion/Summary	: There a	re no data	available on	the mixture it	self.	
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There a	re no data	available on	the mixture it	self.	
Eyes	: There a	re no data	available on	the mixture it	self.	
Respiratory	: There a	re no data	available on	the mixture it	self.	
Sensitization						
Conclusion/Summary						
Skin	: There a	re no data	available on	the mixture it	self.	
Respiratory	: There a	re no data	available on	the mixture it	self.	
<u>Mutagenicity</u>						
Conclusion/Summary	: There a	re no data	available on	the mixture it	self.	
Carcinogenicity						
Conclusion/Summary	: There a	re no data	available on	the mixture it	self.	
<b>Classification</b>						
Product/ingredient name	OSHA	IARC	NTP			
crystalline silica, respirable powder (>10 microns)	-	1	Known to b	e a human ca	rcinogen.	
titanium dioxide	-	2B	-			

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### **Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

3

#### **Teratogenicity**

diiron trioxide

**Conclusion/Summary** : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

Target organs: Contains material which causes damage to the following organs: liver, spleen, bone<br/>marrow.<br/>Contains material which may cause damage to the following organs: kidneys, lungs,<br/>upper respiratory tract, immune system, skin, eyes.

# **SECTION 11: Toxicological information**

#### Aspiration hazard

Not available.

#### Information on the likely routes of exposure

Potential acute health effect	<u>s</u>	
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>om</u>	<u>s</u>
Eye contact	1	No specific data.
Inhalation	:	No specific data.
Skin contact	1	No specific data.
Ingestion	1	No specific data.
Delayed and immediate effe	<u>cts</u>	and also chronic effects from short and long term exposure
Conclusion/Summary	:	There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Potential chronic health effe	cts	
General	1	No known significant effects or critical hazards.
Carcinogenicity	1	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	1	No known significant effects or critical hazards.

#### Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)		(vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
diiron trioxide	10000	N/A	N/A	N/A	N/A

Mexico	Page: 8/11
monioo	i agoi o/ i i

### **SECTION 12: Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# **SECTION 14: Transport information**

	<b>Mexico Classification</b>	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
I		'	Mexico Page: 9/11

SECTION	N 14: Transport information	ation	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.
Additional in	formation		
Mexico	: None identified.		
WEXICO			
IMDG	: None identified.		

Transport in bulk according : Not applicable. to IMO instruments

# **SECTION 15: Regulatory information**

#### **Mexico**

Classification

Flammability : 0 Health : 1 Reactivity : 0

#### International regulations

**Montreal Protocol** 

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **SECTION 16: Other information**

#### Hazardous Material Information System (U.S.A.)

Health : 1 \* Flammability : 0 Physical hazards : 0 (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue

: No previous validation

Organization that prepared : EHS the MSDS

### Product name SL UC TINT GRAY PIGMENT POWDER

### **SECTION 16: Other information**

Key to abbreviations	: ATE = Acute Toxicity Estimate
-	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations
🔽 Indiaataa informatia	n that has changed from providually issued version

#### Indicates information that has changed from previously issued version.

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.