# **SAFETY DATA SHEET**

pPG

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Date of issue/Date of revision 20 November 2020

Version 2

evision	

Section 1. Chem	ical product and company identification
Product code	: 00422659
Product name	: AMERCOAT 220 RAL 7046
Product name	: AMERCOAT 220 RAL 7046
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Supplier's details	: PPG Coatings (Kunshan) Co., Ltd 53 Jinyang Road, Lujia Town, 215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857
Emergency telephone number (with hours of operation)	: 00 86 532 83889090

# Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

 Emergency overview

 Liquid.

 Gray.

 Combustible liquid.

 May damage fertility or the unborn child.

 Harmful to aquatic life.

 IF exposed or concerned: Get medical advice or attention.

 See Section 12 for environmental precautions.

 Classification of the substance or mixture

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :

 :<

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 25.4% (oral), 32.7% (dermal), 35.2% (inhalation)

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 31.4%

#### **GHS label elements**

# Section 2. Hazards identification

ŝ

Hazard	pictograms



Signal word	:	Danger
Hazard statements	:	Combustible liquid. May damage fertility or the unborn child. Harmful to aquatic life.
Precautionary statements		
Prevention	-	Øbtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Keep away from flames and hot surfaces. No smoking. Avoid release to the environment.
Response	1	F exposed or concerned: Get medical advice or attention.
Suitable extinguishing media	:	Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Storage	1	Store in a well-ventilated place. Keep cool.
Disposal	-	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Physical and chemical hazards	:	Combustible liquid.
Health hazards	:	May damage fertility or the unborn child.
Symptoms related to the phy	<u>/sic</u>	al, chemical and toxicological characteristics
Eye contact	1	No specific data.
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate effect	cts	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
		China Page: 2/12

## Section 2. Hazards identification

Environmental hazards : Harmful to aquatic life.

Other hazards which do not : Mone known. result in classification

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

: Not applicable.

#### **CAS number/other identifiers**

CAS number

Ingredient name	%	CAS number
(2-methoxyethoxy)ethanol	1 - <10	111-77-3
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	1 - <10	25265-77-4
dibutyl phthalate	1 - <10	84-74-2
ammonia (more than 10%)	0.1 - <1	1336-21-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

# Description of necessary first aid measures Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and<br/>water or use recognized skin cleanser. Do NOT use solvents or thinners.Ingestion: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

Potential acute healt	h effects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Product code 00422659 Product name AMERCOAT 220 RAL 7046

# Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.

Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

## Section 6. Accidental release measures

Personal	precautions,	protective eq	uipment and	l emergency p	orocedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions for safe Put on appropriate personal protective equipment (see Section 8). Eating, drinking ÷. handling and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Section 7. Handling and storage

Conditions for safe storage,	: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in
including any	accordance with local regulations. Store in a segregated and approved area. Store
incompatibilities	in original container protected from direct sunlight in a dry, cool and well-ventilated
	area, away from incompatible materials (see Section 10) and food and drink. Store
	locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep
	container tightly closed and sealed until ready for use. Containers that have been
	opened must be carefully resealed and kept upright to prevent leakage. Do not
	store in unlabeled containers. Use appropriate containment to avoid environmental
	contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name			Exposure limits
dibutyl phthalate			GBZ 2.1 (China, 8/2019). PC-TWA: 2.5 mg/m <sup>3</sup> 8 hours.
Recommended monitoring procedures	- ()   !	atmosphere or biological monitoring m of the ventilation or other control meas	
Appropriate engineering controls	\ ( ;	contaminants below any recommende	ls to keep worker exposure to airborne d or statutory limits. The engineering controls concentrations below any lower explosive
Environmental exposure controls	t	Emissions from ventilation or work process equipment should be checked to ensurt they comply with the requirements of environmental protection legislation. In som cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
dividual protection measu	<u>ires</u>		
Hygiene measures		eating, smoking and using the lavatory Appropriate techniques should be use	ughly after handling chemical products, before y and at the end of the working period. d to remove potentially contaminated clothing. eusing. Ensure that eyewash stations and tation location.
Eye protection	: 3	Safety glasses with side shields.	
Skin protection			
Hand protection	t 0 9 0 9	be worn at all times when handling che his is necessary. Considering the par check during use that the gloves are s should be noted that the time to break	a complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of e of the gloves cannot be accurately

# Section 8. Exposure controls/personal protection

Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: Viton®
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Gray.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 92°C (197.6°F)
Lower and upper explosive (flammable) limits	: Greatest known range: Lower: 1.6% Upper: 18.1% (2-(2-methoxyethoxy)ethanol)
Relative density	: 1.26
Solubility	: Partially soluble in the following materials: cold water.
Viscosity	: Kinematic (40°C): >0.21 cm²/s

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

## Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-methoxyethoxy)ethanol	LD50 Oral	Rat	9.2 g/kg	-
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	LD50 Dermal	Rabbit	>15.2 g/kg	-
	LD50 Oral	Rat	6.5 g/kg	-
dibutyl phthalate	LD50 Oral	Rat	7499 mg/kg	-
ammonia (more than 10%)	LD50 Oral	Rat	350 mg/kg	-

#### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	-	Development toxin	Species	Dose	Exposure
dîbutyl phthalate	-	-	-	Rat	Oral	-

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
ammonia (more than 10%)	Category 3		Respiratory tract irritation

: No known significant effects or critical hazards.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

#### Information on the likely : Not available.

routes of exposure

<b>Potential</b>	acute	<u>health</u>	<u>effects</u>	

- Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.
- Ingestion

## Section 11. Toxicological information

Symptoms related to the	nhuaiaal ahamiaal	l and taxical aniad	abaraatariatiaa
Symptoms related to the	DOVSICAL COEDICA		characteristics
	privoloui, ononnou		

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: May damage fertility or the unborn child.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
(2-methoxyethoxy)ethanol isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	9200 6500	N/A N/A	N/A N/A	N/A N/A	N/A N/A
dibutyl phthalate ammonia (more than 10%)	7499 350	N/A N/A	N/A N/A	N/A N/A	N/A N/A

#### Other information

1

None known.

# Section 12. Ecological information

Toxicity				
Product/ingredient name	Result	Species	Exposure	
Sobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	Acute LC50 33 mg/l	Fish	96 hours	
dibutyl phthalate	LC50 0.85 mg/l Chronic NOEC 0.5 mg/l Fresh water	Fish Algae - Desmodesmus subspicatus	96 hours 72 hours	

#### Persistence/degradability

Product/ingredient name	Test	Result		Dose		Inoculum
sobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	OECD 301B	>76 % - Re	adily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	<b>Jradability</b>
sobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	-		-		Readily	/

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
, ( , , , , , , , , , , , , , , , , , ,	-1.14 to 0.93 3.47	-	low low
dibutyl phthalate	4.5	165.96	low

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

	Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly
--	------------------	--

China Page: 10/12

## Section 13. Disposal considerations

internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

China	UN	IMDG	ΙΑΤΑ
Not regulated.	Not regulated.	Not regulated.	Not regulated.
-	-	-	-
-	-	-	-
-	-	-	-
No.	No.	No.	No.
Not applicable.	Not applicable.	Not applicable.	Not applicable.
	Not regulated Not regulated. Not regulated.	Not regulated.Not regulatedNo.No.	Not regulated.Not regulatedNo.No.

#### **Additional information**

CN	: None identified.
UN	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

**Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

## Section 15. Regulatory information

China inventory (IECSC)	: All components are listed or exempted.
References	<ul> <li>Production Safety Law of the People's Republic of China Code of Occupational Disease Prevention of the People's Republic of China Environmental Protection Law of the People's Republic of China Fire Control Law of the People's Republic of China Regulations on the Control over Safety of Dangerous Chemicals Occupational exposure limits for hazardous agents in the workplace chemical hazardous agents (GBZ2.1) General rule for classification and hazard communication of chemicals (GB13690) Safety data sheet for chemical products - Content and order of sections (GB/ T16483) Guidance on the compilation of safety data sheet for chemical products (GB/ T17519) General rule for preparation of precautionary label for chemicals (GB15258) Safety rules for classification, precautionary labeling and precautionary statements</li> </ul>

Product code 00422659

Product name AMERCOAT 220 RAL 7046

## Section 15. Regulatory information

of chemicals (GB30000.2-29)

# Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 20 November 2020
Date of previous issue	: 12/22/2018
Version	: 2
	EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	UN = United Nations

**V** Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.