

Date of issue 1/8/2021 (month/day/year)

Version 20

Section 1. Chemical product and company identification

A. **Product name** : SIGMAZINC 158 BIN KRA(EXP)OFFWH
Product code : 00327451

B. **Relevant identified uses of the substance or mixture and uses advised against**

Product use : Professional applications, Used by spraying.

**Use of the substance/
mixture** : Coating.


Uses advised against : Product is not intended, labelled or packaged for consumer use.

C. **Supplier's information** : PPG SSC
(680-090)
19, Yeocheon-ro 217beon-gil, Nam-gu,
Ulsan, Korea
Tel: +82-52-210-8222

Email Address : Korea.MSDS@PPG.COM

**Emergency telephone
number:** : +82-52-210-8222

Section 2. Hazards identification

A. **Hazard classification** :  FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. **GHS label elements, including precautionary statements**

Symbol :   

Signal word : Danger

Section 2. Hazards identification

- Hazard statements** : H226 - Flammable liquid and vapor.
 H315 - Causes skin irritation.
 H319 - Causes serious eye irritation.
 H336 - May cause drowsiness or dizziness.
 H350 - May cause cancer.
 H360 - May damage fertility or the unborn child.
 H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS), kidneys, liver)
- Precautionary statements**
- Prevention** : P201 - Obtain special instructions before use.
 P280 - Wear protective gloves, protective clothing and eye or face protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 - Use explosion-proof electrical, ventilating or lighting equipment.
 P242 - Use non-sparking tools.
 P243 - Take action to prevent static discharges.
 P260 - Do not breathe vapor.
 P270 - Do not eat, drink or smoke when using this product.
 P264 - Wash thoroughly after handling.
- Response** : P308 + P313 - IF exposed or concerned: Get medical advice or attention.
 P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
 P362 + P364 - Take off contaminated clothing and wash it before reuse.
 P302 + P352 - IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 - Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

- C. Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number : Not applicable.

Chemical name	Common name	Identifiers	%
Crystalline silica, respirable powder (<10 microns)	QUARTZ (<10 microns)	CAS: 14808-60-7	10 -<20
Silicic acid, ethyl ester	ETHYL SILICATE POLYMER	CAS: 11099-06-2	10 -<20
Xylene	XYLENES	CAS: 1330-20-7	10 -<20
1-methoxy-2-propanol	PROPYLENE GLYCOL MONOMETHYL ETHER	CAS: 107-98-2	10 -<20
ethanol	ETHYL ALCOHOL	CAS: 64-17-5	5 - <10
tetraethyl silicate	Tetraethyl Silicate	CAS: 78-10-4	5 - <10
Isopropyl alcohol	ISOPROPYL ALCOHOL	CAS: 67-63-0	1 - <5
Mica-group minerals	MICA	CAS: 12001-26-2	1 - <5
ethylbenzene	ETHYLBENZENE	CAS: 100-41-4	1 - <5
Methyl alcohol	METHYL ALCOHOL	CAS: 67-56-1	0.1 - <1

Section 3. Composition/information on ingredients

trimethyl borate	trimethyl borate	CAS: 121-43-7	0.1 - <1
Sulfuric acid	SULFURIC ACID	CAS: 7664-93-9	0.1 - <1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Non displayed substances are regarded as Business Confidential information.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

- A. Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- B. Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- C. Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- D. Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- E. Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

- A. Extinguishing media**
- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- B. Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

Section 5. Fire-fighting measures

- C. Special equipment for fire-fighting** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire-fighting procedures** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- C. Methods and materials for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

- A. Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

- B. Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
crystalline silica, respirable powder (<10 microns)	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 0.05 mg/m ³ 8 hours. Form: Respirable fraction
Xylene	Ministry of Employment and Labor (Republic of Korea, 1/2020). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
1-methoxy-2-propanol	Ministry of Employment and Labor (Republic of Korea, 1/2020). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
ethanol	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 1000 ppm 8 hours.
tetraethyl silicate	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 10 ppm 8 hours.
Isopropyl alcohol	Ministry of Employment and Labor (Republic of Korea, 1/2020). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.
Mica-group minerals	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 3 mg/m ³ 8 hours. Form: Respirable fraction
ethylbenzene	Ministry of Employment and Labor (Republic of Korea, 1/2020). STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours.
Methyl alcohol	Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed through skin. STEL: 250 ppm 15 minutes. TWA: 200 ppm 8 hours.
trimethyl borate	ACGIH TLV (United States). STEL: 6 mg/m ³ TWA: 2 mg/m ³

Section 8. Exposure controls/personal protection

Sulfuric acid

**Ministry of Employment and Labor
(Republic of Korea, 1/2020).**

TWA: 0.2 mg/m³ 8 hours. Form: Thoracic fraction

STEL: 0.6 mg/m³ 15 minutes. Form: Thoracic fraction

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

B. Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Eye protection

: Chemical splash goggles.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: polyvinyl alcohol (PVA), Viton®, butyl rubber, nitrile rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

A. Appearance

Physical state : Liquid.

Color : Off-white.

B. Odor : Aromatic.

C. Odor threshold : Not available.

D. pH : Not applicable.

E. Melting/freezing point : Not available.

F. Boiling point/boiling range : >37.78°C (>100°F)

G. Flash point : Closed cup: 23°C (73.4°F)

H. Evaporation rate : Not available.

I. Flammability (solid, gas) : Not available.

J. Lower and upper explosive (flammable) limits : Greatest known range: Lower: 1.3% Upper: 23% (tetraethyl silicate)

K. Vapor pressure : Not available.

L. Solubility : Insoluble in the following materials: cold water.

Solubility in water : Not available.

M. Vapor density : Not available.

N. Relative density : 1.11

O. Partition coefficient: n-octanol/water : Not available.

P. Auto-ignition temperature : Not available.

Q. Decomposition temperature : Not available.

R. Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

S. Molecular weight : Not applicable.

Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

D. Hazardous decomposition products : Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Ingestion** : Can cause central nervous system (CNS) depression.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Eye contact** : Causes serious eye irritation.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Silicic acid, ethyl ester	LD50 Oral	Rat	6270 mg/kg	-
Xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	5.2 g/kg	-
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Dermal	Rat	17100 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-
tetraethyl silicate	LC50 Inhalation Dusts and mists	Rat	10 to 16 mg/l	4 hours
	LD50 Dermal	Rabbit	5.878 g/kg	-
	LD50 Oral	Rat	6270 mg/kg	-

Section 11. Toxicological information

Isopropyl alcohol	LC50 Inhalation Vapor	Rat	72600 mg/m ³	4 hours
	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5045 mg/kg	-
ethylbenzene	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
Methyl alcohol	LC50 Inhalation Gas.	Rat	145000 ppm	1 hours
	LC50 Inhalation Gas.	Rat	64000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
trimethyl borate	LD50 Oral	Rat	5600 mg/kg	-
	LD50 Dermal	Rabbit	1.98 g/kg	-
	LD50 Oral	Rat	6.14 g/kg	-
Sulfuric acid	LD50 Oral	Rat	2140 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization**Conclusion/Summary**

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

Name	Classification	Route of exposure	Target organs
Xylene	Category 3	-	Narcotic effects
1-methoxy-2-propanol	Category 3	-	Narcotic effects
tetraethyl silicate	Category 3	-	Respiratory tract irritation
Isopropyl alcohol	Category 3	-	Narcotic effects
Methyl alcohol	Category 1	-	-
trimethyl borate	Category 1	-	optic nerve

Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
Xylene	Category 1	-	central nervous system (CNS), kidneys, liver

Aspiration hazard

Name	Result
Isopropyl alcohol	ASPIRATION HAZARD - Category 2
ethylbenzene	ASPIRATION HAZARD - Category 1

Potential chronic health effects

- General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage fertility or the unborn child.

Additional information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Chemical name	Common name	CAS #	GHS Classification
<input checked="" type="checkbox"/> Crystalline silica, respirable powder (<10 microns)	QUARTZ (<10 microns)	14808-60-7	CARCINOGENICITY - Category 1A
Silicic acid, ethyl ester	ETHYL SILICATE	11099-06-2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Xylene	POLYMER XYLENES	1330-20-7	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY

Section 11. Toxicological information

1-methoxy-2-propanol	PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	(SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 FLAMMABLE LIQUIDS - Category 3
ethanol	ETHYL ALCOHOL	64-17-5	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
tetraethyl silicate	Tetraethyl Silicate	78-10-4	CARCINOGENICITY - Category 2 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Isopropyl alcohol	ISOPROPYL ALCOHOL	67-63-0	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Mica-group minerals ethylbenzene	MICA ETHYLBENZENE	12001-26-2 100-41-4	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 ASPIRATION HAZARD - Category 2 Not classified.
Methyl alcohol	METHYL ALCOHOL	67-56-1	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1
trimethyl borate	trimethyl borate	121-43-7	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Sulfuric acid	SULFURIC ACID	7664-93-9	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 TOXIC TO REPRODUCTION - Category 1B
			SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (inhalation) - Category 2 SKIN CORROSION/IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 CARCINOGENICITY - Category 1A

Section 11. Toxicological information

AQUATIC HAZARD (LONG-TERM) -
Category 3

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> methoxy-2-propanol	Acute LC50 23300 mg/l	Daphnia	48 hours
	Acute LC50 >4500 mg/l Fresh water	Fish	96 hours
ethanol	Acute EC50 7640 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
Isopropyl alcohol	Acute EC50 10100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
ethylbenzene	Acute LC50 150 to 200 mg/l Fresh water	Fish	96 hours
Methyl alcohol	Acute LC50 13 mg/l Fresh water	Fish	96 hours

B. Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<input checked="" type="checkbox"/> Xylene	-	-	Readily
ethanol	-	-	Readily
ethylbenzene	-	-	Readily

C. Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
<input checked="" type="checkbox"/> Xylene	3.16	7.4 to 18.5	low
ethanol	-0.31	-	low
Isopropyl alcohol	0.05	-	low
ethylbenzene	3.15	79.43	low
Methyl alcohol	-0.77	-	low
trimethyl borate	-1.9	-	low

D. Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 13. Disposal considerations

- B. Disposal precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	UN1263	UN1263	UN1263
B. UN proper shipping name	PAINT	PAINT	PAINT
C. Transport hazard class(es)	3	3	3
D. Packing group	III	III	III
Environmental hazards	No.	No.	No.
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- UN** : None identified.
IMDG : None identified.
IATA : None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

A. Regulation according to ISHA

- ISHA article 117 (Harmful substances prohibited from manufacture)** : None of the components are listed.
ISHA article 118 (Harmful substances requiring permission) : None of the components are listed.

Section 15. Regulatory information

Article 2 of Youth Protection Act on Substances Hazardous to Youth : It is not allowed to sell to persons under the age of 19.

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

Crystalline silica, respirable powder (<10 microns)

Xylene

1-methoxy-2-propanol

ethanol

tetraethyl silicate

Isopropyl alcohol

Mica-group minerals

ethylbenzene

Methyl alcohol

trimethyl borate

Sulfuric acid

ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors) : The following components are listed: methanol, sulfuric acid

ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement) : The following components are listed: xylene, ethyl benzene, quartz, isopropyl alcohol, mica

ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check-up) : The following components are listed: Xylene, Ethyl benzene, Isopropyl alcohol

Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control) : The following components are listed: xylene, ethyl benzene, isopropyl alcohol, sulfuric acid

B. Regulation according to Chemicals Control Act

CCA Article 11 (TRI) : The following components are listed: Xylene including o-,m-,p- isomer, Ethylbenzene, 2-Propanol

CCA Article 18 Prohibited (K-Reach Article 27) : None of the components are listed.

CCA Article 19 Subject to authorization (K-Reach Article 25) : None of the components are listed.

CCA Article 20 Restricted (K-Reach Article 27) : None of the components are listed.

CCA Article 20 Toxic Chemicals (K-Reach Article 20) : Not applicable

Section 15. Regulatory information

- Korea inventory** : All components are listed or exempted.
- CCA Article 39 (Accident Precaution Chemicals)** : None of the components are listed.
- C. Dangerous Materials Safety Management Act** : **Class:** Class 4 - Flammable Liquid
Item: 4. Class 2 petroleums - Water-insoluble liquid
Threshold: 1000 L
Danger category: III
Signal word: Contact with sources of ignition prohibited
- D. Wastes regulation** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- E. Regulation according to other foreign laws**
- Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

- A. References** : Korean Ministry of Environment; Chemical Control Act
Korean Ministry of Labor; Industrial Safety and Health Act
NIER Notice
Registry of Toxic Effects of Chemical Substances (RTECS)
U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
- B. Date of issue/Date of revision** : 1/8/2021
- C. Version** : 20
- Prepared by** : EHS
- D. Other**

☑ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.