


Date of issue 3/20/2021 (month/day/year)

Version 7

## Section 1. Chemical product and company identification




- A. Product name** : SIGMADUR 550 BASE CNC 4076  
**Product code** : 00375488
- B. Relevant identified uses of the substance or mixture and uses advised against**
- Product use** : Professional applications, Used by spraying.  
**Use of the substance/ mixture** : Coating.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.
- C. Supplier's information** : PPG SSC  
(680-090)  
19, Yeocheon-ro 217beon-gil, Nam-gu,  
Ulsan, Korea  
Tel: +82-52-210-8222
- Email Address** : Korea.MSDS@PPG.COM
- Emergency telephone number:** : +82-52-210-8222

## Section 2. Hazards identification

- A. Hazard classification** :  LAMMABLE LIQUIDS - Category 3  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
AQUATIC HAZARD (LONG-TERM) - Category 3

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

**B. GHS label elements, including precautionary statements**

**Symbol** :   

**Signal word** : Danger

## Section 2. Hazards identification

**Hazard statements** :  H226 - Flammable liquid and vapor.  
 H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H336 - May cause drowsiness or dizziness.  
 H351 - Suspected of causing cancer.  
 H372 - Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS), kidneys, liver)  
 H412 - Harmful to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** :  P201 - Obtain special instructions before use.  
 P280 - Wear protective gloves, protective clothing and eye or face protection.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241 - Use explosion-proof electrical, ventilating or lighting equipment.  
 P242 - Use non-sparking tools.  
 P243 - Take action to prevent static discharges.  
 P273 - Avoid release to the environment.  
 P260 - Do not breathe vapor.  
 P270 - Do not eat, drink or smoke when using this product.  
 P264 - Wash thoroughly after handling.

**Response** :  P308 + P313 - IF exposed or concerned: Get medical advice or attention.  
 P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
 P362 + P364 - Take off contaminated clothing and wash it before reuse.  
 P302 + P352 - IF ON SKIN: Wash with plenty of water.  
 P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 - Keep cool.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**C. Other hazards which do not result in classification** :  Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

### CAS number/other identifiers

**CAS number** : Not applicable.

| Chemical name                                      | Common name  | Identifiers     | %        |
|--|--|-----------------|----------|
| <input checked="" type="checkbox"/> Xylene         | XYLENES  | CAS: 1330-20-7  | 20 - <30 |
| n-butyl acetate                                    | N-BUTYL ACETATE  | CAS: 123-86-4   | 5 - <10  |
| ethylbenzene                                       | ETHYLBENZENE   | CAS: 100-41-4   | 1 - <5   |
| Talc , not containing asbestiform fibres           | Talc, non-asbestos form                                      | CAS: 14807-96-6 | 1 - <5   |
| iron hydroxide oxide yellow                        | IRON HYDROXIDE OXIDE   | CAS: 51274-00-1 | 1 - <5   |
| 2-methoxy-1-methylethyl acetate                    | 1-METHOXY-2-PROPYL ACETATE                                   | CAS: 108-65-6   | 1 - <5   |
| Octadecanamide, N,N'-1,6-hexanediylbis             | N,N-1,6-HEXANEDIYLBIS  | CAS: 55349-01-4 | 1 - <5   |
| [12-hydroxy-<br>Solvent naphtha (petroleum), light | (12-HYDROXY-OCTADECANEIMIDE)<br>SOLVENT NAPHTHA (PETROLEUM), | CAS: 64742-95-6 | 1 - <5   |

### Section 3. Composition/information on ingredients

|  |  |                  |          |
|--|--|------------------|----------|
| aromatic   | LIGHT AROMATIC   |                  |          |
| 2-butoxyethanol  | 2-BUTOXY ETHANOL   | CAS: 111-76-2    | 0.1 - <1 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  | BIS(PENTAMETHYLPYPERIDYL) SEBACATE   | CAS: 41556-26-7  | 0.1 - <1 |
| 2-Propenoicacid,2-ethylhexylester, reactionproductswithethylenediamine-ethyleniminepolymer,compds. withpolyethylene-polypropyleneglycolmono-Buetherphosphate | 2-Propenoicacid,2-ethylhexylester, reactionproductswithethylenediamine-ethyleniminepolymer,compds. withpolyethylene-polypropyleneglycolmono-Buetherphosphate | CAS: 398475-96-2 | 0.1 - <1 |
| cyclohexanone  | CYCLOHEXANONE  | CAS: 108-94-1    | 0.1 - <1 |
| titanium dioxide   | TITANIUM DIOXIDE   | CAS: 13463-67-7  | 0.1 - <1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

- A. Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- B. Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- C. Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- D. Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- E. Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** :  No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

- A. Extinguishing media**
- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

## Section 5. Fire-fighting measures

- B. Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
metal oxide/oxides
- C. Special equipment for fire-fighting** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire-fighting procedures** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

## Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- C. Methods and materials for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

- A. Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- B. Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### A. Occupational exposure limits

| Ingredient name                          | Exposure limits  |
|--|--|
| Xylene                                   | <b>Ministry of Employment and Labor (Republic of Korea, 1/2020).</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.     |
| n-butyl acetate                          | <b>Ministry of Employment and Labor (Republic of Korea, 1/2020).</b><br>STEL: 200 ppm 15 minutes.<br>TWA: 150 ppm 8 hours.     |
| ethylbenzene                             | <b>Ministry of Employment and Labor (Republic of Korea, 1/2020).</b><br>STEL: 125 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.     |
| Talc , not containing asbestiform fibres | <b>ACGIH TLV (United States, 3/2019).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable                                |
| iron hydroxide oxide yellow              | <b>Ministry of Employment and Labor (Republic of Korea, 1/2020).</b><br>TWA: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. Form: Fume |
| 2-butoxyethanol                          | TWA: 5 mg/m <sup>3</sup> , (as Fe) 8 hours.<br><b>Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed</b>   |

## Section 8. Exposure controls/personal protection

cyclohexanone

titanium dioxide

through skin.

TWA: 20 ppm 8 hours.

**Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed through skin.**

TWA: 25 ppm 8 hours.

STEL: 50 ppm 15 minutes.

**Ministry of Employment and Labor (Republic of Korea, 1/2020).**

TWA: 10 mg/m<sup>3</sup> 8 hours. Form: total dust with less than 1% of free SiO<sub>2</sub>

### Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### B. Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### C. Personal protective equipment

#### Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

#### Eye protection

: Chemical splash goggles.

#### Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### Gloves

:  Butyl rubber

#### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

## Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 9. Physical and chemical properties

- A. Appearance**
- Physical state** : Liquid.
- Color** : Not available.
- B. Odor** : Characteristic.
- C. Odor threshold** : Not available.
- D. pH** : Not applicable.
- E. Melting/freezing point** : Not available.
- F. Boiling point/boiling range** : >37.78°C (>100°F)
- G. Flash point** : Closed cup: 25°C (77°F)
- H. Evaporation rate** : Not available.
- I. Flammability (solid, gas)** : Not available.
- J. Lower and upper explosive (flammable) limits** : Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)
- K. Vapor pressure** : Not available.
- L. Solubility** : Insoluble in the following materials: cold water.
- Solubility in water** : Not available.
- M. Vapor density** : Not available.
- N. Relative density** : 1.21
- O. Partition coefficient: n-octanol/water** : Not available.
- P. Auto-ignition temperature** : Not available.
- Q. Decomposition temperature** : Not available.
- R. Viscosity** : Kinematic (40°C (104°F)): >0.21 cm<sup>2</sup>/s (>21 cSt)
- S. Molecular weight** : Not applicable.

## Section 10. Stability and reactivity

- A. Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- B. Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

## Section 10. Stability and reactivity

**C. Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**D. Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides metal oxide/oxides

## Section 11. Toxicological information

**A. Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Ingestion** : Can cause central nervous system (CNS) depression.

**Skin contact** : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye irritation.

### Over-exposure signs/symptoms

**Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Ingestion** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### B. Health hazards

#### Acute toxicity

| Product/ingredient name     | Result                          | Species | Dose         | Exposure |
|-----------------------------|---------------------------------|---------|--------------|----------|
| Xylene                      | LD50 Dermal                     | Rabbit  | 1.7 g/kg     | -        |
|                             | LD50 Oral                       | Rat     | 4.3 g/kg     | -        |
| n-butyl acetate             | LC50 Inhalation Vapor           | Rat     | >21.1 mg/l   | 4 hours  |
|                             | LC50 Inhalation Vapor           | Rat     | 2000 ppm     | 4 hours  |
| ethylbenzene                | LD50 Dermal                     | Rabbit  | >17600 mg/kg | -        |
|                             | LD50 Oral                       | Rat     | 10.768 g/kg  | -        |
|                             | LC50 Inhalation Vapor           | Rat     | 17.8 mg/l    | 4 hours  |
| iron hydroxide oxide yellow | LD50 Dermal                     | Rabbit  | 17.8 g/kg    | -        |
|                             | LD50 Oral                       | Rat     | 3.5 g/kg     | -        |
|                             | LC50 Inhalation Dusts and mists | Rat     | >5.05 mg/l   | 4 hours  |
|                             | LD50 Oral                       | Rat     | >10 g/kg     | -        |



**Section 11. Toxicological information**

|   |                                 |            |             |         |
|---|---------------------------------|------------|-------------|---------|
| 2-methoxy-1-methylethyl acetate                 | LD50 Dermal                     | Rabbit     | >5 g/kg     | -       |
|   | LD50 Oral                       | Rat        | 6190 mg/kg  | -       |
| Solvent naphtha (petroleum), light aromatic     | LD50 Dermal                     | Rabbit     | 3.48 g/kg   | -       |
|   | LD50 Oral                       | Rat        | 8400 mg/kg  | -       |
| 2-butoxyethanol                                 | LD50 Dermal                     | Rabbit     | 1060 mg/kg  | -       |
|   | LD50 Oral                       | Rat - Male | 1480 mg/kg  | -       |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | LD50 Oral                       | Rat        | 3.125 g/kg  | -       |
| cyclohexanone                                   | LC50 Inhalation Gas.            | Rat        | 8000 ppm    | 4 hours |
|   | LC50 Inhalation Vapor           | Rat        | 11 mg/l     | 4 hours |
|   | LD50 Dermal                     | Rabbit     | 1100 mg/kg  | -       |
|   | LD50 Oral                       | Rat        | 1.54 g/kg   | -       |
| titanium dioxide                                | LC50 Inhalation Dusts and mists | Rat        | >6.82 mg/l  | 4 hours |
|   | LD50 Dermal                     | Rabbit     | >5000 mg/kg | -       |
|   | LD50 Oral                       | Rat        | >5000 mg/kg | -       |

**Conclusion/Summary** : There are no data available on the mixture itself.

**Irritation/Corrosion**

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| Xylene                  | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| 2-butoxyethanol         | Skin - Moderate irritant | Rabbit  | -     | 4 hours         | 28 days     |
|                         | Eyes - Irritant          | Rabbit  | -     | 24 hours        | 21 days     |

**Conclusion/Summary**

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

**Sensitization****Conclusion/Summary**

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

**Mutagenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Carcinogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

**Specific target organ toxicity (single exposure)**

**Section 11. Toxicological information**

| Name   | Classification                         | Route of exposure | Target organs  |
|--|--|-------------------|--|
| <input checked="" type="checkbox"/> Xylene<br>n-butyl acetate<br>Talc , not containing asbestiform fibres  | Category 3<br>Category 3<br>Category 3 | -<br>-<br>-       | Narcotic effects<br>Narcotic effects<br>Respiratory tract irritation |
| 2-methoxy-1-methylethyl acetate<br>Solvent naphtha (petroleum), light aromatic   | Category 3<br>Category 3               | -<br>-            | Narcotic effects<br>Respiratory tract irritation                     |
| 2-Propenoicacid,2-ethylhexylester,<br>reactionproductswithethylenediamine-ethyleniminepolymer,<br>compds.withpolyethylene-polypropyleneglycolmono-<br>Buetherphosphate | Category 3<br>Category 3               | -                 | Narcotic effects<br>Respiratory tract irritation                     |

**Specific target organ toxicity (repeated exposure)**

| Name                                       | Classification | Route of exposure | Target organs                                   |
|--|----------------|-------------------|---|
| <input checked="" type="checkbox"/> Xylene | Category 1     | -                 | central nervous system (CNS),<br>kidneys, liver |

**Aspiration hazard**

| Name  | Result   |
|---|--|
| ethylbenzene<br>Solvent naphtha (petroleum), light aromatic | ASPIRATION HAZARD - Category 1<br>ASPIRATION HAZARD - Category 1 |

**Potential chronic health effects**

- General** :  Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** :  No known significant effects or critical hazards.

**Additional information**

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

## Section 11. Toxicological information

| Chemical name  | Common name  | CAS #      | GHS Classification   |
|--|--|------------|--|
| Xylene   | XYLENES  | 1330-20-7  | FLAMMABLE LIQUIDS - Category 3<br>ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN CORROSION/IRRITATION - Category 2<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 |
| n-butyl acetate                                      | N-BUTYL ACETATE                                    | 123-86-4   | FLAMMABLE LIQUIDS - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3   |
| ethylbenzene   | ETHYLBENZENE                                       | 100-41-4   | FLAMMABLE LIQUIDS - Category 2<br>ACUTE TOXICITY (inhalation) - Category 4<br>CARCINOGENICITY - Category 2<br>ASPIRATION HAZARD - Category 1   |
| Talc , not containing asbestiform fibres             | Talc, non-asbestos form                            | 14807-96-6 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3   |
| iron hydroxide oxide yellow                          | IRON HYDROXIDE OXIDE                               | 51274-00-1 | Not classified.  |
| 2-methoxy-1-methylethyl acetate                      | 1-METHOXY-2-PROPYL ACETATE                         | 108-65-6   | FLAMMABLE LIQUIDS - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3   |
| Octadecanamide, N, N'-1,6-hexanediylbis [12-hydroxy- | N,N-1,6-HEXANEDIYLBIS (12-HYDROXY-OCTADECANEIMIDE) | 55349-01-4 | SKIN SENSITIZATION - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 4   |
| Solvent naphtha (petroleum), light aromatic          | SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC        | 64742-95-6 | FLAMMABLE LIQUIDS - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3<br>ASPIRATION HAZARD - Category 1<br>AQUATIC HAZARD (LONG-TERM) - Category 2  |
| 2-butoxyethanol                                      | 2-BUTOXY ETHANOL                                   | 111-76-2   | ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN CORROSION/IRRITATION - Category 2<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  |

## Section 11. Toxicological information

|  |  |             |   |
|--|--|-------------|---|
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  | BIS<br>(PENTAMETHYLPIPERIDYL)<br>SEBACATE  | 41556-26-7  | CARCINOGENICITY - Category 2<br>SKIN SENSITIZATION - Category 1   |
| 2-Propenoicacid,<br>2-ethylhexylester,<br>reactionproductswithethylenediamine-<br>ethyleniminepolymer,<br>compds.withpolyethylene-<br>polypropyleneglycolmono-<br>Buetherphosphate | 2-Propenoicacid,<br>2-ethylhexylester,<br>reactionproductswithethylenediamine-<br>ethyleniminepolymer,<br>compds.withpolyethylene-<br>polypropyleneglycolmono-<br>Buetherphosphate | 398475-96-2 | AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) -<br>Category 1<br>SKIN CORROSION/IRRITATION -<br>Category 2  |
| cyclohexanone  | CYCLOHEXANONE  | 108-94-1    | SERIOUS EYE DAMAGE/ EYE<br>IRRITATION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY<br>(SINGLE EXPOSURE) (Respiratory tract<br>irritation) - Category 3<br>AQUATIC HAZARD (ACUTE) - Category 1<br>AQUATIC HAZARD (LONG-TERM) -<br>Category 1<br>FLAMMABLE LIQUIDS - Category 3<br>ACUTE TOXICITY (oral) - Category 4<br>ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>SKIN CORROSION/IRRITATION -<br>Category 2<br>SERIOUS EYE DAMAGE/ EYE<br>IRRITATION - Category 1<br>GERM CELL MUTAGENICITY - Category 2<br>CARCINOGENICITY - Category 2<br>CARCINOGENICITY - Category 2 |
| titanium dioxide   | TITANIUM DIOXIDE   | 13463-67-7  | CARCINOGENICITY - Category 2<br>CARCINOGENICITY - Category 2  |

## Section 12. Ecological information

### A. Ecotoxicity

| Product/ingredient name                        | Result   | Species                    | Exposure            |
|--|--|----------------------------|---------------------|
| n-butyl acetate                                | Acute LC50 18 mg/l                             | Fish                       | 96 hours            |
| ethylbenzene                                   | Acute LC50 150 to 200 mg/l Fresh<br>water      | Fish                       | 96 hours            |
| iron hydroxide oxide yellow                    | Acute LC50 >100000 mg/l                        | Fish                       | 96 hours            |
| 2-methoxy-1-methylethyl<br>acetate             | Acute LC50 134 mg/l Fresh water                | Fish - Oncorhynchus mykiss | 96 hours            |
| Solvent naphtha<br>(petroleum), light aromatic | Acute LC50 8.2 mg/l                            | Fish                       | 96 hours            |
| 2-butoxyethanol                                | Acute LC50 1474 mg/l<br>Chronic NOEC >100 mg/l | Fish<br>Fish               | 96 hours<br>21 days |
| titanium dioxide                               | Acute LC50 >100 mg/l Fresh water               | Daphnia - Daphnia magna    | 48 hours            |

### B. Persistence and degradability

## Section 12. Ecological information

| Product/ingredient name                             | Test               | Result                   | Dose | Inoculum |
|---|--------------------|--------------------------|------|----------|
| <input checked="" type="checkbox"/> n-butyl acetate | TEPA and OECD 301D | 83 % - Readily - 28 days | -    | -        |
| 2-methoxy-1-methylethyl acetate                     | -                  | 83 % - Readily - 28 days | -    | -        |

| Product/ingredient name                    | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| <input checked="" type="checkbox"/> Xylene | -                 | -          | Readily          |
| n-butyl acetate                            | -                 | -          | Readily          |
| ethylbenzene                               | -                 | -          | Readily          |
| 2-methoxy-1-methylethyl acetate            | -                 | -          | Readily          |
| 2-butoxyethanol                            | -                 | -          | Readily          |

### C. Bioaccumulative potential

| Product/ingredient name                    | LogP <sub>ow</sub> | BCF         | Potential |
|--|--------------------|-------------|-----------|
| <input checked="" type="checkbox"/> Xylene | 3.16               | 7.4 to 18.5 | low       |
| n-butyl acetate                            | 1.78               | -           | low       |
| ethylbenzene                               | 3.15               | 79.43       | low       |
| 2-methoxy-1-methylethyl acetate            | 0.56               | -           | low       |
| 2-butoxyethanol                            | 0.81               | -           | low       |
| cyclohexanone                              | 0.81               | -           | low       |

### D. Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

E. Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**A. Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**B. Disposal precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                | UN              | IMDG            | IATA            |
|--------------------------------|-----------------|-----------------|-----------------|
| A. UN number                   | UN1263          | UN1263          | UN1263          |
| B. UN proper shipping name     | PAINT           | PAINT           | PAINT           |
| C. Transport hazard class(es)  | 3               | 3               | 3               |
| D. Packing group               | III             | III             | III             |
| Environmental hazards          | No.             | No.             | No.             |
| E. Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

### Additional information

UN : None identified.

IMDG : None identified.

IATA : None identified.

### F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

## Section 15. Regulatory information

### A. Regulation according to ISHA

**ISHA article 117 (Harmful substances prohibited from manufacture)** : None of the components are listed.

**ISHA article 118 (Harmful substances requiring permission)** : None of the components are listed.

**Article 2 of Youth Protection Act on Substances Hazardous to Youth** : It is not allowed to sell to persons under the age of 19.

### Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

## Section 15. Regulatory information

Xylene  
 n-butyl acetate  
 ethylbenzene  
 Talc , not containing asbestiform fibres  
 iron hydroxide oxide yellow  
 2-butoxyethanol  
 cyclohexanone  
 titanium dioxide

**ISHA Enforcement Regs** :  The following components are listed: cyclohexanone

**Annex 19 (Exposure standards established for harmful factors)**

**ISHA Enforcement Regs** :  The following components are listed: xylene, n-butyl acetate, ethyl benzene, talc; soapstone, iron oxide

**Annex 21 (Harmful factors subject to Work Environment Measurement)**

**ISHA Enforcement Regs** :  The following components are listed: Xylene, Ethyl benzene, Iron oxide

**Annex 22 (Harmful Factors Subject to Special Health Check-up)**

**Standard of Industrial Safety and Health** : The following components are listed: xylene, n-butyl acetate, ethyl benzene, iron and its compounds

**Annex 12 (Hazardous substances subject to control)**

### B. Regulation according to Chemicals Control Act

**CCA Article 11 (TRI)** : The following components are listed: Xylene including o-,m-,p- isomer, Barium and its compounds, Ethylbenzene

**CCA Article 18 Prohibited (K-Reach Article 27)** : None of the components are listed.

**CCA Article 19 Subject to authorization (K-Reach Article 25)** :  None of the components are listed.

**CCA Article 20 Restricted (K-Reach Article 27)** : None of the components are listed.

**CCA Article 20 Toxic Chemicals (K-Reach Article 20)** : Not applicable

**Korea inventory** : All components are listed or exempted.

**CCA Article 39 (Accident Precaution Chemicals)** : None of the components are listed.

## Section 15. Regulatory information

- C. [Dangerous Materials Safety Management Act](#)** : **Class:** Class 4 - Flammable Liquid  
**Item:** 4. Class 2 petroleums - Water-insoluble liquid  
**Threshold:** 1000 L  
**Danger category:** III  
**Signal word:** Contact with sources of ignition prohibited
- D. [Wastes regulation](#)** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- E. [Regulation according to other foreign laws](#)**  
**Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

## Section 16. Other information

- A. [References](#)** : Korean Ministry of Environment; Chemical Control Act  
Korean Ministry of Labor; Industrial Safety and Health Act  
NIER Notice  
Registry of Toxic Effects of Chemical Substances (RTECS)  
U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.
- B. [Date of issue/Date of revision](#)** : 3/20/2021
- C. [Version](#)** : 7  
**Prepared by** : EHS
- D. [Other](#)**

✔ Indicates information that has changed from previously issued version.

### [Disclaimer](#)

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*