

# SAFETY DATA SHEET

Date of issue/Date of revision 20 May 2021

Version 5

## Section 1. Identification

**Product code** : 00358515  
**Product name** : SIGMAGUARD 603 BASE OFFWHITE  
**Product type** : Liquid.  
**Other means of identification**  
Not available.

### Relevant identified uses of the substance or mixture and uses advised against


**Product use** : Coating.  
Professional applications, Used by spraying.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.  
**Supplier's information** : PPG Asian Paints Private Limited  
6A Shanti Nagar  
Santa Cruz (East)  
Mumbai - 400055  
India  
**Emergency telephone number:** : +91 22 6815 8700

## Section 2. Hazards identification

**Classification of the substance or mixture** :  ACUTE TOXICITY (oral) - Category 5  
ACUTE TOXICITY (dermal) - Category 5  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A  
SKIN SENSITISATION - Category 1  
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2  
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2  
 Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 13.8%  
Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 19.6%  
 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38%

### GHS label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** :  May be harmful if swallowed or in contact with skin.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

## Section 2. Hazards identification

- Prevention** :  Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
- Response** :  Collect spillage. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** :  None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

### CAS number/other identifiers

**CAS number** : Not applicable.

Ingredient name	%	CAS number
<input checked="" type="checkbox"/> epoxy resin (MW ≤ 700)	25 - <50	25068-38-6
1,6-bis(2,3-epoxypropoxy)hexane	5 - <10	16096-31-4
benzyl alcohol	5 - <10	100-51-6
Talc , not containing asbestiform fibres	3 - <5	14807-96-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** :  Causes serious eye irritation.
- Inhalation** :  No known significant effects or critical hazards.
- Skin contact** :  May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

## Section 4. First aid measures

**Ingestion** : May be harmful if swallowed.

### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

## Section 6. Accidental release measures

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
<input checked="" type="checkbox"/> alc , not containing asbestiform fibres	<b>ACGIH TLV (United States, 3/2020).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** :  Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

Physical state	: Liquid.
Colour	: Off-white.
Odour	: Aromatic.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: >37.78°C (>100°F)
Flammability	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Flash point	: Closed cup: 100°C (212°F)
Auto-ignition temperature	: 426°C (798.8°F)
Decomposition temperature	: Not available.
pH	: <input checked="" type="checkbox"/> Not applicable.
Viscosity	: <input checked="" type="checkbox"/> Kinematic (40°C): >21 mm <sup>2</sup> /s
Viscosity	: 60 - 100 s (ISO 6mm)
Solubility	: Insoluble in the following materials: cold water.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: <input checked="" type="checkbox"/> Not applicable.
Vapour pressure	:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
<input checked="" type="checkbox"/> 6-bis (2,3-epoxypropoxy) hexane	0.067505535	0.009				

Relative density	: 1.4
Relative vapour density	: Not available.
Particle characteristics	
Median particle size	: <input checked="" type="checkbox"/> Not applicable.
Evaporation rate	: Not available.

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: <input checked="" type="checkbox"/> Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

## Section 10. Stability and reactivity

**Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

**Hazardous polymerisation** : Under normal conditions of storage and use, hazardous polymerisation will not occur.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
epoxy resin (MW ≤ 700)	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	>2 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
epoxy resin (MW ≤ 700)	Skin - Mild irritant	Rabbit	-	-	-
	Eyes - Mild irritant	Rabbit	-	-	-

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
epoxy resin (MW ≤ 700)	skin	Mouse	Sensitising

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)



## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Alc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May be harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.



## Section 11. Toxicological information

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	3356.99 mg/kg
Dermal	3526.62 mg/kg
Inhalation (dusts and mists)	5.72 mg/l

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
epoxy resin (MW ≤ 700)	Acute LC50 1.8 mg/l Chronic NOEC 0.3 mg/l	Daphnia Daphnia	48 hours 21 days

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
epoxy resin (MW ≤ 700)	OECD 301F	5 % - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
epoxy resin (MW ≤ 700)	-	-	Not readily
benzyl alcohol	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
epoxy resin (MW ≤ 700)	3	31	low
1,6-bis(2,3-epoxypropoxy)hexane	0.822	-	low
benzyl alcohol	0.87	-	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	IMDG	IATA
<b>UN number</b>	UN3082	UN3082	UN3082
<b>UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin (MW ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (MW ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (MW ≤ 700))
<b>Transport hazard class(es)</b>	9	9	9
<b>Packing group</b>	III	III	III
<b>Environmental hazards</b>	Yes.	Yes.	Yes.
<b>Marine pollutant substances</b>	Not applicable.	(Epoxy resin (MW ≤ 700))	Not applicable.

### Additional information

- UN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

## Section 15. Regulatory information

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Section 16. Other information

### History

**Date of issue/Date of revision** : 20 May 2021

**Date of previous issue** : 12/19/2018

**Version** : 5

**Prepared by** : EHS

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 UN = United Nations

### Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 5	Calculation method
ACUTE TOXICITY (dermal) - Category 5	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	Calculation method

✓ Indicates information that has changed from previously issued version.

### Notice to reader

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*