

SAFETY DATA SHEET

Date of issue/Date of revision

: 18 June 2021

Version

: 15



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SIGMADUR 1800 HARDENER

Product code : 00236075

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL

Tweemontstraat 104

B-2100 Deurne

Belgium

Telephone +32-33606311

Fax +32-33606435

e-mail address of person responsible for this SDS : PMC.Safety@PPG.com

National contact

PPG Architectural Coatings UK Ltd, Huddersfield Road, Birstall, West Yorkshire WF17 9XA, Tel: +44 (0) 1924 354000

1.4 Emergency telephone number

Supplier

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Acute Tox. 4, H332

Skin Sens. 1, H317

STOT SE 3, H335

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Code : 00236075

Date of issue/Date of revision

: 18 June 2021

SIGMADUR 1800 HARDENER


SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Warning

Hazard statements

: Flammable liquid and vapour.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapour.

Response

: IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage

: Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Not applicable.
P280, P210, P273, P261, P304 + P312, P403 + P233

Hazardous ingredients

: Hexamethylene diisocyanate, oligomers (isocyanurate type)
hexamethylene-di-isocyanate

Supplemental label elements

: Contains isocyanates. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Prolonged or repeated contact may dry skin and cause irritation.

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % by weight | Classification Regulation (EC) No. 1272/2008 [CLP] | Type |
|---|--|-------------|--|---------|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | REACH #: 01-2119485796-17 EC: 931-274-8 CAS: 28182-81-2 | ≥75 - ≤90 | Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335 | [1] [2] |
| n-butyl acetate | REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1 | ≥5.0 - <10 | Flam. Liq. 3, H226 STOT SE 3, H336 EUH066 | [1] [2] |
| Hydrocarbons, C9, aromatics | REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6 | ≥5.0 - <10 | Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 | [1] |
| hexamethylene-di-isocyanate | REACH #: 01-2119457571-37 EC: 212-485-8 CAS: 822-06-0 Index: 615-011-00-1 | ≤0.30 | Acute Tox. 4, H302 Acute Tox. 1, H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 See Section 16 for the full text of the H statements declared above. | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Code : 00236075

Date of issue/Date of revision

: 18 June 2021

SIGMADUR 1800 HARDENER

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
Cyanate and isocyanate.
hydrogen cyanide

5.3 Advice for firefighters

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- Special provisions** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- Precautions should be taken to minimise exposure to atmospheric humidity or water. CO₂ will be formed, which, in closed containers, could result in pressurisation.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|--|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | EH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours. |
| n-butyl acetate | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 966 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m ³ 8 hours. TWA: 150 ppm 8 hours. |
| hexamethylene-di-isocyanate | EH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation |

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 8: Exposure controls/personal protection

sensitiser.

STEL: 0.07 mg/m³, (as -NCO) 15 minutes.

TWA: 0.02 mg/m³, (as -NCO) 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|---|------|-----------------------|-------------------------|--------------------|----------|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | DNEL | Long term Inhalation | 0.5 mg/m ³ | Workers | Local |
| n-butyl acetate | DNEL | Short term Inhalation | 1 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 300 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 300 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 600 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 600 mg/m ³ | Workers | Systemic |
| Hydrocarbons, C9, aromatics | DNEL | Long term Dermal | 11 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 150 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 25 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 32 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 11 mg/kg bw/day | General population | Systemic |
| hexamethylene-di-isocyanate | DNEL | Long term Oral | 11 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 0.035 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 0.035 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 0.07 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 0.07 mg/m ³ | Workers | Systemic |

PNECs

| Product/ingredient name | Type | Compartment Detail | Value | Method Detail |
|---|-----------------------|------------------------|--------------------------|--------------------------|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | - | Fresh water | 0.127 mg/l | Assessment Factors |
| | - | Marine water | 0.0127 mg/l | Assessment Factors |
| | - | Sewage Treatment Plant | 88 mg/l | Assessment Factors |
| | - | Fresh water sediment | 266701 mg/kg dwt | Equilibrium Partitioning |
| | - | Marine water sediment | 26670 mg/kg dwt | Equilibrium Partitioning |
| n-butyl acetate | - | Soil | 53182 mg/kg | Equilibrium Partitioning |
| | - | Fresh water | 0.18 mg/l | - |
| | - | Marine water | 0.018 mg/l | - |
| | - | Fresh water sediment | 0.981 mg/kg | - |
| | - | Marine water sediment | 0.0981 mg/kg | - |
| hexamethylene-di-isocyanate | - | Sewage Treatment Plant | 35.6 mg/l | - |
| | - | Soil | 0.0903 mg/kg | - |
| | - | Fresh water | 0.0774 mg/l | Assessment Factors |
| | - | Marine water | 0.00774 mg/l | Assessment Factors |
| | - | Sewage Treatment Plant | 8.42 mg/l | Assessment Factors |
| - | Fresh water sediment | 0.01334 mg/kg dwt | Equilibrium Partitioning | |
| - | Marine water sediment | 0.001334 mg/kg dwt | Equilibrium Partitioning | |

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 8: Exposure controls/personal protection

| | | | | |
|--|---|------|------------------|--------------------------|
| | - | Soil | 0.0026 mg/kg dwt | Equilibrium Partitioning |
|--|---|------|------------------|--------------------------|

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields. Use eye protection according to EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use an air-fed respirator unless a site-specific assessment determines that an air-fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Restrictions on use : Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Code : 00236075

Date of issue/Date of revision

: 18 June 2021

SIGMADUR 1800 HARDENER

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties**Appearance**

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Amine-like.
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: -51.3 to -28.4°C (-60.3 to -19.1°F)
This is based on data for the following ingredient: Hexamethylene diisocyanate, oligomers (isocyanurate type). Weighted average: -43.59°C (-46.5°F)
- Initial boiling point and boiling range** : >37.78°C
- Flash point** : Closed cup: 55.7°C
- Evaporation rate** : 1 (n-butyl acetate) compared with butyl acetate
- Flammability (solid, gas)** : liquid
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)
- Vapour pressure** :

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|-----------------|-------------------------|-----|----------------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| n-butyl acetate | 11.25 | 1.5 | DIN EN 13016-2 | | | |

- Vapour density** : Highest known value: 4.1 (Air = 1) (1,2,4-trimethylbenzene). Weighted average: 4.02 (Air = 1)
- Relative density** : 1.13
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : 370°C (698°F)
- Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).
- Viscosity** : Kinematic (room temperature): >400 mm²/s
Kinematic (40°C): >21 mm²/s
- Viscosity** : 60 - 100 s (ISO 6mm)
- Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
- Oxidising properties** : Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : In a fire, hazardous decomposition products may be produced.
Refer to protective measures listed in sections 7 and 8.
- 10.5 Incompatible materials** : Keep away from: oxidising agents, strong alkalis, strong acids, amines, alcohols, water.
Uncontrolled exothermic reactions occur with amines and alcohols.
- 10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials:
Cyanate and isocyanate. carbon oxides nitrogen oxides hydrogen cyanide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|--------------|-----------------------|----------|
| <input checked="" type="checkbox"/> Hexamethylene diisocyanate, oligomers (isocyanurate type) | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat - Female | >2500 mg/kg | - |
| n-butyl acetate | LC50 Inhalation Vapour | Rat | >21.1 mg/l | 4 hours |
| | LC50 Inhalation Vapour | Rat | 2000 ppm | 4 hours |
| Hydrocarbons, C9, aromatics | LD50 Dermal | Rabbit | >17600 mg/kg | - |
| | LD50 Oral | Rat | 10.768 g/kg | - |
| | LD50 Dermal | Rabbit | >3160 mg/kg | - |
| | LD50 Oral | Rat - Female | 3492 mg/kg | - |
| hexamethylene-di-isocyanate | LC50 Inhalation Dusts and mists | Rat | 124 mg/m ³ | 4 hours |
| | LC50 Inhalation Vapour | Rat | 151 mg/m ³ | 4 hours |
| | LC50 Inhalation Vapour | Rat | 22 ppm | 4 hours |
| | LD50 Dermal | Rabbit | 0.57 g/kg | - |
| | LD50 Oral | Rat | 0.71 g/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Route | ATE value |
|------------------------------|-------------|
| Inhalation (vapours) | 101.34 mg/l |
| Inhalation (dusts and mists) | 1.67 mg/l |

Irritation/Corrosion

Conclusion/Summary

- Skin** : There are no data available on the mixture itself.
- Eyes** : There are no data available on the mixture itself.
- Respiratory** : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Code : 00236075

Date of issue/Date of revision

: 18 June 2021

SIGMADUR 1800 HARDENER

SECTION 11: Toxicological information

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|---|------------|-------------------|--|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | Category 3 | - | Respiratory tract irritation |
| n-butyl acetate | Category 3 | - | Narcotic effects |
| Hydrocarbons, C9, aromatics | Category 3 | - | Respiratory tract irritation |
| hexamethylene-di-isocyanate | Category 3 | - | Narcotic effects Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Product/ingredient name | Result |
|-----------------------------|--------------------------------|
| Hydrocarbons, C9, aromatics | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Ingestion : No known significant effects or critical hazards.

Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Ingestion : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Code : 00236075 Date of issue/Date of revision : 18 June 2021
 SIGMADUR 1800 HARDENER

SECTION 11: Toxicological information

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Repeated exposure may lead to permanent respiratory disability. Moisture-sensitive material. Avoid contact with skin and clothing.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|-----------------------|---------------------------------|----------|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | Acute EC50 >1000 mg/l | Algae - scenedesmus subspicatus | 72 hours |
| | Acute EC50 >100 mg/l | Daphnia - daphnia magna | 48 hours |
| | Acute LC50 >100 mg/l | Fish - Danio rerio (zebra fish) | 96 hours |
| n-butyl acetate Hydrocarbons, C9, aromatics | Acute LC50 18 mg/l | Fish | 96 hours |
| | EC50 3.2 mg/l | Daphnia | 48 hours |
| | LC50 9.2 mg/l | Fish | 96 hours |

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|--|--------------------|--------------------------|------|----------|
| n-butyl acetate Hydrocarbons, C9, aromatics | TEPA and OECD 301D | 83 % - Readily - 28 days | - | - |
| | - | 75 % - Readily - 28 days | - | - |

Conclusion/Summary : There are no data available on the mixture itself.

Code : 00236075 Date of issue/Date of revision : 18 June 2021
 SIGMADUR 1800 HARDENER

SECTION 12: Ecological information

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | - | - | Not readily |
| n-butyl acetate | - | - | Readily |
| Hydrocarbons, C9, aromatics | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---|--------------------|-----|-----------|
| Hexamethylene diisocyanate, oligomers (isocyanurate type) | 5.54 | 3.2 | low |
| n-butyl acetate | 2.3 | - | low |
| hexamethylene-di-isocyanate | 0.02 | - | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container | 15 01 06 mixed packaging |

Code : 00236075
SIGMADUR 1800 HARDENER

Date of issue/Date of revision : 18 June 2021

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|------------------------|------------------------|------------------------|------------------------|
| 14.1 UN number | UN1263 | UN1263 | UN1263 | UN1263 |
| 14.2 UN proper shipping name | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es) | 3 | 3 | 3 | 3 |
| 14.4 Packing group | III | III | III | III |
| 14.5 Environmental hazards | No. | Yes. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

Additional information

ADR/RID : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Tunnel code : (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

IMDG : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

Substances of very high concern

None of the components are listed.

| | |
|-------------------------------|--|
| Code : 00236075 | Date of issue/Date of revision : 18 June 2021 |
| SIGMADUR 1800 HARDENER | |

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| |
|-----------------|
| Category |
| P5c |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.


SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- IMDG = International Maritime Dangerous Goods
- IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|--|---|
|  Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412 | On basis of test data Calculation method Calculation method Calculation method Calculation method |

Full text of abbreviated H statements

| | |
|--|---|
| H226 H302 H304 H315 H317 H319 H330 H332 H334 | Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Fatal if inhaled. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
|--|---|

| | |
|-------------------------------|--|
| Code : 00236075 | Date of issue/Date of revision : 18 June 2021 |
| SIGMADUR 1800 HARDENER | |

SECTION 16: Other information

| | |
|--|--|
| H335 H336 H411 H412 EUH066 | May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. |
|--|--|

Full text of classifications [CLP/GHS]

| | |
|--|--|
| Acute Tox. 1 Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Irrit. 2 Flam. Liq. 3 Resp. Sens. 1 Skin Irrit. 2 Skin Sens. 1 STOT SE 3 | ACUTE TOXICITY - Category 1 ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 RESPIRATORY SENSITISATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
|--|--|

History

| | |
|--|--------------------|
| Date of issue/ Date of revision | : 18 June 2021 |
| Date of previous issue | : 23 December 2020 |
| Prepared by | : EHS |
| Version | : 15 |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.