



Date of issue 28 June 2021  
Version 10.02

## Section 1. Product and company identification

**Product name** : PPG VIKOTE 56 BLUE 1188  
**Product code** : 00166732  
**Other means of identification** : Not available.  
**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Coating. Paints. Painting-related materials.

#### Uses advised against

Not applicable.

#### Reason

### Supplier's details:

**Supplier** : PPG Industries Colombia Ltda  
Calle 51 # 40-13  
Municipio de Itagüí  
Antioquia, Colombia  
(57) (4) 3787400 (Porteria)

**Email address:** : HazComLatam@ppg.com

**Emergency telephone number** :  
Colombia: 01 8000 916012 (CISPROQUIM)  
+ 571 288 6012 (CISPROQUIM)  
Ecuador: 1800-59-3005 (CISPROQUIM)  
Peru: 080-050-847 (CISPROQUIM)

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
ACUTE TOXICITY (dermal) - Category 5  
ACUTE TOXICITY (inhalation) - Category 4  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 2  
TOXIC TO REPRODUCTION - Effects on or via lactation  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
AQUATIC HAZARD (ACUTE) - Category 1

## Section 2. Hazards identification

### Target organs

AQUATIC HAZARD (LONG-TERM) - Category 2

- : Contains material which causes damage to the following organs: brain, central nervous system (CNS).  
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, upper respiratory tract, skin, ears, eye, lens or cornea.

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 22%

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 27.2%

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 17.7%

### GHS label elements

#### Hazard pictograms



#### Signal word

- : Warning

#### Hazard statements

- : Flammable liquid and vapor.
- May be harmful in contact with skin.
- Causes skin irritation.
- Causes serious eye irritation.
- Harmful if inhaled.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- Suspected of causing cancer.
- Suspected of damaging fertility or the unborn child.
- May cause harm to breast-fed children.
- Very toxic to aquatic life.
- Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### Prevention

- :  Obtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment. Avoid breathing vapor. Avoid contact during pregnancy or while nursing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

#### Response

- : Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

#### Storage

- : Store in a well-ventilated place. Keep container tightly closed. Keep cool.

#### Disposal

- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Section 2. Hazards identification

**Other hazards which do not result in classification** : Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Other means of identification** : Not available.

### CAS number/other identifiers

**CAS number** : Not applicable.

Ingredient name	%	CAS number
Solvent naphtha (petroleum), light aromatic	20 - <30	64742-95-6
xylene	15 - <20	1330-20-7
1,2,4-trimethylbenzene	10 - <12.5	95-63-6
titanium dioxide	5 - <7	13463-67-7
ethylbenzene	2 - <3	100-41-4
mesitylene	2 - <3	108-67-8
propylbenzene	2 - <3	103-65-1
Paraffin waxes and Hydrocarbon waxes, chloro	1 - <2	63449-39-8
alkanes, C14-17, chloro	1 - <2	85535-85-9
1,2,3-trimethylbenzene	1 - <2	526-73-8
cumene	0.2 - <0.5	98-82-8
toluene	0.1 - <0.2	108-88-3
carbon black	0.1 - <0.2	1333-86-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed.
- Specific treatments** : The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.

## Section 4. First aid measures

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

**Skin contact** : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin.

**Ingestion** : Can cause central nervous system (CNS) depression.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
carbonyl halides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## Section 6. Accidental release measures

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

**Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid contact during pregnancy or while nursing. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
xylene	<b>ACGIH TLV (United States, 3/2020).</b> STEL: 651 mg/m <sup>3</sup> 15 minutes. STEL: 150 ppm 15 minutes. TWA: 434 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours.
1,2,4-trimethylbenzene	<b>ACGIH TLV (United States, 3/2020).</b> TWA: 123 mg/m <sup>3</sup> 8 hours. TWA: 25 ppm 8 hours.
titanium dioxide	<b>ACGIH TLV (United States, 3/2020).</b> TWA: 10 mg/m <sup>3</sup> 8 hours.
ethylbenzene	<b>ACGIH TLV (United States, 3/2020).</b> TWA: 20 ppm 8 hours.
mesitylene	<b>ACGIH TLV (United States, 3/2020).</b> TWA: 123 mg/m <sup>3</sup> 8 hours. TWA: 25 ppm 8 hours.
1,2,3-trimethylbenzene	<b>ACGIH TLV (United States, 3/2020).</b> TWA: 123 mg/m <sup>3</sup> 8 hours. TWA: 25 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye protection** : Chemical splash goggles.  
**Skin protection**

## Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:  
  
May be used: nitrile rubber  
Recommended: polyvinyl alcohol (PVA), Viton®
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Various
- Odor** : Aromatic.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 34.4°C (93.9°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.01
- Solubility** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : 210°C (410°F)

## Section 9. Physical and chemical properties

- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)
- Viscosity** : 60 - 100 s (ISO 6mm)

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides carbonyl halides metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), light aromatic	LD50 Dermal	Rabbit	3.48 g/kg	-
xylene	LD50 Oral	Rat	8400 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
1,2,4-trimethylbenzene	LD50 Oral	Rat	4.3 g/kg	-
	LC50 Inhalation Vapor	Rat	18000 mg/m <sup>3</sup>	4 hours
titanium dioxide	LD50 Oral	Rat	5 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
mesitylene	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
propylbenzene	LD50 Oral	Rat	3.5 g/kg	-
	LC50 Inhalation Vapor	Rat	24000 mg/m <sup>3</sup>	4 hours
Paraffin waxes and Hydrocarbon waxes, chloro alkanes, C14-17, chloro	LD50 Oral	Rat	5000 mg/kg	-
	LD50 Oral	Rat	6040 mg/kg	-
1,2,3-trimethylbenzene	LD50 Oral	Rat	26100 mg/kg	-
	LC50 Inhalation Vapor	Rat	>48.17 g/m <sup>3</sup>	1 hours
cumene	LD50 Oral	Rat	>5 g/kg	-
	LD50 Oral	Rat	11.4 g/kg	-
toluene	LC50 Inhalation Vapor	Rat	39000 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	12.3 g/kg	-
	LD50 Oral	Rat	1400 mg/kg	-
	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours



## Section 11. Toxicological information

carbon black	LD50 Dermal	Rabbit	8.39 g/kg	-
	LD50 Oral	Rat	5580 mg/kg	-
	LD50 Oral	Rat	>10 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

Not available.

### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

Not available.

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

Not available.

**Conclusion/Summary** : There are no data available on the mixture itself.

### Classification

Product/ingredient name	OSHA	IARC	NTP
xylene	-	3	-
titanium dioxide	-	2B	-
ethylbenzene	-	2B	-
cumene	-	2B	Reasonably anticipated to be a human carcinogen.
toluene	-	3	-
carbon black	-	2B	-

**Carcinogen Classification code:**

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### Reproductive toxicity

Not available.

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

Not available.

**Conclusion/Summary** : There are no data available on the mixture itself.

## Section 11. Toxicological information

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light aromatic	Category 3	-	Respiratory tract irritation
xylene	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
1,2,4-trimethylbenzene	Category 3	-	Respiratory tract irritation
mesitylene	Category 3	-	Respiratory tract irritation
propylbenzene	Category 3	-	Respiratory tract irritation
cumene	Category 3	-	Respiratory tract irritation
toluene	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
cumene	Category 2	-	-
toluene	Category 2	-	-

### Target organs

- : Contains material which causes damage to the following organs: brain, central nervous system (CNS).
- Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, upper respiratory tract, skin, ears, eye, lens or cornea.

### Aspiration hazard

Name	Result
Solvent naphtha (petroleum), light aromatic	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
propylbenzene	ASPIRATION HAZARD - Category 1
cumene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

### Information on the likely routes of exposure

- : Not available.

### Potential acute health effects

#### Eye contact

- : Causes serious eye irritation.

#### Inhalation

- : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

#### Skin contact

- : May be harmful in contact with skin. Causes skin irritation. Defatting to the skin.

#### Ingestion

- : Can cause central nervous system (CNS) depression.

## Section 11. Toxicological information

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. For many PPG products, TiO<sub>2</sub> is utilized as a raw material in a liquid coating formulation. In this case, the TiO<sub>2</sub> particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO<sub>2</sub> when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Carbon black is utilized as a raw material in many liquid coating formulations. In this case, the carbon black particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of carbon black when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Most carbon blacks contain trace quantities of polyaromatic hydrocarbons (PAH). PAHs are not expected to be released in biological fluids and are therefore not likely available for biological activity. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some

## Section 11. Toxicological information

evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Short term exposure

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

### Long term exposure

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : Suspected of damaging fertility or the unborn child. May cause harm to breast-fed children.

### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PPG VIKOTE 56 BLUE 1188	13433.4	4996.9	N/A	31.6	3.5
Solvent naphtha (petroleum), light aromatic	8400	3480	N/A	N/A	N/A
xylene	4300	1700	N/A	11	1.5
1,2,4-trimethylbenzene	5000	N/A	N/A	18	1.5
ethylbenzene	3500	17800	N/A	17.8	1.5
mesitylene	5000	N/A	N/A	24	N/A
propylbenzene	6040	N/A	N/A	N/A	N/A
Paraffin waxes and Hydrocarbon waxes, chloro	26100	N/A	N/A	N/A	N/A
1,2,3-trimethylbenzene	11400	N/A	N/A	N/A	N/A
cumene	1400	12300	N/A	39	N/A
toluene	5580	8390	N/A	49	N/A

**Other information** : Not available.

## Section 12. Ecological information

### Ecotoxicity

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light aromatic titanium dioxide ethylbenzene	Acute LC50 8.2 mg/l	Fish	96 hours
	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 150 to 200 mg/l Fresh water	Fish	96 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Ceriodaphnia dubia	-

### Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
ethylbenzene	-	-	Readily
toluene	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
xylene	3.12	7.4 to 18.5	low
1,2,4-trimethylbenzene	3.63	120.23	low
ethylbenzene	3.6	79.43	low
mesitylene	3.42	186.21	low
propylbenzene	3.69	-	low
Paraffin waxes and Hydrocarbon waxes, chloro alkanes, C14-17, chloro	7.46 to 11.48	-	high
1,2,3-trimethylbenzene	4.7 to 8.3	-	high
cumene	3.66	194.98	low
toluene	3.55	35.48	low
	2.73	8.32	low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material

## Section 13. Disposal considerations

and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	IATA
<b>UN number</b>	UN1263	UN1263	UN1263	UN1263
<b>UN proper shipping name</b>	PAINT	PAINT	PAINT	PAINT
<b>Transport hazard class(es)</b>	3	3	3	3
<b>Packing group</b>	III	III	III	III
<b>Environmental hazards</b>	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
<b>Marine pollutant substances</b>	Not applicable.	Not applicable.	(Solvent naphtha (petroleum), light aromatic, 1,2,4-trimethylbenzene)	Not applicable.

### Additional information

- UN** : None identified.
- Brazil** : None identified.
- Risk number** : 30
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

Code	00166732	Date of issue	28 June 2021	Version	10.02
Product name	PPG VIKOTE 56 BLUE 1188				

## Section 15. Regulatory information

**Safety, health and environmental regulations specific for the product** : No known specific national and/or regional regulations applicable to this product (including its ingredients).

## Section 16. Other information

### History

**Date of previous issue** : 6/2/2020

**Version** : 10.02

EHS

### Key to abbreviations

: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 UN = United Nations

### References

: ABNT NBR 14725-4: 2014  
 ANTT - National Land Transportation Agency

 Indicates information that has changed from previously issued version.

### Disclaimer

***The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.***