SAFETY DATA SHEET

Date of issue/Date of revision 29 June 2021

Version3

G

Section 1. Identification

Product code	: 00326552
Product name	: SIGMASHIELD 905 BASE YELLOW 10E53
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses	s of the substance or mixture and uses advised against
Product use	: Coating. Professional applications, Used by spraying.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PT PPG Coatings Indonesia JI. Rawagelam III No.1 13930 Jakarta Indonesia Tel +62 21 4605710 PMC.Safety@PPG.com
Emergency telephone number	: CHEMTREC 001-803-017-9114 (CCN 17704)

Section 2. Hazards identification

Classification of the	: ACUTE TOXICITY (inhalation) - Category 4
substance or mixture	SKIN CORROSION/IRRITATION - Category 2
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
	AQUATIC HAZARD (LONG-TERM) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 70%
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 38.1%
GHS label elements, includ	ling precautionary statements

Hazard pictograms			
Signal word Hazard statements	 Warning Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. 		
	Toxic to aquatic life with long lasting effects.	Indonesia	[:] Pa

Product name SIGMASHIELD 905 BASE YELLOW 10E53

Date of issue 29 June 2021

Version 3

Section 2. Hazards identification

Precautionary statements		
Prevention	:	wear protective gloves. Wear eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	:	Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	:	None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number	: Not applicable
	• • • • • • • • • •

EC number : Mixture.

Ingredient name	%	CAS number
Epoxy resin (MW ≤ 700)	25- <50	25068-38-6
1,6-bis(2,3-epoxypropoxy)hexane	5- <10	16096-31-4
benzyl alcohol	5- <10	100-51-6
Talc, not containing asbestiform fibers	3- <5	14807-96-6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessar	<u>/ first aid measures</u>
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Section 4. First aid measures

Most important symptoms/e	ffec	ts, acute and delayed
Potential acute health effect	<u>ts</u> :	
Eye contact	:	Causes serious eye irritation.
Inhalation	:	Harmful if inhaled.
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	1	No known significant effects or critical hazards.
Over-exposure signs/symp	ton	<u>15</u>
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	1	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate med	lica	l attention and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	1	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
	Indonesia ² Page: 3/12

Date of issue 29 June 2021

Version 3

Product name SIGMASHIELD 905 BASE YELLOW 10E53

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	onta	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal

Section 7. Handling and storage

13 for waste disposal.

Precautions for safe handling

Protective measures	 Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage,	: Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local
including any	regulations. Store in original container protected from direct sunlight in a dry, cool
incompatibilities	and well-ventilated area, away from incompatible materials (see Section 10) and
	food and drink. Keep container tightly closed and sealed until ready for use.
	Containers that have been opened must be carefully resealed and kept upright to
	prevent leakage. Do not store in unlabeled containers. Use appropriate
	containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits		
		hister of Labor of the Republic of onesia (Indonesia, 4/2018). NA: 2 mg/m ³ 8 hours. Form: respirable ticles		
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.			
Appropriate engineering controls	: Use only with adequate ventilation. Use p ventilation or other engineering controls to contaminants below any recommended or	keep worker exposure to airborne		
Environmental exposure controls	: Emissions from ventilation or work proces they comply with the requirements of envir cases, fume scrubbers, filters or engineeri equipment will be necessary to reduce em	onmental protection legislation. In some ng modifications to the process		
ndividual protection measu	<u>s</u>			
Hygiene measures	: Wash hands, forearms and face thorough eating, smoking and using the lavatory and Appropriate techniques should be used to Contaminated work clothing should not be contaminated clothing before reusing. En- showers are close to the workstation locat	d at the end of the working period. remove potentially contaminated clothing. allowed out of the workplace. Wash sure that eyewash stations and safety		
Eye/face protection	: Chemical splash goggles.			
Skin protection				
Hand protection	: Chemical-resistant, impervious gloves cor be worn at all times when handling chemic this is necessary. Considering the parame check during use that the gloves are still re should be noted that the time to breakthro different for different glove manufacturers. several substances, the protection time of estimated.	cal products if a risk assessment indicates eters specified by the glove manufacturer, etaining their protective properties. It ugh for any glove material may be In the case of mixtures, consisting of		

Version 3

Product name SIGMASHIELD 905 BASE YELLOW 10E53

Section 8. Exposure controls/personal protection

Gloves	: butyl rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	Liquid.	
Color	Yellow.	
Odor	Aromatic.	
Odor threshold	Not available.	
рН	Not applicable.	
Melting point	Not available.	
Boiling point	>37.78°C (>100°F)	
Flash point	Closed cup: 120°C (248°F)	
Evaporation rate	Not available.	
Flammability/Combustible properties (solid, gas)	Not available.	
Lower and upper explosive (flammable) limits	Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcoh	ol)
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	1.4	
Solubility	Insoluble in the following materials: cold water.	
Partition coefficient: n- octanol/water	Not applicable.	
Auto-ignition temperature	415°C (779°F)	
Decomposition temperature	Not available.	
Viscosity	Kinematic (40°C): >21 mm²/s	
Viscosity	60 - 100 s (ISO 6mm)	

Date of issue 29 June 2021

Version 3

Section 10. Stability and reactivity

	5
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Result	Species	Dose	Exposure
_D50 Dermal	Rabbit	>2 g/kg	-
_D50 Oral	Rat	>2 g/kg	
C50 Inhalation Dusts and mists	Rabbit	>4178 mg/m³	4 hours
D50 Dermal		2000 mg/kg	-
_ _ _(D50 Dermal D50 Oral C50 Inhalation Dusts and mists	D50 Dermal D50 Oral C50 Inhalation Dusts and mists D50 Dermal Rat Rat Rat Rabbit	D50 DermalRabbit>2 g/kgD50 OralRat>2 g/kgC50 Inhalation Dusts and mistsRat>4178 mg/m³D50 DermalRabbit2000 mg/kg

Conclusion/Summary Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Epoxy resin (MW ≤ 700)	Skin - Mild irritant	Rabbit	-	-	-
	Eyes - Mild irritant	Rabbit	-	-	-

: There are no data available on the mixture itself.

Conclusion/Summary

Skin : There are no data availab	e on the mixture itself.
----------------------------------	--------------------------

Eyes : The Respiratory : The

There are no data available on the mixture itself.There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Epoxy resin (MW ≤ 700)	skin	Mouse	Sensitizing
Conclusion/Summary	·		
Skin	: There are no d	ata available on the mixture its	elf.
Respiratory	: There are no data available on the mixture itself.		
Mutagenicity			

Conclusion/Summary : There are no data available on the mixture itself. Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Section 11. Toxicological information

Reproductive toxicity

Conclusion/Summary

: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
F alc, not containing asbestiform fibers	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
<u>Long term exposure</u>		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
Potential chronic health effe	fects	

Product name SIGMASHIELD 905 BASE YELLOW 10E53

Section 11. Toxicological information

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: 📈 known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Øral	11031.34 mg/kg
Dermal	16690.97 mg/kg
Inhalation (dusts and mists)	4.96 mg/l

Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Epoxy resin (MW ≤ 700)	Acute LC50 1.8 mg/l	Daphnia	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days

Persistence/degradability

Not available.

Product/ingredient name	Test	Result		Dose	Inoculum
Epoxy resin (MW ≤ 700)	OECD 301F	5 % - 28 days		-	-
Product/ingredient name	Aquatic half-life		Photolysi	S	Biodegradability
E∕poxy resin (MW ≤ 700) benzyl alcohol	-		-		Not readily Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Epoxy resin (MW ≤ 700) 1,6-bis(2,3-epoxypropoxy)	3 0.822	31 -	low low
hexane benzyl alcohol	0.87	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Date of issue 29 June 2021

Date of issue 29 June 2021

Version 3

Section 12. Ecological information

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (MW ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (MW ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin (MW ≤ 700))
Transport hazard class(es)	9	9	9
Packing group		III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Epoxy resin (MW ≤ 700))	Not applicable.

Additional information

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

ż

Safety, health and : No known specific national and/or regional regulations applicable to this product environmental regulations specific for the product

Classification



(including its ingredients).

Law No. 74/2001 - Banned

None of the components are listed.

Law No. 74/2001 - Restricted

None of the components are listed.

Law No. 74/2001 -: Not determined Chemicals that may be used

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 29 June 2021
Date of previous issue	: 3/26/2018
Version	: 3
Prepared by	: EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations

V Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.